Apache Xalan-J's, XSLT 3.0 specification implementation status (as of, 2024-06-04)

Document author : Apache Xalan-J team

(1) XSLT 3.0 & XPath 3.1

Following are details of "Xalan-J, XSL 3.0 family of languages" features, whose working implementation is available on Xalan-J XSLT 3.0 dev repos branch 'xalan-j_xslt3.0' (ref, https://github.com/apache/xalan-java/tree/xalan-j xslt3.0).

(1.1) XSLT 3.0 features

XSLT 3.0 language home page: https://www.w3.org/TR/xslt-30/

- 1) xsl:for-each-group instruction
- 2) xsl:analyze-string instruction
- 3) xsl:iterate instruction
- 4) xsl:for-each instruction implementation is modified, to handle few XSLT 3.0 requirements.
- 5) xsl:function instruction
- 6) xsl:sequence instruction
- 7) xsl:attribute element can now have "select" attribute as well in addition to mutually exclusive child content as well, as specified by XSLT 3.0 spec.
- 8) xsl:import-schema instruction

Currently, the XML Schema simple types imported via xsl:import-schema instruction within an XSLT stylesheet, can be used with "as" attribute of XSLT xsl:variable elements to enforce schema type constraints on xsl:variable data contents.

- 9) xsl:variable instruction evaluation to node set instead of result tree fragment (RTF). This is a XSLT spec change first introduced within XSLT 2.0 language, as compared to XSLT 1.0.
- 10) The sequence type expression "as" attribute on XSLT elements xsl:variable, xsl:template, xs:function, xsl:param, xsl:with-param.
- 11) Function implementations
 - a) New function implementations: fn:current-grouping-key, fn:current-group, fn:regex-group
 - b) Function implementation enhancements: fn:system-property

(1.2) XPath 3.1 expression language features

XPath 3.1 language home page: https://www.w3.org/TR/xpath-31/

- 1) Range "to" expression
- 2) Value comparison operators eq, ne, lt, le, gt, ge
- 3) Function item "inline function expression"
- 4) Dynamic function calls
- 5) "if" expression
- 6) "for" expression
- 7) Quantified expressions 'some', 'every'
- 8) "let" expression
- 9) Sequence constructor expression, using comma operator

For e.g, XPath expressions like (1, 2, 3) etc.

- 10) String concatenation operator "||"
- 11) Node comparison operators "is", "<<", ">>>"
- 12) Simple map operator '!'
- 13) Instance Of expression
- 14) Implementation of various new XML Schema built-in data types for use within XSLT 3.0 stylesheets and XPath 3.1 expressions. Implementation of, XPath constructor function calls (for e.g, xs:string('hello'), xs:date('2005-10-07') etc) for these supported XML Schema data types.

Currently, following XML Schema built-in data types are supported (depicted with XML Schema data type and subtype hierarchy as specified by "W3C XML Schema" data types specification), for this work:

```
xs:anyType
xs:anySimpleType
xs:anyAtomicType
xs:anyURI
xs:boolean
xs:date
xs:dateTime
xs:decimal
```

```
xs:integer
xs:long
xs:int
xs:double
xs:duration
xs:dayTimeDuration
xs:yearMonthDuration
xs:float
xs:QName
xs:string
xs:normalizedString
xs:token
xs:Name
xs:Name
xs:NCName
```

In addition to above mentioned XML Schema built-in data types, an XML Schema type xs:untyped specified by XPath 3.1 specification has also been implemented.

15) Collation support

As specified by XPath 3.1 F&O spec, implementations of following collations are supported:

- 15.1) The Unicode Codepoint Collation
- 15.2) The Unicode Collation Algorithm

Support for following collation uri query parameters is available: 'fallback', 'lang', 'strength'

For the collation's query "lang" parameter, all languages as those supported by Java's 'java.util.Locale' class are available within Xalan-J's XSLT 3.0 implementation (ref, https://docs.oracle.com/javase/8/docs/api/java/util/Locale.html).

For the collation's query "strength" parameter, following values are supported: 'primary', 'secondary', 'tertiary', 'identical'.

- 15.3) The HTML ASCII Case-Insensitive Collation
- 16) Sequence type expressions
- 17) Map expressions
- 18) Array expressions
- 19) Arrow operator, =>
- 20) Cast expression
- 21) Castable expression

(1.3) XPath 3.1 functions

XPath 3.1 F&O home page: https://www.w3.org/TR/xpath-functions-31/

Implementation of built-in functions namespace uri: http://www.w3.org/2005/xpath-functions

Implementation of built-in math functions namespace uri: http://www.w3.org/2005/xpath-functions/math

1) String functions that use regular expressions

fn:matches fn:replace fn:tokenize

2) Functions on numeric values

fn:abs

fn:round (implementation of an optional second argument, that's used to specify 'precision')

3) Functions giving access to external information

fn:doc

fn:unparsed-text

4) Functions on strings

fn:string-join fn:upper-case fn:lower-case

fn:codepoints-to-string fn:string-to-codepoints

fn:compare (with support for collation argument)

fn:codepoint-equal

fn:contains-token (with support for collation argument)

5) Context functions

fn:current-dateTime fn:current-date fn:current-time fn:implicit-timezone fn:default-collation

6) Functions that compare values in sequences

fn:distinct-values (with support for collation argument) fn:index-of (with support for collation argument)

fn:deep-equal

(with support for collation argument)

7) Mathematical trigonometric and exponential functions

math:pi

math:exp

math:exp10

math:log

math:log10

math:pow

math:sqrt

math:sin

math:cos

math:tan

math:asin

math:acos

math:atan

math:atan2

8) Component extraction functions on durations

fn:years-from-duration

fn:months-from-duration

fn:days-from-duration

fn:hours-from-duration

fn:minutes-from-duration

fn:seconds-from-duration

9) Constructing xs:dateTime value

fn:dateTime

10) Component extraction functions on dates and times

fn:year-from-dateTime

fn:month-from-dateTime

fn:day-from-dateTime

fn:hours-from-dateTime

fn:minutes-from-dateTime

fn:seconds-from-dateTime

fn:timezone-from-dateTime

fn:year-from-date

fn:month-from-date

fn:day-from-date

fn:timezone-from-date

fn:hours-from-time

fn:minutes-from-time

fn:seconds-from-time

fn:timezone-from-time

11) Built-in higher-order functions

fn:for-each

fn:filter

fn:fold-left

fn:fold-right

fn:for-each-pair

fn:sort

(with support for collation argument)

12) Functions on sequences

12.1 General functions on sequences

fn:empty

fn:exists

fn:head

fn:tail

fn:insert-before

fn:remove

fn:reverse

fn:subsequence

fn:unordered

12.2 Aggregate functions

fn:avg

fn:max

fn:min

13) Parsing and serializing

fn:parse-xml

fn:parse-xml-fragment

14) Accessors

fn:node-name

fn:data

fn:base-uri

fn:document-uri

15) Functions related to QNames

fn:resolve-QName

fn:QName

16) Functions related to maps

map:size

map:keys

map:contains map:get map:put map:entry map:remove map:for-each

17) Functions related to arrays

array:size
array:get
array:put
array:append
array:subarray
array:remove
array:insert-before
array:head
array:tail
array:reverse
array:join

18) Functions on JSON data

fn:parse-json

Other than the above mentioned newly implemented XPath 3.1 functions, all the functions that are already available within XPath 1.0 (all of them are common with XPath 3.1 function library as well) are available within Xalan-J's XPath 3.1 implementation as well.

Please refer to the web link https://www.w3.org/TR/1999/REC-xpath-19991116/ (section "4 Core Function Library"), for XPath 1.0 functions that shall work with Xalan-J's XSLT 3.0 implementation as well.

(2) Xalan-J XSLT 3.0 test suite

For the Xalan-J XSLT 3.0 implementation described within this document, a working test suite is available at the location: https://github.com/apache/xalan-java/tree/xalan-j_xslt3.0/tests.

Apache Xalan-J home page : https://xalan.apache.org/xalan-j/

Copyright © 1999-2024 The Apache Software Foundation