

Apache Xalan-J, XSLT 3.0 and XPath 3.1 implementation status

Last modified : 2026-06-22

Authors:

Gary Gregory <ggregory@apache.org>
(Apache Xalan PMC Chair, member & committer)

Joseph Kesselman <keshlam@alum.mit.edu>
(Apache Xalan PMC member & committer)

Mukul Gandhi <mukulg@apache.org>
(Apache Xalan PMC member & committer)

(1) XSL Transformations (XSLT) 3.0 and XML Path Language (XPath) 3.1

The XSLT 3.0 specification, mentions the following XSLT and XPath conformance features, and Apache Xalan-J XSLT 3.0 implementation status for these.

(Apache Xalan-J XSL 3 implementation quality for each of these mentioned conformance features, may not be complete as per XSLT 3.0 and XPath 3.1 specifications, and is available within Xalan-J results for W3C XSLT 3.0 and XPath 3.1 test suites, and Xalan-J results for its own XSL 3 test suite available within Xalan-J XSLT 3.0 development branch)

a) Basic XSLT processor	Supported
b) Schema aware XSLT processor	Supported
c) Serialization feature	Supported
d) Streaming feature	Not supported
e) Dynamic evaluation feature	Supported
f) XPath 3.1 feature, for arrays	Supported
g) Higher-order functions feature	Supported

Following are details of XSL 3.0 family of language features, whose working implementation is available on Xalan's dev repos branch 'xalan-j_xslt3.0_mvn':

1.1) XSLT 3.0

XSLT version 3.0 specification : <https://www.w3.org/TR/xslt-30/>

- 1) xsl:for-each-group instruction

- 2) `xsl:analyze-string` instruction
- 3) `xsl:iterate` instruction
- 4) `xsl:for-each` instruction implementation improvements, for new XSLT 3.0 requirements.
Particularly, `xsl:for-each` instruction being able to iterate XPath atomic values in addition to nodes.
- 5) `xsl:evaluate` instruction
- 6) `xsl:function` instruction
- 7) > `xsl:sequence` instruction
> `xsl:variable` and `xsl:param` instruction's attribute "static"
> XSL stylesheet instruction attribute "use-when" implementation
> `xsl:next-match` instruction
- 8) The following XSL stylesheet elements can now have attributes 'type' and 'validation' : `xsl:element`, literal result element (`xsl:validation` and `xsl:attribute`), `xsl:attribute`, `xsl:copy-of`, `xsl:copy`.
- 9) `xsl:attribute` element can now have both, "select" attribute and child sequence constructor. But only one of these is allowed to be present on `xsl:attribute` instruction as specified by XSLT 3.0 specification.
- 10) `xsl:import-schema` instruction
- 11) `xsl:variable` instruction evaluation to node set instead of result tree fragment (RTF). This XSLT specification change was first introduced in XSLT 2.0. With XSLT 1.0, if RTF has to be used as node set, then it has to be converted to node set using node-set extension function.
- 12) The sequence type expression "as" attribute on XSLT elements `xsl:variable`, `xsl:template`, `xs:function`, `xsl:param`, `xsl:with-param`, `xsl:evaluate`.
- 13) XSL template tunnel parameters
- 14) `xsl:value-of` instruction can now produce result either via its "select" attribute, or by `xsl:value-of` instruction's child sequence constructor. `xsl:value-of` instruction can now have an attribute named 'separator' as well.
- 15) `xsl:merge` instruction
- 16) `xsl:fork` instruction
- 17) `xsl:source-document` instruction
- 18) `xsl:try` and `xsl:catch` instructions
- 19) `xsl:character-map` instruction

20) Specifying XSL transformation's initial template name, or initial function name. Specification of XSL stylesheet initial template's default name `xsl:initial-template`.

21) XSLT function implementations

a) New function implementations : `fn:current-grouping-key`, `fn:current-group`, `fn:regex-group`, `fn:current-merge-group`, `fn:current-merge-key`, `fn:copy-of`

b) Function implementation enhancements : `fn:system-property`

22) Implementation of XSLT 3.0 attributes `xpath-default-namespace` and `expand-text`

23) `xsl:mode` instruction

24) `xsl:perform-sort` instruction

25) `xsl:map` instruction,
`xsl:package` instruction

Support for following new Xalan XSL transformation properties:

`http://apache.org/xalan/validation` (used to enable XML input document validation when `xsl:import-schema` instruction is used within an XSL stylesheet, with default value false)

`http://apache.org/xalan/xslevaluate` (used to enable XSL stylesheet instruction `xsl:evaluate`, with default value false)

These new XSL transformation properties can be set, using Xalan's class `TransformerImpl` when XSL transformation is invoked via API, or via Xalan command line.

1.2) XPath 3.1

XPath version 3.1 specification : <https://www.w3.org/TR/xpath-31/>

1) Range "to" expression

2) Value comparison operators `eq`, `ne`, `lt`, `le`, `gt`, `ge`

3) Function item "inline function expression"

4) Dynamic function calls

5) "if" expression

6) "for" expression

7) Quantified expressions 'some', 'every'

- 8) "let" expression
- 9) Sequence constructor expression, using comma operator
- 10) String concatenation operator "||"
- 11) Node comparison operators "is", "<<", ">>"
- 12) Simple map operator '!'
- 13) Instance Of expression
- 14) Implementation of various new XML Schema built-in data types for use in XSLT 3.0 stylesheets and XPath 3.1 expressions. Implementation of, XPath constructor function calls (for e.g, `xs:string('hello')`, `xs:date('2005-10-07')` etc) for these supported XML Schema data types.

Following XML Schema built-in types are supported (depicted with XML Schema data type and subtype hierarchy as specified by W3C XML Schema data types specification):

```
xs:anyType
  xs:anySimpleType
    xs:anyAtomicType
      xs:anyURI
      xs:base64Binary
      xs:boolean
      xs:decimal
      xs:integer
        xs:long
          xs:int
            xs:short
              xs:byte
                xs:nonNegativeInteger
                  xs:positiveInteger
                    xs:unsignedLong
                      xs:unsignedInt
                        xs:unsignedShort
                          xs:unsignedByte
                            xs:nonPositiveInteger
                              xs:negativeInteger
                                xs:double
                                xs:float
                                xs:date
                                xs:dateTime
                                xs:time
                                xs:duration
                                  xs:dayTimeDuration
                                  xs:yearMonthDuration
                                xs:gDay
```

- xs:gMonth
- xs:gMonthDay
- xs:gYear
- xs:gYearMonth
- xs:hexBinary
- xs:QName
- xs:string
 - xs:normalizedString
 - xs:token
 - xs:language
 - xs:Name
 - xs:NCName
 - xs:ID
 - xs:IDREF
 - xs:NMTOKEN

In addition to above mentioned XML Schema built-in data types, an XML Schema type `xs:untyped` specified by XPath 3.1 specification has also been implemented.

15) Collation support

Within the context of XSL languages, a collation is a method by which text information is compared and sorted.

As specified by XPath 3.1 F&O spec, implementations of following collations are available:

15.1) The Unicode Codepoint Collation

15.2) The Unicode Collation Algorithm

Support for following collation uri query parameters is available : 'fallback', 'lang', 'strength'

For the collation's query "lang" parameter, all languages as those supported by Java's 'java.util.Locale' class are available within Xalan's XSLT 3.0 implementation (ref, <https://docs.oracle.com/javase/8/docs/api/java/util/Locale.html>).

For the collation's query "strength" parameter, following values are supported : 'primary', 'secondary', 'tertiary', 'identical'.

15.3) The HTML ASCII Case-Insensitive Collation

16) Sequence type expression

17) Map expression

18) Array expression

19) Cast expression

- 20) Castable expression
- 21) Treat expression
- 22) Named function reference
- 23) Map and array lookup using function call syntax,
Map and array lookup using unary lookup operator “?”
- 24) Arrow operator (=>)
- 25) Node combination operators union, intersect and except

1.3) XPath 3.1 functions

XPath version 3.1 F&O specification : <https://www.w3.org/TR/xpath-functions-31/>

Implementation of XPath built-in default functions namespace : <http://www.w3.org/2005/xpath-functions>

Implementation of XPath built-in math functions namespace : <http://www.w3.org/2005/xpath-functions/math>

Implementation of XPath built-in map functions namespace : <http://www.w3.org/2005/xpath-functions/map>

Implementation of XPath built-in array functions namespace : <http://www.w3.org/2005/xpath-functions/array>

1) Functions on numeric values

fn:abs

fn:ceiling

fn:floor

fn:round (implementation of an optional second argument, that's used to specify 'precision')

fn:round-half-to-even

Formatting integer

fn:format-integer

2) Context functions

fn:current-dateTime

fn:current-date

fn:current-time

fn:implicit-timezone

fn:default-collation

3) Functions giving access to external information

fn:doc
fn:doc-available
fn:collection
fn:unparsed-text
fn:unparsed-text-lines
fn:unparsed-text-available
fn:environment-variable
fn:available-environment-variables

4) Functions on strings

fn:string-join
fn:upper-case
fn:lower-case
fn:codepoints-to-string
fn:string-to-codepoints
fn:compare (with support for collation argument)
fn:codepoint-equal
fn:contains-token (with support for collation argument)
fn:contains (added support for collation argument)
fn:starts-with (added support for collation argument)
fn:ends-with (with support for collation argument)
fn:substring-before (added support for collation argument)
fn:substring-after (added support for collation argument)

5) String functions that use regular expressions

fn:matches
fn:replace
fn:tokenize
fn:analyze-string

6) Functions that compare values in sequences

fn:distinct-values (with support for collation argument)
fn:index-of (with support for collation argument)
fn:deep-equal (with support for collation argument)

7) Maths trigonometric and exponential functions

math:pi
math:exp
math:exp10
math:log
math:log10
math:pow

math:sqrt
math:sin
math:cos
math:tan
math:asin
math:acos
math:atan
math:atan2

8) Random numbers

fn:random-number-generator

9) Component extraction functions on durations

fn:years-from-duration
fn:months-from-duration
fn:days-from-duration
fn:hours-from-duration
fn:minutes-from-duration
fn:seconds-from-duration

10) Constructing xs:dateTime value

fn:dateTime

11) Component extraction functions on dates and times

fn:year-from-dateTime
fn:month-from-dateTime
fn:day-from-dateTime
fn:hours-from-dateTime
fn:minutes-from-dateTime
fn:seconds-from-dateTime
fn:timezone-from-dateTime
fn:year-from-date
fn:month-from-date
fn:day-from-date
fn:timezone-from-date
fn:hours-from-time
fn:minutes-from-time
fn:seconds-from-time
fn:timezone-from-time

12) Timezone adjustment functions on dates and time values

fn:adjust-dateTime-to-timezone
fn:adjust-date-to-timezone
fn:adjust-time-to-timezone

fn:format-dateTime
fn:format-date
fn:format-time

fn:parse-ietf-date

13) Built-in higher-order functions

fn:for-each
fn:filter
fn:fold-left
fn:fold-right
fn:for-each-pair
fn:sort (with support for collation argument)
fn:apply

Dynamic loading and execution, of XSLT stylesheets:

fn:transform

14) Functions on sequences

14.1 General functions on sequences

fn:empty
fn:exists
fn:head
fn:tail
fn:insert-before
fn:remove
fn:reverse
fn:subsequence
fn:unordered

14.2 Aggregate functions

fn:avg
fn:max
fn:min

15) Parsing and serializing

fn:parse-xml
fn:parse-xml-fragment
fn:serialize

16) Accessors

fn:node-name
fn:string
fn:data

fn:base-uri
fn:document-uri

17) Functions related to QNames

fn:resolve-QName
fn:QName
fn:prefix-from-QName
fn:local-name-from-QName
fn:namespace-uri-from-QName
fn:namespace-uri-for-prefix
fn:in-scope-prefixes

18) Functions related to maps

map:merge
map:size
map:keys
map:contains
map:get
map:find
map:put
map:entry
map:remove
map:for-each

19) Functions related to arrays

array:size
array:get
array:put
array:append
array:subarray
array:remove
array:insert-before
array:head
array:tail
array:reverse
array:join
array:for-each
array:filter
array:fold-left
array:fold-right
array:for-each-pair
array:sort (with support for collation argument)
array:flatten

20) Functions related to nodes

fn:name
fn:local-name
fn:namespace-uri
fn:lang
fn:root
fn:path

21) Functions related to JSON data

fn:parse-json
fn:json-doc
fn:json-to-xml
fn:xml-to-json

(2) Features yet not implemented, or partially implemented

XSLT 3.0 instructions

a) “Conditional Content Construction” instructions `xsl:where-populated`, `xsl:on-empty`, `xsl:on-non-empty`

Not implemented.

XSLT 3.0 spec, ref : These facilities are available whether or not streaming is in use, but they are introduced to the language specifically to make streaming easier.

XPath 3.1 features

Partially implemented features:

a) Few XML Schema data types, for use with XPath 3.1 constructor function calls and sequence types are yet not supported.

The list of supported XML Schema data types with Apache Xalan-J, are described within this document’s section 1.2) XPath 3.1 point 14) above.

(3) Xalan’s XSLT 3.0 and XPath 3.1 test suite details

- 1) Xalan-J XSLT 3.0 development code’s latest conformance results with W3C XSLT 3.0 test suite is available here : https://github.com/apache/xalan-java/blob/xalan-j_xslt3.0_mvn/src/test/java/org/apache/xalan/tests/w3c/xslt3/result/w3c_xslt3_testsuite_xalan-j_result.xml
- 2) Xalan-J XSLT 3.0 development code’s latest conformance results with W3C XPath 3.1 test suite is available here :

https://github.com/apache/xalan-java/blob/xalan-j_xslt3.0_mvn/src/test/java/org/apache/xalan/tests/w3c/xpath3/result/w3c_xpath3_testsuite_xalan-j_result.xml

- 3) Xalan XSLT 3.0 development code's own XSL test suite is available here :
https://github.com/apache/xalan-java/tree/xalan-j_xslt3.0_mvn/src/test

Apache Xalan-J site
<https://xalan.apache.org/xalan-j/>

Copyright © 1999-2026 The Apache Software Foundation