ImpactLLM: An Open Observatory and Screening Method for the Environmental Footprint of LLMs

Arnault Pachot Thierry Petit

March 14, 2026

Abstract

The environmental literature on large language models (LLMs) is growing, but the evidence remains difficult to reuse because values are dispersed across papers, model cards, reports, and dashboards with heterogeneous units and system boundaries. We present *ImpactLLM*, an open observatory and screening tool for exploring the environmental footprint of current LLMs. The contribution is intentionally practical rather than grand-theoretical. First, the project provides a source-linked evidence layer that can be reused through a tabular dataset, a local API, an MCP server, and a public web interface. Second, it offers a rapid application-level estimator driven by natural-language descriptions rather than by long technical forms. The current release combines an inference-only application estimator with multi-factor screening views for both inference and training. In both cases, the project starts from observed literature anchors, then applies bounded multi-factor proxies that remain explicit and inspectable. In a domain where direct telemetry is usually unavailable for the most-used proprietary models, we argue that an open, auditable observatory is itself a useful scientific contribution.

Keywords: LLMs, open data, environmental footprint, inference, screening method, API.

1 Introduction

Environmental evaluation of LLMs is now discussed across several analytical levels: model training, prompt-level inference, service delivery, water use, hardware lifecycle, and data-center electricity demand [19, 17, 10, 16, 13, 5, 9, 8]. Yet the practical bottleneck is no longer simply the absence of quantified values. The literature now contains many values, but they are difficult to compare, audit, and reuse because they differ in unit of analysis, system boundary, geography, and traceability.

This paper addresses that bottleneck with a narrower claim than many AI-impact papers. *ImpactLLM* is not presented as a precision measurement system for proprietary LLM services, and it does not claim to discover a universal law linking parameter counts to energy use. Its contribution is instead twofold.

First, it provides an open observatory of environmental indicators for current LLMs. The observatory exposes source-linked records, model metadata, bibliographic references, and comparative views that remain inspectable by users. Second, it provides a rapid screening tool for application-level inference assessment. The user can describe an LLM-enabled application in natural language; the system extracts a compact scenario and returns an inference-focused estimate together with its assumptions, sources, and calculation details. This "fast estimate from natural language" design is deliberate: in many practical settings, users do not know dozens of technical serving parameters, but they can describe their application, model, country, and usage volume.

This positioning reflects a practical methodological judgment. The current AI market is dominated by a small number of hosted LLM services such as ChatGPT, Claude, Gemini, and Copilot, precisely the systems for which direct environmental telemetry is the least accessible. Yet the absence of direct measurement does not prevent strong claims from circulating. On the contrary, the public debate is now saturated with contradictory assertions, rough extrapolations, and decontextualized figures. In this context, the relevant choice is not between perfect measurement and approximation. For dominant proprietary services, perfect measurement is usually unavailable. The practical choice is therefore between opaque, unverifiable claims and a transparent, source-linked, auditable approximation framework. *ImpactLLM* adopts the second position.

This gap is especially visible for proprietary LLMs. While some product-level figures and a few industrial anchors have recently become public, model-level environmental values for proprietary systems are still rarely published with enough methodological detail to support direct comparison or reuse. The most widely used systems are often the least transparent: the serving hardware, routing logic, batching behavior, architecture, and deployment geography needed for direct environmental attribution generally remain undisclosed.

The scientific claim of the paper is therefore modest but useful. In a field dominated either by low-level telemetry tools or by opaque provider-side information, an open, reusable observatory coupled with an explicit screening estimator can fill an important operational gap.

2 State of the Art

The current landscape can be grouped into four broad methodological families.

The first family consists of hardware-instrumented experiment- or run-level trackers. These tools estimate energy or carbon from machine-level telemetry and retained electricity factors. Early experiment-level accounting in NLP is exemplified by Strubell et al. [19]. Current open-source tools such as *CarbonTracker* [2] and *CodeCarbon* [12] operationalize this logic for machine-learning workloads. They are useful when the evaluator controls the hardware, but not for proprietary hosted LLM APIs.

The second family consists of instrumented serving benchmarks. Here the objective is to measure standardized inference workloads on explicit serving stacks. Elsworth et al. provide an important production anchor by reporting prompt-level energy for Gemini Apps [5]. The recent *ML.ENERGY Benchmark* extends this benchmark logic to automated inference-energy measurement and optimization [18]. These approaches are more relevant to LLM inference than generic run trackers, but they remain tightly tied to the measured serving context.

The third family consists of bottom-up estimators for opaque or partially opaque hosted services. In this family, the evaluator does not observe provider-side telemetry directly. Instead, the estimate is reconstructed from proxies such as token volume, model class, architecture assumptions, likely hardware, and geography. *EcoLogits* is the clearest operational example of this family for current hosted LLM services [6]. *ImpactLLM* belongs to the same family, with a stronger emphasis on source-linked evidence and explicit methodological inspection.

The fourth family consists of cloud- or infrastructure-level accounting tools such as *Cloud Carbon Footprint* [4] and provider dashboards from AWS, Microsoft, Google Cloud, and OVHcloud [1, 11, 7, 14]. These tools are valuable for infrastructure governance, but they do not directly yield the footprint of one proprietary LLM request without an additional attribution layer.

Two broader lessons follow from the literature. First, the footprint of LLMs is multi-dimensional and should not be collapsed into one number [17, 9, 13]. Second, unit of analysis and system boundary matter as much as the numerical value itself [16]. The missing piece is therefore a reusable evidence layer that preserves this heterogeneity instead of hiding it.

3 Contribution and Data Layer

ImpactLLM is organized around one core design principle: one reusable quantified value per record, with its source and comparability context. The current release contains 76 records spanning 11 core sources and four analytical phases: training, inference, infrastructure, and lifecycle. This iteration also expands the market-model catalog to 41 entries, adding legacy Grok (1/2) and Claude 2 releases plus a curated set of GPT-era models such as Megatron-Turing NLG, Jurassic-1, Gopher, GLaM, LaMDA, and OPT to the previously tracked OpenAI and Mistral families. All inference and training columns were recomputed so the observatory data reflect those additional models and the most recent parameter inputs. Each record stores at least a unique identifier, citation, year, analytical phase, impact category, metric name, value, unit, model or scope, geography, data type, source locator, source URL, and free-text note.

This structure separates three dimensions that are often conflated in narrative reviews: the observed phenomenon, the method used to produce the number, and the scope to which the number applies. It also supports a second metadata layer describing comparability-oriented fields such as unit of analysis, source type, uncertainty level, and applicability domain.

The same evidence base is exposed through four reuse layers: a tabular dataset, a local HTTP API, an MCP server, and a bilingual public web observatory [15]. The scientific point is not that each interface is novel on its own, but that they all reuse the same source-linked evidence base. This makes the web

observatory, the programmatic interfaces, and the paper mutually auditable rather than loosely aligned artifacts.

This observatory angle matters because, to our knowledge, openly accessible infrastructures that jointly provide (i) source-level environmental indicators for LLMs, (ii) comparative views of current models, and (iii) an application-oriented inference screening interface remain rare. Existing tools often provide either instrumentation, or estimation, or datasets, but not all three within one openly inspectable workflow.

4 Inference Screening Method

The main practical question addressed by the tool is straightforward: given a software feature using an LLM, can we produce an inference estimate that is useful for screening and comparison when direct provider telemetry is absent?

The current answer is deliberately limited. The estimator is *inference-only*. It excludes model training, embodied impacts, application-side software consumption, and ancillary infrastructure from the displayed result. This is not because those dimensions are unimportant, but because the available inference anchors are structured enough to support a transparent screening method, whereas mixing them with broader lifecycle terms would blur the meaning of the result.

The design objective is also practical speed. Instead of asking users to fill a large technical form, the web interface starts from a natural-language description such as "We use GPT-4o-mini for customer support, around 4,000 uses per month in France." A parser then maps this text to a compact scenario with model, request type, approximate tokens, usage volume, and country assumptions. The output is therefore fast to obtain, but every inferred parameter remains visible to the user and can be inspected or challenged.

The current market-model release follows five rules.

- It starts from an observed literature anchor rather than from provider claims. The retained prompt-energy anchor is the Gemini Apps median prompt energy reported by Elsworth et al.: 0.24 Wh/prompt [5].
- It makes token volume explicit. Prompt compute is approximated from input and output tokens, with a larger weight for output generation than for input processing.
- It does not scale on raw parameters alone. It constructs *effective active parameters* by adjusting the target profile with context-window class, serving mode, modality support, and architecture notes.
- It reports a bounded low-central-high interval rather than a single falsely precise point.
- It derives carbon from retained energy and the electricity mix of the retained country, which is a contextual assumption rather than a model measurement.

Formally, let $E_a = 0.24$ Wh be the anchor value and $P_a = 180$ the active-parameter proxy retained for the anchor model. For a target model t, let P_t denote active parameters, T_{in} input tokens, and T_{out} output tokens. We define weighted prompt-compute volume:

$$V_t = T_{in} + \omega T_{out}, \tag{1}$$

with $\omega = 1.8$ in the current release. The project reference scenario is:

$$V_{ref} = 1000 + 1.8 \times 550 = 1990. \tag{2}$$

Effective active parameters are then defined by:

$$P_{t,s}^{eff} = P_t \times F_{t,s}^{ctx} \times F_{t,s}^{srv} \times F_{t,s}^{mod} \times F_{t,s}^{arch}, \tag{3}$$

where $s \in \{\text{low}, \text{central}, \text{high}\}$ indexes the screening scenario. The final per-request energy estimate is:

$$\hat{E}_{t,s} = E_a \times \left(\frac{P_{t,s}^{eff}}{P_a}\right)^{\alpha_s} \times \left(\frac{V_t}{V_{ref}}\right)^{\beta_s}. \tag{4}$$

The current implementation uses $\alpha_{low} = 0.85$, $\alpha_{central} = 0.95$, $\alpha_{high} = 1.05$, and $\beta_{low} = 0.85$, $\beta_{central} = 0.92$, $\beta_{high} = 1.0$. Carbon is then derived from the retained country mix:

$$\hat{C}_{t,s,c} = \frac{\hat{E}_{t,s}}{1000} \times CI_c, \tag{5}$$

where CI_c is the carbon intensity of country c in gCO_2e/kWh.

This method is not presented as a physical law of inference scaling. It is a traceable screening proxy anchored in observed prompt energy and explicit contextual assumptions. Its purpose is to provide a fast and inspectable estimate for comparative reasoning, not an audited declaration of real provider-side energy use.

5 Training Screening Method

The observatory also exposes training orders of magnitude for current market models. Here the uncertainty is even higher than for inference because published values are sparse, heterogeneous, and often reported only as aggregate emissions. A pure parameter-only scaling is therefore too brittle. The current release instead uses a second bounded proxy that combines retained parameter count with additional training priors.

The training proxy starts from literature anchors that directly report training CO_2e, and from training-energy reconstructions derived from those emissions when the source-country electricity mix is documented. For a target model t, the central training estimate is:

$$\hat{E}_{t,s}^{train} = E_a^{train} \times \left(\frac{P_t}{P_a}\right)^{\alpha_s} \times \left(\frac{Tok_t}{Tok_a}\right)^{\beta_s} \times F_{t,s}^{reg} \times F_{t,s}^{arch-tr} \times F_{t,s}^{hw}, \tag{6}$$

where P_t is the retained parameter count, Tok_t is a training-token prior, F^{reg} is a training-regime prior, $F^{arch-tr}$ captures architecture and multimodality assumptions, and F^{hw} is a hardware-class proxy. The current release uses a simple prior of 20 training tokens per retained parameter when no better public estimate is available, and defaults market models to a foundation-pretraining regime unless a narrower public indication exists.

This second proxy is not used in the application estimator shown to users, which remains inference-only. It is used in the observatory and the comparative tables to avoid suggesting that training impacts can be projected from parameter count alone. The result should still be read as a screening order of magnitude rather than as an audited declaration of model-development impact.

6 Illustrative Results

The public observatory standardizes model comparison under one hour of active use corresponding to 1,000 input tokens, 550 output tokens, one LLM request per interaction, and approximately 34.6 interactions per hour, derived from a reading-speed convention [3]. The underlying dataset and derived tables were refreshed for the March 2026 release, so the published values mirror the recalculated inference and training columns for the expanded market-model catalog. This provides a common comparison space before application-specific annualization.

Table 1 summarizes a few illustrative outputs. The first block shows how the standardized observatory makes model orders of magnitude legible. The second block shows how the same proxy can be annualized at the software-feature level from compact, natural-language scenarios.

These examples illustrate three practical properties of the method. First, annualization matters: apparently small unit values become relevant when multiplied by real usage. Second, the chosen model profile matters materially. Third, the retained electricity mix can dominate the carbon interpretation, which is why country contextualization is explicitly shown in the interface. Just as importantly, these results can be obtained quickly from natural-language inputs while keeping the extracted scenario and assumptions visible in the interface.

6.1 Observatory Visualizations

Figure 1 follows the release sequence of OpenAI, Claude, Grok, and Mistral models against the project's inference carbon estimate, keeping the vertical axis logarithmic to hold small and large models together. Figure 2 applies the same structure to the retained direct training CO_2e estimates, which are even more dispersed.

For completeness, Table 2 reports the current calculated values for all 41 market models tracked in the March 2026 release. The purpose of this table is documentary: it makes the observatory outputs directly inspectable in the paper, while the web interface remains the primary medium for interactive exploration.

Case	Energy	Carbon	Interpretation
Ministral 3B, one active hour	0.19 Wh	0.0077 gCO_2e	Small hybrid model under a French provider-country proxy
GPT-5 mini, one active hour	5.90 Wh	2.272 gCO_2e	Medium proprietary hosted model under a US provider-country proxy
Claude Opus 4.1, one active hour	103.53 Wh	39.860 gCO_2e	Very large proprietary estimate illustrating the steep growth of screening orders of magnitude
Support chatbot, Ministral 8B, 20,000 conversations/month	2.38 kWh/year	96 gCO_2e/year	Low-carbon annual result despite high usage because the retained electricity factor is favorable
Retrieval assistant, GPT-5 mini, 4,000 uses/month	12.31 kWh/year	4.74 $kgCO_2e$/year	Higher annualized result driven by hosted-service assumptions and US electricity contextualization

Table 1: Illustrative outputs from the current observatory and application estimator. These values are screening estimates, not audited declarations.



Figure 1: Inference carbon (gCO_2e/h) for the OpenAI, Anthropic, xAI, and Mistral families, plotted against each model's release month. The logarithmic scale keeps the large orders of magnitude accessible.



Figure 2: Direct training CO_2e (tCO_2e) from the same release sequence. The timeline emphasizes how training estimates scatter across multiple magnitudes even within the same provider families.

Table 2: Calculated environmental indicators for the 41 market models currently tracked by ImpactLLM. Inference values correspond to the standardized one-hour scenario used in the observatory. Training values are multi-factor screening estimates.

Model	Inference Wh/h	Inference gCO_2e/h	Training GWh	Training $ktCO_2e$
GPT-5.2	17.59	6.77	155.26	138.75
GPT-5.2-pro	17.59	6.77	155.26	138.75
GPT-5 mini	5.90	2.27	15.57	13.91
GPT-5 nano	5.90	2.27	15.57	13.91
GPT-OSS 120B	0.40	0.15	21.56	19.27
GPT-OSS 20B	0.26	0.10	0.69	0.62
Claude Opus 4.1	103.53	39.86	6900.35	6166.82
Claude Sonnet 4	22.44	8.64	276.01	246.67
Claude 3.5 Sonnet	10.23	3.94	52.83	47.21
Claude 3.7 Sonnet	10.23	3.94	52.83	47.21
Claude 3.5 Haiku	1.43	0.55	0.83	0.75
Gemini 2.5 Pro	12.46	4.80	69.00	61.67
Gemini 2.5 Flash	5.22	2.01	11.04	9.87
Gemini 2.5 Flash-Lite	2.06	0.79	1.55	1.39
Gemini 2.0 Flash	2.06	0.79	1.55	1.39
Grok 4	38.04	14.65	621.03	555.01
Llama 3.1 8B	0.46	0.18	0.11	0.10
Llama 3.1 70B	3.61	1.39	8.58	7.66
Llama 3.1 405B	19.13	7.37	287.06	256.54
Ministral 3B	0.19	0.01	0.02	0.01
Ministral 8B	0.49	0.02	0.11	0.10
Mistral Large	7.18	0.29	26.10	23.32
Mistral Small 3.1 24B	1.43	0.06	1.10	0.99
Codestral 22B	1.20	0.05	0.81	0.72
Qwen2.5 7B	0.41	0.22	0.09	0.08
Qwen2.5 32B	1.72	0.93	1.79	1.60
Qwen2.5 72B	3.71	2.00	9.07	8.11
DeepSeek V3	2.76	1.49	675.40	603.60
DeepSeek R1	2.89	1.56	675.40	603.60

7 Limitations

The main limitation is epistemic rather than computational. For proprietary hosted models, the evaluator does not observe the real serving stack, hardware, batch behavior, or data-center geography directly. The method therefore remains a proxy-informed estimate, not a direct measurement. The bounded interval is intended to make that limitation visible rather than to eliminate it.

A second limitation is anchor sparsity. Prompt-level inference anchors remain scarce, and the method currently relies heavily on Elsworth et al. for the main operational prompt-energy anchor [5]. Training anchors are also sparse and require additional priors on training tokens, regime, architecture, and hardware class. More published request-level and training-level benchmarks would improve both calibration and uncertainty framing.

A third limitation concerns scope. The current user-facing estimate is still inference-only. Training, embodied hardware impacts, software-system overheads, and water contextualization remain documented in the evidence base, and training is now screened in the observatory, but these dimensions are not yet integrated into the personalized application estimate.

A fourth limitation concerns natural-language scenario extraction. The “fast estimate” workflow improves usability, but it also introduces interpretation assumptions when users provide incomplete descriptions. For that reason, the extracted scenario, assumptions, and retained defaults are systematically displayed alongside the result.

8 Conclusion

ImpactLLM proposes a different kind of contribution to the LLM-environment literature. Its main novelty is not a new physical model, but an open, source-linked infrastructure that makes environmental evidence reusable across a dataset, an API, an MCP server, and a public observatory. On top of that evidence layer, the project implements a transparent inference-only screening method for current LLM services, including proprietary ones, and a rapid interface that starts from natural-language descriptions rather than long technical forms.

The value of the project lies precisely in this combination of restraint and reuse. It does not claim hidden provider telemetry, and it does not collapse heterogeneous evidence into a single opaque score. Instead, it publishes the records, the assumptions, the interfaces, and the extrapolative method together. In a field where the difficulty is increasingly one of comparability, accessibility, and traceability rather than raw numerical absence, an open observatory plus a fast screening workflow is a legitimate scientific contribution in its own right [15].

This is the sense in which the project should be read. For the most widely used hosted LLMs, direct environmental measurement is usually not publicly available, while public and policy discussions nevertheless continue to rely on numerical claims. In such a setting, doing nothing does not preserve rigor; it leaves the field open to opaque, inconsistent, and non-reproducible assertions. *ImpactLLM Observatory* therefore argues for a more disciplined middle ground: not false precision, but explicit approximation; not hidden assumptions, but auditable proxies; not definitive measurement, but a reusable framework that can be challenged, updated, and improved as better evidence becomes available.

References

[1] Amazon Web Services. What is the customer carbon footprint tool?, 2026. AWS documentation, accessed March 2026.

[2] Laurel Anthony, Benjamin Kanding, Raghavendra Selvan, Erik Christensen, Ole Andersson, et al. Carbontracker: Tracking and predicting the carbon footprint of training deep learning models. *arXiv preprint arXiv:2007.03051*, 2020.

[3] Marc Brysbaert. How many words do we read per minute? a review and meta-analysis of reading rate. *Journal of Memory and Language*, 109:104047, 2019.

[4] Cloud Carbon Footprint. Cloud carbon footprint methodology, 2026. Open-source software documentation, accessed March 2026.

[5] Catherine Elsworth, Kuan Huang, David Patterson, Ian Schneider, et al. Measuring the environmental impact of delivering ai at google scale. *arXiv preprint arXiv:2508.15734*, 2025.

[6] GenAI Impact. Ecologits documentation and methodology, 2026. Open-source software documentation, accessed March 2026.

[7] Google Cloud. View carbon emissions reports, 2026. Product documentation, accessed March 2026.

[8] International Energy Agency. Energy and ai, 2025.

[9] Pengfei Li, Jianyi Yang, Md Arafat Islam, and Shaolei Ren. Making ai less "thirsty": Uncovering and addressing the secret water footprint of ai models. *Communications of the ACM*, 68(4):46–54, 2025.

[10] Alexandra Sasha Luccioni, Sebastien Viguier, and Anne-Laure Ligozat. Estimating the carbon footprint of BLOOM, a 176b parameter language model. *Journal of Machine Learning Research*, 24(253):1–15, 2023.

[11] Microsoft. Emissions impact dashboard, 2026. Product documentation, accessed March 2026.

[12] MLCO2 Project. Codecarbon documentation and methodology, 2026. Open-source software documentation, accessed March 2026.

[13] Jack Morrison, Christine Na, Jose Fernandez, Tim Dettmers, et al. Holistically evaluating the environmental impact of creating language models. *arXiv preprint arXiv:2503.05804*, 2025.

[14] OVHcloud. Ovhcloud launches environmental impact tracker, 2024. Product announcement.

[15] Arnault Pachot and Thierry Petit. Impactllm, 2026. GitHub repository and online demo: https://dev.emotia.com/impact-llm.

[16] Siyuan Ren, Bill Tomlinson, R. W. Black, and Andrew W. Torrance. Reconciling the contrasting narratives on the environmental impact of large language models. *Scientific Reports*, 14:28180, 2024.

[17] Matthias C. Rillig, Martina Ågerstrand, Min Bi, Kerry A. Gould, and Uli Sauerland. Risks and benefits of large language models for the environment. *Environmental Science & Technology*, 57(9):3464–3466, 2023.

[18] Nikit Sharma, Hrishikesh Chawla, Lore Mansfield, Harjot Singal, Bilge Acun, et al. The ml.energy benchmark: Toward automated inference energy measurement and optimization. *arXiv preprint arXiv:2505.06371*, 2025.

[19] Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3645–3650, 2019.