

Learning Outcomes

By the end of this unit, you will be able to:

01

Create a data model to represent the objects and relationships in

a dataset.

02

Create schemas, tables, and databases for relational data. 03

Retrieve data using advanced database queries.

Class Objectives

By the end of today's class, you will:



Install and run PostgreSQL (SQL) and pgAdmin (GUI) on your computer.



Create databases and tables using pgAdmin.



Define SQL data types, primary keys, and unique values.



Load CSV files into a database and query the data.



Articulate and apply the four basic functions of persistent storage: Create, Read, Update, and Delete (CRUD) and apply them to a database.



Combine data from multiple tables using JOINs.

Why SQL?

Structured **Q**uery **L**anguage (SQL) is one of the main query languages used to access data within relational databases.

SQL is designed to efficiently handle large amounts of data, resulting in high value to organizations.

Data is stored in tables similar to spreadsheets that you would create in Microsoft Excel, making it easy to visualize and search.

Experienced **SQL** programmers are in high demand.


Programming, Scripting, and Markup Languages (all respondents) JavaScript 69.8% HTML 68.5% CSS 65.1% SOL 57.0% Java 45.3% Bash/Shell 39.8% Python 38.8% C# 34.4% PHP 30.7% C++25.4% 23.0% **TypeScript** 17.4% Ruby 10.1% Swift

Postgres and pgAdmin

Postgres

PostgreSQL (usually referred to as "Postgres") is an object-relational database system that uses the SQL language.

- Database engine
- Open source
- Great functionality



pgAdmin

pgAdmin is a database management tool used with Postgres. It simplifies creation, maintenance, and use of database objects by providing a Graphical User Interface (GUI)







Create, Read, Update, Delete (CRUD)

CRUD Operations

Create Read Update Delete is a set of operations used with persistent storage.

Create	INSERT INTO table (column1, column2, column3)
Read	SELECT * FROM table
Update	UPDATE table SET column1 = VALUE WHERE id = 1
These tools are	DELETE FROM table WHERE id = 5 fundamental to all programming languages, not just SQL.

11



Wildcards: % and _

Wildcards are used to substitute zero, one, or multiple characters in a string. The keyword **LIKE** indicates the use of a wildcard.

```
SELECT *
FROM actor
WHERE last_name LIKE 'Will%';
```

The % will substitute **zero**, **one**, or **multiple** characters in a query.

For example, all of the following will match: Will, Willa, and Willows.

```
SELECT *
FROM actor
WHERE first_name LIKE '_AN';
```

The _ will substitute one—and only one—character in a query.

_AN returns all actors whose first name contains three letters, the second and third of which are AN.

