

CS 500: Scene File Format

DIGIPEN INSTITUTE OF TECHNOLOGY

Fall 2010

This handout gives the format of the file used to specify the object, light, and camera information needed to render a scene.

Conventions. Objects, lights, and cameras are placed within a *right-handed* coordinate system. It is convenient to imagine that the units of length have been chosen so as to have most of the objects in a scene lie within the cube $[-1, 1] \times [-1, 1] \times [-1, 1]$. Note that this does not mean that objects outside this cube will not be rendered, or that one should not place objects outside this cube; rather, it is simply a matter of convenience to imagine that objects have dimensions on the order of unity.

In general, the scene file consists of five types of entries:

1. Comments
2. Objects
3. Lights
4. Camera
5. Global Quantities

Details about each of these types is given in the following sections.

1 Comments

A comment line starts with the '#' character, and ends with a newline. To make life as simple as possible, the comment marker '#' can only appear at the beginning of a line. Blank lines are ignored.

2 Objects

Objects are specified by a line, or lines, of the following form. Note that newline characters are considered whitespace (so that an object specification may span multiple lines).

`<identifier> <spacial data> <surface properties>`

where

<identifier> is one of the following: SPHERE, BOX, POLYGON, or ELLIPSOID.

<spacial data> gives a list of data (vectors and/or values) specifying the spacial dimensions of the object (see below for the specifics).

<surface properties> specifies the surface characteristics for use with the lighting model, and always has the form

$$(D_r, D_g, D_b) S_c S_e (A_r, A_g, A_b) \epsilon_r \mu_r$$

where (D_r, D_g, D_b) are the diffuse reflection color coefficients (for the ray casting assignment, use this value and ignore all remaining values), S_c is the specular reflection coefficient, S_e is the specular reflection exponent (Phong model), (A_r, A_g, A_b) are the transmission attenuation factors, ϵ_r is the relative electric permittivity, and μ_r is the relative magnetic permeability (so that the index of refraction is given by $n = \sqrt{\epsilon_r \mu_r}$). All values are floating point values in the range $[0, 1]$.

The **<spacial data>** list for an object depends on the specific object. The following specifies the format for each specific object.

SPHERE $(c_x, c_y, c_z) r$ **<surface properties>**

A sphere with center (c_x, c_y, c_z) and radius r .

BOX $(v_x, v_y, v_z) (l_x, l_y, l_z) (w_x, w_y, w_z) (h_x, h_y, h_z)$ **<surface properties>**

A rectangular box with corner (v_x, v_y, v_z) , length vector (l_x, l_y, l_z) , width vector (w_x, w_y, w_z) , and height vector (h_x, h_y, h_z) .

POLYGON $n (v_{1,x}, v_{1,y}, v_{1,z}) \dots (v_{n,x}, v_{n,y}, v_{n,z})$ **<surface properties>**

An n -sided convex polygon with vertices $(v_{1,x}, v_{1,y}, v_{1,z}), \dots, (v_{n,x}, v_{n,y}, v_{n,z})$.

ELLIPSOID $(c_x, c_y, c_z) (u_x, u_y, u_z) (v_x, v_y, v_z) (w_x, w_y, w_z)$ **<surface properties>**

An ellipsoid with center (c_x, c_y, c_z) and semiaxes (u_x, u_y, u_z) , (v_x, v_y, v_z) , and (w_x, w_y, w_z) .

Individual quantities are separated by one or more whitespace characters; a vector quantity may, but is not required to, have whitespace between component values, parentheses, and commas.

3 Lights

A spherical light source centered at the point (p_x, p_y, p_z) with RGB color (I_r, I_g, I_b) and radius r is specified by the line:

$$\text{LIGHT } (p_x, p_y, p_z) (I_r, I_g, I_b) r$$

(the RGB values are floating point numbers, typically between 0 and 1). The value for the radius is for use in modeling soft shadows.

4 Camera

Our ‘camera’ model is as follows. The center of the view plane is located at $c = (c_x, c_y, c_z)$; the view window (whose center is also p) is defined by two vectors $u = (u_x, u_y, u_z)$ and $v = (v_x, v_y, v_z)$ in the view plane:

$$\text{view window} = \{c + au + bv \mid -1 \leq a \leq 1, -1 \leq b \leq 1\}$$

(the vectors u and v are assumed to be orthogonal). The view reference point (eye) is located at $c + e$. With these conventions, the camera is specified by the line (or lines):

$$\text{CAMERA } (c_x, c_y, c_z) (u_x, u_y, u_z) (v_x, v_y, v_z) (e_x, e_y, e_z)$$

Some things to note about our camera model:

- The eye vector e is not necessarily orthogonal to the view plane!
- The width of the view window is $2|u|$, and the height is $2|v|$.
- The normal to the view window/plane is $u \times v$.

5 Global Quantities

We consider two basic quantities that will affect the overall appearance of the rendered scene: ambient light and air.

$$\text{AMBIENT } (I_r, I_g, I_b)$$

Ambient light of RGB color (I_r, I_g, I_b) . If the **AMBIENT** identifier is not present in the scene file, the color should be assumed to be $(0, 0, 0)$.

$$\text{AIR } \epsilon_r \mu_r (A_r, A_g, A_b)$$

All objects in the scene are surrounded by ‘air’, which has relative electric permittivity ϵ_r , relative magnetic permeability μ_r , and RGB attenuation factors (A_r, A_g, A_b) . If the **AIR** identifier is not present in the scene file, all values should be assumed to be unity .

6 Sample scene file

Here is an example scene file

```
# Sample scene file

SPHERE (0.5,0.25,-0.5) 0.25
  (0.5,0.7,0.5) 0.3 70 (0,0,0) 1e6 1

BOX (-0.2623,0.001,-0.7042)
  (0.6495,0,-0.375) (-0.125,0,-0.2165) (0,0.75,0)
  (0.3,0.3,0.5) 0.8 20 (0.5,0.5,0.5) 2.3716 1

POLYGON 4 (1,0,0) (1,0,-2) (-1,0,-2) (-1,0,0)
  (0.6,0.6,0.6) 0.4 20 (0,0,0) 1e6 1

ELLIPSOID (-0.5,0.5,-1.5) (0.25,0,0) (0,0.5,0) (0,0,0.25)
  (0.7,0.5,0.5) 0.3 70 (0,0,0) 1e6 1

LIGHT (-1,1,0) (1,1,1) 0.1
LIGHT (0.75,0.5,0) (0.8,0.8,0.8) 0.2

AMBIENT (0.1,0.1,0.1)

CAMERA (0,0.5,0) (0.5,0,0) (0,0.5,0) (0,0,1)
```