

# Algebraic lattices in cryptography

Alice Pellet-Mary

Université de Bordeaux

Journées d'inauguration de la fédération MARGAUx  
La Rochelle

# Motivation: cryptography

## Cryptographic primitives

public key  
encryption

signature

homomorphic  
encryption

...

error correcting codes

lattices

isogenies

factoring

discrete logarithm

...

(Supposedly intractable) algorithmic problems

# Motivation: cryptography

## Cryptographic primitives

public key  
encryption

signature

homomorphic  
encryption

...

error correcting codes

lattices

isogenies

~~factoring~~

~~discrete logarithm~~

...

(Supposedly intractable) algorithmic problems  
in a quantum world

# Motivation: cryptography

## Cryptographic primitives

public key  
encryption

signature

homomorphic  
encryption

...

error correcting codes

**lattices**

isogenies

~~factoring~~


~~discrete logarithm~~

...

(Supposedly intractable) algorithmic problems  
in a quantum world


# Lattices

# Lattices



- ▶  $L = \{Bx \mid x \in \mathbb{Z}^n\}$  is a **lattice**
- ▶  $B \in \text{GL}_n(\mathbb{R})$  is a **basis**
- ▶  $n$  is the **dimension** of  $L$


# Algorithmic problems



SVP : Shortest Vector Problem

CVP : Closest Vector Problem

# Algorithmic problems




approx-SVP : Shortest Vector Problem

approx-CVP : Closest Vector Problem



# Algorithmic problems



approx-SVP : Shortest Vector Problem

approx-CVP : Closest Vector Problem


Supposedly **hard** to solve when  $n$  is large (input: a bad basis of  $L$ )

- ▶ even with a **quantum** computer
- ▶ even with a small **approximation factor** ( $\text{poly}(n)$ )

# Hardness of SVP and CVP

Best Time/Approximation trade-off for SVP, CVP (even quantumly):

BKZ algorithm [Sch87,SE94]




[Sch87] C.-P. Schnorr. A hierarchy of polynomial time lattice basis reduction algorithms. TCS.

[SE94] C.-P. Schnorr and M. Euchner. Lattice basis reduction: improved practical algorithms and solving subset sum problems. Mathematical programming.

# Hardness of SVP and CVP

Best Time/Approximation trade-off for SVP, CVP (even quantumly):


BKZ algorithm [Sch87,SE94]




[Sch87] C.-P. Schnorr. A hierarchy of polynomial time lattice basis reduction algorithms. TCS.

[SE94] C.-P. Schnorr and M. Euchner. Lattice basis reduction: improved practical algorithms and solving subset sum problems. Mathematical programming.

# Public key encryption from lattices



# Public key encryption from lattices




$$\text{pk} = (B_p, x)$$

$$\text{sk} = B_s$$

message:  $m \in \{0, 1\}$

# Public key encryption from lattices



$\text{pk} = (B_p, x)$


$\text{sk} = B_s$

message:  $m \in \{0, 1\}$

Encryption( $m, \text{pk}$ ):

- ▶ sample random  $v \in L$
- ▶ sample small  $e \in \mathbb{R}^n$
- ▶ return  $c = v + e + m \cdot x$

# Public key encryption from lattices



$$\text{pk} = (B_p, x)$$

$$\text{sk} = B_s$$

message:  $m \in \{0, 1\}$

Encryption( $m, \text{pk}$ ):

- ▶ sample random  $v \in L$
- ▶ sample small  $e \in \mathbb{R}^n$
- ▶ return  $c = v + e + m \cdot x$

Decryption( $c, \text{sk}$ ):

- ▶ find  $w \in L$  closest to  $c$
- ▶ if  $c$  is very close to  $w$ , return  $m = 0$
- ▶ otherwise return  $m = 1$

# Structured lattices



# Why?

## Motivation

Schemes using lattices are usually not efficient

(storage:  $n^2$ , matrix-vector mult:  $n^2$ )

⇒ improve efficiency using **structured lattices**

# Why?

## Motivation

Schemes using lattices are usually not efficient

(storage:  $n^2$ , matrix-vector mult:  $n^2$ )

⇒ improve efficiency using **structured lattices**

**Two examples:** (submitted to the NIST post-quantum standardization process)

	Frodo (unstructured lattices)	Kyber (structured lattices)
secret key size (in Bytes)	19 888	1 632
public key size (in Bytes)	9 616	800

# Structured lattices: example


$$M_a = \begin{pmatrix} a_1 & -a_n & \cdots & -a_2 \\ a_2 & a_1 & \cdots & -a_3 \\ \vdots & \ddots & \ddots & \vdots \\ a_n & a_{n-1} & \cdots & a_1 \end{pmatrix}$$

basis of a special case of  
ideal lattice

# Structured lattices: example

$$M_a = \begin{pmatrix} a_1 & -a_n & \cdots & -a_2 \\ a_2 & a_1 & \cdots & -a_3 \\ \vdots & \ddots & \ddots & \vdots \\ a_n & a_{n-1} & \cdots & a_1 \end{pmatrix}$$

basis of a special case of  
ideal lattice




basis of a special case of  
module lattice  
of rank  $m$

# Structured lattices: example

$$M_a = \begin{pmatrix} a_1 & -a_n & \cdots & -a_2 \\ a_2 & a_1 & \cdots & -a_3 \\ \vdots & \ddots & \ddots & \vdots \\ a_n & a_{n-1} & \cdots & a_1 \end{pmatrix}$$


basis of a special case of  
ideal lattice




basis of a special case of  
module lattice  
of rank  $m$

*Is SVP still hard when restricted to ideal/module lattices?*


# SVP in modules and ideals



Modules  
(rank  $\geq 2$ )




ideals  
(in cyclotomic fields)




ideals  
(with  $2^{O(n)}$  pre-processing)


# SVP in modules and ideals



Modules  
(rank  $\geq 2$ )




ideals  
(in cyclotomic fields)




ideals  
(with  $2^{O(n)}$  pre-processing)


# Impact on cryptography



Modules  
(rank  $\geq 2$ )




ideals  
(in cyclotomic fields)



ideals  
(with  $2^{O(n)}$  pre-processing)



# Impact on cryptography



# Algorithms for ideal lattices

# History: algorithms for ideal-SVP

[RBV04]: principal ideals in small dimension

---

[RBV04] G. Rekeya, J.-C. Belfiore, E. Viterbo. A very efficient lattice reduction tool on fast fading channels. ISITA.

# History: algorithms for ideal-SVP

[RBV04]: principal ideals in small dimension

[CGS14]: principal ideals in cyclotomic fields  
(without analysis)

---

[CGS14]: P. Campbell, M. Groves, and D. Shepherd. Soliloquy: a cautionary tale.

# History: algorithms for ideal-SVP

[RBV04]: principal ideals in small dimension

[CGS14]: principal ideals in cyclotomic fields  
(without analysis)

[CDPR16]: analysis of [CGS14]  
 $\Rightarrow 2^{O(\sqrt{n})}$  approximation factor in quantum poly time

---

[CDPR16] R. Cramer, L. Ducas, C. Peikert and O. Regev. Recovering short generators of principal ideals in cyclotomic rings. Eurocrypt.

# History: algorithms for ideal-SVP

[RBV04]: principal ideals in small dimension

[CGS14]: principal ideals in cyclotomic fields  
(without analysis)

[CDPR16]: analysis of [CGS14]  
 $\Rightarrow 2^{O(\sqrt{n})}$  approximation factor in quantum poly time

[CDW17]: any ideal in cyclotomic fields

---

[CDW17] R. Cramer, L. Ducas, B. Wesolowski. Short stickelberger class relations and application to ideal-SVP.  
Eurocrypt.

# History: algorithms for ideal-SVP

[RBV04]: principal ideals in small dimension

[CGS14]: principal ideals in cyclotomic fields  
(without analysis)

[CDPR16]: analysis of [CGS14]  
 $\Rightarrow 2^{O(\sqrt{n})}$  approximation factor in quantum poly time

[CDW17]: any ideal in cyclotomic fields

[PHS19]: more trade-offs but exponential pre-processing  
(any ideal, any number field)

---

[PHS19] A. Pellet-Mary, G. Hanrot, D. Stehlé. Approx-SVP in ideal lattices with pre-processing. Eurocrypt.

# History: algorithms for ideal-SVP

[RBV04]: principal ideals in small dimension

[CGS14]: principal ideals in cyclotomic fields  
(without analysis)

[CDPR16]: analysis of [CGS14]  
 $\Rightarrow 2^{O(\sqrt{n})}$  approximation factor in quantum poly time

[CDW17]: any ideal in cyclotomic fields

[PHS19]: more trade-offs but exponential pre-processing  
(any ideal, any number field)

---

[PHS19] A. Pellet-Mary, G. Hanrot, D. Stehlé. Approx-SVP in ideal lattices with pre-processing. Eurocrypt.



## Notation

$K = \mathbb{Q}[X]/(X^n + 1)$ , with  $n = 2^k$  (or any cyclotomic field)

$O_K = \mathbb{Z}[X]/(X^n + 1)$

## Notation

$K = \mathbb{Q}[X]/(X^n + 1)$ , with  $n = 2^k$  (or any cyclotomic field)

$$O_K = \mathbb{Z}[X]/(X^n + 1)$$

► **Units:**  $O_K^\times = \{a \in O_K \mid \exists b \in O_K, ab = 1\}$

## Notation

$K = \mathbb{Q}[X]/(X^n + 1)$ , with  $n = 2^k$  (or any cyclotomic field)

$$O_K = \mathbb{Z}[X]/(X^n + 1)$$


- ▶ **Units:**  $O_K^\times = \{a \in O_K \mid \exists b \in O_K, ab = 1\}$
- ▶ **Principal ideals:**  $\langle g \rangle = \{gr \mid r \in O_K\}$ 
  - ▶  $g$  is a **generator** of  $\langle g \rangle$
  - ▶  $\{\text{generators of } \langle g \rangle\} = \{gu \mid u \in O_K^\times\}$

# Why is $\langle g \rangle$ a lattice?

$O_K$  is a lattice

$$O_K = \mathbb{Z}[X]/(X^n + 1) \rightarrow \mathbb{C}^n$$
$$r(X) \mapsto (r(\alpha_1), r(\alpha_2), \dots, r(\alpha_n)),$$

where  $\alpha_1, \dots, \alpha_n$  are the roots of  $X^n + 1$  in  $\mathbb{C}$




# Why is $\langle g \rangle$ a lattice?

$O_K$  is a lattice

$$O_K = \mathbb{Z}[X]/(X^n + 1) \rightarrow \mathbb{C}^n$$
$$r(X) \mapsto (r(\alpha_1), r(\alpha_2), \dots, r(\alpha_n)),$$

where  $\alpha_1, \dots, \alpha_n$  are the roots of  $X^n + 1$  in  $\mathbb{C}$

$$\begin{cases} \langle g \rangle \subseteq O_K \simeq \mathbb{Z}^n \\ \text{stable by '+' and '-'} \end{cases} \Rightarrow \text{ideal lattice}$$



# Objective and first idea [CDPR,CGS14]

**Objective:** Given a basis of  $\langle g \rangle$ , find a (somehow) small element  $gr \in \langle g \rangle$

# Objective and first idea [CDPR,CGS14]

**Objective:** Given a basis of  $\langle g \rangle$ , find a (somehow) small element  $gr \in \langle g \rangle$

**Idea:** Maybe  $g$  is a somehow small element of  $\langle g \rangle$

# Objective and first idea [CDPR,CGS14]

**Objective:** Given a basis of  $\langle g \rangle$ , find a (somehow) small element  $gr \in \langle g \rangle$

**Idea:** Maybe  $g$  is a somehow small element of  $\langle g \rangle$

► If  $n = 1$ : e.g.  $\langle 2 \rangle \Rightarrow 2$  and  $-2$  are the smallest elements.





# Objective and first idea [CDPR,CGS14]

**Objective:** Given a basis of  $\langle g \rangle$ , find a (somehow) small element  $gr \in \langle g \rangle$

**Idea:** Maybe  $g$  is a somehow small element of  $\langle g \rangle$

► If  $n = 1$ : e.g.  $\langle 2 \rangle \Rightarrow 2$  and  $-2$  are the smallest elements.




► For larger  $n$ : one of the generators is somehow small

# The Log space

$\text{Log} : O_K \rightarrow \mathbb{R}^n$  (take the log of every coordinate)

Let  $\mathbf{1} = (1, \dots, 1)$  and  $H = \mathbf{1}^\perp$ .



# The Log space


$\text{Log} : O_K \rightarrow \mathbb{R}^n$  (take the log of every coordinate)

Let  $1 = (1, \dots, 1)$  and  $H = 1^\perp$ .

Properties ( $r \in O_K$ )

$\text{Log } r = h + a \cdot 1$ , with  $h \in H$

- $\text{Log}(r_1 \cdot r_2) = \text{Log}(r_1) + \text{Log}(r_2)$



# The Log space


$\text{Log} : O_K \rightarrow \mathbb{R}^n$  (take the log of every coordinate)

Let  $\mathbf{1} = (1, \dots, 1)$  and  $H = \mathbf{1}^\perp$ .

Properties ( $r \in O_K$ )

$\text{Log } r = h + a \cdot \mathbf{1}$ , with  $h \in H$

- $\text{Log}(r_1 \cdot r_2) = \text{Log}(r_1) + \text{Log}(r_2)$
- $a \geq 0$



# The Log space


$\text{Log} : O_K \rightarrow \mathbb{R}^n$  (take the log of every coordinate)

Let  $\mathbf{1} = (1, \dots, 1)$  and  $H = \mathbf{1}^\perp$ .

Properties ( $r \in O_K$ )

$\text{Log } r = h + a \cdot \mathbf{1}$ , with  $h \in H$

- $\text{Log}(r_1 \cdot r_2) = \text{Log}(r_1) + \text{Log}(r_2)$
- $a \geq 0$
- $a = 0$  iff  $r$  is a unit



# The Log space


$\text{Log} : O_K \rightarrow \mathbb{R}^n$  (take the log of every coordinate)

Let  $\mathbf{1} = (1, \dots, 1)$  and  $H = \mathbf{1}^\perp$ .

Properties ( $r \in O_K$ )

$\text{Log } r = h + a \cdot \mathbf{1}$ , with  $h \in H$

- $\text{Log}(r_1 \cdot r_2) = \text{Log}(r_1) + \text{Log}(r_2)$
- $a \geq 0$
- $a = 0$  iff  $r$  is a unit



The Log unit lattice

$\Lambda := \text{Log}(O_K^\times)$  is a lattice in  $H$ .

# The Log space


$\text{Log} : O_K \rightarrow \mathbb{R}^n$  (take the log of every coordinate)

Let  $\mathbf{1} = (1, \dots, 1)$  and  $H = \mathbf{1}^\perp$ .

## Properties ( $r \in O_K$ )

$\text{Log } r = h + a \cdot \mathbf{1}$ , with  $h \in H$

- $\text{Log}(r_1 \cdot r_2) = \text{Log}(r_1) + \text{Log}(r_2)$
- $a \geq 0$
- $a = 0$  iff  $r$  is a unit
- $\|r\| \simeq \exp(\|\text{Log } r\|_\infty)$




## The Log unit lattice

$\Lambda := \text{Log}(O_K^\times)$  is a lattice in  $H$ .

# The algorithm [CGS14,CDPR16]


What does  $\text{Log}\langle g \rangle$  look like?






# The algorithm [CGS14,CDPR16]

What does  $\text{Log}\langle g \rangle$  look like?




# The algorithm [CGS14,CDPR16]

What does  $\text{Log}\langle g \rangle$  look like?



# The algorithm [CGS14,CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time




---

[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.

# The algorithm [CGS14, CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time




---

[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.

# The algorithm [CGS14,CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time
- ▶ Solve CVP in  $\Lambda$




---

[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.

# The algorithm [CGS14,CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time
- ▶ Solve CVP in  $\Lambda$




---

[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.

# The algorithm [CGS14,CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time
- ▶ Solve CVP in  $\Lambda$ 
  - ▶ Good basis of  $\Lambda$  (cyclotomic field)
    - $\Rightarrow$  CVP in poly time
    - $\Rightarrow \|h\| \leq \tilde{O}(\sqrt{n})$




---

[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.

# The algorithm [CGS14, CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time
- ▶ Solve CVP in  $\Lambda$ 
  - ▶ Good basis of  $\Lambda$  (cyclotomic field)
    - $\Rightarrow$  CVP in poly time
    - $\Rightarrow \|h\| \leq \tilde{O}(\sqrt{n})$

$$\|ug_1\| \leq 2^{\tilde{O}(\sqrt{n})} \cdot \lambda_1$$




[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.



# The algorithm [CGS14,CDPR16]

- ▶ Find a generator  $g_1$  of  $\langle g \rangle$ .
  - ▶ [BS16]: quantum poly time
- ▶ Solve CVP in  $\Lambda$ 
  - ▶ Good basis of  $\Lambda$  (cyclotomic field)
    - $\Rightarrow$  CVP in poly time
    - $\Rightarrow \|h\| \leq \tilde{O}(\sqrt{n})$

$$\|ug_1\| \leq 2^{\tilde{O}(\sqrt{n})} \cdot \lambda_1$$



• Heuristic

• Cyclotomic fields

[BS16]: J.-F. Biasse, F. Song. Efficient quantum algorithms for computing class groups and solving the principal ideal problem in arbitrary degree number fields. SODA.

## Conclusion

# Some open questions

- ▶ Are there some number fields stronger than others?  
(are cyclotomic fields particularly weak?)

# Some open questions

- ▶ Are there some number fields stronger than others?  
(are cyclotomic fields particularly weak?)
- ▶ Are modules of rank  $\geq 2$  really safer than ideals?

# Some open questions

- ▶ Are there some number fields stronger than others?  
(are cyclotomic fields particularly weak?)
- ▶ Are modules of rank  $\geq 2$  really safer than ideals?
- ▶ Are there some better structured lattices?

# Some open questions

- ▶ Are there some number fields stronger than others?  
(are cyclotomic fields particularly weak?)
- ▶ Are modules of rank  $\geq 2$  really safer than ideals?
- ▶ Are there some better structured lattices?

Thank you