

SCRIPT BASE DE DATOS NEO4J

CREACIÓN BASE DE DATOS

```
LOAD CSV WITH HEADERS FROM 'file:///top50Songs.csv' AS line WITH line LIMIT 1000
```

```
MERGE (s:Style {name: "Estilos Musicales"})
```

```
CREATE (c:Canciones { name: line.TrackName, artist: line.ArtistName, genre: line.Genre, energy: toInteger(line.Energy), danceability: toInteger(line.Danceability), valence: toInteger(line.Valence), popularity: toInteger(line.Popularity), cover: line.TrackCover, preview: line.TrackPreview, fav: "false"})
```

```
FOREACH (n IN (CASE WHEN line.ArtistName IS NULL THEN [] ELSE [1] END) |
```

```
MERGE (a:ArtistName {name: line.ArtistName})
```

```
CREATE (a)-[:MADE]->(c)
```

```
)
```

```
FOREACH (n IN (CASE WHEN line.Genre IS NULL THEN [] ELSE [1] END) | MERGE
```

```
(g:Genre {name: line.Genre})
```

```
CREATE (c)-[:OF_GENRE]->(g)
```

```
MERGE (s)-[:IS_STYLE]->(g)
```

```
)
```

BORRAR NODOS Y RELACIONES

```
match (n)
with n limit 10000
DETACH DELETE n
```