

## 2013 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

2. A multiplayer game called Token Pass has the following rules.

Each player begins with a random number of tokens (at least 1, but no more than 10) that are placed on a linear game board. There is one position on the game board for each player. After the game board has been filled, a player is randomly chosen to begin the game. Each position on the board is numbered, starting with 0.

The following rules apply for a player's turn.

- The tokens are collected and removed from the game board at that player's position.
- The collected tokens are distributed one at a time, to each player, beginning with the next player in order of increasing position.
- If there are still tokens to distribute after the player at the highest position gets a token, the next token will be distributed to the player at position 0.
- The distribution of tokens continues until there are no more tokens to distribute.

The Token Pass game board is represented by an array of integers. The indexes of the array represent the player positions on the game board, and the corresponding values in the array represent the number of tokens that each player has. The following example illustrates one player's turn.

### Example

The following represents a game with 4 players. The player at position 2 was chosen to go first.

	0	1	2	3
Player Tokens	3	2	6	10

The tokens at position 2 are collected and distributed as follows.

- 1st token - to position 3 (The highest position is reached, so the next token goes to position 0.)
- 2nd token - to position 0
- 3rd token - to position 1
- 4th token - to position 2
- 5th token - to position 3 (The highest position is reached, so the next token goes to position 0.)
- 6th token - to position 0

After player 2's turn, the values in the array will be as follows.

	0	1	2	3
Player Tokens	5	3	1	12

## 2013 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

The Token Pass game is represented by the `TokenPass` class.

```
public class TokenPass
{
    private int[] board;
    private int currentPlayer;

    /** Creates the board array to be of size playerCount and fills it with
     *  random integer values from 1 to 10, inclusive. Initializes currentPlayer to a
     *  random integer value in the range between 0 and playerCount-1, inclusive.
     *  @param playerCount the number of players
     */
    public TokenPass(int playerCount)
    { /* to be implemented in part (a) */ }

    /** Distributes the tokens from the current player's position one at a time to each player in
     *  the game. Distribution begins with the next position and continues until all the tokens
     *  have been distributed. If there are still tokens to distribute when the player at the
     *  highest position is reached, the next token will be distributed to the player at position 0.
     *  Precondition: the current player has at least one token.
     *  Postcondition: the current player has not changed.
     */
    public void distributeCurrentPlayerTokens()
    { /* to be implemented in part (b) */ }

    // There may be instance variables, constructors, and methods that are not shown.
}
```