

Begin your response to **QUESTION 3** on this page.





Figure 1

3. A wire is connected to a resistor of resistance  $R$  to form a rigid rectangular loop of width  $L$  and height  $2L$ . An external force is exerted on the loop so that the loop always moves with constant speed  $v$  in the  $+x$ -direction, as shown in Figure 1. The loop then enters Region 1 of external uniform magnetic field of magnitude  $B$  that is directed in the  $-z$ -direction. Region 1 has boundaries  $x = L$  and  $x = 2.5L$ . The loop later enters Region 2 with two external, uniform magnetic fields, each of magnitude  $B$ , that are parallel but are directed in opposite  $z$ -directions. Region 2 has boundaries  $x = 2.5L$  and  $x = 3.5L$ . Point S is the midpoint of the leading edge of the loop and is aligned with the horizontal boundary in Region 2 that separates the two magnetic fields.

**GO ON TO THE NEXT PAGE.**

Continue your response to **QUESTION 3** on this page.

- (a) On the following axes, **sketch** a graph of the magnetic flux  $\Phi$  through the rectangular loop as a function of the position  $x$  of Point S from  $x = 0$  to  $x = 4.5L$ . The  $+z$ -direction indicated in Figure 1 corresponds to  $+\Phi$ .



- (b) Consider the instant when Point S reaches  $x = 1.5L$ .

i. **Indicate** whether the current  $I_R$  that is induced in the rectangular loop when Point S reaches  $x = 1.5L$  is clockwise, counterclockwise, or zero.

\_\_\_\_\_ Clockwise      \_\_\_\_\_ Counterclockwise      \_\_\_\_\_ Zero

Briefly **justify** your answer.

**GO ON TO THE NEXT PAGE.**

Continue your response to **QUESTION 3** on this page.

ii. **Derive** an expression for  $I_R$  when Point S reaches  $x = 1.5L$ . If  $I_R = 0$ , indicate how the derived expression shows that  $I_R = 0$ . Express your answer in terms of  $R$ ,  $L$ ,  $v$ ,  $B$ , and physical constants, as appropriate.

iii. **Derive** an expression for the power  $P$  dissipated by the resistor when Point S reaches  $x = 1.5L$ . Express your answer in terms of  $R$ ,  $L$ ,  $v$ ,  $B$ , and physical constants, as appropriate.

**GO ON TO THE NEXT PAGE.**

Continue your response to **QUESTION 3** on this page.

The total energy dissipated by the resistor in the rectangular loop as Point S moves from  $x = 0$  to  $x = 4.5L$  is  $E_{\text{original}}$ .

The vertical boundary between regions 1 and 2 is now shifted to  $x = 1.5L$ . After the boundary is shifted, the rectangular loop again moves with speed  $v$  in the  $+x$ -direction, as shown in Figure 2. The total energy dissipated by the resistor as Point S moves from  $x = 0$  to  $x = 4.5L$  is  $E_{\text{new}}$ .




Figure 2

(c) **Indicate** whether  $E_{\text{new}}$  is greater than, less than, or equal to  $E_{\text{original}}$ .

\_\_\_\_\_  $E_{\text{new}} > E_{\text{original}}$       \_\_\_\_\_  $E_{\text{new}} < E_{\text{original}}$       \_\_\_\_\_  $E_{\text{new}} = E_{\text{original}}$

Briefly **justify** your answer.

**GO ON TO THE NEXT PAGE.**

Continue your response to **QUESTION 3** on this page.

The original magnetic fields are modified so that the region  $L < x < 3.5L$  contains an external uniform magnetic field of magnitude  $B$  that is directed in the  $-z$ -direction.

A new wire is connected to a resistor of resistance  $R$  to form a rigid triangular loop with base length  $L$  and height  $2L$ . An external force is exerted on the loop so that the loop always moves with speed  $v$  in the  $+x$ -direction, as shown in Figure 3. Point S represents the lower-leading corner of the loop.





Figure 3

- (d) On the following axes, **sketch** a graph of the induced current  $I_T$  in the triangular loop as Point S moves from  $x = L$  to  $x = 3L$ .



**GO ON TO THE NEXT PAGE.**