Complete Execution Traces Degrade Verdict Prediction: A Diagnostic Signal Analysis

Anonymous ACL submission

Abstract

Complete execution traces contain all information needed for verdict prediction, yet they actively degrade supervised fine-tuning (SFT) based learning. Across four code-specialized models spanning three architecture families, compact exception events close an 18–23 percentage-point gap over complete traces, reaching near-perfect accuracy where verbose traces plateau near the source-code-only baseline. A controlled gradient-masking experiment attributes the vast majority of this degradation to content quality at inference rather than training-time gradient dilution: diagnostic tokens are simply too sparse in verbose traces for the model to extract reliably. The practical consequence is striking: with exception-only input a 7B model surpasses GPT-4o by 12 points, a ranking that reverses without trace information, showing that input density dominates model scale. Format-marker removal and cross-dataset transfer indicate the learned signal reflects diagnostic patterns rather than surface shortcuts. These results establish an empirical two-tier signal hierarchy: extract exception events first; when unavailable, tail-truncated traces provide a viable fallback.

1 Introduction

Execution traces (line-by-line records of a program's runtime behavior) have emerged as a promising input modality for code language models (Liu et al., 2023; Chen et al., 2025; Ding et al., 2024b,a; Wang et al., 2025b; Ni et al., 2024). The intuition is straightforward: more execution information should help the model make better predictions. Yet for verdict prediction (classifying whether a test passes or fails), this intuition is wrong. Complete traces *actively degrade* accuracy compared to compact exception events, despite containing strictly more information.

Prior work found trace utility to be task-dependent (Wang et al., 2025b), but focused on generation-oriented tasks where output noise confounds the analysis. Verdict prediction offers a cleaner testbed: as binary classification, it isolates the learning signal from generation noise, and controlled component ablation directly measures how trace content affects SFT learning. This approach aligns with recent *ACL precedent: CRUXEval (Gu et al., 2024) uses execution prediction to probe code reasoning, and NExT (Ni et al., 2024) uses trace-augmented chain-of-thought for program repair.

We present a systematic component ablation of trace representations for verdict prediction. Using 591 problems from HumanEval (Chen et al., 2021) and Mostly Basic Python Problems–sanitized (MBPP-sanitized) (Austin et al., 2021), we evaluate four models across three architecture families and 1.5B to 13B parameters: Qwen-2.5-Coder-7B/1.5B-Instruct (Team, 2024), CodeLlama-13B-Instruct (Rozière et al., 2024), and DeepSeek-Coder-6.7B-Instruct (Guo et al., 2024).

The central result: complete traces (77–82%) barely improve over source code alone, while compact exception events achieve near-perfect accuracy ($\geq$99%) across all four models, an 18–23 percentage-point (pp) gap (§4.1). A simple regex exploiting a format marker matches this ceiling, so the interesting question is not why exceptions help but *why complete traces hurt*. Marker removal collapses the regex to near-chance while SFT retains >97%; cross-dataset transfer confirms SFT acquires diagnostic patterns beyond format matching (§4.3).

Gradient masking attributes $\leq$4% of the degradation to gradient dilution; content quality at inference accounts for the majority (§4.4). Training dynamics corroborate this: `exception_only` converges within 50 steps while `full_trace` oscillates without convergence (Appendix O). A tail-truncation budget sweep reveals a sharp performance transition near 512 tokens, coinciding with




Figure 1: Overview of the verdict prediction pipeline. Source code and a test input are executed to produce a full raw trace, from which four conditions extract different representations: `no_trace` (source code only), `full_trace` (complete line-by-line trace), VOTA (Verdict-Optimized Trace Abstraction: exception events, assertion comparisons, and loop summaries), and `exception_only` (only exception/error events). Information density decreases from `full_trace` to `exception_only`, yet accuracy follows the opposite direction (Table 1). Appendix D provides input/output examples.

the first appearance of structured execution markers (§4.5).

While exception events structurally encode verdict direction (exception present typically implies failure), the non-trivial finding is that providing strictly more information (complete traces containing all exception data) degrades performance by 18–23pp. Our contributions:

1. **Complete traces degrade SFT verdict accuracy** despite containing all diagnostic information: across four models (1.5B–13B, three families), complete traces (77–82%) remain near source-code-only levels while compact exception events close an 18–23pp gap to $\geq$99.33% (§4.1).

2. **Semantic vs. format-marker decomposition**: marker removal collapses a format-exploiting regex by 71pp while SFT drops only 2pp; cross-dataset transfer (99.4–100%) shows the learned signal generalizes beyond format markers (§4.3).

3. **A two-tier signal hierarchy and its mechanistic explanation**: exception/assertion signals ($\geq$98.53%) dominate loop compression (77–86%) by 12+pp with non-overlapping CIs, and a sharp transition at $\sim$512 tail tokens yields a practical fallback (§4.2, §4.5). Controlled gradient masking attributes $\leq$4% of the degradation to gradient dilution, assigning the majority to content quality at inference (§4.4).

2 Related Work

Execution Traces for Code Large Language Models (LLMs). TracePile (Chen et al., 2025) scaled trace-augmented training to 2.6M samples; Wang et al. (2025b) found trace utility task- and format-dependent, which we extend by showing that complete traces degrade SFT performance while compact exception events suffice. Earlier, Liu et al. (2023) pre-trained on execution prediction, SemCoder (Ding et al., 2024a) introduced monologue reasoning to link code with runtime states, and Menna et al. (2025) studied execution-aware models for code optimization. NExT (Ni et al., 2024) and ET-CoT (Eguchi and Akiba, 2025) used trace chain-of-thought for repair and execution reasoning; Armengol-Estape et al. (2025) found compact traces comparable to

full traces, and Haque et al. (2025) showed trace utility for repair diminishes with complexity, both supporting our density finding. CRUXEval (Gu et al., 2024; Xu et al., 2025) and LiveCodeBench (Jain et al., 2024) established execution reasoning benchmarks, but none decompose which trace components contribute to classification accuracy.

Verdict Prediction and Fault Localization. TRACED (Ding et al., 2024b) showed execution-aware pretraining improves vulnerability detection; CC2Vec (Hoang et al., 2020), APPT (Zhang et al., 2024), and LLM-based patch assessment (Zhou et al., 2024) developed representation learning and evaluation of code changes, extending just-in-time quality assurance (Kamei et al., 2013); verdict prediction is an instance of the test oracle problem (Barr et al., 2015; Bodicoat et al., 2025). Spectrum-based fault localization (SBFL; Jones et al., 2002; Abreu et al., 2007; Wong et al., 2014) and LLM-based fault localization (Kang et al., 2024; Qin et al., 2024; Shi et al., 2025) share our insight that anomalous execution events carry the strongest diagnostic signal, though LLM fault localizability remains fragile under semantic-preserving mutations (Haroon et al., 2026). TraceCoder (Huang et al., 2026) and InspectCoder (Wang et al., 2025d) use selective trace extraction, and LLM repair agents (Jimenez et al., 2024; Yang et al., 2024b; Xia et al., 2024; Bouzenia et al., 2025; Wang et al., 2025c) increasingly leverage execution feedback, yet which trace components carry verdict signals most efficiently remains unstudied.

Calibration and Data Selection. Neural network calibration (Guo et al., 2017), extended to LLMs (Kadavath et al., 2022; Geng et al., 2024; Liu et al., 2025), studies confidence-correctness alignment; our Expected Calibration Error (ECE) < 0.007 suggests compact inputs improve calibration. The Information Bottleneck (Tishby et al., 2000), feature selection theory (Guyon and Elisseeff, 2003), IB-guided code fine-tuning (Wang et al., 2025a), and LIMA (Zhou et al., 2023) predict that compressing task-irrelevant information improves learning; data pruning (Paul et al., 2021; Sorscher et al., 2022), curriculum learning (Bengio et al., 2009), and data-efficient code SFT (Lv et al., 2025; Shang et al., 2025) confirm this empirically, consistent with our finding that compact exceptions converge rapidly while verbose traces oscillate. Prompt compression methods (Jiang et al., 2023; Li et al., 2023) pursue a complementary goal at inference time.

3 Method

3.1 Task Definition and Diagnostic Signal Metrics

We study *verdict prediction*: given a Python function, a test input, and an optional execution trace, predict whether the test passes or fails. The model produces a single token (`pass` or `fail`), making this a binary classification task. Unlike code generation (Chen et al., 2025) or output prediction (Gu et al., 2024), verdict prediction isolates the model's ability to detect faults from its ability to simulate execution, providing cleaner ablation contrasts than generation tasks.

To quantify signal quality without circular reference to model accuracy, we define the *diagnostic token ratio* $d = n_{\text{diag}}/n_{\text{total}}$, where n_{diag} counts tokens matching exception or assertion patterns. This model-free metric correlates with accuracy at Pearson r=0.949 (p=0.014, N=5, df=3; treat as descriptive), but captures only the *explicit* diagnostic pathway; tail-truncated conditions achieve 93–98% with $d \approx 0$, indicating a second, implicit signal channel operating through terminal execution state (§4.4).

3.2 Dataset

We sampled 10 candidate solutions per problem from Qwen-2.5-Coder-7B-Instruct (temperature 0.8, top_p 0.95) for 591 problems from HumanEval (Chen et al., 2021) (164) and MBPP-sanitized (Austin et al., 2021) (427), executed each against canonical tests with `sys.settrace` to obtain line-level traces and pass/fail verdicts, yielding 5,910 pairs (67% pass, 33% fail). The dataset is split 80/20 by problem ID into 4,720 training and 1,190 test samples (majority baseline: 71.51%). The `exception_only` format collapses passing solutions into identical rows (39.45% train, 48.99% test duplicates); these duplicates arise from multiple candidate solutions per problem, with the train–test split enforced at the problem level (472 train / 119 test problems, zero crossover; Appendix P).

3.3 Trace Representations

We define seven conditions that vary the trace information available (Figure 1):

- `notrace`: Source code and test input only.

- `full_trace`: Complete line-by-line trace with variable states.
- `VOTA` (Verdict-Optimized Trace Abstraction): Exception events + assertion-point comparisons + loop compression (Appendix C).
- `exception_only`: Only exception/error events.
- `ae_only`: Only assertion-point actual/expected pairs.
- `loop_only`: Only loop compression summaries.
- `VOTA_no_ae`: VOTA without assertion-point information.

3.4 Models and Training

We evaluate four models spanning three architecture families: **Qwen-2.5-Coder-7B/1.5B-Instruct** (Team, 2024), **CodeLlama-13B-Instruct** (Rozière et al., 2024), and **DeepSeek-Coder-6.7B-Instruct** (Guo et al., 2024), covering a 1.5B–13B parameter range (8.7×). All conditions use Low-Rank Adaptation (LoRA; Hu et al., 2022) with rank=16, α=32, dropout=0.05 on all linear layers, 3 epochs, effective batch size 32, learning rate 2×10^{-4} with linear warmup/decay, max sequence length 2,048 tokens. Sequences exceeding this limit are truncated while preserving the verdict label. The primary seed is 42; seeds 123 and 456 test `exception_only` robustness (Appendix B).

3.5 Loss Ablation

To probe the contribution of gradient dilution, we introduce `full_trace_label_only`: identical full-trace input but loss computed only on the verdict token (trace positions masked). The SFTTrainer (from the TRL library) computes mean cross-entropy over label tokens, so label-only loss does not amplify the effective learning rate. However, this ablation simultaneously changes three variables: (1) which tokens receive gradient updates, (2) the implicit regularization from predicting trace tokens, and (3) the training signal distribution. The resulting improvement over standard `full_trace` provides a confounded upper bound on gradient dilution's contribution. A cleaner test (masking 99.8% of gradient updates during `exception_only` training) matches the diagnostic token ratio of full traces while preserving compact input, isolating gradient dilution from content quality (§4.4).

4 Experiments

We evaluate across two research questions: (1) Why do complete traces degrade SFT verdict accuracy despite containing all diagnostic information? (2) Which trace components carry the verdict signal, and how does their density affect learning? All experiments use N=1,190 test samples; accuracy is reported with Wilson 95% confidence intervals (CIs).[1] Pairwise comparisons use paired bootstrap resampling (B=10,000, seed=42); all differences are significant at $p<.0001$ unless noted. Under problem-level clustered bootstrap (n_{eff}=119), all cross-tier gaps remain significant ($p<.001$); 3 of 80 within-tier pairwise comparisons lose significance after Holm–Bonferroni correction.

4.1 Cross-Model Comparison

Table 1 compares four models spanning an 8.7× parameter range (1.5B–13B) and three architecture families under key conditions; single-seed entries are marked with †. Regex B5 (99.33%) exploits the `[No exception data in trace]` format marker, providing a non-learned baseline; its collapse to 28.49% under marker removal (§4.3) shows the SFT advantage is not format-driven.

Exception dominance across families. Under `exception_only`, all four models achieve ≥99.33% across all available seeds (Table 1), spanning only 0.50pp across architectures (the tightest of any condition). CodeLlama-13B seed 123 achieves 100%, indicating the 2 persistent errors (`GeneratorExit`; Appendix G) are convergence artifacts; 99.83% is a floor, not a ceiling.

Scale effects concentrate in Tier 2. Tier 1 signals are scale-robust across 1.5B–13B (8.7×): both `exception_only` and `ae_only` span ≤1.2pp. `loop_only` spans 8.65pp, with CodeLlama-13B below Qwen-1.5B, suggesting architecture matters more than parameter count for lower-density signals. In contrast, `no_trace`

[1] Problem-level partition (472 train / 119 test, zero crossover; §3.2). `exception_only` duplicates (48.99% test; Appendix P) arise from within-problem variants; deduplication yields negligible (<0.1pp) delta.

Table 1: Cross-model verdict accuracy (%, N=1,190) across four models (1.5B–13B) and three architecture families. Multi-seed entries report mean±std over 2–3 seeds; † = single seed (seed 42). Bold: best per model. Full per-seed breakdowns in Appendix E; per-class metrics in Appendix A.

Condition	Qwen-7B	Qwen-1.5B	CL-13B	DS-6.7B
exception_only	**99.83**±0.00	**99.83**±0.00	**99.89**±0.10	**99.39**±0.10
ae_only	99.64±0.49	98.83±0.36	99.08±0.00	98.53±0.30
VOTA	99.05±0.38	99.54±0.06	98.74±0.24	99.25‡
loop_only	86.05±0.52	79.54±1.42	77.40±1.54	80.31±1.65
full_trace	81.44±1.11	77.06†	79.9§	79.16†
no_trace	75.13†	72.35±4.48	76.47†	73.36†
Regex B5 (marker)		99.33		
Majority baseline		71.51		

‡DeepSeek VOTA seed 42 (84.45%) is a tokenizer-driven truncation failure (Appendix F), reported as 2-seed mean. §CodeLlama `full_trace` not available; head-2048 proxy reported. Per-seed breakdowns for all conditions in Appendix E.




Figure 2: Verdict accuracy vs. model scale. `exception_only` maintains ≥99.33% regardless of scale, while `no_trace` shows monotonic sensitivity (+4.12pp). `nomarker` (markers removed) shows no scale degradation.

scales with capacity (Figure 2) and shows the highest seed variance (σ=4.48pp).

VOTA cross-family variation. Excluding outlier seeds, VOTA achieves ≥98.57% across all four models (0.80pp range). DeepSeek seed 42 (84.45%) is a tokenizer-driven truncation failure (91.7% of samples exceed 2,048 tokens after tokenization; Appendix F), demonstrating that VOTA's longer sequences are sensitive to tokenizer efficiency: 1/4 models suffers catastrophic truncation under standard training length. `exception_only`'s compact inputs (median 150 tokens) sidestep this vulnerability entirely.

4.2 Component Ablation

Multi-seed `ae_only` ablations use Qwen-7B; `loop_only` is evaluated across three models to test Tier 2 generalization (Table 1). Table 2 decomposes VOTA on Qwen-2.5-7B and reveals a two-tier hierarchy validated across all four models and three architecture families (Table 1): Tier 1 (≥98.53%) and Tier 2 (77–86%) are separated by 12+pp with non-overlapping CIs.

Table 2: Component ablation on Qwen-2.5-7B (N=1,190). Tier 1 signals achieve near-perfect accuracy; combining them (VOTA) slightly dilutes performance. Entries marked †/§/‡ are 3-seed mean±std; unmarked entries are single seed (seed 42). Per-seed breakdowns in Appendix E. Seed σ negatively correlates with density (0.00 for exception to 0.52 for loop).

Condition	Components	Acc (%)	95% CI	Tier
ae_only	assertion-point	99.64†	[99.26, 99.87]	1
exception_only	exception events	**99.83**	[99.58, 100.00]	1
VOTA	exc+ae+loop	99.05§	[98.49, 99.50]	—
VOTA_no_ae	exc+loop	99.41	[98.90, 99.80]	—
loop_only	loop compression	86.05‡	[83.97, 87.96]	2
full_trace	complete trace	81.44±1.11	—	—
no_trace	none	75.13	[72.77, 77.48]	—
Regex (best)	exc. type regex	93.61	—	—
3-shot (Qwen-7B)	in-context learning	90.84	—	—
Zero-shot (4 models)	prompting	51.0–93.5	—	—

Tier 1 signals are individually sufficient: `exception_only` (99.83%±0.00) exceeds VOTA (99.05%±0.38) by +0.78pp (2/3 seeds p<.05, all directionally consistent), implying that combining signals introduces noise. Removing assertion points has no effect (`VOTA_no_ae` = 99.41%, single seed), indicating exception dominance. Individual exception subcomponents (type, stacktrace, message) each independently achieve ≥99.50%, indicating that the binary presence of an exception event, rather than any specific subcomponent, drives Tier 1 performance (Appendix I). The Tier 1/2 boundary is unambiguous: the lowest Tier 1 condition (`ae_only` on DeepSeek, 98.53%±0.30, 2 seeds) exceeds the highest Tier 2 (`loop_only` on Qwen-7B, 86.05%, CI [83.97, 87.96]) by 12.48 pp with non-overlapping CIs (gap statistic supports k=2 clusters, silhouette ≥0.74). Tier 2 `loop_only` lifts over `no_trace` are model-dependent: Qwen +10.92pp (7B) and +7.19pp (1.5B); DeepSeek +6.95pp; CodeLlama +0.93pp (n.s.).

Rule-based baseline comparison. The strongest non-trivial regex heuristic (B4: exception class name matching; Table 20) achieves 93.61% accuracy (F1=0.876), trailing SFT `exception_only` (99.83%, F1=0.997) by 6.22pp (McNemar p<.001). The gap concentrates on caught-exception boundary cases: regex flags all exception events as failures, while SFT learns to distinguish caught exceptions (benign,

inside `try/except`) from uncaught faults, correctly resolving 6/8 boundary samples (Appendix Q). Across all formats, SFT outperforms the best applicable regex by +3.62–23.86pp (Appendix Q).

Zero-shot and few-shot LLM baselines. Zero-shot prompting spans 51.0–93.5% across four models (42.44pp range); three-shot in-context learning on Qwen-7B (90.84%) improves only 1.76pp. SFT compresses this range to 0.50pp (99.39–99.89%), closing a 6–49pp gap with 4,720 samples (Appendix R).

Frontier model crossover. Two frontier models illustrate that SFT's advantage depends on input density: under `no_trace`, GPT-4o (84.45%) and GPT-4.1 (77.31%) outperform SFT Qwen-7B (75.13%), but under `exception_only` the ranking reverses (SFT 99.83% vs. GPT-4o 87.98%). Compact diagnostic input unlocks SFT's full advantage over general reasoning capacity.

4.3 Format Marker Ablation

The `exception_only` format includes a `[No exception data in trace]` marker in all pass-class samples (regex baseline B5 exploits this for 99.33% accuracy; Appendix Q). To quantify the marker's contribution, we retrain with all format markers removed (`nomarker` condition).

Qwen-7B 3-seed mean: 97.65% ± 0.96 (seeds 42/123/456: 96.55/98.32/98.07%), a drop of 2.18pp from `exception_only` (99.83%). Qwen-1.5B: 97.82%, drop of 2.01pp. The marker contribution (∼2pp) accounts for only ∼9% of the total exception lift over `no_trace` (24.70pp on 7B). Regex baselines illustrate this decomposition: B5 (`[No exception data]`→pass, 99.33% with markers) collapses to 28.49% without markers, showing it is entirely format-dependent. The strongest semantic regex B4 (exception class matching, 93.61%) is marker-invariant; SFT `nomarker` (97.65%) exceeds it by 4.04pp, isolating the learned semantic contribution beyond pattern matching.

Cross-dataset transfer. Bidirectional evaluation demonstrates generalization: HumanEval→MBPP `exception_only` achieves 99.41% (N=4,270) and MBPP→HumanEval achieves 100.0% (N=1,640), while `no_trace` drops to near-majority baseline in both directions (70.56% vs. 69.02% majority; 67.99% vs. 61.65%). The near-zero transfer loss for exception signals, across independently authored problem sets with no problem overlap, shows SFT learns language-level diagnostic patterns, not dataset-specific artifacts. Under marker removal, cross-dataset accuracy drops to 95.5% (−3.9pp), indicating that the majority of cross-dataset transfer relies on learned diagnostic patterns rather than format markers.

4.4 Decomposing the Full-Trace Degradation

The 18.07pp gap between `exception_only` (99.83%) and `full_trace` (81.76%) could reflect gradient dilution (diagnostic tokens are ∼1/500 of full traces, diluting gradient signal during training) or content quality (verbose input buries diagnostic signals at inference).

Controlled gradient masking. To isolate gradient dilution, we mask 99.8% of gradient updates during `exception_only` training, matching the diagnostic token ratio of full traces while preserving compact input. This yields 99.22% (mean −0.61pp from `exception_only`, 3 seeds), limiting gradient dilution to ≤4% of the 18.07pp gap (Table 3). The gradient masking bound attributes the remaining ≥96% to content quality (diagnostic signal density at inference), though forward-pass attention during masked training is an unquantified residual. Note that masking affects only the backward pass; the model still attends to all input tokens during the forward pass, so this bounds gradient dilution's contribution but does not rule out attention-based information flow as a residual confound.

Complementary evidence. Label-only loss on full traces (+4.50pp, 3 seeds) yields a confounded upper bound of ≤26% gradient contribution, consistent with the masking estimate (≤4%) but not significant under clustered bootstrap (95% CI [−0.6, +9.8]pp). Qwen-1.5B shows a similar label-only pattern (17%/83%, 3 seeds); CodeLlama and DeepSeek exhibit label-only collapse to majority baseline (28.5%), limiting this complementary analysis to the Qwen family. The architecture dependence suggests label-only training is sensitive to model capacity or optimization landscape; the gradient masking ablation provides a more robust, architecture-independent decomposition. Cross-architecture validation on two additional families is directionally consistent (sin-

Table 3: Decomposition of the full-trace degradation (Qwen-7B). Gradient masking attributes ≤4% to gradient dilution; the bound assigns the remainder to content quality, though forward-pass attention is a residual confound (§4.4). Label-only loss provides a confounded but directionally consistent complementary estimate.

Condition	Acc (%)	Δ
exception_only	99.83±0.00	—
+ grad mask (99.8%)	99.22±0.20[§]	−0.61pp
full_trace	81.76[‡]	−18.07pp
Complementary (confounded):		
full_trace + label-only loss	85.94±1.12	+4.50pp[†]

[§]Mean ± std over 3 seeds (42, 123, 456). [‡]Matched-seed baseline; 3-seed mean 81.44%±1.11 (Table 1). [†]vs. `full_trace` (81.44%±1.11); not significant under clustered bootstrap (95% CI [−0.6, +9.8]pp, n_{eff}=119).




Figure 3: Tail-truncation budget curve across four models and three architecture families (N=1,190). A sharp phase transition at 384→512 tokens (+13.2–22.0pp) coincides with the globals module dump boundary. Dashed lines: `exception_only` ceiling and `no_trace` floor.

gle seed each): DeepSeek-Coder-6.7B achieves 99.33% and CodeLlama-13B achieves 100% under 99.8% masking, both well above the full-trace range (77–82%, Table 1), supporting content quality as the dominant factor across architectures. Error analysis supports the content quality interpretation: all 217 `full_trace` errors occur where tokenizer truncation removes diagnostic markers, manifesting through mechanical truncation rather than semantic confusion.

4.5 Complementary Analyses

Trace length ablation. Varying the head-truncated trace token budget (256–no limit) on Qwen-7B yields accuracy in a narrow 77.2%–81.8% band with a non-monotonic pattern: 1024-token prefixes (77.23%) underperform 512-token prefixes (80.42%, p=.002), because mid-length prefixes retain enough irrelevant content to mislead the model while discarding diagnostic events near the trace terminus (Appendix J). Critically, removing the token budget entirely (no truncation) yields 81.76%, identical to head-2048, ruling out truncation as the explanation for the full-trace degradation. This non-monotonicity is specific to head-truncation; under tail-truncation, accuracy increases monotonically for two of three models (Table 13 in Appendix), with only DeepSeek showing a mild architecture-specific reversal at tail-1024→tail-2048 (−1.5pp).

Truncation direction and budget curve. Tail-truncation dramatically outperforms head-truncation: tail-2048 exceeds head-2048 by 15.5–22.6pp across three models (Appendix J). Figure 3 reveals a sharp phase transition at 384→512 tail tokens: all four models simultaneously jump +13.2–22.0pp, crossing from near-baseline to 93–98%. This threshold coincides with the globals module dump boundary (∼384 tokens), beyond which structured execution markers become visible (Table 13). Beyond 512 tokens, all 12 model×seed combinations converge into [93.61%, 98.24%] (Table 15). `tail_2048` captures 95–98% of `exception_only`'s accuracy; the residual 2–5pp gap shows semantic extraction still outperforms positional extraction.

Calibration. Calibration mirrors the tier hierarchy: `exception_only` achieves ECE = 0.0027 vs. 0.171 for `no_trace`, a 63× gap (Figure 4). This calibration advantage generalizes across architectures and scales: all four models (1.5B–13B) achieve ECE < 0.007 under `exception_only` (Table 17 in Appendix), indicating well-calibrated predictions rather than overfit confidence.

Error analysis. `exception_only`'s 2 errors have zero overlap with all other conditions' error sets (Jaccard = 0.000; Appendix L); per-type breakdown shows all standard exception types achieve 100% accuracy, with only `GeneratorExit` (a benign `BaseException` subclass) causing failures (Appendix H).

Length control. Padding `exception_only` to 2,048 tokens, even in a semantically loaded position (after the verdict region), yields identical accuracy (99.83%), indicating the 18–23pp gap arises from spurious patterns in verbose trace content, not sequence length.




Figure 4: Reliability diagrams for four trace conditions on Qwen-2.5-7B (N=1,190, seed=42). `exception_only` (ECE=0.0027) clusters near the diagonal, while `no_trace` (ECE=0.171) exhibits systematic overconfidence, a 63× gap.

Supplementary out-of-distribution analysis. On DebugBench (Tian et al., 2024) (N=426), the condition ranking is preserved: `exception_only` 100%, VOTA 99.77%, `no_trace` 96.71%. However, narrow margins (3.29pp headroom from `no_trace`) limit discriminative power; this supplementary analysis preserves the ranking but cannot establish effect sizes comparable to the primary dataset (Appendix M).

5 Discussion

Explicit pathway: diagnostic tokens. The diagnostic token ratio d (§2.1) correlates strongly with accuracy, and all four models achieve near-perfect accuracy under `exception_only` (Table 1); `ae_only`, a strict superset, slightly underperforms (Table 2), confirming that extra content introduces noise even within exception events.

Implicit pathway: terminal execution state. Tail-truncated traces achieve 93–98% accuracy (Table 13) despite $d \approx 0$: at ≥512 tokens, tail truncation captures terminal variable values implicitly encoding verdict direction; below 384 tokens, the globals dump consumes the budget, yielding near-`no_trace` performance.




Figure 5: Training dynamics: `exception_only` converges to 99.83% by step 150; `full_trace` with label-only loss oscillates (82–89%) without convergence.

Signal dilution in complete traces. Both pathways' signals exist in full traces but are buried under thousands of intermediate tokens. Controlled gradient masking (§4.4) attributes ≤4% of the gap to gradient dilution; the majority reflects content quality at inference, as diagnostic tokens are too sparse for reliable extraction (Figure 5).

Why SFT over regex? SFT retains 97.65% under marker removal while regex collapses to 28.49% (§4.3), and transfers across datasets with negligible loss—confirming diagnostic semantics beyond surface shortcuts.

Design implications. Exception events capture 23–27pp of the ∼25pp headroom over source code, while complete traces recover only 3–6pp—counter to the assumption that more information helps (Chen et al., 2025; Wang et al., 2025b). Tier 2 tail truncation is model-dependent (Qwen +10.9pp; CodeLlama +0.9pp; Appendix N).

6 Conclusion

Across four code-specialized models (1.5B–13B, three families), compact exception events (≥99.33%) outperform complete traces (77–82%) by 18–23pp. The question was never why exceptions help, but why complete traces hurt: gradient masking, cross-dataset transfer, and marker-removal robustness all point to diagnostic density rather than information quantity as the driver of SFT learning. For practitioners, exception extraction should be the default preprocessing; when unavailable, tail-truncated traces (≥512 tokens) recover 93–98%. That a 7B SFT model surpasses GPT-4o by 12pp under compact input suggests that, within the ≤13B code-specialized models studied, input curation matters more than model scaling for this task; whether this holds at 30B+ or for general-purpose LLMs remains open.

Limitations

Scope. All experiments use Python-only benchmarks (HumanEval, MBPP-sanitized; 591 problems with simple assert-based tests); generalization to other languages, non-assert test frameworks, and multi-file projects is unverified. Python's structured exception hierarchy makes exception events particularly informative; languages with less structured error reporting (e.g., C/C++ segmentation faults) may exhibit different signal distributions. All four models (1.5B–13B) are code-specialized; 30B+ models or general-purpose LLMs may behave differently, and whether larger models can overcome signal dilution in verbose traces is untested.

Variance and robustness. Core results are validated with 3 seeds; supplementary comparisons use single-seed runs with Wilson CI estimates for variance. VOTA's longer sequences are vulnerable to tokenizer-driven truncation: 1 of 12 model-seed combinations suffered catastrophic failure (DeepSeek seed 42: 84.45%), indicating that VOTA robustness depends on tokenizer efficiency.

Mechanistic analysis. The gradient masking experiment isolates backward-pass dilution but does not quantify forward-pass attention effects, leaving a residual confound between gradient and inference-time factors.

References

Rui Abreu, Peter Zoeteweij, and Arjan J.C. van Gemund. 2007. On the accuracy of spectrum-based fault localization. *Testing: Academic and Industrial Conference Practice and Research Techniques (MUTATION)*.

Jordi Armengol-Estape, Quentin Carbonneaux, Tianjun Zhang, Aram H. Markosyan, Volker Seeker, Chris Cummins, Melanie Kambadur, Michael F.P. O'Boyle, Sida Wang, Gabriel Synnaeve, and Hugh Leather. 2025. What i cannot execute, i do not understand: Training and evaluating LLMs on program execution traces. *arXiv preprint arXiv:2503.05703*.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Earl T. Barr, Mark Harman, Phil McMinn, Muzammil Shahbaz, and Shin Yoo. 2015. The oracle problem in software testing: A survey. *IEEE Transactions on Software Engineering*, 41(5):507–525.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. 2009. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning (ICML)*, pages 41–48.

Adam Bodicoat, Gunel Jahangirova, and Valerio Terragni. 2025. Understanding LLM-driven test oracle generation. In *Proceedings of the 2nd ACM International Conference on AI-powered Software (AIware)*.

Islem Bouzenia, Premkumar Devanbu, and Michael Pradel. 2025. RepairAgent: An autonomous, LLM-based agent for program repair. In *Proceedings of the 47th IEEE/ACM International Conference on Software Engineering (ICSE)*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Nuo Chen, Zehua Li, Keqin Bao, Junyang Lin, and Dayiheng Liu. 2025. Chain of execution supervision promotes general reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*. Introduces the TracePile dataset.

Yangruibo Ding, Jinjun Peng, Marcus J. Min, Gail Kaiser, Junfeng Yang, and Baishakhi Ray. 2024a. SemCoder: Training code language models with comprehensive semantics reasoning. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Yangruibo Ding, Ben Steenhoek, Kexin Pei, Gail Kaiser, Wei Le, and Baishakhi Ray. 2024b. Traced: Execution-aware pre-training for source code. In *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering (ICSE)*.

Koshi Eguchi and Takuya Akiba. 2025. Making llms program interpreters via execution trace chain of thought. In *ICML 2025 Workshop on Programmatic Representations for Agent Learning (PRAL)*.

Jiahui Geng, Fengyu Cai, Yuxia Wang, Heinz Koeppl, Preslav Nakov, and Iryna Gurevych. 2024. A survey of confidence estimation and calibration in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*.

Alex Gu, Baptiste Rozière, Hugh Leather, Armando Solar-Lezama, Gabriel Synnaeve, and Sida I. Wang. 2024. Cruxeval: A benchmark for code reasoning, understanding and execution. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. 2017. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, pages 1321–1330.

Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Y. Wu, Y.K. Li, Fuli Luo, Yingfei Xiong, and Wenfeng Liang. 2024. Deepseek-coder: When the large language model meets programming – the rise of code intelligence. *arXiv preprint arXiv:2401.14196*.

Isabelle Guyon and André Elisseeff. 2003. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3:1157–1182.

Mirazul Haque, Petr Babkin, Farima Farmahinifarahani, and Manuela Veloso. 2025. Towards effectively leveraging execution traces for program repair with code LLMs. *arXiv preprint arXiv:2505.04441*.

Sabaat Haroon, Ahmad Faraz Khan, Ahmad Humayun, Waris Gill, Abdul Haddi Amjad, Ali R. Butt, Mohammad Taha Khan, and Muhammad Ali Gulzar. 2026. Assessing the impact of code changes on the fault localizability of large language models. In *Proceedings of the 2026 IEEE International Conference on Software Testing, Verification and Validation (ICST)*.

Thong Hoang, Hong Jin Kang, Julia Lawall, and David Lo. 2020. CC2Vec: Distributed representations of code changes. In *Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (ICSE)*, pages 518–529.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. Lora: Low-rank adaptation of large language models. In *Proceedings of the 10th International Conference on Learning Representations (ICLR)*.

Jiangping Huang, Wenguang Ye, Weisong Sun, Jian Zhang, Mingyue Zhang, and Yang Liu. 2026. TraceCoder: A trace-driven multi-agent framework for automated debugging of LLM-generated code. In *Proceedings of the 48th IEEE/ACM International Conference on Software Engineering (ICSE)*.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2024. Livecodebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*.

Huiqiang Jiang, Qianhui Wu, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. 2023. LLMLingua: Compressing prompts for accelerated inference of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 13358–13376.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. 2024. SWE-bench: Can language models resolve real-world GitHub issues? In *Proceedings of the 12th International Conference on Learning Representations (ICLR)*.

James A. Jones, Mary Jean Harrold, and John Stasko. 2002. Visualization of test information to assist fault localization. In *Proceedings of the 24th International Conference on Software Engineering (ICSE)*.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, and 17 others. 2022. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*.

Yasutaka Kamei, Emad Shihab, Bram Adams, Ahmed E. Hassan, Audris Mockus, Anand Sinha, and Naoyasu Ubayashi. 2013. A large-scale empirical study of just-in-time quality assurance. *IEEE Transactions on Software Engineering*, 39(6):757–773.

Sungmin Kang, Gabin An, and Shin Yoo. 2024. A quantitative and qualitative evaluation of LLM-based explainable fault localization. *Proceedings of the ACM on Software Engineering*, 1(FSE):1424–1446.

Yucheng Li, Bo Dong, Frank Guerin, and Chenghua Lin. 2023. Compressing context to enhance inference efficiency of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Chenxiao Liu, Shuai Lu, Weizhu Chen, Daxin Jiang, Alexey Svyatkovskiy, Shengyu Fu, Neel Sundaresan, and Nan Duan. 2023. Code execution with pre-trained language models. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 4984–4999.

Xiaoou Liu, Tiejin Chen, Longchao Da, Chacha Chen, Zhen Lin, and Hua Wei. 2025. Uncertainty quantification and confidence calibration in large language models: A survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining*.

Weijie Lv, Xuan Xia, and Sheng-Jun Huang. 2025. Data-efficient LLM fine-tuning for code generation. In *Proceedings of the International Joint Conference on Neural Networks (IJCNN)*.

Federico Di Menna, Luca Traini, Gabriele Bavota, and Vittorio Cortellessa. 2025. Investigating execution-aware language models for code optimization. In *Proceedings of the 33rd IEEE/ACM International Conference on Program Comprehension (ICPC)*.

Ansong Ni, Miltiadis Allamanis, Arman Cohan, Yinlin Deng, Kensen Shi, Charles Sutton, and Pengcheng Yin. 2024. Next: Teaching large language models to reason about code execution. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*.

Mansheej Paul, Surya Ganguli, and Gintare Karolina Dziugaite. 2021. Deep learning on a data diet: Finding important examples early in training. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Yihao Qin, Shangwen Wang, Yiling Lou, Jinhao Dong, Kaixin Wang, Xiaoling Li, and Xiaoguang Mao. 2024. AgentFL: Scaling llm-based fault localization to project-level context. In *Proceedings of the 39th IEEE/ACM International Conference on Automated Software Engineering (ASE)*.

Baptiste Rozière, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Rémi Lacroix, Tal Remez, Jérémy Rapin, Artyom Kozhevnikov, Ivan Evtimov, Joanna Bitton, Manish Bhatt, Cristian Canton Ferrer, Aaron Grattafiori, Wenhan Xiong, Alexandre Défossez, and 7 others. 2024. Code llama: Open foundation models for code. *arXiv preprint arXiv:2308.12950*.

Zhaoyang Shang, Sibo Wei, Jianbin Guo, Rui Zhou, Lifeng Dong, and Yin Luo. 2025. The harder the better: Maintaining supervised fine-tuning generalization with less but harder data. *arXiv preprint arXiv:2510.13892*.

Xinyu Shi, Zhenhao Li, and An Ran Chen. 2025. Enhancing LLM-based fault localization with a functionality-aware retrieval-augmented generation framework. *arXiv preprint arXiv:2509.20552*.

Ben Sorscher, Robert Geirhos, Shobha Vasu, Boris Hanin, and Ari S. Morcos. 2022. Beyond neural scaling laws: Beating power law scaling via data pruning. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Claudio Spiess, David Gros, and 1 others. 2025. Calibration and correctness of language models for code. In *Proceedings of the 47th IEEE/ACM International Conference on Software Engineering (ICSE)*.

Qwen Team. 2024. Qwen2.5-coder technical report. *arXiv preprint arXiv:2409.12186*.

Runchu Tian, Yining Ye, Yujia Qin, Xin Cong, Yankai Lin, Yinxu Pan, Yesai Wu, Haotian Hui, Weichuan Liu, Zhiyuan Liu, and Maosong Sun. 2024. DebugBench: Evaluating debugging capability of large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*.

Naftali Tishby, Fernando C. Pereira, and William Bialek. 2000. The information bottleneck method. *arXiv preprint physics/0004057*.

Changsheng Wang, Xin Chen, Sijia Liu, and Ke Ding. 2025a. Breaking memorization barriers in LLM code fine-tuning via information bottleneck for improved generalization. *arXiv preprint arXiv:2510.16022*.

Jian Wang, Xiaofei Xie, Qiang Hu, Shangqing Liu, and Yi Li. 2025b. Do code semantics help? a comprehensive study on execution trace-based information for code large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2025*.

Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, Hoang Tran, Fuqiang Li, Ren Ma, Mingzhang Zheng, Bill Qian, Daniel Shao, Niklas Muennighoff, Yizhe Zhang, Binyuan Hui, and 5 others. 2025c. OpenHands: An open platform for AI software developers as generalist agents. In *Proceedings of the 13th International Conference on Learning Representations (ICLR)*.

Yunkun Wang, Yue Zhang, Guochang Li, Chen Zhi, Binhua Li, Fei Huang, Yongbin Li, and Shuiguang Deng. 2025d. InspectCoder: Dynamic analysis-enabled self repair through interactive LLM-debugger collaboration. *arXiv preprint arXiv:2510.18327*.

W. Eric Wong, Vidroha Debroy, Ruizhi Gao, and Yihao Li. 2014. The DStar method for effective software fault localization. *IEEE Transactions on Reliability*, 63:290–308.

Chunqiu Steven Xia, Yinlin Deng, Soren Dunn, and Lingming Zhang. 2024. Agentless: Demystifying LLM-based software engineering agents. *arXiv preprint arXiv:2407.01489*.

Ruiyang Xu and 1 others. 2025. CRUXEval-X: A benchmark for multilingual code reasoning, understanding and execution. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*.

Haoran Yang, Yumeng Zhang, Jiaqi Xu, Hongyuan Lu, Pheng Ann Heng, and Wai Lam. 2024a. Unveiling the generalization power of fine-tuned large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. 2024b. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Quanjun Zhang, Chunrong Fang, Weisong Sun, Yan Liu, Tieke He, Xiaodong Hao, and Zhenyu Chen. 2024. APPT: Boosting automated patch correctness prediction via fine-tuning pre-trained models. *IEEE Transactions on Software Engineering*, 50(3).

Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avi Efrat, Ping Yu, Lili Yu, Susan Zhang, Gargi Ghosh, Mike Lewis, Luke Zettlemoyer, and Omer Levy. 2023. LIMA: Less is more for alignment. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36.

Algorithm 1 VOTA Trace Extraction

Require: Raw trace T from `sys.settrace` (list of events)
Ensure: Compressed VOTA representation V

$V \leftarrow$ empty string
// Component 1: Exception summary
for each event e in T with type `exception` **do**
  Parse traceback $\rightarrow$ extract error type, message, file, line
  Append `[ERROR] type: message (file:line)` to V
end for
if no exception events found **then**
  Append `[No exception data in trace]` to V
end if
// Component 2: Assertion-point comparison
for each `assert` or `return` event e in T **do**
  Extract actual value from execution state
  Extract expected value from test assertion
  Append `[ASSERT] actual=... expected=... match=T/F` to V
end for
// Component 3: Loop compression
for each consecutive repeated line sequence S in T **do**
  if $|S| \geq 2$ iterations of same loop body **then**
    Replace S with single iteration + `[repeated ×N]`
  end if
end for
Append compressed non-exception lines to V
return V

Xin Zhou, Bowen Xu, Kisub Kim, DongGyun Han, Hung Huu Nguyen, Thanh Le-Cong, Junda He, Bach Le, and David Lo. 2024. Leveraging large language model for automatic patch correctness assessment. *IEEE Transactions on Software Engineering*, 50(11).

A Per-Class Performance Breakdown

Table 4 reports per-class precision, recall, and F1 for all experimental conditions.

B Training Details

Table 5 summarizes the training hyperparameters shared across all conditions. All experiments use the HuggingFace TRL `SFTTrainer` with LoRA (Hu et al., 2022) applied to all linear layers.

Table 6 reports per-condition training wall-clock times. Conditions with longer trace inputs (e.g., `full_trace`, VOTA) require proportionally more training time due to increased sequence lengths.

C VOTA Extraction Algorithm

Algorithm 1 describes the three-component VOTA extraction pipeline applied to a raw `sys.settrace` execution log.

D VOTA Trace Examples

We provide two representative VOTA trace examples illustrating the fail and pass cases. In the fail case, the exception event provides an unambiguous fault signal. In the pass case, the absence of an exception event combined with a matching assertion point confirms correct execution.

Fail example. A `ZeroDivisionError` triggers an `[ERROR]` event, providing a direct fault signal that is sufficient for the model to predict `fail`.

```
## Function
def divide(a, b):
    return a / b

## Test Input
divide(1, 0)

## Expected Output
inf

## VOTA Trace
[ERROR] ZeroDivisionError: division by zero

## Verdict
fail
```

Pass example. No exception is raised, and the assertion point confirms that the actual output matches the expected value.

```
## Function
def add(a, b):
    return a + b

## Test Input
add(2, 3)

## Expected Output
5

## VOTA Trace
[No exception data in trace]
[ASSERT] actual=5, expected=5
[LOOP] No loops detected.

## Verdict
pass
```

These examples illustrate the core asymmetry exploited by the `exception_only` condition: fail cases produce an explicit `[ERROR]` event, while pass cases are characterized by its absence. This binary signal (presence vs. absence of an exception) is sufficient for near-perfect verdict prediction.

E Full Experimental Results

Tables 7 and 8 report the complete experimental results across all conditions, models, and seeds.

F Tokenizer and Truncation Analysis

DeepSeek VOTA seed 42 (84.45%) is a training failure driven by tokenizer-induced truncation. Re-evaluation of the seed 42 checkpoint

Table 4: Per-class precision, recall, and F1 for all experimental conditions (seed 42). DeepSeek VOTA seed 42 is a training failure (84.45%, fail recall = 45.4%) due to tokenizer-driven truncation; seeds 123/456 achieve 99.16%/99.33%.

Condition	Model	Acc	Pass P	Pass R	Pass F1	Fail P	Fail R	Fail F1
No Trace	Qwen-2.5-7B	75.13	87.76	75.79	81.34	54.73	73.45	62.72
Full Trace	Qwen-2.5-7B	81.76	87.74	86.60	87.17	67.43	69.62	68.51
Full Trace (LO)	Qwen-2.5-7B	86.22	88.21	93.18	90.63	80.07	68.73	73.97
VOTA	Qwen-2.5-7B	99.41	100.00	99.18	99.59	97.98	100.00	98.98
Exception Only	Qwen-2.5-7B	99.83	100.00	99.76	99.88	99.41	100.00	99.71
AE Only	Qwen-2.5-7B	99.92	100.00	99.88	99.94	99.71	100.00	99.85
Loop Only	Qwen-2.5-7B	85.63	92.39	87.07	89.66	71.65	82.01	76.48
VOTA_no_ae	Qwen-2.5-7B	99.41	99.88	99.29	99.59	98.26	99.71	98.98
No Trace	DeepSeek-6.7B	73.36	81.71	80.85	81.28	53.16	54.57	53.86
Full Trace	DeepSeek-6.7B	79.16	85.70	85.10	85.40	63.20	64.30	63.70
VOTA	DeepSeek-6.7B	84.45	82.14	100.00	90.20	100.00	45.40	62.50
Exception Only	DeepSeek-6.7B	99.33	100.00	99.06	99.53	97.69	100.00	98.83
AE Only	DeepSeek-6.7B	98.74	98.40	99.90	99.10	99.70	95.90	97.70

Table 5: Training hyperparameters (shared across all conditions).

Hyperparameter	Value
LoRA rank (r)	16
LoRA alpha (α)	32
LoRA dropout	0.05
LoRA target modules	all linear layers
Epochs	3
Per-device batch size	4
Gradient accumulation steps	8
Effective batch size	32
Learning rate	2×10^{-4}
LR scheduler	linear decay
Warmup ratio	0.1
Weight decay	0.01
Max sequence length	2048 tokens
Primary seed	42
Robustness seeds	123, 456
Hardware	1× NVIDIA RTX PRO 6000 (96 GB VRAM)
Framework	HuggingFace TRL SFTTrainer

Table 6: Training wall-clock time per condition on a single NVIDIA RTX PRO 6000 (96 GB VRAM). Where multiple seeds were run, individual times are listed.

Condition	Seed(s)	Time (h)
no_trace	42	∼0.5
full_trace	42	∼2.2
label_only	42	∼2.2
VOTA	42	∼2.3
exception_only	42	∼2.1
exception_only	123	∼2.1
exception_only	456	∼1.3
ae_only	42	∼1.8
loop_only	42	∼2.1
VOTA_no_ae	42	∼1.8

with the standard max_length=2048 yields 16% accuracy, consistent with complete model collapse rather than marginal degradation. The previously reported 84.45% was obtained with max_length=16384, which partially bypasses tokenizer truncation. Seeds 123 and 456, evaluated under identical conditions, achieve 99.16% and 99.33% respectively. The DeepSeek tokenizer averages 2,626 tokens per VOTA sample versus 1,929 for Qwen, causing 91.7% of DeepSeek VOTA training samples to exceed the 2,048-token context window. The training framework preserves the verdict label but truncates trace content, so the model trains with incomplete diagnostic information for the majority of samples. Seeds 123 and 456 (99.16% and 99.33%) demonstrate that DeepSeek can learn VOTA when LoRA initialization avoids the truncation-sensitive basin; the 2-seed mean (99.25%±0.12) matches the cross-model VOTA range (98.74–99.54%).

A post-hoc group analysis on seed 42 provides directional evidence: partitioning test samples by whether their training-set counterparts exceeded the context window, intact samples (N=99) achieve 100% accuracy while truncated samples (N=1,091) achieve 83.04% (95% CI [80.75%, 85.24%]; Fisher exact $p<.001$), with all 185 errors concentrated in the fail class (fail recall = 31.23%). Per-class analysis (Table 4) shows that seed 42 achieves 100% fail precision but only 45.43% fail recall, systematically defaulting to `pass`.

Seed robustness is consistent across models: Qwen `exception_only` produces identical 99.83% across all three seeds (σ=0), and DeepSeek achieves 99.39%±0.10 (seeds 42/456: 99.33%, seed 123: 99.50%). Because `exception_only` test inputs contain 48.99% duplicates (607 unique of 1,190; §3.2), CIs assume

Table 7: Full results for Qwen-2.5-Coder-7B across all conditions and seeds. Conditions with a single seed report no variance. `exception_only` achieves 99.83% across all three seeds (σ=0). `ae_only` achieves 99.64% mean ($\pm$0.49; seed 123 at 99.08% is the outlier).

Condition	S42	S123	S456	Mean $\pm$ Std
exception_only	99.83	99.83	99.83	99.83 $\pm$ 0.00
ae_only	99.92	99.08	99.92	99.64 $\pm$ 0.49
VOTA	99.41	98.66	99.08	99.05 $\pm$ 0.38
VOTA_no_ae	99.41	—	—	—
label_only	86.22	86.89	84.70	85.94 $\pm$ 1.12
loop_only	85.63	85.88	86.64	86.05 $\pm$ 0.52
full_trace	81.76	80.20	82.35	81.44 $\pm$ 1.11
no_trace	75.13	—	—	—

Table 8: Full results for DeepSeek-Coder-6.7B across all conditions and seeds. `exception_only` is consistent across seeds: 99.33/99.50/99.33 (σ=0.10pp).

Condition	Seed	Accuracy	Notes
exception_only	42	99.33	epoch 1: 99.83
exception_only	456	99.33	CI [98.82, 99.75]
exception_only	123	99.50	
VOTA	42	84.45	training failure; fail recall = 45.4%
VOTA	123	99.16	
VOTA	456	99.33	
no_trace	42	73.36	
full_trace	42	79.16	CI [76.80, 81.30]

n=1,190 independent trials; under deduplication (n=607), Qwen's accuracy is 99.67% (Wilson CI [98.81, 99.91]).

G Persistent Error Analysis

The `exception_only` condition with Qwen-2.5-Coder-7B misclassifies exactly 2 out of 1,190 test samples across all three seeds (42, 123, 456), with 100% overlap across seeds. Both samples (IDs 901 and 905) share the following characteristics:

- **Function:** `check_dict_case` (HumanEval/95), a function that checks whether all dictionary keys are uniformly upper-case or lower-case strings.
- **Ground-truth label:** `pass`.
- **Predicted label:** `fail` (false negative).
- **Cross-seed consistency:** Both samples are misclassified identically by all three seeds, indicating a systematic rather than stochastic error.

Manual inspection reveals the root cause: `check_dict_case` uses `all()` over a generator expression, and Python's `all()` short-circuits on the first `True` value, raising `GeneratorExit` to terminate the generator. Because `GeneratorExit` is a `BaseException` subclass, the tracer records it as seven `[ERROR] GeneratorExit` lines, even though the function executes correctly and the test passes. The model observes these spurious error markers and reasonably but incorrectly predicts `fail`. This is not a model failure but a representation ambiguity: the `exception_only` format cannot distinguish genuine exceptions from benign `BaseException` subclasses triggered by Python's iterator protocol.

Most configurations converge to these same 2 errors: Qwen-1.5B, Qwen-7B (3 seeds), CodeLlama-13B (seeds 42/456), and DeepSeek-6.7B (seeds 42/456) all produce error set $\{901, 905\}$. However, CodeLlama-13B seed 123 achieves 100% accuracy (0/1190 errors), correctly classifying both samples. This demonstrates that 99.83% is a near-perfect *floor* (the convergence attractor for most LoRA initializations) rather than a hard data ceiling: the representation supports perfect accuracy, but most initializations converge to the same 2-error basin. The practical implication is that these errors are high-probability convergence artifacts addressable through seed selection or ensemble methods, not fundamental limitations of the exception-based representation.

H Exception Type Accuracy Breakdown

Table 9 reports `exception_only` accuracy stratified by exception type on Qwen-2.5-7B (seed=42, N=1,190). All standard exception types (`TypeError`, `ValueError`, `IndexError`, etc.) achieve 100% accuracy. The only misclassifications arise from `GeneratorExit`, a `BaseException` subclass that is not an `Exception`. It is raised by Python's iterator protocol during generator short-circuiting, not by actual program errors.

This is consistent with the model having learned a clean decision boundary: any true `Exception` subclass in the trace implies failure. The `GeneratorExit` case represents a semantic ambiguity in the trace format rather than a model failure, as discussed in §G.

Table 9: Exception type accuracy breakdown for `exception_only` (Qwen-7B, seed=42). All true error types achieve 100%. The only failures come from `GeneratorExit` (a `BaseException` subclass, not an `Exception`), which appears in 2 passing samples.

Exception Type	Samples	Accuracy
TypeError	96	100%
ValueError	62	100%
IndexError	41	100%
KeyError	28	100%
AttributeError	19	100%
AssertionError	15	100%
RecursionError	12	100%
Other Exception	66	100%
GeneratorExit (BaseException)	2	0%
No exception (pass class)	849	100%

Table 10: Exception subcomponent ablation (Qwen-2.5-7B, seed 42, N=1,190). All three subcomponents independently achieve ≥99.50%. †Retains `[ERROR]` format marker; ‡no format markers, bare exception class name only.

Condition	Acc (%)	Fail R	Pass R
exc_type_only†	**100.00**	100.00	100.00
exc_stacktrace_only†	99.83	100.00	99.76
exc_message_only‡	99.50	100.00	99.29
exception_only (ref.)	99.83	100.00	99.76

Table 11: Trace length and truncation direction ablation on Qwen-2.5-7B (N=1,190, seed=42). Head = standard left-truncation (retain first k tokens); Tail = retain last k tokens. Per-condition bootstrap 95% CIs (B=10,000).

Direction	Max Tokens	Acc (%)	95% CI
Head	256	78.82	[76.4, 81.0]
Head	512	80.42	[78.2, 82.6]
Head	1024	77.23	[74.9, 79.6]
Head	no_limit (∞)	81.76	[79.7, 83.9]
Tail	256	77.48	—
Tail	512	93.61	—
Tail	1024	96.47	—
Tail	2048	97.31	—

Table 12: Pairwise paired bootstrap comparisons for trace length ablation (B=10,000, seed=42). Δ = accuracy difference between the two conditions (first − second in the budget group; condition − baseline in the other groups). **p<.01; ***p<.001.

	Comparison	Δ (pp)	95% CI	p-value
Budget	512 vs. 256	+1.60	[−0.34, +3.53]	0.117
	1024 vs. 512	−3.19	[−5.29, −1.09]	0.002**
	no_limit vs. 1024	+4.54	[+2.52, +6.55]	<0.001***
	no_limit vs. 256	+2.94	[+0.84, +5.04]	0.006**
vs. no_trace	256 − no_trace	+3.70	[+1.43, +6.05]	0.002**
	512 − no_trace	+5.29	[+3.03, +7.56]	<0.001***
	1024 − no_trace	+2.10	[−0.17, +4.37]	0.078
	no_limit − no_trace	+6.64	[+4.37, +8.99]	<0.001***
vs. exc.	256 − exc_only	−21.01	[−23.45, −18.74]	<0.001***
	512 − exc_only	−19.41	[−21.76, −17.14]	<0.001***
	1024 − exc_only	−22.61	[−25.04, −20.25]	<0.001***
	no_limit − exc_only	−18.07	[−20.34, −15.88]	<0.001***

I Exception Subcomponent Ablation

To test whether verdict prediction depends on a specific exception subcomponent or merely the binary presence of an exception event, we train Qwen-2.5-7B on three subcomponent-only conditions (seed 42, N=1,190).

All three subcomponents independently achieve ≥99.50% with 100% fail recall (Table 10), showing that no single subcomponent is necessary for Tier 1 performance.

Format marker confound. `exc_type_only` and `exc_stacktrace_only` retain the `[ERROR]` prefix marker present in the full `exception_only` format; `exc_message_only` contains only the bare exception class name and message text without any format markers. Because the marker alone is sufficient for near-perfect regex accuracy (B5: 99.33%; §4.3), `exc_type_only` (100.00%) and `exc_stacktrace_only` (99.83%) are confounded with marker-based classification; we therefore do not make hierarchy claims among subcomponents. `exc_message_only` (99.50%) provides a clean test: without any format markers, it achieves accuracy comparable to the full `exception_only` condition (99.83%), complementing the dedicated marker-removal ablation (`nomarker`: 97.65%; §4.3) as additional evidence that the model learns semantic exception patterns rather than format shortcuts.

J Trace Length Ablation

To test whether the `full_trace` performance gap is caused by input truncation at training time, we vary the maximum trace token budget on Qwen-2.5-7B (seed=42) while keeping all other hyperparameters fixed.

As shown in Table 11 and Figure 3, all four trace length conditions fall within a 5pp range (77.2%–81.8%). To quantify the reliability of the observed differences, Table 12 reports paired bootstrap comparisons (B=10,000, seed=42) across all condition pairs.

Non-monotonic pattern (head-truncation). Under head-truncation (retaining trace prefixes), the trend is non-monotonic: 512 tokens (80.42%) slightly outperforms 256 tokens (78.82%), but doubling to 1024 tokens *decreases* accuracy to 77.23%, a statistically significant 3.19pp drop (p=.002, 95% CI [−5.29, −1.09]). The no-limit condition (81.76%) recovers and significantly exceeds 1024 tokens (p<.001), but 1024 tokens is not significantly better than `no_trace` (75.13%; Δ=+2.10pp, p=.078, 95% CI [−0.17, +4.37]). This non-monotonicity is specific to head-truncation: the 1024-token prefix retains enough irrelevant content to mislead the model while discarding diagnostic events that appear near the trace terminus. Under tail-truncation, accuracy increases monotonically for Qwen-7B and Qwen-1.5B (Table 13); only DeepSeek-6.7B shows a mild −1.5pp decrease at tail-1024→tail-2048, attributable to architecture-specific long-context sensitivity rather than a systematic mid-length pathology.

Comparison to baselines. All four trace budget conditions significantly exceed `no_trace` except 1024 tokens (p=.078), indicating that raw trace content provides some signal but unreliably so. The gap to `exception_only` (99.83%) is massive for every budget condition (18–23pp, all p<.001), underscoring that even unlimited raw traces cannot substitute for targeted signal extraction. The best full-trace condition (no_limit, 81.76%) still lags `exception_only` by 18.07pp (95% CI [−20.34, −15.88]).

Interpretation. These results rule out input truncation as the primary explanation for the full-trace performance gap: even with unlimited tokens, the model cannot extract the diagnostic signal that VOTA's targeted compression provides. The non-monotonic dip at 1024 tokens is consistent with a "worst-of-both-worlds" regime where the model receives enough noisy context to dilute the signal but not enough to compensate through broader coverage. The result reinforces the information density interpretation (§4.4): the gap between full traces and VOTA is driven by the *content* of the trace (irrelevant lines diluting the diagnostic signal), not its *length*. In contrast, VOTA's compressed representation concentrates the diagnostic signal into fewer tokens, making it sensitive to truncation when those tokens are removed (§4.1).

Table 13: Cross-model tail-truncation budget curve (N=1,190). All four models exhibit a transition between tail-384 and tail-512 (+11–22pp). ↓: non-monotonic decrease. †CodeLlama tail-384/512/1024 trained with label-only loss to address tokenizer-driven gradient dilution (§F); tail-1024 reports best-epoch accuracy (epoch 1). CodeLlama tail entries are not directly comparable to other models (which use full-sequence loss). ‡CodeLlama tail-2048 outlier (41.8%): LoRA long-sequence instability under label-only loss; excluded from cross-model analysis.

Model	tail-256	tail-384	tail-512	tail-1024	tail-2048	exc_only
Qwen-7B (7B)	77.5	79.9	93.6	96.5	97.3	99.83
DeepSeek (6.7B)	76.4	80.7	93.9	96.5	95.0↓	99.33
CodeLlama (13B)	77.9	82.7†	98.2†	98.2†	41.8‡	99.89
Qwen-1.5B (1.5B)	72.6	73.6	95.6	96.6	97.9	99.83

Truncation direction. Tail-truncation (retaining the last k tokens) dramatically outperforms head-truncation: `tail_2048` achieves 97.31% vs. `head_2048` (no_limit) at 81.76%, a 15.55pp improvement. Even `tail_512` (93.61%) exceeds every head-truncation condition by over 11pp.

However, `tail_256` (77.48%) performs at the `no_trace` baseline level (75.13%), indicating that the diagnostic signal does not reside in the very last trace lines. The critical jump occurs between 256 and 512 tail tokens (+16.13pp), localizing the signal window to approximately 256–512 tokens from the trace terminus. This is consistent with the trace format: the globals module dump consumes the first ∼384 tail tokens (pure noise), so structured execution markers (`[Line X]` variable values) only become visible when the budget exceeds this threshold.

The 18.07pp gap from `full_trace` to `exception_only` decomposes as: 86% positional concentration (recovered by tail-truncation at 2048 tokens) and 14% residual content noise (the 2.52pp gap from `tail_2048` to `exception_only` that persists regardless of truncation direction). The fact that `exception_only` (99.83%) still outperforms `tail_2048` (97.31%) indicates that semantic extraction (identifying the exception type and message) is superior to positional extraction (keeping a fixed window), because the model need not filter out non-diagnostic lines that happen to fall within the window.

Cross-model budget curve. Table 13 extends the tail-truncation analysis to a full budget sweep across four models spanning three architecture families and an 8.7× parameter range.

Table 14: Cross-model truncation direction comparison (N=1,190). Head-truncation retains the first 2,048 tokens; tail-truncation retains the last 2,048. All four models' head-2048 accuracies converge into a narrow 75.3–81.8% band (6.5pp), comparable to the tail-256 signal-poor band (72.6–77.9%, 5.3pp). †CodeLlama tail-2048 pending retraining (§F).

Model	head-2048 (%)	tail-2048 (%)	Gap (pp)
Qwen-1.5B	75.3	97.9	+22.6
DeepSeek-6.7B	78.7	95.0	+16.3
CodeLlama-13B	79.9	—†	—†
Qwen-7B	81.8	97.3	+15.5

Table 15: Cross-seed convergence at the tail-512 truncation point (N=1,190 per seed). All 12 model×seed combinations fall within a 4.63pp band [93.61%, 98.24%]. CodeLlama-13B achieves identical accuracy across all three seeds (σ=0).

Model	S42	S123	S456	Mean	σ
Qwen-7B (7B)	93.61	96.00	97.65	95.75	2.05
DeepSeek (6.7B)	93.95	95.04	96.10	95.03	1.08
Qwen-1.5B (1.5B)	95.63	97.65	96.72	96.67	1.01
CodeLlama (13B)	98.24	98.24	98.24	**98.24**	**0.00**
Cross-model band				[93.61, 98.24] = 4.63pp	

Four patterns emerge from the budget curve. *Phase transition between 384 and 512 tokens*: the tail-384 column reveals that the transition is not instantaneous at 256→512 but localized between 384 and 512 tokens. At tail-384, all four models remain near baseline (73.6–80.7%), gaining only +1.0–4.8pp over tail-256. The steep jump occurs at 384→512: +13.7pp (Qwen-7B), +13.2pp (DeepSeek), +15.5pp (CodeLlama), +22.0pp (Qwen-1.5B), crossing from near-baseline to near-ceiling. This localizes the critical threshold to ∼400–500 tokens: below ∼384 tokens, the entire token budget is consumed by globals module dumps (pure noise); above ∼512, at least one `[Line X]` execution event marker becomes visible, regardless of model capacity or architecture.

Convergence at tail-512+: once the sharp performance jump is crossed, accuracy converges across all models into a 93.6–98.2% band at tail-512 (seed 42). Multi-seed validation shows robustness: across all 12 model×seed combinations at tail-512 (Table 15), all accuracies fall within [93.61%, 98.24%], a 4.63pp band that compresses the signal-poor tail-256 spread (6.3pp) by 27%. CodeLlama-13B shows perfect per-model convergence at tail-512: all three seeds achieve 98.24% (σ=0), consistent with the 13B scale and label-only loss providing a stronger optimization signal in the signal-rich regime (Table 15). However, CodeLlama's higher tail-512 accuracy may partly reflect label-only loss rather than model capacity; direct comparison with other models (which use full-sequence loss) is confounded by this training difference.

At tail-1024, four models reach 96.5–98.2% (CodeLlama 98.2% under label-only loss, three others 96.5–96.6%). Scale and architecture differences that dominate the signal-poor regime (tail-256 range: 72.6–77.9%, 5.3pp) compress dramatically in the signal-rich regime.

Signal-poor convergence band: head-2048 accuracies across all four models also converge into a narrow 75.3–81.8% band (6.5pp; Table 14), comparable in width to the tail-256 band (72.6–77.9%, 5.3pp). When the diagnostic signal is absent (head-truncation discards trace terminus) or unreachable (tail-256 is too short), models of different scale and architecture collapse to similar performance, suggesting a shared floor determined by code comprehension rather than trace processing.

Scale behavior inversion: in the signal-poor regime (tail-256), smaller models perform worse (Qwen-1.5B 72.6% vs. Qwen-7B 77.5%, −4.9pp), mirroring the `no_trace` scale pattern. In the signal-rich regime (tail-512+), this reverses: Qwen-1.5B matches or exceeds Qwen-7B (95.6% vs. 93.6% at tail-512; 97.9% vs. 97.3% at tail-2048), consistent with sufficient trace signal eliminating the capacity advantage.

Non-monotonicity at long sequences: two models show accuracy decreases beyond tail-1024. DeepSeek-6.7B drops −1.5pp from tail-1024 (96.5%) to tail-2048 (95.0%), consistent with its known long-context sensitivity (§O). CodeLlama-13B exhibits a more severe collapse: tail-2048 under label-only loss drops to 41.8% (vs. tail-1024 = 98.2%), which we attribute to LoRA long-sequence instability under the label-only loss regime; this outlier is excluded from cross-model tail-2048 analysis. Qwen-7B and Qwen-1.5B increase monotonically across all budgets.

Table 14 shows the truncation direction effect: among the three models with complete data, tail-2048 outperforms head-2048 by 15.5–22.6pp. The gap is largest for Qwen-1.5B (+22.6pp), indicating that smaller models benefit most from positional proximity to the diagnostic signal, as they lack the

Table 16: Calibration metrics on Qwen-2.5-7B (N=1,190, seed=42). ECE = expected calibration error; Brier = Brier score. Lower is better for both.

Condition	ECE ↓	Brier ↓
ae_only	**0.0004**	**0.0008**
exception_only	0.0027	0.0013
VOTA	0.0054	0.005
full_trace	0.096	0.144
no_trace	0.171	0.197

capacity to locate it within longer, noisier prefixes.

K Calibration Analysis

Beyond accuracy, we evaluate whether trace conditions affect prediction calibration, motivated by recent findings that code LLM confidence is often poorly calibrated (Spiess et al., 2025).

Table 16 shows that calibration quality mirrors the Tier 1/2 hierarchy. Tier 1 conditions (`ae_only`: ECE=0.0004; `exception_only`: ECE=0.0027) produce near-perfectly calibrated predictions, while `full_trace` (ECE=0.096) and `no_trace` (ECE=0.171) exhibit substantial miscalibration. VOTA (ECE=0.0054) is well-calibrated but slightly worse than either Tier 1 component alone, reinforcing the pattern that combining trace signals dilutes rather than improves the prediction signal.

The Brier scores tell a consistent story: `ae_only` (0.0008) and `exception_only` (0.0013) achieve near-zero scores, while `no_trace` (0.197) indicates substantial miscalibration.

Cross-model calibration. Table 17 extends the calibration analysis to four models (1.5B–13B) under `exception_only`. All four models achieve ECE < 0.007 and Brier < 0.007, indicating that calibration quality generalizes across architectures and scales. CodeLlama-13B achieves the lowest ECE (0.0020) and MCE (0.0411), while DeepSeek-6.7B shows the highest ECE (0.0064) and Brier (0.0061), consistent with its higher error rate (8 errors vs. 2 for Qwen/CodeLlama).

L Error Overlap Analysis

We analyze the overlap between error sets of different conditions to determine whether they fail on the same samples (Figure 6).

`exception_only`'s 2 errors (samples 901 and 905) have zero intersection with the error

Table 17: Cross-model calibration for `exception_only` (N=1,190, seed=42). ECE = expected calibration error; Brier = Brier score; MCE = maximum calibration error. All four models (1.5B–13B) achieve ECE < 0.007.

Model	ECE ↓	Brier ↓	MCE ↓
Qwen-1.5B	**0.0020**	**0.0013**	—
CodeLlama-13B	**0.0020**	**0.0013**	**0.0411**
Qwen-7B	0.0027	**0.0013**	0.8355
DeepSeek-6.7B	0.0064	0.0061	0.7756




Figure 6: Jaccard similarity between error sets of different conditions (Qwen-7B, seed=42, N=1,190). `exception_only` (exc_only) has zero overlap with all other conditions, indicating it operates on an independent signal dimension.

sets of all other conditions (Jaccard = 0.000 in all pairwise comparisons). This orthogonality arises because `exception_only` errors are caused by `GeneratorExit` false positives (pass samples misclassified as fail due to benign `BaseException` events), while errors from other conditions are predominantly fail samples misclassified as pass due to insufficient signal.

Among non-exception conditions, error sets exhibit hierarchical containment: `ae_only` ⊂ VOTA ⊂ `loop_only` ⊂ `no_trace`, with pairwise Jaccard indices increasing with signal overlap. `loop_only` and `full_trace` share the highest overlap (Jaccard ∼0.65), reflecting their shared reliance on behavioral patterns rather than explicit fault indicators.

This analysis indicates that `exception_only` operates on an independent signal dimension: its errors are representation ambiguities (iterator protocol artifacts) rather than information deficits, explaining why combining it with other signals cannot eliminate these specific errors.

M Cross-Dataset Generalization: DebugBench

To test whether exception-based verdict prediction generalizes beyond LLM-generated solutions, we evaluate on DebugBench (Tian et al., 2024), a

Table 18: Generalization to DebugBench (N=426, Qwen-2.5-7B, seed=42). Wilson 95% CIs. The component ranking (exception_only $\geq$ VOTA $>$ no_trace) is preserved, and exception_only achieves perfect accuracy.

Condition	Acc (%)	95% CI
exception_only	**100.00**	[99.14, 100.00]
VOTA	99.77	[99.30, 100.00]
no_trace	96.71	[94.80, 98.40]
Majority baseline	51.41	—

dataset of human-written programs with synthetically injected bugs (single-point mutations such as operator replacement, variable misuse, and missing statements). After filtering for executable Python samples with valid traces, we retain 426 samples with a near-balanced class distribution (majority baseline: 51.4%).

Table 18 shows that the component ranking from the main experiments is preserved: `exception_only` (100.00%) $\geq$ VOTA (99.77%) $>$ `no_trace` (96.71%). The `exception_only` condition achieves perfect accuracy, showing that the exception-based representation generalizes to a different fault distribution without degradation.

The absolute margins are much narrower than on the main dataset: the `no_trace` baseline already achieves 96.71% (compared to 75.13% on HumanEval+MBPP), leaving only 3.29pp of headroom for trace-based improvement. This ceiling effect reflects a fundamental difference in fault characteristics: DebugBench bugs are synthetically injected single-point mutations, which produce code that is structurally dissimilar from the original correct solution; a model can often identify the fault from source code alone. In contrast, the HumanEval+MBPP solutions are LLM-generated, producing natural errors (logic mistakes, edge-case failures) where the faulty and correct solutions may be structurally similar, making code-only verdict prediction substantially harder.

These results support exception-based verdict prediction as a generalizable approach: the method does not degrade on an out-of-distribution dataset, and the exception dominance ranking (exception_only $\geq$ VOTA $>$ no_trace) is consistent across both datasets. However, the narrow DebugBench margins are insufficient to independently validate trace importance. The 24.70pp trace lift on the main dataset (no_trace 75.13% $\rightarrow$ exception_only 99.83%) remains the primary evidence for the value of exception-based trace signals.

N Cross-Model Robustness Analysis

The cross-model gap pattern (Table 1) suggests a design principle: *trace representations should match the model capability floor, not the ceiling.* Exception events are consistently the most effective component on both models, and their structural simplicity (a fixed-format error message) ensures that the relative advantage over richer representations holds across all seeds. All three DeepSeek `exception_only` seeds achieve $\geq$99.33% (99.33/99.50/99.33, σ=0.10pp), matching Qwen and CodeLlama at $\geq$99.83%. VOTA achieves $\geq$98.57% across all models when excluding outlier seeds (cross-model range: 0.80pp), but DeepSeek VOTA exhibits seed-dependent instability: seed 42 (84.45%) is a training failure due to tokenizer-induced truncation (91.7% of training samples affected), while seeds 123/456 (99.16%/99.33%) match cross-model performance. This VOTA instability is confounded by tokenizer efficiency and base model differences (Yang et al., 2024a). Our `exception_only` design sidesteps the truncation confound entirely: inputs have a median of 150 tokens (mean 398), well below the 2,048-token context window, so no training samples are truncated on either model. The resulting 0.50pp cross-model gap (Table 1) is therefore a clean measure of model capability differences, making the "capability floor" principle directly testable. The practical implication is that trace-based systems should default to the simplest sufficient signal.

O Training Dynamics and Loss Decoupling

The DeepSeek `exception_only` results are consistent across all three seeds (99.33/99.50/99.33, σ=0.10pp), matching Qwen's cross-seed stability. Epoch-level analysis shows mild degradation in seed 42: accuracy peaks at 99.83% after epoch 1 but settles at 99.33% by epoch 3 ($-$0.50pp), while seed 456 shows no degradation (99.33% at both epochs). Early stopping may yield marginal gains, but the epoch effect is small ($\leq$0.5pp). The practical recommendation: for deployment, use task-specific metrics (accuracy, fail recall) for checkpoint and

seed selection rather than training loss, and train multiple seeds to select the best.

The contrast with VOTA is instructive: DeepSeek VOTA seed 42 accuracy monotonically increases from 78.15% to 84.45% across epochs, consistent with a performance limit from high trace truncation (91.7% of samples; §F). Seeds 123/456, which avoid the truncation-sensitive initialization basin, achieve 99.16%/99.33%, indicating that the deficit is seed-specific rather than a fundamental model limitation.

P Deduplication Statistics

Table 19 reports the duplication rates across trace formats. Because multiple passing solutions to the same problem produce identical (input, output) pairs in the `exception_only` format (correct executions raise no exceptions, so the trace content is the same regardless of the solution's internal logic), the dataset contains duplicate rows. Train–test input overlap is zero (split by problem ID), so no information leakage occurs. The high duplication in `exception_only` does not affect our experimental conclusions: after deduplication the training set still contains 2,858 unique samples and the test set 607, providing sufficient coverage for the 591-problem benchmark.

Problem-level partitioning and sensitivity analysis. Data is partitioned at the problem level: 472 training problems and 119 test problems, with zero crossover. Duplicates arise from multiple candidate solutions per problem (up to 10 solutions each), not from cross-problem overlap. To verify that deduplication does not alter any finding, we ran a sensitivity analysis across all 19 experimental conditions (7 trace formats $\times$ 4 models, minus conditions not run): deduplication produces a negligible ($<$0.1pp) accuracy delta in every case. This shows that duplicate samples neither inflate nor deflate accuracy, because duplicates share the same ground-truth label and the model's prediction is deterministic at inference time. Duplicates arise because the `exception_only` format collapses passing solutions (which share identical "no exception" output) into identical rows; the redundancy is a property of the format's compactness for pass-class samples. The `exception_only` test set contains 48.99% such duplicates; all confidence intervals treat samples as independent Bernoulli trials.

Table 19: Deduplication statistics. The `exception_only` format collapses multiple passing solutions into identical rows because correct executions produce no exception events. Train–test input overlap is 0 (no leakage).

Split	Total	Unique	Dup. rate
exception_only train	4,720	2,858	39.45%
exception_only test	1,190	607	48.99%
raw_traces (full)	5,910	5,803	1.81%

Table 20: Regex baseline accuracy (N=1,190). B4 is the strongest semantic baseline (6.22pp below SFT `exception_only`, McNemar $p<.001$). B6 uses an error count threshold. ‡B5 exploits a data formatting artifact: the `[No exception data in trace]` marker is deterministically present in all pass samples, making this a format-level shortcut rather than a genuine exception-based heuristic.

Baseline	Method	Acc (%)
B1: `[ERROR]` presence	string match	93.45
B2: Traceback presence	string match	71.51
B3: Any keyword	union of B1+B2+Exception	93.45
B4: Exception type regex	regex on exception class names	**93.61**
B5: Format marker	`[No exception data]` $\rightarrow$ pass	99.33‡
B6: Error count $\geq$2	count threshold	92.02
VOTA format regex	best regex on VOTA traces	75.55
full_trace format regex	best regex on full traces	77.39

Q Regex Baseline Analysis

To establish a non-learning upper bound, we evaluate six regex-based baselines on the `exception_only` test set (N=1,190) and two format-specific baselines on VOTA and `full_trace` inputs.

The strongest legitimate baseline (B4, 93.61%) applies regex pattern-matching on Python exception class names (e.g., `ValueError`, `TypeError`). Its errors concentrate on 8 boundary samples where a `ValueError` is raised inside a `try/except` block and caught; the program passes despite an exception occurring in the trace. SFT `exception_only` correctly classifies 6 of these 8 samples, indicating that the model learns the semantic distinction between caught (benign) and uncaught (fault-indicating) exceptions. B5 (99.33%) achieves near-SFT accuracy but relies on the deterministic presence of a format marker in pass-class traces, which is an artifact of the trace preprocessing pipeline rather than a generalizable signal; McNemar test vs. SFT yields p=.041, indicating a statistically significant difference.

Table 21: SFT vs. best regex baseline by trace format (N=1,190). Regex baselines: majority class for `no_trace`, keyword matching for `full_trace`, pattern matching for VOTA, exception type regex (B4) for `exception_only`.

Format	SFT (%)	Regex (%)	Δ (pp)
exception_only	99.83	93.61	+6.22
VOTA	99.41	75.55	+23.86
full_trace	81.76	77.39	+4.37
no_trace	75.13	71.51	+3.62

Table 22: Zero-shot vs. SFT `exception_only` across four models (N=1,190). Zero-shot accuracy is uncorrelated with model size; SFT normalizes cross-architecture variance from 42.44pp to 0.50pp.

Model	Size	Zero-shot (%)	SFT (%)	Δ (pp)
Qwen-1.5B	1.5B	93.45	99.83	+6.38
DeepSeek-6.7B	6.7B	90.59	99.39	+8.80
Qwen-7B	7B	89.08	99.83	+10.75
CodeLlama-13B	13B	51.01	99.89	+48.88
Range	—	42.44pp	0.50pp	—

Cross-format comparison. Table 21 compares SFT and the best applicable regex baseline for each trace format. The SFT advantage increases with format complexity: `no_trace` (+3.62pp over majority baseline) < `full_trace` (+4.37pp) < `exception_only` (+6.22pp) ≪ VOTA (+23.86pp). The VOTA gap is largest because its structured multi-component format carries semantic content that regex cannot parse, while `exception_only`'s simpler format allows regex to capture most of the signal.

R Cross-Model Zero-Shot Comparison

Table 22 compares zero-shot and SFT `exception_only` accuracy across four models. Zero-shot performance does not correlate with model size: the smallest model (Qwen-1.5B, 93.45%) outperforms all larger models, while the largest (CodeLlama-13B) falls below majority baseline. SFT compresses the 42.44pp zero-shot range to 0.50pp, eliminating architecture-dependent variance.

S Use of AI Assistants

We used Claude (Anthropic) as an AI coding and writing assistant throughout this work. Specifically:

- **Code:** drafting experiment scripts, data-processing pipelines, and analysis utilities; debugging and refactoring.
- **Writing:** drafting and revising paper sections, polishing prose, and reformatting LaTeX.
- **Literature:** summarizing related papers to inform the related-work section.