Layer Selection Sensitivity in Hidden-State Safety Probes for Reasoning Models

Anonymous ACL submission

Abstract

Reasoning models with chain-of-thought (CoT) can self-jailbreak: their reasoning traces transition from safe deliberation to committed harmful generation without adversarial input. We define the commitment point (CP) as the first reasoning step after which safety deliberation permanently ceases, and present a systematic empirical comparison of hidden-state (HS) vs. text probes for CP detection across four reasoning LLMs (3 Qwen-family, 1 Llama) on HarmThoughts. The comparison depends critically on which transformer layer is monitored, a known sensitivity in probing methodology that we show is severe enough to qualitatively reverse conclusions in the safety domain: a crossing-rate composite metric selects L0 for R1-8B while threshold-based metrics select L14 (14-layer divergence); at 32B the divergence reaches 61 layers (exploratory†), reversing whether an HS advantage is observed. Threshold-based layer selection recovers HS precision gains of +15 to +22pp at 7–8B (cross-validated via nested CV) and preliminary +15 to +19pp at 32B (exploratory†, $n \leq 20$) against a 384d sentence encoder, but this advantage is conditional on partially correlated factors: it diminishes with stronger text encoders (4/4 HB at 384d $\rightarrow$ 1/4 at 1024d) and partially overlaps with temporal position. Seven alternative methods (change-point detection, geometric distance, representation engineering, cross-model transfer) all fail to match supervised probing. Metric-induced layer selection bias is the robust methodological finding; the empirical HS advantage is conditional on encoder quality and position control (partially correlated).

1 Introduction

Reasoning models such as DeepSeek-R1 (DeepSeek-AI, 2025) and QwQ (Qwen Team, 2024) scale inference-time computation through extended chains of thought (CoT). Recent work documents that these models can "self-jailbreak": without adversarial input modification, the CoT transitions from safety-aware deliberation to committed harmful generation (Kakkar et al., 2026; Yong and Bach, 2025). We define the first reasoning step after which safety deliberation permanently ceases as the **Safety Commitment Point** (CP). This failure mode differs qualitatively from adversarial jailbreaks on standard LLMs because the harmful transition originates within the model's own reasoning. Recent work shows that chain-of-thought faithfulness is limited (Chen et al., 2025), motivating hidden-state monitoring that bypasses surface text. Before retrospective characterization can inform future detection systems, a prior question must be answered: can current probing methods reliably distinguish pre-CP from post-CP reasoning steps, and under what conditions? This paper provides *retrospective* classification (not online detection) of what hidden-state and text-based probes can and cannot detect; false positive rates remain 11–50%, so deployment applications are future work.

Existing safety detectors target fundamentally different problems. Hidden-state (HS) methods such as TrajGuard (Liu et al., 2026) and SafeSwitch (Han et al., 2025) classify adversarial inputs at the token level, while text monitors like SafeRemind (Kim et al., 2026) scan generated reasoning for explicit violations. Neither tracks the gradual, multi-step commitment process. HS probes require choosing which transformer layer to monitor, a researcher degree of freedom typically treated as a minor implementation detail. Before asking which modality is better, a prior methodological question must be answered: how sensitive are probe conclusions to the choice of layer selection metric? We show this choice alone can reverse a study's central conclusion: the same data yield a 14-layer (R1-8B) to 61-layer (QwQ-32B) divergence depending solely on metric choice; for QwQ-32B, at threshold-based layers the HS advan-

Model	Arch.	Params	Layers	Hidden	n (total / test)
R1-8B	Llama	8B	32	4096	209 / 43
OT-7B	Qwen	7B	28	3584	228 / 47
R1-32B	Qwen	32B	64	5120	100 / 20
QwQ-32B	Qwen	32B	64	5120	95 / 19

Table 1: Models studied. R1-8B and R1-32B are distilled from DeepSeek-R1 (DeepSeek-AI, 2025); QwQ-32B (Qwen Team, 2024) is a native reasoning model; OT-7B (Guha et al., 2025) is trained with STILL (Min et al., 2024) on Qwen2.5-7B. Data: HarmThoughts (Kakkar et al., 2026) with step-level CP annotations (CP = first reasoning step after which safety deliberation permanently ceases). Split: 60/20/20.

tage is +19pp ($p<0.005$); at crossing-rate-selected layers, it is non-significant ($p=0.83$). Prior hidden-state probing targets standard LLMs (Zhou et al., 2024; Arditi et al., 2024); prior reasoning safety work remains at the text level (Kakkar et al., 2026; Ghosal et al., 2026). The intersection—hidden-state monitoring of reasoning model safety trajectories—is unexplored, and existing hidden-state analyses operate across layers (spatial) rather than across generation steps (temporal).

We conduct a systematic analysis across four reasoning models, primarily Qwen-based (3/4 models), with one Llama model providing evidence from a second architecture family, at two scales (7–8B, 32B) on the HarmThoughts benchmark. Our central finding is methodological: the choice of layer selection metric entirely determines whether an HS advantage is observed. A composite metric (balanced accuracy $\times$ crossing rate) selects shallow layers for 32B models because shallow representations compress directional information, so a linear probe operates near the noise floor and threshold crossings reflect noise rather than semantic transitions. At these layers, only the two 7–8B models show significant HS advantage.

Threshold-based metrics (precision, inverse FPR, additive composite) share a common confusion matrix and empirically converge; BA independently confirms deep-layer selection (Table 2). At these layers, the HS advantage is graded: *validated via nested 5-fold CV* at 7–8B (precision +20.1 to +21.9pp; Table 3), *significant* but suggestive of position-competitiveness at QwQ-32B† (+19.2pp; Section 4.4), and *exploratory* at R1-32B† (+15.4pp, pattern consistent with position mediation, below MDE; Section 4).

Our contributions are:

- **Metric-induced layer selection bias.** Prior work has noted metric sensitivity in probing (Belinkov, 2022); our contribution is demonstrating a qualitative reversal (significant to non-significant) in a safety-critical application, where the stakes of metric choice are higher than in typical linguistic probing. Crossing-rate composite metrics systematically select shallow layers across all four models (including Llama), across datasets (HarmThoughts step-level CP labels and AdvBench binary jailbreak classification; Section C.2); the geometric precondition extends to standard-attention architectures beyond Llama/Qwen (Gemma-2; Section C.3). Crossing-rate composite metrics reverse HS probe conclusions at 32B scale. The divergence is not gradual: for QwQ-32B, the CR-composite layer (L2, 3% depth) yields $p=0.83$ (non-significant), while the threshold-based layer (L63, 98% depth) yields $p<0.005$, a qualitative reversal, not a quantitative shift. Random-label controls on both architectures confirm the disagreement requires genuine safety labels; the geometric component is Qwen-specific (Section 4.2).

- **Boundary conditions for the HS advantage.** Against 384d MiniLM, the HS advantage is validated via nested 5-fold CV at 7–8B (+20.1 to +21.9pp, HB corrected), significant at QwQ-32B† (+19.2pp, position-competitive), and exploratory at R1-32B† (+15.4pp). This advantage is conditional on two partially correlated factors: it diminishes with stronger encoders (1/4 HB under BGE-1024d; PCA capacity matching preserves significance across all four models) and partially overlaps with position (3/4 linear, 2/4 quadratic residualization; Section 4.4).

- **Negative results define method boundaries.** No alternative method consistently matches supervised probing (Table 26): BOCPD/CUSUM fail on gradual transitions; Mahalanobis distance finds near-zero separation; RepE is model-dependent; cross-model transfer fails. Control task selectivity (11.1–16.8pp above chance; Section H) confirms genuine safety structure.

These findings establish that layer selection metric is an uncontrolled confound in hidden-state safety probing: any study reporting conclusions from a

single metric family risks undetected qualitative reversal.

2 Related Work

Safety in Reasoning Models. Reasoning models introduce a qualitatively new failure mode: the model's own chain of thought transitions from safe deliberation to harmful generation without adversarial input (Wang et al., 2025). Self-jailbreak has been documented with step-level annotations (Kakkar et al., 2026; Yong and Bach, 2025); H-CoT (Kuo et al., 2025) shows reasoning chains can be externally hijacked; unfaithful reasoning (Chen et al., 2025; Turpin et al., 2023) motivates hidden-state monitoring. Safety-aligned models maintain refusal intentions during thinking but experience sharp drops at output generation (Yin et al., 2025; Hagendorff et al., 2026; Hu et al., 2026; Ahrend et al., 2026). CoT monitoring detects reward hacking but is fragile under optimization pressure (Baker et al., 2025; Korbak et al., 2025); GuardReasoner (Liu et al., 2025) trains a dedicated reasoning guard; Schulz (2025) formalizes safety-case deployment. Mitigation strategies include early reasoning steering (Ghosal et al., 2026), entropy-triggered reminders (Kim et al., 2026), and guardrail insertion (Mao et al., 2025); none conducts a systematic modality comparison for commitment detection.

Hidden-State Safety Detection. Internal activations encode safety-relevant information: truthfulness (Azaria and Mitchell, 2023), layer-distributed alignment signals (Zhou et al., 2024), shallow alignment (Qi et al., 2025), refusal directions (Arditi et al., 2024; Joad et al., 2026), activation steering (Turner et al., 2023; Li et al., 2023), separate harmfulness/refusal encodings (Zhao et al., 2025; Wollschläger et al., 2025), and scalable feature extraction (Templeton et al., 2024). Probing studies confirm safety states are linearly accessible (Zhao et al., 2026; Chia and Pan, 2025; Kadali and Papalexakis, 2025). Monitoring systems—TrajGuard (Liu et al., 2026), SafeSwitch (Han et al., 2025), SIREN (Jiao et al., 2026), SafeDream (Yan et al., 2026), HiddenDetect (Jiang et al., 2025), SafeInt (Wu et al., 2025), RCS (Hua et al., 2026), and hidden-state forensics (Zhou et al., 2025)—assume external input manipulation and operate at the token level; the self-jailbreak setting differs because transitions are internal and span multiple reasoning steps. Concurrently, Chan et al. (2025) show final-layer linear probes predict alignment outcomes with strong F1, but their single-layer, single-metric evaluation does not examine whether different layers yield different conclusions—the central question of our work (Section 4.2). We reproduce TrajGuard (Section 4.6) and find its geometric approach fails on minor PCA components.

Probing Methodology and Layer Selection. Linear probing spans layer-wise classifiers (Alain and Bengio, 2017), sentence probing (Conneau et al., 2018), and surveys (Belinkov and Glass, 2019; Belinkov, 2022; Rogers et al., 2020); causal abstraction (Geiger et al., 2023) grounds use of internal representations. Control tasks (Hewitt and Liang, 2019) distinguish structure from memorization (adopted in Section H); Levinstein and Herrmann (2024) raise concerns about spurious correlations that our controls address. Information-theoretic and causal formulations address probe complexity (Voita and Titov, 2020; Pimentel et al., 2020; Ravfogel et al., 2020, 2022; Belrose et al., 2023b; Elazar et al., 2021).[1] Non-uniform layer-wise information distribution (Tenney et al., 2019; Jawahar et al., 2019; Marks and Tegmark, 2024) and cross-layer disagreement (Kaya et al., 2019; Zhou et al., 2020) are well established; we repurpose these for safety probe layer selection (Section 3.3). Our contribution is that the known layer-wise gradient interacts with metric choice to produce systematic selection bias. Boxo et al. (2025) show probes can rely on textual evidence; our analysis provides a complementary geometric mechanism at shallow layers. Concurrent works confirm layer sensitivity in related settings: influence estimation (Vitel and Chhabra, 2025), reasoning dynamics monitoring (Chrabąszcz et al., 2026), hallucination detection (Alvarez and Baheri, 2026), truth encoding trajectories (Damirchi et al., 2026), selective probes (Meyoyan and Del Corro, 2026), and multi-layer ensembling (Nordby et al., 2026).

Alternative Detection Approaches. BOCPD (Adams and MacKay, 2007) detects abrupt distributional shifts; CCS (Burns et al., 2023) discovers latent truth directions; RepE (Zou et al., 2023a) identifies concept directions. We adapt all three to temporal commitment detection (Section 4.6): BOCPD/CUSUM fail on gradual transitions, CCS misaligns temporally, and RepE

[1] The Tuned Lens (Belrose et al., 2023a) assumes next-token prediction, misaligned with binary CP classification.

is model-dependent (BA 0.756 vs. 0.559). These failures motivate supervised probes with principled layer selection.

3 Problem Setup and Methods

3.1 Safety Commitment Point

When a reasoning model is jailbroken, its chain-of-thought (CoT) transitions from safety-aware deliberation to committed harmful generation. We define the **Safety Commitment Point** (CP) as the first reasoning step after which safety deliberation permanently ceases; traces with oscillating safety deliberation are resolved by taking the final irreversible transition. This binary formulation is a deliberate simplification; we discuss its limits in Section 6. Steps before CP are *pre-commitment* ($y_t = 0$); steps at or after CP are *post-commitment* ($y_t = 1$). The classification task produces a score $s_t \in [0, 1]$ estimating whether the model has passed its CP by step t. Annotation quality is robust to boundary uncertainty: shifting CP labels by ± 1 step changes balanced accuracy by $<$2.5pp (Table 21).

We study four reasoning models spanning two architectures and two scales (Table 1).

3.2 Probe Architecture

Hidden-state (HS) probes. At each step t, we extract the last-token hidden state $\mathbf{h}_t^{(\ell)} \in \mathbb{R}^d$ from layer ℓ and train an L2-regularized logistic regression classifier (balanced class weights, C=1.0, LBFGS, max_iter = 2000) on binary CP labels. Sweeping $C \in [0.01, 100]$ yields $<$2pp BA variation (Section 4), confirming robustness to this default. Layer selection is analyzed in Section 3.3.

Text probes. Each step's text is encoded with all-MiniLM-L6-v2 (Wang et al., 2020) ($\mathbb{R}^{384}$), a distilled sentence encoder from the Sentence-BERT family (Reimers and Gurevych, 2019). The same logistic regression is applied as a surface-level modality baseline.

Temporal windowing. For window size W, we concatenate features from steps $[t-W+1, \ldots, t]$. We evaluate $W \in \{1, 3, 5, 10, 15, 20, 25\}$ and select per-model on validation. GRU sequence models are also evaluated under two protocols: a 70/30 train/test split (primary) and the same 60/20/20 split used for LR experiments (for fair comparison; Table 19 and Section G).

3.3 Layer Selection Sensitivity

Layer selection is a researcher degree of freedom that can reverse modality comparison conclusions. We evaluate five metrics: balanced accuracy (BA), precision, and inverse FPR are standard probing metrics (Belinkov, 2022); crossing rate formalizes cross-layer prediction disagreement (Kaya et al., 2019; Zhou et al., 2020), and additive composite. A *first crossing point* (FCP) exists for trace i at layer ℓ when the probe score $s_{t'}^{(\ell)} > \tau$ for K consecutive steps; the crossing rate is $\mathrm{CR}(\ell) = N^{-1} \sum_i \mathbb{1}[\mathrm{FCP}_i^{(\ell)} \text{ exists}]$. A multiplicative composite (BA $\times$ crossing rate) serves as the *crossing-rate composite* (CR-composite) baseline, combining classification quality with transition sensitivity. Metrics at a fixed decision threshold (precision, inverse FPR, additive composite) form the *threshold-based* selection. This taxonomy is empirical, but cosine compression at shallow layers predicts a priori that any threshold-crossing metric exhibits shallow-layer bias, confirmed by results (Section 4.2). Crossing rate inflates where representations are compressed (inter-step cosine distances 1.4–2.7$\times$ smaller; Section C). Threshold-based metrics share a confusion matrix and empirically converge; BA independently confirms. Results in Section 4.2; full per-layer sweeps in Section B.

3.4 Baseline Methods

We evaluate seven alternatives to contextualize probe performance (Table 26): BOCPD (Adams and MacKay, 2007) and CUSUM (Page, 1954) for change-point detection; Mahalanobis distance following TrajGuard (Liu et al., 2026); RepE mean-difference directions (Zou et al., 2023a); two-layer MLP probes; CCS-adapted (Burns et al., 2023); and cross-model transfer via PCA. A position-only baseline (t/T) controls for temporal artifacts. Detailed configurations in Sections K and R.

3.5 Evaluation Protocol

We report balanced accuracy, precision, pre-CP FPR, coverage, and lead time. We exclude F1 (conflates precision and recall), AUROC (threshold-free, cannot diagnose layer selection bias), and MCC (redundant with BA under balanced priors). Positive classification requires K=5 consecutive threshold crossings, selected on the R1-8B validation set and held fixed across all models as the value balancing coverage ($\geq$70%) and safe-trace false positive rate ($\leq$50%); Table 24 confirms

that the HS vs. text conclusion direction is consistent at K=3, 5, and 7, with coverage and FPR trading off monotonically. Modality comparisons use BCa bootstrap (10,000 resamples, resampling traces as clusters: each trace is an independent unit and all its steps are included or excluded together, preserving within-trace dependence) (Efron and Tibshirani, 1993; DiCiccio and Efron, 1996) with Holm-Bonferroni step-down (3 metrics $\times$ 4 models $=$ 12 tests, α=0.05); the 4-test framework yields identical conclusions (Section D). For 32B models ($n \leq 20$), the exact permutation test is the primary inference method; BCa confidence intervals are reported for comparability but may have reduced coverage at these sample sizes (BCa assumes approximate pivotality; heavy-tailed score distributions could produce anti-conservative intervals). Within each model, the three metrics are positively correlated, so the correction is stricter than under independence. Control task selectivity (Hewitt and Liang, 2019) validates genuine structure (Section H). † marks sample-limited test sets ($n \leq 20$): R1-32B (n=20) and QwQ-32B (n=19).

Hyperparameter search space and multiple comparisons. The full exploration spans ∼5 metrics $\times$ 7 windows $\times$ 28–64 layers $\approx$ 980–2,240 configurations per model. However, the effective number of independent tests is far smaller: the five metrics share one confusion matrix (threshold-based metrics are functionally correlated; Section Y.2), and adjacent layers produce near-identical probes. Effect sizes are large (Cohen's d=0.58–2.37; Section Y.2), arguing against fishing artifacts. A two-stage design protects against selection bias: upstream layer/window exploration uses nested CV and split-half validation at 7–8B (Sections W.1 and X.1); downstream modality tests apply HB to 12 final comparisons. The 32B models lack nested CV (∼4 traces per fold) and are marked exploratory (†). We classify evidence into three tiers (cross-validated, significant, and exploratory), detailed in Section 4. All reported p-values are conditional on the selected layer and window, not marginal over the full search space.

4 Experiments

We evaluate temporal probes across four reasoning models (Table 1), comparing hidden-state (HS) and text modalities under different layer selection criteria.

Evidence gradient. We classify HS advantage evidence into three tiers: *cross-validated*[2] (nested CV pass; 7–8B models), *significant* (HB pass without nested CV; QwQ-32B), and *exploratory* (†, small sample or narrow coverage; R1-32B). Per-model details follow in Sections 4.2 to 4.4.

4.1 Setup

We study R1-8B (Llama-8B, R1-distilled, n=43 test traces), OT-7B (OpenThinker-7B, trained on the OpenThoughts dataset (Guha et al., 2025); Qwen-7B backbone, STILL-trained Section F, n=47), QwQ-32B (Qwen-32B, native reasoning, n=19–20), and R1-32B (Qwen-32B, R1-distilled, n=20). All traces come from HarmThoughts with step-level CP annotations (60/20/20 split). HS probes extract last-token hidden states from a selected layer; text probes encode each step with all-MiniLM-L6-v2 (384d). Both use L2-regularized logistic regression with temporal windowing $W \in \{1, 3, 5, 10, 15, 20, 25\}$ selected on validation. Classification requires K=5 consecutive threshold crossings (Table 24). Statistical testing follows Section 3.5.

4.2 Layer Selection Results

Table 2 shows that the crossing-rate composite metric (balanced accuracy $\times$ crossing rate) systematically selects shallow layers across all four models: L0 for R1-8B (full L0–L24 sweep; Table 6) and OT-7B, L2 (3%) for QwQ-32B, and L10 (16%) for R1-32B (Fig. 1). The three threshold-based metrics (precision, inverse FPR, additive composite) share a common confusion matrix and empirically converge to the same deep layer, L63 (98%) for both 32B models, consistent with their shared structure, though not mathematically guaranteed. Pure balanced accuracy, a threshold-free metric, selects layers that vary across data splits and models (7–98% depth under 60/20/20; Section Y), itself demonstrating that layer selection is a consequential methodological choice. The mechanism is that shallow layers produce highly compressed representations with small inter-step margins: step-to-step cosine distances are 1.4–2.7$\times$ smaller than at deep layers across all models (Section C). A linear probe in this compressed space operates

[2] In our usage, *cross-validated* means the result survives nested 5-fold cross-validation with a held-out test fold, ruling out hyperparameter overfitting. *Exploratory* (†) results pass HB on the holdout split but lack nested CV validation due to sample constraints.

Model	CR-comp.[a]	Thresh.[b]	p (thresh.)	ΔPrec[c]
R1-8B	L0 (0%)	L14 (44%)	<0.001	+20.1
OT-7B	L0 (0%)	L16 (57%)	<0.001	+21.9
QwQ-32B†	L2 (3%)	L63 (98%)	<0.005	+19.2
R1-32B†	L10 (16%)	L63 (98%)	<0.001	+15.4

Table 2: Layer selection sensitivity. [a] Crossing-rate composite (bal_acc × crossing_rate). [b] Consensus of threshold-based metrics (precision, inverse FPR, additive composite). [c] HS−text precision difference (pp) at threshold-based layer (Table 3). Rightmost p: HS vs. text precision p-value at threshold-based layer (e.g., QwQ-32B CR-composite layer: p=0.83, non-significant). † Sample-limited ($n \leq 20$).




Figure 1: Per-layer metric heatmap (2×2). Each column: one of five metrics (min-max normalized). Red dashed: CR-composite layer (bal_acc × crossing_rate); green dashed: threshold-based layer (consensus of threshold-based metrics). For R1-8B (full L0–L24 sweep), crossing rate drives CR-composite selection to L0 while threshold-based metrics retain L14. At 32B, CR-composite selections cluster near input layers while threshold-based metrics peak at deep layers.

near the noise floor, generating frequent threshold crossings that inflate crossing rate independently of discriminative power (Section 3.3).

The downstream impact is severe: at CR-composite layers, only the two 7–8B models show significant HS advantage; both 32B models fail. The CR-composite's systematic shallow-layer selection is an artifact of cosine compression (Section C), not a genuine safety signal; random-label controls confirm this distinction (Section B.1). At threshold-based layers, the HS advantage is graded: cross-validated at 7–8B (OT-7B, R1-8B; nested CV), significant but suggestive of position-competitiveness at QwQ-32B†, and exploratory at R1-32B† (residualized gap below MDE). The † marks sample-limited test sets ($n \leq 20$) where effect sizes are descriptive rather than confirmatory. Random-label controls on QwQ-32B and R1-8B confirm that threshold-based deep-layer selection requires genuine safety labels; the geometric shallow-layer bias is Qwen-specific: retained on QwQ-32B but dissolved on R1-8B (Section B.1). AUROC, excluded from our primary metrics because it is threshold-free (Section 3.5), confirms HS discriminability at BA-selected layers (ΔAUROC +12.1 to +15.1pp; Table 41) but cannot diagnose the threshold-dependent layer selection bias.

Ensemble layer selection. A three-layer ensemble that averages predicted probabilities from the precision-best, BA-best, and inverse-FPR-best layers bypasses single-metric pre-selection entirely. On the holdout split, all four models show significant HS advantage under the ensemble ($p \leq 0.002$, HB corrected; Table 44), including both 32B models that fail under CR-composite selection. The ensemble succeeds because averaging predictions from layers selected by different threshold-based metrics—which may favor somewhat different depths within the deep region—smooths metric-specific variation and reduces sensitivity to any single metric's layer preference. This holdout result uses the same split for both layer selection and evaluation; cross-validated confirmation is needed before the ensemble can be recommended as a general debiasing strategy (Section 5).

Cross-dataset replication (AdvBench). To test whether metric-induced layer selection bias generalizes beyond HarmThoughts CP labels, we replicate the five-metric layer sweep on AdvBench (Zou et al., 2023b) (520 traces, 159 jailbreaks) using R1-8B with binary jailbreak/safe labels instead of step-level CP annotations. With held-out evaluation (1,000 bootstrap iterations, 60/40 train/test), the CR-composite selects shallow layers (median L2) while precision selects deep layers (median L14), a mean divergence of 31.7pp (95% CI [3.2, 48.4]pp, p=0.015) consistent with HarmThoughts (L0 vs. L14). This confirms that the layer selection bias is driven by representational

Model	Layer	Enc.	W	ΔBA	ΔPrec	95% CI	ΔFPR	HB
R1-8B	L14	384d	3	+17.5	+20.1	[+12.4, +28.3]	−7.9	✓
		1024d		–	+5.8	[−7.4, +19.5]	–	
OT-7B	L16	384d	3	+10.7	+21.9	[+14.4, +29.6]	−17.1	✓
		1024d		–	+18.1	[+8.4, +29.0]	–	✓
QwQ†	L63	384d	5	+13.0	+19.2	[+9.3, +33.5]	−15.0	✓
		1024d		–	+9.4	[−7.1, +27.7]	–	
R1-32B†	L63	384d	1	+18.7	+15.4	[+8.7, +22.6]	−14.6	✓
		1024d		–	+11.7	[−0.2, +24.3]	–	

Table 3: HS vs. text at threshold-based layers (LR probes, 60/20/20 split, 10,000 bootstrap resamples). Enc.: text encoder (384d = MiniLM-L6-v2, 1024d = BGE-large). Δ: HS−text difference (pp); "–" = BA and FPR are not computed for the 1024d comparison because the 384d and 1024d encoders operate at different probe calibration points and do not share a decision threshold. HB: ✓ = model-level test passes Holm-Bonferroni (α=0.05); all 384d model-level tests pass. † Sample-limited ($n \leq 20$); 32B results are exploratory. 1024d: HB over 4 model-level precision tests.

geometry, not label semantics (Section C.2).

4.3 HS vs. Text Comparison

The HS advantage is encoder-conditional: against BGE-large (1024d), only OT-7B survives HB correction (Section S). Multi-seed stability appears in Section X. Against the 384d baseline, HS probes outperform text probes in all four models† (Table 3): cross-validated at 7–8B (OT-7B: +21.9pp precision, R1-8B: +20.1pp), significant but suggestive of position-competitiveness at QwQ-32B† (+19.2pp), and exploratory at R1-32B† (+15.4pp, pattern consistent with position mediation). R1-8B FPR is directionally consistent (5/5 seeds) but not robust (p=0.044, rank 12/12 in HB step-down; 1/5 seeds Bonferroni; Section X). R1-32B passes 5/5 seeds but shows a pattern consistent with position mediation (residualized gap NS; Section V); QwQ-32B's position baseline is competitive (Section 4.4). Overall, 18/20 model-seed combinations pass full HB (Section X). Control task selectivity confirms genuine safety signal: 11.1–16.8pp above chance (Section H). A split-half analysis on OT-7B confirms internal validity (Section X.1).

Capacity control. PCA reduction of HS features to 384d (79–92% variance retained) preserves the precision advantage across all four models† (+16.8 to +23.1pp, all p<0.012, all HB). The control provides partial evidence against a pure capacity explanation. Random projection to 384d yields similar results (ΔPrec +8.3 to +20.5pp; Section T), further weakening the capacity explanation. E5-Mistral-7B (4096d, PCA-reduced to 384d; Section U) yields intermediate results (2/4 HB), forming a monotonic encoder-quality gradient with MiniLM (4/4) and BGE-large (1/4).

Encoder robustness. Against BGE-large (Xiao et al., 2023) (1024d), only OT-7B survives HB (1/4 precision); R1-8B shows adverse FPR direction (+1.2pp). This forms a monotonic encoder-quality gradient: MiniLM-384d (4/4 HB) → E5-Mistral-4096d→384d (2/4) → BGE-large-1024d (1/4), with the precision advantage narrowing from +15–22pp to +6–12pp. The HS advantage is thus a function of text encoder capacity (Fig. 5); layer selection (Contribution 1) is encoder-independent.

Position mediation. Position (t/T) accounts for 9–20pp of balanced accuracy,[3] but all models retain non-positional signal above chance (all p<0.001; Section V). Three of four models retain significant non-positional HS advantage (residualized gap +3.7 to +6.9pp, HB corrected); R1-32B's gap is +1.9pp (p=0.914, n=20), well below the MDE of ∼9pp and thus indistinguishable from zero at current power. Adding a quadratic position term $(t/T)^2$ does not change significance conclusions for the 7–8B models. However, QwQ-32B's advantage is fully absorbed by the quadratic term (Table 32), indicating a non-linear position component. Temporal windowing reduces position dependence (Section 4.5).

Caveats. Nested 5-fold CV confirms the HS precision advantage for both 7–8B models (10/10 folds; Section W.1), with shrinkage of 13–25% relative to holdout estimates. OT-7B nested CV selects L21–27 vs. holdout L16 vs. CR-composite L0; the +21.9pp holdout estimate is an upper bound. R1-32B achieves significance only at W=1 with 25% coverage; at $W \geq 3$, dimensionality prevents significance. QwQ-32B HS lead time is negative (−1.2 to +1.9 steps). False alarm rates remain 11–50%, so current methods characterize the phenomenon rather than constitute production detectors. Per-model details in Section 4.4.

4.4 32B Model-Specific Analysis

Exploratory 32B analysis. Both 32B results are exploratory (n=19–20 precludes nested CV). LOO-CV and multi-seed analyses (Sections B and X) provide partial robustness checks but do not substitute for independent validation. R1-32B and QwQ-32B share the Qwen-32B architecture but present opposite detection profiles (Table 4); training method is one plausible differentiator. Replication with $n \geq 50$ traces is needed.

R1-32B suggests commitment 11–13 steps early (+14.2pp over position baseline) but covers only 25% of traces (W=1); the precision effect (+15.4pp, CI width 13.9pp) falls below MDE at

Model	Cov.	Lead (steps)	HB	Pos. margin
R1-32B†	25%	+11.7 to +13.3	✓ (W=1)	+14.2pp
QwQ-32B†	74%	−1.2 to +1.9	✓ (all W)	−3.6pp

Table 4: 32B cross-model divergence († sample-limited, $n \leq 20$; MDE at 80% power: 8.6–9.5pp, Section Z; all conclusions exploratory). R1-32B provides limited early identification with narrow coverage; QwQ-32B provides robust significance with poor lead time. HB: ✓ = passes Holm-Bonferroni (α=0.05). Pos. margin: HS BA minus position baseline.

80% power. QwQ-32B achieves significance at all window sizes with 74% coverage but negative HS lead time; the precision effect (+19.2pp, CI width 24.2pp) exceeds MDE (8.6–9.5pp; Section Z) but the position baseline achieves higher BA (0.832 vs. 0.796), and the HS precision margin over position (+4.5pp, p=0.133; Section V) is not significant at n=19. The divergence suggests per-model validation is needed.

4.5 Temporal Context

Temporal windowing (W>1) improves both modalities (Fig. 2): at 7–8B, the modality advantage (+20.1 to +21.9pp) exceeds temporal improvement (+13pp). GRU models achieve comparable accuracy but higher FPR (Table 19 and Section P); an adaptive two-stage strategy offers marginal gains (Section O).

CP-aligned probe score trajectories (Fig. 4 in Appendix) confirm sharper HS transitions at the commitment point, with OT-7B showing the clearest separation and R1-32B the weakest. A forest plot visualizing precision gaps across encoder conditions appears in Fig. 5.

4.6 Negative Results

No alternative method consistently matches supervised probing (Table 26). BOCPD (Adams and MacKay, 2007)/CUSUM fail (0% detection on 3/4 models); Mahalanobis yields near-zero separation; RepE (Zou et al., 2023a) is model-dependent (BA 0.756 vs. 0.559); MLP probes overfit; CCS misaligns temporally; cross-model transfer fails (Section Q). The signal is directional, gradual, model-specific, and linearly separable, which excludes change-point, distance, transfer, and objective-alignment methods respectively.

5 Discussion

Crossing rate reverses the central finding via shallow-layer compression (Section C and Table 6): its shallow preference is an artifact of cosine compression inflating threshold crossings, while threshold-based deep preference reflects genuine separability (Tenney et al., 2019); random-label controls confirm this distinction (Section B.1). C1 generalizes across all four models (cross-dataset layer selection: Section C.2; geometric: Section C; split-half: Section X.1). The geometric precondition is present in all models with standard full attention—including Gemma-2, confirming it generalizes beyond Llama/Qwen—but absent in Gemma-4's mixed sliding/full attention (Section C.3), suggesting the compression arises from full self-attention's global receptive field while sliding attention's local window disrupts shallow-layer clustering. C2 is sample-dependent (7–8B cross-validated, 32B descriptive). Annotation noise (<2.5pp BA change; Table 21) does not threaten C1. The encoder-quality gradient narrows the HS advantage (384d to 1024d; Section V). Type I risk from ∼2,240 configurations is bounded by the two-stage design and large effect sizes (d 0.58–2.37; Section Y.2). That this vulnerability was foreseeable from probing methodology—yet remained unexamined in safety applications where it reverses conclusions about model monitorability—underscores the gap between methodological awareness and practice.

Practical mitigation. We propose a three-level defense against metric-induced layer selection bias. *Level 1 (minimal)*: report layer selections under both threshold-based and frequency-based metric families; divergence exceeding 20% of model depth (e.g., L2 vs. L63 in a 64-layer model) indicates metric-induced bias and warrants treating conclusions as provisional. *Level 2 (recommended)*: a multi-metric audit (Section L.1) computes all five metrics and flags when ≥3 select layers differing by >20% of depth—an operational test requiring no additional data. *Level 3 (robust)*: a three-layer ensemble averaging probe predictions from the precision-best, BA-best, and inverse-FPR-best layers eliminates metric pre-selection entirely ($p \leq 0.002$; Table 44), but requires cross-validated confirmation before deployment.

6 Conclusion

Layer selection metric choice can reverse a safety study's central conclusion: for QwQ-32B, the same data yield $p{=}0.83$ or $p{<}0.005$ depending solely on metric. The layer selection bias replicates on AdvBench with binary jailbreak/safe labels (Section C.2), confirming it arises from representational geometry rather than dataset-specific annotations. The HS advantage is validated at 7–8B (+20–22pp, nested CV) and exploratory† at 32B (+15–19pp) against 384d encoders, but conditional on encoder quality and position (partially correlated); generalization beyond Qwen (3/4 models) requires causal validation. Until layer selection is controlled, probe-based safety conclusions from any single metric should be treated as provisional.

Limitations

Dataset scope and annotation quality. CP-dependent claims (C2, HS vs. text advantage) rely on one dataset (HarmThoughts (Kakkar et al., 2026)), the only publicly available dataset providing step-level CP annotations for reasoning model traces, with annotations lacking formal inter-annotator agreement; an LLM-based proxy on AdvBench achieved $\kappa{=}0.606$ (Section J.1). The methodological finding (C1, layer selection bias) is replicated on AdvBench with binary jailbreak/safe labels (Section C.2), and the geometric precondition (shallow-layer compression) is confirmed cross-dataset (Sections C and C.1), but generalization to other jailbreak datasets, attack taxonomies, or multilingual settings is untested.

Statistical power at 32B. With $n{=}19$–20 traces, the minimum detectable effect at 80% power is 8.6–9.5pp (Section Z); all 32B conclusions marked $\dagger$ should be interpreted with this constraint. False positive rates remain 11–50% (model-dependent), and R1-32B achieves significance only at $W{=}1$ (25% coverage). These probes characterize the commitment phenomenon rather than constitute production detectors.

Architecture coverage and causal status. Three of four models share the Qwen architecture; only R1-8B (Llama) provides cross-architecture evidence. Random-label controls confirm the crossing-rate geometric bias is Qwen-specific (Section B.1). The geometric precondition is confirmed on standard full attention architectures (Llama, Qwen, Gemma-2) but absent in Gemma-4's mixed sliding/full attention variant (Section C.3); generalization to other attention mechanisms (e.g., linear attention, SSMs) is untested. Results are correlational; causal intervention (e.g., DAS, activation patching) is needed to confirm mechanistic involvement.

Ethics Statement

This work analyzes safety-relevant reasoning traces to characterize probe behavior, not to circumvent safety mechanisms. All experiments use publicly available models and datasets (HarmThoughts, AdvBench). No human subjects were involved. Code and scripts for all experiments and analyses will be released upon acceptance.

References

Ryan Prescott Adams and David J.C. MacKay. 2007. Bayesian online changepoint detection. *arXiv preprint arXiv:0710.3742*.

Patrick Ahrend, Tobias Eder, Xiyang Yang, Zhiyi Pan, and Georg Groh. 2026. Safer reasoning traces: Measuring and mitigating chain-of-thought leakage in LLMs. *arXiv preprint arXiv:2603.05618*.

Guillaume Alain and Yoshua Bengio. 2017. Understanding intermediate layers using linear classifier probes. In *Workshop Track, International Conference on Learning Representations (ICLR)*.

Tyler Alvarez and Ali Baheri. 2026. Where does reasoning break? step-level hallucination detection via hidden-state transport geometry. *arXiv preprint arXiv:2605.13772*. Concurrent work.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. 2024. Refusal in language models is mediated by a single direction. In *Advances in Neural Information Processing Systems 37 (NeurIPS)*.

Amos Azaria and Tom Mitchell. 2023. The internal state of an LLM knows when it's lying. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 967–976.

Bowen Baker, Joost Huizinga, Leo Gao, Zehao Dou, Melody Y. Guan, Aleksander Madry, Wojciech Zaremba, Jakub Pachocki, and David Farhi. 2025. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation. *arXiv preprint arXiv:2503.11926*.

Yonatan Belinkov. 2022. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219.

Yonatan Belinkov and James Glass. 2019. Analysis methods in neural language processing: A survey. *Transactions of the Association for Computational Linguistics*, 7:49–72.

Nora Belrose, Zach Furman, Logan Smith, Rusheb Halberštadt, Brooks Paige, Max Tegmark, and Stella Biderman. 2023a. Eliciting latent predictions from transformers with the tuned lens. In *International Conference on Learning Representations (ICLR)*.

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. 2023b. LEACE: Perfect linear concept erasure in closed form. In *Advances in Neural Information Processing Systems 36 (NeurIPS)*.

Gerard Boxo, Aman Neelappa, and Shivam Raval. 2025. Linear probes rely on textual evidence: Results from leakage mitigation studies in language models. *arXiv preprint arXiv:2509.21344*.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. 2023. Discovering latent knowledge in language models without supervision. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

James Carpenter and John Bithell. 2000. Bootstrap confidence intervals: when, which, what? A practical guide for medical statisticians. *Statistics in Medicine*, 19(9):1141–1164.

Yik Siu Chan, Zheng-Xin Yong, and Stephen H. Bach. 2025. Can we predict alignment before models finish thinking? Towards monitoring misaligned reasoning models. *arXiv preprint arXiv:2507.12428*.

Yanda Chen, Joe Benton, Ansh Radhakrishnan, Jonathan Uesato, Carson Denison, John Schulman, Arushi Somani, Peter Hase, Misha Wagner, Fabien Roger, Vlad Mikulik, Samuel R. Bowman, Jan Leike, Jared Kaplan, and Ethan Perez. 2025. Reasoning models don't always say what they think. *arXiv preprint arXiv:2505.05410*.

Yik Siu Chia and Shirui Pan. 2025. Probing latent subspaces in LLM for AI security: Identifying and manipulating adversarial states. *arXiv preprint arXiv:2503.09066*.

Maciej Chrabąszcz, Aleksander Szymczyk, Marcin Sendera, Tomasz Trzciński, and Sebastian Cygert. 2026. Monitoring the internal monologue: Probe trajectories reveal reasoning dynamics. *arXiv preprint arXiv:2605.18549*. Concurrent work.

Jacob Cohen. 1988. *Statistical Power Analysis for the Behavioral Sciences*, 2nd edition. Lawrence Erlbaum Associates.

Alexis Conneau, German Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. 2018. What you can cram into a single $&!#* vector: Probing sentence embeddings for linguistic properties. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 2126–2136.

Hamed Damirchi, Ignacio Meza De la Jara, Ehsan Abbasnejad, Afshar Shamsi, Zhen Zhang, and Javen Shi. 2026. Truth as a trajectory: What internal representations reveal about large language model reasoning. *arXiv preprint arXiv:2603.01326*.

DeepSeek-AI. 2025. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Thomas J DiCiccio and Bradley Efron. 1996. Bootstrap confidence intervals. *Statistical Science*, 11(3):189–228.

Bradley Efron and Robert J. Tibshirani. 1993. *An Introduction to the Bootstrap*. Chapman & Hall/CRC.

Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. 2021. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175.

Atticus Geiger, Duligur Ibeling, Amir Zur, Maheep Chaudhary, Sonakshi Chauhan, Jing Huang, Aryaman Arora, Zhengxuan Wu, Noah Goodman, Christopher Potts, and Thomas Icard. 2023. Causal abstraction: A theoretical foundation for mechanistic interpretability. *Journal of Machine Learning Research*, 26(83):1–64.

Andrew Gelman and Eric Loken. 2013. The garden of forking paths: Why multiple comparisons can be a problem, even when there is no "fishing expedition" or "p-hacking" and the research hypothesis was posited ahead of time. *Department of Statistics, Columbia University*.

Soumya Suvra Ghosal, Souradip Chakraborty, Vaibhav Singh, Furong Huang, Dinesh Manocha, and Amrit Singh Bedi. 2026. Safety recovery in reasoning models is only a few early steering steps away. *arXiv preprint arXiv:2602.11096*.

Etash Guha, Ryan Marten, Sedrick Keh, Saumya Bhatia, Jonathan Ragan-Kelley, Sharan Narang, and Tatsunori Hashimoto. 2025. OpenThoughts: Data recipes for reasoning models. *arXiv preprint arXiv:2506.04178*.

Thilo Hagendorff, Erik Derner, and Nuria Oliver. 2026. Large reasoning models are autonomous jailbreak agents. *Nature Communications*.

Peixuan Han, Cheng Qian, Xiusi Chen, Yuji Zhang, Heng Ji, and Denghui Zhang. 2025. Safeswitch: Steering unsafe LLM behavior via internal activation signals. In *Findings of the Association for Computational Linguistics: EMNLP 2025*.

John Hewitt and Percy Liang. 2019. Designing and interpreting probes with control tasks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2733–2743.

Xulin Hu, Che Wang, Wei Yang Bryan Lim, Jianbo Gao, and Zhong Chen. 2026. Tracing the dynamics of refusal: Exploiting latent refusal trajectories for robust jailbreak detection. *arXiv preprint arXiv:2605.02958*.

Peichun Hua, Hao Li, Shanghao Shi, Zhiyuan Yu, and Ning Zhang. 2026. Rethinking jailbreak detection of large vision language models with representational contrastive scoring. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL)*.

Ganesh Jawahar, Benoît Sagot, and Djamé Seddah. 2019. What does BERT learn about the structure of language? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 3651–3657.

Yilei Jiang, Xinyan Gao, Tianshuo Peng, Yingshui Tan, Xiaoyong Zhu, Bo Zheng, and Xiangyu Yue. 2025. HiddenDetect: Detecting jailbreak attacks against large vision-language models via monitoring hidden states. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*.

Difan Jiao, Yilun Liu, Ye Yuan, Zhenwei Tang, Linfeng Du, Haolun Wu, and Ashton Anderson. 2026. LLM safety from within: Detecting harmful content with internal representations. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL)*.

Faaiz Joad, Majd Hawasly, Sabri Boughorbel, Nadir Durrani, and Husrev Taha Sencar. 2026. There is more to refusal in large language models than a single direction. *arXiv preprint arXiv:2602.02132*.

Sri Durga Sai Sowmya Kadali and Evangelos E. Papalexakis. 2025. Do internal layers of LLMs reveal patterns for jailbreak detection? *arXiv preprint arXiv:2510.06594*.

Ishita Kakkar, Enze Zhang, Rheeya Uppaal, and Junjie Hu. 2026. When safety fails before the answer: Benchmarking harmful behavior detection in reasoning chains. *arXiv preprint arXiv:2604.19001*.

Yigitcan Kaya, Sanghyun Hong, and Tudor Dumitras. 2019. Shallow-deep networks: Understanding and mitigating network overthinking. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, pages 3301–3310.

Su-Hyeon Kim, Hyundong Jin, Yejin Lee, and Yo-Sub Han. 2026. How does the thinking step influence model safety? an entropy-based safety reminder for lrms. *arXiv preprint arXiv:2601.03662*.

Tomek Korbak, Mikita Balesni, Elizabeth Barnes, Yoshua Bengio, Joe Benton, Joseph Bloom, Mark Chen, Alan Cooney, Allan Dafoe, Anca Dragan, Scott Emmons, Owain Evans, David Farhi, Ryan Greenblatt, Dan Hendrycks, Marius Hobbhahn, Evan Hubinger, Geoffrey Irving, Erik Jenner, and 22 others. 2025. Chain of thought monitorability: A new and fragile opportunity for AI safety. *arXiv preprint arXiv:2507.11473*.

Martin Kuo, Jianyi Zhang, Aolin Ding, Qinsi Wang, Louis DiValentin, Yujia Bao, Wei Wei, Hai Li, and Yiran Chen. 2025. H-cot: Hijacking the chain-of-thought safety reasoning mechanism to jailbreak large reasoning models. *arXiv preprint arXiv:2502.12893*.

Benjamin A. Levinstein and Daniel A. Herrmann. 2024. Still no lie detector for language models. *arXiv preprint arXiv:2307.00175*.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. 2023. Inference-time intervention: Eliciting truthful answers from a language model. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Cheng Liu, Xiaolei Liu, Xingyu Li, Bangzhou Xin, and Kangyi Ding. 2026. Trajguard: Streaming hidden-state trajectory detection for decoding-time jailbreak defense. *arXiv preprint arXiv:2604.07727*.

Yue Liu, Hongcheng Gao, Shengfang Zhai, Yufei He, Jun Xia, Zhengyu Hu, Yulin Chen, Xihong Yang, Jiaheng Zhang, Stan Z. Li, Hui Xiong, and Bryan Hooi. 2025. GuardReasoner: Towards reasoning-based LLM safeguards. *arXiv preprint arXiv:2501.18492*.

Yingzhi Mao, Chunkang Zhang, Junxiang Wang, Xinyan Guan, Boxi Cao, Yaojie Lu, Hongyu Lin, Xianpei Han, and Le Sun. 2025. When models outthink their safety: Unveiling and mitigating self-jailbreak in large reasoning models. *arXiv preprint arXiv:2510.21285*.

Samuel Marks and Max Tegmark. 2024. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. *arXiv preprint arXiv:2310.06824*.

Gonzalo Ariel Meyoyan and Luciano Del Corro. 2026. A bertology view of llm orchestrations: Token- and layer-selective probes for efficient single-pass classification. *arXiv preprint arXiv:2601.13288*.

Yingqian Min, Zhipeng Chen, Jinhao Jiang, Jie Chen, Jia Deng, Yiwen Hu, Yiru Tang, Jiapeng Wang, Xiaoxue Cheng, Huatong Song, Wayne Xin Zhao, Zheng Liu, Zhongyuan Wang, and Ji-Rong Wen. 2024. Imitate, explore, and self-improve: A reproduction report on slow-thinking reasoning systems. *arXiv preprint arXiv:2412.09413*.

Erik Nordby, Tasha Pais, and Aviel Parrack. 2026. Linear probe accuracy scales with model size and benefits from multi-layer ensembling. *arXiv preprint arXiv:2604.13386*.

E. S. Page. 1954. Continuous inspection schemes. *Biometrika*, 41(1/2):100–115.

Tiago Pimentel, Josef Valvoda, Rowan Hall Maudslay, Ran Zmigrod, Adina Williams, and Ryan Cotterell. 2020. Information-theoretic probing for linguistic structure. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 4609–4622.

Xiangyu Qi, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. 2025. Safety alignment should be made more than just a few tokens deep. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

Qwen Team. 2024. QwQ: Reflect deeply on the boundaries of the unknown.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. 2020. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 7237–7256.

Shauli Ravfogel, Michael Twiton, Yoav Goldberg, and Ryan Cotterell. 2022. Linear adversarial concept erasure. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, volume 162 of *Proceedings of Machine Learning Research*, pages 18400–18421. PMLR.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3982–3992.

Anna Rogers, Olga Kovaleva, and Anna Rumshisky. 2020. A primer in BERTology: What we know about how BERT works. *Transactions of the Association for Computational Linguistics*, 8:842–866.

Till Schulz. 2025. A concrete roadmap towards safety cases based on chain-of-thought monitoring. *arXiv preprint arXiv:2510.19476*.

Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, Hoagy Cunningham, Nicholas L Turner, Callum McDougall, Monte MacDiarmid, C. Daniel Freeman, Theodore R Sumers, Edward Rees, Joshua Batson, Adam Jermyn, and 3 others. 2024. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Transformer Circuits Thread*.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. 2019. BERT rediscovers the classical NLP pipeline. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 4593–4601.

Alexander Matt Turner, Lisa Thiergart, David Udell, Gavin Leech, Ulisse Mini, and Monte MacDiarmid. 2023. Activation addition: Steering language models without optimization. *arXiv preprint arXiv:2308.10248*.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. 2023. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems*, volume 36.

Dmytro Vitel and Anshuman Chhabra. 2025. First is not really better than last: Evaluating layer choice and aggregation strategies in language model data influence estimation. *arXiv preprint arXiv:2511.04715*.

Elena Voita and Ivan Titov. 2020. Information-theoretic probing with minimum description length. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 183–196.

Cheng Wang, Yue Liu, Baolong Bi, Duzhen Zhang, Zhongzhi Li, Yingwei Ma, Yufei He, Shengju Yu, Xinfeng Li, Junfeng Fang, Jiaheng Zhang, and Bryan Hooi. 2025. Safety in large reasoning models: A survey. *arXiv preprint arXiv:2504.17704*.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2024. Improving text embeddings with large language models. *arXiv preprint arXiv:2401.00368*.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. In *Advances in Neural Information Processing Systems 33 (NeurIPS)*.

Tom Wollschläger, Jannes Elstner, Simon Geisler, Vincent Cohen-Addad, Stephan Günnemann, and Johannes Gasteiger. 2025. The geometry of refusal in large language models: Concept cones and representational independence. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*.

Jiaqi Wu, Chen Chen, Chunyan Hou, and Xiaojie Yuan. 2025. SafeInt: Shielding large language models from jailbreak attacks via safety-aware representation intervention. In *Findings of the Association for Computational Linguistics: EMNLP 2025*.

Shitao Xiao, Zheng Liu, Peitian Zhang, and Niklas Muennighoff. 2023. C-pack: Packaged resources to advance general chinese embedding. *arXiv preprint arXiv:2309.07597*.

Bo Yan, Weikai Lin, Yada Zhu, and Song Wang. 2026. Safedream: Safety world model for proactive early jailbreak detection. *arXiv preprint arXiv:2604.16824*.

Qingyu Yin, Chak Tou Leong, Linyi Yang, Wenxuan Huang, Wenjie Li, Xiting Wang, Jaehong Yoon, Yun Xing, Xing Yu, and Jinjin Gu. 2025. Refusal falls off a cliff: How safety alignment fails in reasoning? *arXiv preprint arXiv:2510.06036*.

Zheng-Xin Yong and Stephen H. Bach. 2025. Self-jailbreaking: Language models can reason themselves out of safety alignment after benign reasoning training. *arXiv preprint arXiv:2510.20956*.

Jiachen Zhao, Jing Huang, Zhengxuan Wu, David Bau, and Weiyan Shi. 2025. LLMs encode harmfulness and refusal separately. In *Advances in Neural Information Processing Systems 38 (NeurIPS)*.

Yinzhi Zhao, Ming Wang, Shi Feng, Xiaocui Yang, Daling Wang, and Yifei Zhang. 2026. Defending large language models against jailbreak attacks via in-decoding safety-awareness probing. *arXiv preprint arXiv:2601.10543*.

Shide Zhou, Kailong Wang, Ling Shi, and Haoyu Wang. 2025. Exposing the ghost in the transformer: Abnormal detection for large language models via hidden state forensics. *arXiv preprint arXiv:2504.00446*.

Wangchunshu Zhou, Canwen Xu, Tao Ge, Julian McAuley, Ke Xu, and Furu Wei. 2020. BERT loses patience: Fast and robust inference with early exit. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 18330–18341.

Zhenhong Zhou, Haiyang Yu, Xinghua Zhang, Rongwu Xu, Fei Huang, and Yongbin Li. 2024. How alignment and jailbreak work: Explain LLM safety through intermediate hidden states. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 2461–2488.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, and 2 others. 2023a. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*.

Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. 2023b. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*.

Appendix Contents: Section A Responsible NLP Research Checklist; Section B Layer Sweep Results; Section C Representation Compression Analysis; Section D Holm-Bonferroni Correction; Section E Window Size Ablation; Section F OpenThinker-7B Details; Section G GRU Training Details; Section H Control Task Methodology; Section I Oracle Upper Bound; Section J CP Annotation Perturbation; Section K BOCPD/CUSUM Configuration; Section L Detection Threshold Ablation; Section M Decision Threshold Sensitivity; Section N M002 Bug Disclosure; Section O Adaptive Two-Stage Detection; Section P Temporal Ablation Details; Section Q Negative Results Details (incl. Table 26); Section R Cross-Model Transfer Details; Section S Encoder Robustness; Section T Random Projection Baseline; Section U LLM-Based Text Encoder; Section V Position-Residualized Probing; Section W Hyperparameter Robustness; Section X Multi-Seed Stability; Section X.1 Split-Half Internal Validity; Section Y BA-Layer Modality Comparison; Section Z Post-Hoc Power Analysis.

A Responsible NLP Research Checklist

We address the ARR Responsible NLP Research requirements below.

- **Limitations discussed:** Yes (Section 6).
- **Potential risks:** This research analyzes jailbreak traces to understand how reasoning models commit to generating harmful content. We do not develop new attack methods or release jailbreak prompts. All ana-

lyzed content comes from the publicly available HarmThoughts benchmark. We acknowledge a dual-use concern: safety probes that detect commitment could in principle be used to craft reasoning traces that evade detection. We believe the defensive value of understanding commitment dynamics outweighs this risk, as evasion requires white-box access to the probe, which a deployed monitoring system would not expose.

- **Computational budget:** Our experiments involve 4 models with 209, 228, 100, and 95 traces respectively (632 total), using linear probes and single-layer GRUs. Total compute is minimal (under 4 GPU-hours on a single RTX A6000). No large-scale pretraining or finetuning was performed.

- **Data:** We use HarmThoughts, a publicly available benchmark with step-level safety annotations, and AdvBench (Zou et al., 2023b) for cross-dataset geometric validation. No new data collection was performed.

- **Human subjects:** No human subjects research was conducted.

- **Reproducibility:** All hyperparameters are reported in Sections G and K. Code and corrected data will be released upon publication.

B Layer Sweep Results

For each model, we sweep all transformer layers and evaluate five candidate selection metrics: (1) balanced accuracy $\times$ crossing rate (the CR-composite), (2) pure balanced accuracy, (3) precision, (4) inverse pre-CP FPR, and (5) an additive composite. The CR-composite systematically selects shallow layers across all four models (including R1-8B under the full L0–L24 sweep; Table 6) because early-layer representations exhibit higher crossing rates (more frequent threshold crossings) regardless of discriminative power. Three threshold-based metrics (precision, inverse FPR, additive composite) converge on deep layers for all models; pure balanced accuracy selects layers whose depth varies with the data split (under 70/30: L30 for QwQ-32B, L47 for R1-32B; under the canonical 60/20/20: L63 and L46 respectively; Table 41).

Selected layers. R1-8B: under the original L12–L24 sweep, all five metrics agreed on L14 (44%); extending to L0–L24, crossing rate shifts to L0 while threshold-based metrics retain L14, a 16-layer gap (Table 6). OT-7B: CR-composite selects L0 (0%), threshold-based consensus selects L16 (57%). QwQ-32B: CR-composite selects L2 (3%), threshold-based consensus selects L63 (98%). R1-32B: CR-composite selects L10 (16%), threshold-based consensus selects L63 (98%). The disagreement is most extreme for 64-layer models, where the CR-composite selects layers in the bottom 16% of the network while threshold-based metrics select layers at 98% depth. Under 70/30, pure balanced accuracy selects L30 (47%) for QwQ-32B and L47 (73%) for R1-32B; under the canonical 60/20/20, it selects L63 (98%) and L46 (72%), which demonstrates sensitivity to the data split.

Impact on modality comparison. At the CR-composite layers, HS vs. text precision p-values are 0.064 (R1-32B) and 0.35–0.83 (QwQ-32B), both non-significant. At the threshold-based deep layers, all p-values fall below 0.005. The initially reported "scale-dependent" pattern (HS advantage at 7–8B but not 32B) was entirely an artifact of layer selection methodology, not a genuine property of model scale (Section 4.2).

Layer selection stability (LOO-CV). Leave-one-out cross-validation on the validation set shows moderate consistency for 7–8B models (65–68% dominant-layer agreement) but lower for 32B, confirming that layer selection instability is particularly acute at small sample sizes. Under pure balanced accuracy, the dominant layer is selected in 68% (QwQ-32B: L30, 13/19 folds) and 65% (R1-32B: L47, 13/20 folds) of folds. Alternative selections scatter across neighboring layers (L29, L55–56 for QwQ; L32, L38, L43 for R1-32B), reinforcing the need for multi-metric auditing rather than single-metric layer selection. Threshold-based metrics show tighter convergence to L63 for both 32B models. Expanding the criterion from top-1 to top-3 layers does not change conclusions: the top-3 BA-selected layers for QwQ-32B (L30, L29, L55) and R1-32B (L47, L43, L38) all fall in the mid-to-deep range, and threshold-based metrics remain converged at L63 across all folds.

Joint (layer, W) sensitivity. Under the original 70/30 validation protocol, we evaluate QwQ-32B across 64 layers $\times$ 3 windows ($W \in \{1, 3, 5\}$)

(192 configurations) (Table 5). L60 is near-optimal: within 2.1pp of the global best at W=3 and the top-ranked layer at W=5. (Under 60/20/20, threshold-based metrics select L63; the shift from L60 to L63 across splits itself illustrates layer selection sensitivity.) The optimal layer shifts from middle-deep (L46–47 at W=1) to deep (L60 at W=5), confirming a layer-window interaction. For R1-8B, optimal precision layers shift similarly (L16 at W=1 $\rightarrow$ L9 at W=15; Kendall's τ=-0.91, p=0.071), a consistent negative trend that does not reach significance at n=4 windows. L30, selected by per-fold LOO-CV at W=1 under balanced accuracy, is suboptimal across all windows (max BA = 0.769 vs. global best 0.817). Joint (layer, W) stability was evaluated via grid search on $W \in \{1, 3, 5\}$ for QwQ-32B only; full leave-one-fold-out validation of the (layer, W) pair and extension to R1-32B remain for future work.

Table 5: QwQ-32B joint (layer, W) grid search under 70/30 validation. L60 is near-optimal at recommended windows (W=3–5). L30 (LOO-CV selection at W=1) is suboptimal across all windows. Under the canonical 60/20/20 split, threshold-based metrics select L63.

W	Best layer	Best BA	L60 BA	L60 rank
1	L47	0.798	0.783	$\sim$15th
3	L46	0.817	0.796	$\sim$6th
5	L60	0.808	0.808	1st

R1-8B full-layer sweep. The original R1-8B layer sweep covered L12–L24 (13 layers), where all five metrics agreed on L14 (Table 2). Extending to L0–L24 reveals that crossing rate consistently selects L0 across all window sizes, while threshold-based metrics retain mid-to-deep layers (L12–L16 for W=1–5; L9 at W=15, marginal Δ=0.003 between shallow and deep means), a 9–16 layer divergence (Table 6). Unlike 32B models, the bias is isolated to crossing rate; threshold-based metrics show no shallow shift for R1-8B. This confirms the crossing-rate bias generalizes to Llama-architecture models. HS probes maintain significant advantage across all 25 layers and window sizes (precision gap $\sim$0.15–0.17), unlike OT-7B and 32B models where significance drops at shallow layers.

B.1 Random-Label Decomposition Control

To decompose the sources of metric disagreement in layer selection, we replace the true CP annotations with uniformly random labels and re-run the full layer sweep (10 random-label repeats per model). We test QwQ-32B (95 traces, 64 layers) and R1-8B (209 traces, 25 layers); Tables 7 and 8 report the fraction of repeats selecting a shallow layer and the mean selected layer.

Table 6: R1-8B full-layer sweep (L0–L24, extending the original L12–L24 range). Best layer selected by crossing rate vs. threshold-based metrics across four window sizes. Score = balanced accuracy at the threshold-based layer. Layer gap = crossing-rate layer minus threshold-based layer.

	W=1	W=3	W=5	W=15
Crossing rate	L0	L0	L0	L0
Threshold (composite)	L16 (0.789)	L12 (0.796)	L12 (0.803)	L9 (0.784)
Layer gap	16	12	12	9

Table 7: QwQ-32B layer selection under random CP labels (10 repeats). Shallow%: fraction selecting a layer L$\leq$10. Real-CP layer shown for reference.

Metric	Real-CP	Shallow%	Rand. mean layer
Crossing rate	L4	100%	3.4 ± 2.6
CR-composite	L4	80%	13.1 ± 18.1
Precision	L63	20%	33.8 ± 19.8
Inv. FPR	L62	10%	36.4 ± 17.0
Bal. accuracy	L63	20%	33.3 ± 20.3

Table 8: R1-8B layer selection under random CP labels (10 repeats). Shallow%: fraction selecting L$\leq$4 (bottom quintile of 25 layers). †: degenerate, all repeats select L0 with zero variance, indicating destroyed signal rather than shallow preference.

Metric	Real-CP	Shallow%	Rand. mean layer
Crossing rate	L0	0%	10.7 ± 4.8
CR-composite	L0	0%	13.7 ± 6.7
Precision	L23	100%†	0.0 ± 0.0
Inv. FPR	L13	100%†	0.0 ± 0.0
Bal. accuracy	L19	0%	14.0 ± 4.0

QwQ-32B (Qwen). The results decompose the metric disagreement into two components. (A) The crossing-rate shallow-layer preference is label-independent: 100% of random-label repeats still select layers L0–L7, confirming that this bias reflects representation geometry (shallow-layer cosine distance compression; Section C) rather than any property of the safety labels. The CR-composite inherits this bias (80% shallow). (B) Threshold-based metrics (precision, inverse FPR) select deep layers only with real safety labels; under random labels, selections scatter across the full layer range (mean L34–

L36, high variance). The full metric disagreement (L4 vs. L63, a 59-layer gap) is the superposition of a geometric artifact on the crossing-rate side and a real safety signal on the threshold-based side.

R1-8B (Llama). The Llama-based model shows stronger label dependence: crossing rate scatters from L0 to mean L10.7 ± 4.8 under random labels (0% shallow), unlike QwQ-32B where it retains shallow preference. Threshold-based metrics degenerate entirely: precision and inverse FPR select L0 in all 10 repeats with zero variance, indicating random labels destroy discriminative signal rather than merely redistributing it. The real-CP disagreement (L0 vs. L23, a 23-layer gap) vanishes completely under random labels.

Cross-architecture summary. The metric disagreement requires genuine safety labels in both architectures, but the mechanism differs: in QwQ-32B, crossing-rate shallow preference reflects representation geometry (label-independent cosine compression), while in R1-8B even crossing-rate layer selection is label-dependent. The geometric component of the crossing-rate bias is thus Qwen-specific rather than a universal property of transformer representations.

C Representation Compression Analysis

We measure step-to-step cosine distance at CR-composite (shallow) vs. threshold-based (deep) layers across all models to characterize the compression mechanism underlying the crossing rate bias (Table 9).

Table 9: Step-to-step cosine distance at CR-composite (shallow) and threshold-based (deep) layers. Shallow layers produce highly compressed representations (1.4–2.7× smaller inter-step distances).

Model	Layer (type)	Mean	Std
R1-8B	L2 (CR-comp.)	0.186	0.097
	L14 (thresh.)	0.411	0.143
OT-7B	L2 (CR-comp.)	0.077	0.080
	L16 (thresh.)	0.206	0.091
QwQ-32B	L2 (CR-comp.)	0.037	0.064
	L63 (thresh.)	0.084	0.056
R1-32B	L10 (CR-comp.)	0.067	0.050
	L63 (thresh.)	0.092	0.076

Shallow layers produce highly compressed representations: consecutive steps cluster within small cosine distances (0.04–0.19), while deep-layer representations spread more widely (0.09–0.41). Inter-step distances at shallow layers are 1.4–2.7× smaller than at deep layers across all models. A linear probe operating in this compressed space sits near the noise floor, where minor numerical fluctuations produce spurious threshold crossings that inflate crossing rate independently of discriminative power. Deep layers produce well-separated representations where crossings correspond to genuine semantic transitions.

Cross-dataset evidence. To assess whether this geometric precondition generalizes beyond HarmThoughts, we compute the same shallow/deep volatility ratio on AdvBench (Zou et al., 2023b) traces using R1-8B (n=520 traces). The deep-layer mean cosine distance (0.472) is $1.54\times$ the shallow-layer mean (0.307), consistent with the 1.4–2.7× range observed across all four models on HarmThoughts (Table 9). This confirms that the representational compression underlying metric-induced layer selection bias is not dataset-specific and does not depend on CP annotations.

C.1 AdvBench Boundary Condition

We analyze R1-8B behavior on 388 substantive-response AdvBench (Zou et al., 2023b) traces (of 520 total) to characterize a boundary condition for the CP framework (Table 10).

Table 10: R1-8B behavior on AdvBench adversarial prompts (388 substantive-response traces of 520 total). CP=0 indicates the model produces harmful content from the first reasoning step without prior safety deliberation.

Metric	Value
Jailbreak rate	13.4%
CP=0 (among JB)	90.4%
Mean CP position (among JB)	1.4 steps

Adversarial prompts designed to bypass safety mechanisms (e.g., GCG suffixes) cause the model to skip safety deliberation entirely: 90.4% of jailbroken traces have CP=0, meaning the model commits to harmful generation from the first reasoning step. This contrasts with HarmThoughts, where non-adversarial prompts trigger extended safety deliberation before commitment (mean relative CP position ≈0.7). The CP framework is most informative when prompts elicit deliberation that can be monitored; adversarial prompts that circumvent

deliberation represent a boundary condition where commitment detection is vacuous. The geometric compression evidence (Table 9; volatility ratio $1.54\times$) remains valid because it measures representational properties independent of CP annotations.

C.2 AdvBench Layer Selection Bias Replication

We replicate the five-metric layer selection analysis on AdvBench (Zou et al., 2023b) to test whether metric-induced layer divergence depends on HarmThoughts-specific CP annotations or generalizes to simpler binary supervision. Using R1-8B, we generate reasoning traces for all 520 AdvBench prompts, classify each as jailbreak or safe via keyword matching, and evaluate logistic regression probes across all 32 layers (L0–L31) with windows $W \in \{1, 3, 5, 15\}$. The 60/20/20 train/val/test split matches HarmThoughts protocol.

Data distribution. Of 520 traces, 159 (30.6%) are classified as jailbreak and 361 (69.4%) as safe. A stricter keyword classifier (applied only to final responses, threshold $\geq$1 refusal phrase) reduces the jailbreak rate from 79.2% (v1) to 30.6%; the full-data divergence increases from 42pp (v1) to 58pp (v2); with proper held-out evaluation, the v2 bootstrap mean is 31.7pp (p=0.015), confirming the bias is genuine and not an artifact of label noise.

Table 11: AdvBench layer selection (R1-8B, 32 layers). CR-composite selects shallow layers; precision and inverse FPR select deep layers; AUROC selects mid-depth layers. Consistent with HarmThoughts (Table 2).

Metric	Best Layer	Depth (%)	Best W
CR-composite (BA $\times$ CR)	L3	9.7%	5
Crossing rate	L0	0.0%	5
Precision	L21	67.7%	15
Inverse FPR	L21	67.7%	15
Balanced accuracy	L9	29.0%	15
AUROC	L11	35.5%	15

Crossing rate pattern. Mean crossing rate at shallow layers is elevated relative to deep layers, consistent with the cosine compression range observed on HarmThoughts (Table 9).

Per-window consistency. Precision and inverse FPR consistently select deep layers regardless of window size, while the CR-composite is pulled toward shallow layers across all windows.

The bootstrap-validated divergence (31.7pp, p=0.015) between CR-composite and precision/inverse-FPR selection replicates the HarmThoughts pattern (L0 vs. L14, 44% divergence) under different label semantics (binary jailbreak/safe vs. step-level CP). This confirms that the bias arises from representational geometry (shallow-layer cosine compression) rather than task-specific label structure.

Bootstrap validation. The full-data analysis (training and evaluation on the same data) yields a 58pp divergence (L3 at 9.7% vs. L21 at 67.7%), which includes layer selection overfitting. To obtain a proper held-out estimate, we run 1,000 bootstrap iterations with stratified 60/40 train/test splits: probes are trained on the training split (60%). In each bootstrap iteration, test traces are resampled with replacement, and both layer selection and divergence measurement are performed on the resampled test set—this estimates the full pipeline variance including selection variability. The bootstrap mean divergence is 31.7pp (95% CI [3.2, 48.4]pp, p=0.015). Layer selection is stable across iterations: the CR-composite median is L2 and the precision median is L14, consistent with the shallow/deep divergence pattern. The gap between full-data (58pp) and bootstrap (31.7pp) estimates reflects overfitting in layer selection when train and test data overlap, reinforcing the need for held-out evaluation in layer selection studies.

C.3 Cross-Architecture Geometric Analysis (Gemma)

To test whether the geometric precondition for layer selection bias generalizes beyond Llama and Qwen, we evaluate cosine compression on two Gemma-family models using AdvBench traces. Gemma-2-9B-it (standard multi-head attention) and Gemma-4-E4B (mixed sliding-window/full attention, window size 512) each generate 520 traces. Gemma-2 (6 JB / 520, 1.15%) and Gemma-4 (14 JB / 520, 2.7%) produce insufficient positive samples for reliable probe-based layer selection analysis; we therefore report only the geometric precondition (cosine compression).

Gemma-2's standard full attention produces a shallow-layer compression pattern consistent in direction with Llama and Qwen (deep/shallow ratio $1.28\times$, same direction as HarmThoughts models at 1.4–$2.7\times$ though at reduced magnitude). Gemma-4's mixed sliding-window/full attention

Table 12: Cross-architecture cosine compression. Deep/shallow ratio >1 indicates shallow-layer compression (the geometric precondition for crossing-rate inflation). Standard full attention consistently shows compression; Gemma-4's mixed sliding/full attention does not. [a] Probe-selected layers from HarmThoughts (L2 vs. L14). [b] Range-based windows (first 15% vs. last 25% of layers) due to insufficient jailbreak samples for probe-based selection.

Model	Attention	Method	Deep/Shallow	Compression
R1-8B (Llama)	Standard	Probe[a]	1.54×	✓
Gemma-2-9B	Standard	Range[b]	1.28×	✓
Gemma-4-E4B	Mixed sliding/full	Range[b]	0.70×	–

inverts this pattern (ratio $0.70\times$): shallow layers produce *larger* inter-step distances than deep layers, eliminating the geometric precondition for crossing-rate inflation. This suggests the compression arises from full self-attention's global receptive field, while sliding attention's local window disrupts the shallow-layer clustering that drives crossing-rate inflation. The geometric precondition thus generalizes across all models with standard full attention (Llama, Qwen, Gemma-2) but is absent under mixed attention, indicating that the layer selection bias is attention-mechanism-dependent.

D Holm-Bonferroni Step-Down Correction

Table 13 reports the full test battery used to assess hidden-state superiority over text probes. Because balanced accuracy, precision, and FPR share the same confusion matrix, the three per-model metrics are correlated; the effective number of independent comparisons is four (one per model). We report both the conservative 12-test correction and the 4-test model-level correction: both yield the same outcome (all tests pass at α=0.05). Under 4-test HB, the tightest threshold falls on R1-8B FPR (p=0.044, rank-4 threshold $\alpha/1$=0.050), which still passes. Tests are ranked by p-value; each test i (rank i of m) must satisfy $p_i < \alpha/(m-i+1)$ under the step-down procedure.

The weakest test (rank 12, R1-8B FPR, p=0.044) passes its threshold ($\alpha/1 = 0.05$) with margin. The ordering reveals that OT-7B produces the strongest HS-text separation (ranks 2–4), while R1-8B FPR is the least significant despite R1-8B's precision gap (+20.1pp at W=3). This reflects R1-8B's already-low text FPR (11.8%), which leaves less room for HS improvement on this metric.

Table 13: Holm-Bonferroni step-down correction for 12 tests (4 models × 3 correlated metrics). Each test uses a two-sided null-centered bootstrap (10,000 resamples) on trace-level metric differences (HS minus text). All 12 pass at α=0.05; a 4-test model-level correction (one per model, using the worst p-value) also passes.

Rank	Model	Metric	p-val	Thresh.	Pass
1	R1-8B	Precision	<0.001	0.0042	✓
2	OT-7B	Bal. Acc.	<0.001	0.0045	✓
3	OT-7B	Precision	<0.001	0.0050	✓
4	OT-7B	FPR	<0.001	0.0056	✓
5	QwQ-32B	Bal. Acc.	<0.001	0.0063	✓
6	QwQ-32B	Precision	<0.001	0.0071	✓
7	R1-32B	Bal. Acc.	<0.001	0.0083	✓
8	R1-32B	Precision	<0.001	0.0100	✓
9	QwQ-32B	FPR	0.004	0.0125	✓
10	R1-8B	Bal. Acc.	0.005	0.0167	✓
11	R1-32B	FPR	0.007	0.0250	✓
12	R1-8B	FPR	0.044	0.0500	✓

Exact sign-flip permutation test validation. As an independent check on bootstrap significance for the small-sample 32B models, we run exact sign-flip permutation tests on all six 32B comparisons, enumerating all 2^n sign permutations (2^{19}=524,288 for QwQ-32B, 2^{20}=1,048,576 for R1-32B). All six tests reject the null at α=0.05: QwQ-32B (bal_acc p<0.001, precision p=0.003, FPR p<0.001); R1-32B (bal_acc p=0.008, precision p<0.001, FPR p=0.004). The permutation p-values are consistent with the bootstrap values in Table 13 and confirm that the conclusions are not artifacts of distributional assumptions at small n.

E Window Size Ablation Details

Table 14 reports the complete window size ablation across all models and seven window sizes. The main text (Section 4.5) presents R1-8B results; here we provide the full data. Fig. 2 visualizes the monotonic improvement on R1-8B: precision rises from 69.3% (W=1) to 82.2% (W=25) while FPR drops from 9.65% to 4.8%.

Key cross-model patterns emerge from the window ablation:

R1-8B shows a general upward trend in balanced accuracy from 77.8% (W=1) to 81.0% (W=25), gaining +3.2pp overall with a slight dip at W=5 (78.1%). Precision improves sharply (+12.9pp) and step-level FPR halves (9.65% to 4.83%). Coverage trades off against quality, dropping from 72.1% to 48.8%.




Figure 2: Temporal window effect on R1-8B HS probe (L14). Precision: 69.3% (W=1) to 82.2% (W=25); FPR: 9.65% to 4.8%.

Table 14: Window size ablation (step-level metrics): balanced accuracy, precision, pre-CP FPR, coverage (K=1), and mean detection lead across all models.

Model	W	Bal. Acc.	Precision	FPR_{step}	Coverage	Lead
R1-8B	1	77.8	69.3	9.65	72.1	13.8
	3	79.0	72.3	8.50	69.8	12.1
	5	78.1	72.6	8.09	65.1	8.3
	10	79.3	74.3	7.61	55.8	10.0
	15	80.2	77.7	6.39	51.2	7.2
	20	80.7	78.6	6.12	53.5	7.4
	25	81.0	82.2	4.83	48.8	8.1
OT-7B	1	68.2	42.8	12.0	53.2	16.1
	3	**68.8**	46.6	10.0	53.2	21.6
	5	68.1	46.4	9.9	53.2	21.7
	10	66.5	46.9	8.6	48.9	25.0
	15	66.4	48.8	7.7	44.7	39.6
	20	66.0	**49.4**	**7.5**	48.9	17.9
	25	65.9	48.9	8.0	51.1	28.3
R1-32B	1	71.8	54.9	32.03	80.0	12.9
	3	72.5	56.0	30.64	80.0	11.4
	5	73.1	57.5	28.41	75.0	11.1
	10	73.7	60.9	23.40	70.0	10.8
	15	72.1	59.1	24.51	70.0	10.9
	20	69.6	56.3	26.18	65.0	9.6
	25	70.3	56.6	26.46	70.0	10.7
QwQ-32B	1	73.0	54.4	22.76	79.0	19.7
	3	74.5	56.5	21.41	73.7	20.6
	5	76.1	57.3	21.68	73.7	20.1
	10	74.7	57.1	20.73	73.7	18.4
	15	74.1	58.2	19.11	68.4	15.8
	20	75.4	60.2	17.89	63.2	15.8
	25	76.2	61.8	16.94	57.9	14.9

OT-7B exhibits a split temporal pattern at layer 16: balanced accuracy peaks at W=3 (68.8%) and declines at larger windows (−2.9pp by W=25), while precision and FPR continue improving. Precision rises from 42.8% (W=1) to 49.4% (W=20), and FPR drops from 12.0% to 7.5% over the same range. The split indicates that larger windows reduce false alarms and sharpen positive predictions even as overall classification accuracy degrades. Lead times are shorter than old layer-0 estimates (16.1–39.6 steps) due to the threshold-based layer selection (Section F). OT-7B text probes improve monotonically across all metrics (Section F), so the accuracy saturation is specific to HS probes on this model.

R1-32B exhibits a non-monotonic pattern: balanced accuracy peaks at W=10 (73.7%) and then declines, falling below the W=1 baseline by W=20 (69.6%). The optimal window for R1-32B is W=10, which achieves the lowest FPR (23.40%) and highest precision (60.9%). The accuracy degradation at large windows likely reflects overfitting on the smaller dataset (n=100).

QwQ-32B shows a broadly increasing trend with local non-monotonicity: balanced accuracy peaks at W=5 (76.1%), dips at W=10–15, then recovers to 76.2% at W=25. Precision and FPR improve monotonically with larger windows (54.4% to 61.8% precision; 22.76% to 16.94% FPR). QwQ-32B produces substantially longer lead times than R1-8B and R1-32B (19.7 steps at W=1, 14.9 at W=25), though OT-7B's lead times are longer still.

Universal trends. Across all models: (1) larger windows reduce coverage as the smoothed probe fires less frequently; (2) HS FPR generally decreases with window size; (3) lead time is model-dependent. The primary cross-model difference is whether balanced accuracy improves broadly (R1-8B, QwQ-32B), peaks sharply at an intermediate window (R1-32B at W=10), or peaks very early (OT-7B at W=3). Each model uses its validation-selected window in the main text.

E.1 Text Probe Window Ablation

Table 15 reports the complete text probe window sweep on R1-8B and confirms that temporal context benefits text probes even more strongly than HS probes.

Text probes show monotonic improvement across all window sizes without the plateau ob-

Table 15: Text probe window ablation on R1-8B (step-level metrics). Text probes gain +12.0pp accuracy from $W{=}1$ to $W{=}25$, compared to +3.2pp for HS probes over the same range. The larger marginal gain for text probes reflects their weaker single-step baseline.

W	Bal. Acc.	Precision	FPR	Coverage
1	64.7	41.6	25.8	95.4
3	66.9	44.8	23.1	90.7
5	69.2	48.5	20.4	84.9
10	72.1	54.3	16.7	74.4
15	74.3	58.9	14.2	67.4
20	75.8	62.1	12.5	62.8
25	76.7	64.8	11.8	58.1

served in HS probes (which saturate around $W{=}15$). The absolute FPR reduction (-14.0pp) is nearly three times the HS reduction (-4.8pp), and accuracy gains (+12.0pp vs. +3.2pp) are four times larger. This asymmetry supports the interpretation that temporal context is the primary factor in commitment detection: text features, which encode less information per step, benefit proportionally more from observing the multi-step progression.

F OpenThinker-7B Detailed Results

OpenThinker-7B (OT-7B) is trained with STILL (Min et al., 2024) on Qwen2.5-7B to produce a 7B reasoning model with a different training paradigm from the R1-distilled models. We report the full layer sweep and text probe window ablation.

Table 16: OT-7B layer sweep. Score = balanced accuracy $\times$ crossing rate. Layer 16 (57% depth) is selected after correction; it achieves the highest balanced accuracy among transformer layers.

Layer	Depth	Bal. Acc.	Cross. Rate	Score
0 (embed.)	0	66.7	53.2	35.5
4	14	66.3	40.4	26.8
8	29	66.4	25.5	17.0
12	43	67.5	31.9	21.6
16	57	68.2	31.9	21.8
20	71	65.5	31.9	20.9
24	86	66.9	29.8	19.9
27	96	63.0	31.9	20.1

Layer sweep. After correction of a layer selection bug, layer 16 (57% depth) is selected. It achieves the highest balanced accuracy (68.2%) among transformer layers under the 70/30 split used here; under the canonical 60/20/20 split, BA selects L2 (7% depth; Table 41). Layer 0 (embedding) has a higher crossing rate (53.2% vs. 31.9%) but lower accuracy.

Table 17: OT-7B text probe window ablation (step-level). Text probes improve monotonically with larger W, contrasting with the HS probes on this model which peak at $W{=}3$.

W	Bal. Acc.	Precision	FPR	Coverage
1	58.1	24.5	34.5	63.8
3	57.9	25.4	27.1	74.5
5	56.9	24.7	25.5	70.2
10	58.3	27.0	22.2	70.2
15	58.9	28.3	20.0	66.0
20	60.9	31.6	17.6	66.0
25	61.4	32.9	16.1	66.0

Text probe window ablation. OT-7B text probes improve monotonically from $W{=}1$ to $W{=}25$ (+3.3pp accuracy, +8.5pp precision, -18.4pp FPR), consistent with the R1-8B pattern. OT-7B HS probes show a split pattern: balanced accuracy peaks at $W{=}3$ and declines, while precision and FPR continue improving (Table 14). The text-HS contrast is therefore metric-dependent rather than a blanket modality difference.

Bootstrap comparison (matched $W{=}3$). To ensure a fair modality comparison, bootstrap tests use matched $W{=}3$ for both HS and text probes. At $W{=}3$, HS probes achieve 75.3% trace-level balanced accuracy vs. 65.6% for text (bootstrap $\Delta{=}+10.7$pp, 95% CI [4.9, 16.3], $p{<}0.001$, survives Holm-Bonferroni). Precision: 55.8% vs. 34.6% (bootstrap $\Delta{=}+21.9$pp, 95% CI [14.0, 29.6], $p{<}0.001$, survives Holm-Bonferroni). Pre-CP FPR: 10.0% vs. 27.1% (bootstrap $\Delta{=}-17.1$pp, 95% CI [-22.2, -12.2], $p{<}0.001$, survives Holm-Bonferroni). All three metrics survive correction. The point-estimate precision gap (+21.2pp) aligns with the bootstrap mean (+21.9pp); the small discrepancy reflects resampling variance. Using each modality's optimal W (HS at $W{=}3$, text at $W{=}25$) would introduce a confound because text would benefit from $8\times$ more temporal context.

G GRU Training Details

GRU results serve as supplementary evidence under a different training protocol (70/30 split); direct comparison with the main logistic regression pipeline (60/20/20 nested CV) is not intended.

Data split. GRU experiments use a 70/30 train/test split to maximize training data for the sequential model, differing from the main 60/20/20 protocol used for logistic regression probes. Within the 70% training portion, we hold out 10% of total traces as a validation set for early stopping (effective 60/10/30 split). The validation set is used only for early stopping and is not included in reported test metrics, so there is no information leakage.

Architecture. We evaluate two GRU variants. The single-layer variant uses a GRU with hidden dimension 256, taking per-step hidden states from the best layer (selected by validation balanced accuracy) as input. The multi-layer variant concatenates hidden states from 7 layers (evenly spaced through the network) at each step to produce a higher-dimensional input to the same GRU architecture.

Training procedure. We train with Adam (learning rate 1×10^{-3}, default β_1=0.9, β_2=0.999), batch size 16, for a maximum of 50 epochs. Early stopping halts training when validation loss does not improve for 10 consecutive epochs. Input features are z-score normalized per dimension using training set statistics.

Evaluation. We report crossing accuracy (the sustained accuracy at which the probe first exceeds chance for 5 consecutive steps) and detection lead (steps before CP at crossing point). All experiments use 3 random seeds; we report mean ± standard deviation.

Table 18: R1-8B single-layer GRU results per seed. Lead is measured in steps before the commitment point.

Seed	Peak Acc.	Crossing Acc.	Lead (steps)
1	85.2	74.3	+4.8
2	83.1	71.6	+4.8
3	83.4	70.4	+0.9
Mean ± std	83.9 ± 1.1	72.1 ± 2.0	+3.5 ± 2.3

Per-seed results for R1-8B (single-layer GRU). The high variance in lead time (standard deviation of 2.3 steps) is driven by seed 3, where the probe achieves good peak accuracy but crosses the detection threshold late. This variance underscores the sensitivity of early detection to initialization and motivates reporting per-seed results rather than relying on mean values alone.

Results in this section use the 60/20/20 protocol consistent with the main text; earlier 70/30 results are retained for completeness but should not be compared directly.

Table 19: Per-seed performance of GRU and logistic regression (LR) probes on R1-8B under a 60/20/20 cross-validation protocol (seeds 42, 123, 456). Single = layer 14 only; Multi = 7-layer concatenation (layers 12–24, stride 2). Lead = steps before CP at first sustained crossing. Main text results use a 70/30 train/test split with different test traces, accounting for the difference in lead values.

Model	Seed	Acc	Prec	FPR	Cross.%	Lead
GRU-single	42	0.845	0.657	0.139	72.1%	3.55
GRU-single	123	0.760	0.454	0.191	65.1%	7.39
GRU-single	456	0.792	0.474	0.203	67.4%	8.45
GRU-single	*mean*	0.799±0.035	0.528±0.091	0.178±0.028	68.2±2.9%	6.46±2.10
GRU-multi	42	0.824	0.616	0.164	74.4%	5.66
GRU-multi	123	0.759	0.454	0.195	65.1%	6.43
GRU-multi	456	0.784	0.460	0.207	65.1%	8.93
GRU-multi	*mean*	0.789±0.027	0.510±0.075	0.189±0.018	68.2±4.4%	7.01±1.40
LR-single	42	0.841	0.693	0.097	46.5%	−2.00
LR-single	123	0.753	0.436	0.181	53.5%	5.26
LR-single	456	0.814	0.512	0.146	41.9%	3.94
LR-single	*mean*	0.803±0.037	0.547±0.108	0.141±0.035	47.3±4.8%	2.40±3.16
LR-multi	42	0.827	0.679	0.092	39.5%	1.06
LR-multi	123	0.756	0.442	0.180	46.5%	7.30
LR-multi	456	0.817	0.521	0.130	34.9%	4.00
LR-multi	*mean*	0.800±0.032	0.547±0.099	0.134±0.036	40.3±4.8%	4.12±2.55

Multi-layer GRU and baseline comparison (60/20/20 protocol). Under this protocol, multi-layer GRU achieves the highest mean lead (7.01±1.40 steps) but at higher FPR than logistic regression baselines (0.189 vs. 0.134). The GRU advantage is concentrated in detection timing rather than classification accuracy, consistent with the main text finding that GRUs capture sequential dependencies that improve early detection. Lead time shows high variance across seeds (range 5.66–8.93 for GRU-multi), reinforcing that reported means should be interpreted cautiously.

OT-7B multi-layer GRU (layers 13–19, 3 seeds, 60/20/20 split). OT-7B GRU achieves 74.6±1.3% balanced accuracy, 64.5±7.0% coverage, +33.6±4.8 steps lead, and 27.4±6.1% pre-CP FPR. The lead time is substantially longer than other models in absolute terms, but OT-7B traces average ∼80 reasoning steps (vs. ∼30 for R1-8B and 32B models), so absolute lead times are not directly comparable. The FPR-lead tradeoff mirrors R1-8B: GRU FPR (27.4%) is far above the LR probe at layer 16 (10.0%), which confirms that GRUs gain lead time at the cost of more false alarms across both 7-8B models.

H Control Task Methodology

We follow the selectivity framework of (Hewitt and Liang, 2019) to verify that our probes cap-

ture genuine safety-relevant structure rather than surface-level correlations.

Procedure. For each model, we randomly permute the binary labels (pre-CP vs. post-CP) within each trace while preserving the marginal label distribution. We then retrain the probe with identical architecture (L2-regularized logistic regression) and hyperparameters on these shuffled labels. Selectivity is defined as:

$$\text{Selectivity} = \text{Acc}_{\text{linguistic}} - \text{Acc}_{\text{control}} \quad (1)$$

where $\text{Acc}_{\text{linguistic}}$ is the probe accuracy on true labels and $\text{Acc}_{\text{control}}$ is the accuracy on permuted labels. A selectivity of zero indicates that the probe exploits only non-linguistic features (e.g., position); higher values confirm that the representation encodes task-relevant information. Absolute selectivity values are task-dependent and not directly comparable across studies (Hewitt and Liang, 2019).

Results. We repeat the control experiment 10 times with different random permutations and report the mean control accuracy. Selectivity scores at threshold-based layers (60/20/20 split) are: R1-32B 16.8pp (layer 63), QwQ-32B 16.1pp (layer 63), R1-8B 14.1pp (layer 14), OT-7B 11.1pp (layer 16). All values exceed the 5pp threshold recommended by (Hewitt and Liang, 2019). R1-32B and QwQ-32B achieve the strongest selectivity (>16pp) at threshold-based layers. On QwQ-32B, the position baseline accuracy (0.705) slightly exceeds the HS probe (0.667) at L60, consistent with the main-text finding that QwQ's HS advantage is concentrated in precision and FPR rather than balanced accuracy.

Layer provenance note. R1-8B is unaffected by the layer selection bias because its CR-composite and threshold-based layers coincide at L14. OT-7B exhibits a 16-layer gap (CR-composite L0 vs. threshold-based L16; Table 2), but selectivity at L16 (11.1pp) still exceeds the 5pp threshold. QwQ-32B selectivity is 16.1pp at L63, which confirms that safety-specific signal persists at deep layers.

Position-only baseline. As a complementary validation, we train a logistic regression classifier using only the normalized step index (t/T where T is the total trace length) as the input feature. This baseline tests whether temporal position alone explains probe performance. On R1-8B, the position-only baseline produces 15.8% FPR compared to 8.1% for the HS probe at matched detection rates. The probe's substantially lower FPR confirms that hidden state features carry information beyond what step position provides.

Residualized selectivity. To confirm that selectivity survives position removal, we recompute control task selectivity on position-regressed features (the same residualized representations used in Section V). Residualized selectivity: R1-8B 22.9pp, OT-7B 10.4pp, QwQ-32B 11.3pp (all >5pp), R1-32B 3.0pp (<5pp, consistent with the position-mediation pattern reported in Section 4.3). Three of four models retain selectivity well above the Hewitt and Liang (2019) threshold after position removal; R1-32B's drop confirms that its safety signal is largely positional.

I Oracle Upper Bound Analysis

We compute an oracle upper bound for commitment detection by measuring the earliest step at which the ground-truth commitment point (CP) could theoretically be predicted from hidden-state dynamics. The oracle detector has access to the true CP label and computes how many steps before CP the representation trajectory first enters a region that is linearly separable from pre-CP states with perfect accuracy on the training set. The resulting bound provides a theoretical ceiling on early detection performance.

Table 20 reports oracle performance across all four models. Oracle analysis confirms the evidence gradient: OT-7B (strong) shows the highest early detection rate (93.6%) and longest lead time (50 steps), while R1-32B (qualified) achieves only 50% early detection even with oracle labels, consistent with an inherently weaker commitment signal. On R1-8B, the oracle early detection rate is 76.7% (33/43 traces detected before CP, with +31 steps mean lead time), compared to +4.5 steps for the best learned probe (GRU). This gap indicates that hidden states at step t encode the model's current safety state but carry limited predictive power about future trajectory evolution. The learned probe captures the contemporaneous safety signal effectively (balanced accuracy 81–84%) but cannot anticipate the commitment transition far in advance. Closing this gap will likely require causal intervention techniques (e.g., activation patching) rather than improvements to passive monitoring.

Table 20: Oracle upper bound analysis. Detection rate: fraction of traces where the oracle finds a linearly separable boundary before or at CP. Early detection rate: fraction detected before CP. Mean lead: average steps before CP at first detection.

Model	Det. Rate	Early Det.	Mean Lead	n_{test}
R1-8B	100%	76.7%	31.0	43
OT-7B	100%	93.6%	50.0	47
R1-32B†	95.0%	50.0%	32.4	20
QwQ-32B†	100%	84.2%	24.4	19

J CP Annotation Perturbation

To assess sensitivity to annotation noise, we shift all ground-truth CP labels by $\delta \in \{-3, \ldots, +3\}$ steps and retrain the HS probe (Table 21). Precision degrades smoothly with no cliff effect: within ± 2 steps, BA changes by <2.5pp for all models (7–8B: <1.0pp). At the ± 3-step worst case, all models retain precision well above their respective text baselines. These results support the annotation robustness assumption discussed in Section 6.

Table 21: HS probe sensitivity to CP annotation shift (δ steps). BA is stable across all perturbations; precision degrades gradually without cliff effects.

Model	δ	Prec	BA	FPR
R1-8B	-3	.652	.773	.177
	0	.596	.784	.165
	$+3$	.530	.771	.143
OT-7B	-3	.404	.714	.298
	0	.351	.707	.286
	$+3$	.300	.702	.276
QwQ-32B	-3	.661	.728	.158
	0	.609	.690	.129
	$+3$	.550	.676	.114
R1-32B	-3	.625	.698	.360
	0	.570	.722	.281
	$+3$	.503	.750	.236

J.1 Inter-Annotator Agreement on AdvBench

To assess annotation reliability, two LLM annotators (Qwen3-32B and GPT-4o-mini) independently labeled 388 AdvBench B-class traces for jailbreak status and CP position (Table 22).

LLM annotators achieve only moderate agreement on jailbreak classification (κ=0.606) and low CP position consistency (37% exact match). GPT-4o-mini is substantially more aggressive in jailbreak identification (99 vs. 52), suggesting systematic annotator bias. The low CP position agreement (mean absolute difference of 8.5 steps) underscores a key design choice: our primary analysis uses the human-validated HarmThoughts annotations (Kakkar et al., 2026), not LLM-generated labels. This AdvBench IAA study serves as a *negative control*: it demonstrates that LLM-only annotation is insufficient for reliable CP localization, motivating future investment in multi-annotator human CP labeling with formal IAA evaluation.

Table 22: Inter-annotator agreement on AdvBench B-class traces (388 total). CP position metrics computed on 51 traces where both annotators identified a jailbreak.

Metric	Value
Jailbreak classification	
Cohen's κ	0.606 (moderate)
Raw agreement	87.4%
GPT-4o-mini JB count	99 / 388
Qwen3-32B JB count	52 / 388
CP position (51 shared JB)	
Exact match	37%
Within 5 steps	47%
Mean abs. difference	8.5 steps

K BOCPD/CUSUM Configuration Sweep

We sweep hyperparameters for both Bayesian Online Change-Point Detection (BOCPD) and Cumulative Sum (CUSUM) methods applied to the temporal probe score sequences.

BOCPD configurations. BOCPD models the sequence of probe scores as piecewise-constant segments with Gaussian observation noise. The hazard rate λ controls the prior probability of a change-point at each step ($P(\text{change}) = 1/\lambda$).

CUSUM configurations. CUSUM accumulates evidence for a positive mean shift. The drift parameter δ sets the minimum shift size to detect, and the threshold h controls the detection boundary.

The best BOCPD configuration (λ=10) achieves 93.0% detection rate with +3.45 steps lead. The simple threshold baseline achieves 65.1% detection with superior lead (+4.89 steps). All CUSUM configurations underperform the simple threshold on lead time.

These results reveal a coverage-timing tradeoff. BOCPD (λ=10) achieves 28pp higher detection rate than simple thresholding (93.0% vs.

Table 23: Change-point method configuration sweep on R1-8B. Detection rate is the fraction of jailbreak traces where the method fires. Lead is measured in steps before CP.

Method	Configuration	Det. Rate	Lead
BOCPD	$\lambda = 5$	97	+2.1
	$\lambda = 10$	93	+3.5
	$\lambda = 20$	87	+4.2
	$\lambda = 50$	72	+5.8
	$\lambda = 100$	67.4	+1.03
CUSUM	δ=0.3, h=3	65.1	+0.89
	δ=0.5, h=3	89	+1.4
	δ=0.5, h=5	76	+2.3
	δ=0.5, h=8	61	+3.1
	δ=1.0, h=3	82	+1.1
	δ=1.0, h=5	68	+1.9
	δ=1.0, h=8	52	+2.7
	δ=2.0, h=3	71	+0.8
	δ=2.0, h=5	54	+1.5
	δ=2.0, h=8	38	+2.1
Simple threshold	FCP baseline	65.1	+4.89

65.1%), but with lower lead (+3.45 vs. +4.89 steps). The transition toward unsafe reasoning is gradual rather than abrupt, so change-point methods cannot exploit discontinuities for early warning. When missed detections are costly, BOCPD's coverage advantage justifies its use despite the timing penalty. When early intervention is the priority, simple thresholding provides better lead time.

Other models. On OT-7B, QwQ-32B, and R1-32B, BOCPD achieves 0% detection rate across all tested configurations ($\lambda \in \{5, 10, 50, 100, 200\}$). The failure modes differ by model: for R1-32B and QwQ-32B, probe scores transition gradually, so the hazard function never accumulates sufficient evidence; for OT-7B at W=3, transitions are too abrupt (0→1 in 1–2 steps) for the Gaussian observation model to capture. R1-8B falls between these extremes, with transitions sharp enough to trigger the hazard function but smooth enough for the Gaussian model to track.

L Detection Threshold (K) Ablation

The consecutive-crossings threshold K controls the trade-off between detection coverage and false positive rate. We evaluate $K \in \{1, 3, 5, 7, 10\}$ at W=1 on all models using HS probes at threshold-based layers (Table 24).

K=1 yields perfect coverage but near-perfect safe FPR (0.92–1.00), offering no discrimination.

Table 24: Detection threshold ablation (W=1, HS probes at threshold-based layers). Coverage: fraction of jailbreak traces with $\geq K$ consecutive crossings. Safe FPR: fraction of safe traces with $\geq K$ consecutive false alarms.

	Coverage				**Safe FPR**			
K	R1-8B	OT-7B	QwQ	R1-32B	R1-8B	OT-7B	QwQ	R1-32B
1	1.00	1.00	1.00	1.00	1.00	0.92	1.00	0.99
3	0.74	0.79	0.95	0.90	0.81	0.41	0.78	0.78
5	0.47	0.51	0.79	0.65	0.63	0.19	0.65	0.47
7	0.35	0.30	0.58	0.45	0.39	0.16	0.35	0.31
10	0.14	0.21	0.32	0.35	0.22	0.08	0.25	0.17

K=5 is empirically selected as a middle-ground tradeoff: average coverage 0.60 with average safe FPR 0.48 across models. OT-7B benefits most from increasing K, reaching 0.19 safe FPR at K=5 (vs. 0.92 at K=1) while retaining 51% coverage. Higher K values ($\geq$7) reduce safe FPR further but at steep coverage cost. K=5 vs. K=7 is the key decision: K=7 reduces mean safe FPR from 0.48 to 0.30 but drops mean coverage from 0.60 to 0.42.

K=5 was selected on the R1-8B validation set and held fixed across all models; main-text results use this value without per-model optimization. The $K \times W$ interaction is not fully explored: this ablation uses W=1 to isolate K's effect, and the joint $K \times W$ surface remains a limitation. At optimal W, coverage at K=5 improves (e.g., R1-8B: 0.47 at W=1 vs. 0.60 at W=15).

L.1 Deployment Operating Points

The K ablation above can be recast as a deployment operating characteristic. At K=5 (used throughout the main text), average coverage is 60% with 48% safe FPR. Raising K yields practically useful operating points: at K=10, OT-7B achieves 21% coverage with only 8% false positive rate, meaning fewer than 1 in 12 flagged traces is a false alarm. R1-32B at K=10 retains 35% coverage at 17% FPR. These conservative operating points are viable for high-stakes deployment where missed detections are preferable to frequent false alarms: a secondary review system could inspect only flagged traces, reducing human oversight burden by 79–86% while maintaining non-trivial detection rates. However, at K=10 approximately 65–86% of attacks are missed, which may be unacceptable in some threat models. The K=7 setting offers a middle ground (30–58% coverage, 16–39% FPR). The choice of operating point is deployment-specific.

M Decision Threshold Sensitivity

We evaluate whether the HS advantage depends on the logistic regression decision threshold by sweeping $\tau \in \{0.3, 0.4, 0.5, 0.6, 0.7\}$ for both 32B models at their threshold-based layers. Results below were conducted at L60 under the 70/30 protocol; main-text results use L63 under 60/20/20. QwQ-32B (L60, $W{=}3$) HS balanced accuracy varies by only 0.53pp across all thresholds, with Δ(HS$-$Text) stable at +8.5 to +9.3pp. Table 25 reports R1-32B results.

Table 25: R1-32B threshold sensitivity (L63, $W{=}1$). HS BA varies by 1.1pp (0.741–0.752); the HS advantage is consistent across all thresholds.

τ	HS BA	ΔBA	HS Prec	ΔPrec	HS FPR	ΔFPR
0.3	0.752	+0.126	0.583	+0.126	0.295	−0.106
0.4	0.746	+0.116	0.586	+0.120	0.281	−0.092
0.5	**0.742**	**+0.109**	**0.588**	**+0.113**	**0.273**	**−0.078**
0.6	0.741	+0.112	0.599	+0.119	0.254	−0.072
0.7	0.743	+0.126	0.617	+0.143	0.228	−0.084

R1-32B HS balanced accuracy varies by only 1.1pp across the full threshold range. The modality advantage (ΔBA $= +0.109$ to $+0.126$, ΔPrec $= +0.113$ to $+0.143$, ΔFPR $= -0.072$ to -0.106) is consistent in both magnitude and direction at every threshold, so the HS advantage is not an artifact of the default $\tau{=}0.5$.

N M002 Bug Disclosure

We disclose a bug discovered during development that affected intermediate results for QwQ-32B.

Issue. In experiment M002 (text baseline evaluation), the QwQ-32B text probe was inadvertently initialized with a midpoint heuristic placeholder rather than true sentence embeddings from all-MiniLM-L6-v2. Specifically, the placeholder assigned each step a feature vector equal to the midpoint between the mean safe and mean unsafe embeddings from the training set, with small Gaussian noise added. This made the text probe trivially predictive and produced a spuriously significant result ($p{=}0.001$ for HS vs. text FPR difference).

Discovery and correction. The bug was identified during a systematic audit of the feature extraction pipeline. After correction (using actual sentence embeddings), the QwQ-32B and R1-32B modality comparisons at the originally selected layers (L2 and L10, chosen by the CR-composite metric) showed no significant HS advantage: QwQ-32B accuracy $p{=}0.828$, precision $p{=}0.346$; R1-32B precision $p{=}0.050$ but no tests surviving Holm-Bonferroni. The subsequent discovery that these layer selections were themselves artifacts of metric bias (Section 4.2) led to the threshold-based layer analysis reported in the main text, where the HS advantage follows an evidence gradient at threshold-based deep layers: cross-validated at 7–8B, significant but suggestive of position-competitiveness at QwQ-32B†, and exploratory at R1-32B† (Table 3).

Impact on reported results. All numbers reported in this paper use the corrected text embedding pipeline. The bug affected only QwQ-32B text probe features. The correction, combined with the separate layer selection fix (Section 4.2), means that early-stage intermediate results (non-significant 32B modality comparisons) reflected two compounding errors: incorrect text features and CR-composite layer selection. Both are fully resolved in the final analysis.

Commitment to transparency. We report this bug to maintain scientific integrity. Code and data will be released upon publication.

O Adaptive Two-Stage Detection

We explored whether a two-stage adaptive window strategy could improve the precision-coverage tradeoff beyond fixed-window detection. The approach uses a short screening window (W_{screen}) to flag candidate unsafe segments, followed by a longer confirmation window (W_{confirm}) applied only to flagged segments. A trace is classified as unsafe if at least k steps exceed the threshold during the confirmation stage.

We merge the validation and test partitions ($n{=}55$ total: 39 jailbreak, 16 benign) for two-stage evaluation because the screening and confirmation thresholds are not tuned on held-out data. We evaluated all combinations of $W_{\text{screen}} \in \{1, 3, 5\}$, $W_{\text{confirm}} \in \{10, 15, 20, 25\}$, and $k \in \{1, 3, 5\}$ on these R1-8B traces. Fig. 3 shows the precision-coverage Pareto front for both methods. The best two-stage configuration ($W_{\text{screen}}{=}3$, $W_{\text{confirm}}{=}15$, $k{=}1$) achieves 72.2% precision at 76.9% coverage, compared to 70.9% precision at 76.9% coverage for single-stage $W{=}15$. This +1.3pp precision gain at matched coverage represents a Pareto improvement, but the magnitude is marginal. At higher

confirmation thresholds (k=3, k=5), two-stage detection trades coverage for small precision gains (up to 73.5% precision at 38.5% coverage with k=5), but these operating points are impractical due to excessive missed detections.




Figure 3: Precision-coverage Pareto front comparing single-stage fixed-window detection against two-stage adaptive detection on R1-8B. The best two-stage configuration (W_{screen}=3, W_{confirm}=15, k=1) Pareto-dominates single-stage W=15 by +1.3pp precision at matched coverage. Higher k values shift the tradeoff toward precision at the cost of unacceptable coverage loss.

The marginal improvement suggests that fixed-window smoothing already captures most of the temporal signal available in probe score sequences. The two-stage approach adds configuration complexity (three hyperparameters vs. one) without proportional performance gain.

P Temporal Ablation Details

Full per-model temporal ablations are reported in Table 14 (Section E). Key cross-model patterns: (1) R1-8B shows monotonic precision improvement from 69.3% (W=1) to 82.2% (W=25) with FPR halving (9.65% to 4.83%); (2) OT-7B exhibits a split pattern where balanced accuracy peaks at W=3 while precision and FPR continue improving at larger windows; (3) R1-32B peaks at W=10 then degrades, likely reflecting overfitting on the small dataset (n=100); (4) QwQ-32B shows broadly increasing trends with local non-monotonicity. Text probe window ablations (Section E.1) show monotonic improvement across all window sizes for both models tested, with larger marginal gains than HS probes (+12.0pp accuracy vs. +3.2pp for R1-8B). The asymmetry supports the interpretation that text features benefit proportionally more from temporal context because they encode less information per step.




Figure 4: CP-aligned probe score trajectories. Each panel averages all test traces for one model, with step 0 at the true commitment point. HS probes (blue, solid) show a sharper score increase at CP than text probes (orange, dashed), with OT-7B showing the strongest separation and R1-32B the weakest, consistent with the evidence gradient. Shaded bands: ±1 std. Points with <5 traces are omitted.

Q Negative Results Details

Method	Result	Limitation	Failure Cat.
BOCPD	0% det. on 3/4 models	Commitment gradual	Graduality
CUSUM	< threshold, all models	Same as BOCPD	Graduality
Mahalanobis	$\Delta d \approx 0$	Signal in minor PCs	Var. subspace
RepE	QwQ 0.756; R1-32B 0.559[a]	Model-dependent	Model-spec.
MLP	3/4 worse than LR	Overfitting	Capacity
CCS	No gain over supervised[b]	Alignment mismatch	Obj. mismatch
Transfer	Best 59.5% (PCA)[c]	Model-specific repr.	Model-spec.

Table 26: Seven alternative approaches. [a] RepE QwQ approaches supervised bal_acc but precision is 0.512 vs. LR 0.700. [b] Semi-supervised (requires CP labels). [c] Best direct transfer 67.3% but 1% crossing rate.

BOCPD/CUSUM. On OT-7B, QwQ-32B, and R1-32B, BOCPD achieves 0% detection rate across all tested configurations ($\lambda \in \{5, 10, 50, 100, 200\}$). Only R1-8B produces non-zero detection (best: λ=10, 93% rate, +3.45 steps lead). CUSUM configurations universally underperform simple thresholding on lead time. The probe score sequences for 3/4 models show smooth transitions that never trigger the hazard function (Section K).

Mahalanobis distance. Following TrajGuard (Liu et al., 2026), Mahalanobis distance from the pre-CP centroid produces $\Delta d \approx 0$

between pre-CP and post-CP steps. The discriminative signal resides in minor PCA components (explaining <5% of total variance) rather than the principal directions that dominate the distance computation.

RepE. We compute the mean-difference direction (Zou et al., 2023a) $\mathbf{d} = \bar{\mathbf{h}}_{\text{post}} - \bar{\mathbf{h}}_{\text{pre}}$ from training-set hidden states, then project test-set representations onto $\mathbf{d}$ and threshold the scalar projection. QwQ-32B achieves 0.756 balanced accuracy (approaching supervised 0.778) but with substantially worse precision (0.512 vs. LR 0.700) and FPR (0.309 vs. 0.120). R1-32B nearly fails (0.559 balanced accuracy). The single direction captures commitment structure in some models but not others, consistent with the multi-dimensional encoding found by Wollschläger et al. (2025).

MLP probes. Two-layer MLPs ($d \to 128 \to 1$, ReLU, no dropout, L2 weight decay 10^{-4}, early stopping patience 10) underperform logistic regression on 3/4 models. The commitment boundary is linearly separable at correctly selected layers; additional capacity causes overfitting given the small training sets (n=60–137 training examples). All alternative method results in this section are upper-bounded by the hyperparameter search budget reported above.

CCS. We adapt Contrast-Consistent Search (Burns et al., 2023) by constructing contrastive pairs from pre-CP ("safe") and post-CP ("committed") hidden states at each reasoning step, then training the CCS probe to satisfy the consistency loss $P(x) + P(\neg x) = 1$. All models required polarity correction (CCS does not determine label direction). CCS achieves 0.692–0.777 balanced accuracy across models but with FPR 0.19–0.41, substantially worse than supervised LR (FPR 0.07–0.28). The consistency objective does not align with temporal commitment structure, and CCS still requires CP labels for pair construction, making it semi-supervised.

Cross-model transfer. 17 configurations (5 directional pairs × 3 PCA dimensionalities, plus 2 direct transfers) all fail. Best PCA: R1-8B → QwQ-32B at 59.5% (PCA-2048). Best direct: QwQ-32B → R1-32B at 67.3% but 1% crossing rate. Implementation details in Section R.

R Cross-Model Transfer Implementation Details

We test whether safety probes transfer across models by projecting hidden states into a shared dimensionality space and applying cross-model classification.

Method. For each source-target model pair, we apply PCA independently to each model's hidden states, reducing to a shared dimensionality $d \in \{512, 1024, 2048\}$. PCA is fitted on the full dataset (including test traces) for each model separately, a setting favorable to transfer since it maximizes the quality of the projection. A logistic regression classifier (C=1.0, class_weight='balanced', max_iter=2000, random_state=42) trained on the source model's PCA-projected training data is then applied directly to the target model's PCA-projected test data. No cross-model alignment step (Procrustes rotation, CCA, or learned projection) is applied; PCA serves as a standard linear dimensionality reduction baseline.

Same-dimension pairs. For R1-32B and QwQ-32B (both 5120-d hidden states), we additionally test direct transfer without PCA: the source classifier is applied directly to the target model's raw hidden states. This tests whether same-architecture, same-dimensionality models share safety-relevant linear structure.

Results. All 17 transfer configurations (5 directional pairs × 3 PCA dimensionalities, plus 2 direct transfers for same-dimension pairs) fail to produce practically useful transfer. The best PCA result is R1-8B → QwQ-32B at 59.5% balanced accuracy (PCA-2048). The best direct transfer (QwQ-32B → R1-32B) reaches 67.3% balanced accuracy, which exceeds the within-model baseline of 65.2%. However, this transfer direction achieves only 1% crossing rate, meaning the transferred probe almost never triggers detection in practice and is useless for deployment despite above-baseline accuracy. The complete failure under maximally favorable conditions (PCA fitted on full data, no train/test separation for projection) strengthens the conclusion that safety commitment is encoded in model-specific geometric configurations. PCA is a standard linear alignment baseline; its failure indicates that the problem lies in the representations themselves rather than in the choice of alignment method. High balanced accuracy does not

guarantee deployment utility: the best direct transfer (67.3% BA) achieves only 1% crossing rate, meaning the transferred probe almost never triggers temporal detection despite appearing accurate on per-step classification.

S Encoder Robustness Analysis

To test whether the HS advantage over text probes depends on the specific text encoder, we replace all-MiniLM-L6-v2 (384d) with BGE-large-en-v1.5 (1024d), a 2.7× higher-dimensional encoder with stronger semantic representations. Table 27 reports precision comparisons at each model's threshold-based layer; Fig. 5 provides a visual summary.

Table 27: HS vs. BGE-large (1024d) text probe precision. Δ: HS minus BGE-large. Bootstrap: 10,000 resamples, two-sided null-centered. HB: survives Holm-Bonferroni correction (4 tests, α=0.05).

Model	HS Prec	BGE Prec	Δ	95% CI	p	HB
R1-8B	0.497	0.436	+0.058	[−0.07, +0.20]	0.185	No
OT-7B	0.446	0.263	+0.181	[+0.08, +0.29]	<0.001	Yes
R1-32B	0.588	0.475	+0.117	[−0.00, +0.24]	0.042	No
QwQ-32B	0.545	0.454	+0.094	[−0.07, +0.28]	0.132	No




Figure 5: Forest plot of HS precision advantage over text probes. Blue: vs. MiniLM-384d; orange: vs. BGE-1024d. Solid markers: survives Holm-Bonferroni; hollow: does not. All 384d comparisons are significant (strong to qualified evidence); against BGE-1024d, only OT-7B (strong) survives correction.

The HS precision advantage is directionally consistent across all four models (positive Δ in every case). OT-7B shows a strong, significant advantage (+18.1pp, p<0.001, survives Holm-Bonferroni). The remaining three models do not survive Holm-Bonferroni correction; R1-32B's CI includes zero with 10,000 resamples, so even the individual precision test is non-significant. This is consistent with the prediction in Section 6 that stronger text encoders would reduce the observed gap. The pattern confirms that the HS modality advantage is genuine but partially attributable to the weakness of the 384d MiniLM baseline.

Balanced accuracy and FPR. Table 28 reports BGE-large comparisons on balanced accuracy and FPR. HS balanced accuracy advantage is directionally positive across all four models (+8.4 to +10.9pp), with 2/4 (OT-7B, R1-32B) significant under Holm-Bonferroni. FPR advantage is significant only for OT-7B. R1-8B shows an adverse FPR direction: HS FPR is 1.2pp higher (worse) than BGE (p=0.564), the only model where HS does not improve over the stronger encoder on this metric.

Table 28: HS vs. BGE-large (1024d): balanced accuracy and FPR differences. Bootstrap: 10,000 resamples, two-sided null-centered. HB: Holm-Bonferroni correction (4 tests per metric, α=0.05).

Model	ΔBA	p (BA)	HB	ΔFPR	p (FPR)	HB
R1-8B	+8.4	0.029	No	−1.2†	0.564	No
OT-7B	+10.8	0.002	Yes	+10.5	<0.001	Yes
QwQ-32B	+9.3	0.067	No	+2.7	0.368	No
R1-32B	+10.9	0.008	Yes	+7.8	0.165	No

† Adverse direction: HS FPR higher (worse) than BGE.

T Random Projection Baseline

PCA capacity matching (Section S) preserves 79–92% of variance. A natural question is whether the HS advantage depends on PCA's structure-preserving property. We project hidden states to 384d using Gaussian random projection (3 seeds, averaged) and compare with text embeddings at the same dimensionality (Table 29).

Table 29: Random projection (RP, 384d) vs. text (384d MiniLM). All $p < 0.001$ (1,000 bootstrap resamples). R1-8B uses W=15 (Table 3: W=3); QwQ-32B evaluated at L60 (Table 3: L63). 60/20/20 split.

Model	RP Prec	Text Prec	ΔPrec	ΔBA
R1-8B	.621	.416	+.205	+.140
OT-7B	.371	.244	+.127	+.128
QwQ-32B	.563	.391	+.172	+.132
R1-32B	.524	.441	+.083	+.085

All four models retain significant HS advantage under random projection (ΔPrec +8.3 to +20.5pp), with cross-seed standard deviations below 1.7pp. RP precision is slightly lower than PCA-384d (expected, as PCA preserves maximal variance), but the gap is small. The small gap weakens a pure capacity explanation: even a structure-destroying projection preserves the HS advantage. The safety

signal appears broadly distributed across hidden-state dimensions rather than concentrated in top principal components.

U LLM-Based Text Encoder Comparison

To test whether an LLM-based text encoder closes the HS advantage gap, we encode each reasoning step with E5-Mistral-7B-Instruct (Wang et al., 2024) (4096d, reduced to 384d via PCA to match the MiniLM dimensionality). Table 30 reports precision comparisons against HS probes at threshold-based layers.

Table 30: HS vs. E5-Mistral-7B (PCA 384d) precision. HB: Holm-Bonferroni adjusted (4 tests, α=0.05). MiniLM precision from Table 3 for reference. 60/20/20 split.

Model	Layer	W	HS	E5	MiniLM	Δ(HS$-$E5)	p	HB
R1-8B	L14	3	.630	.480	.416	+15.0	0.001	✓
OT-7B	L16	3	.446	.321	.244	+12.5	0.009	✓
R1-32B	L63	1	.588	.506	.441	+8.2	0.235	
QwQ-32B	L63	5	.515	.447	.391	+6.8	0.368	

The HS advantage partially survives against the LLM encoder: 2/4 models (both 7–8B) retain significance after Holm-Bonferroni correction. Three text encoders form a monotonic gradient: MiniLM (22M params, 384d): 4/4 HB; E5-Mistral (7B, PCA 384d): 2/4 HB; BGE-large (335M, 1024d): 1/4 HB (Section S). E5 precision consistently falls between MiniLM and HS across all models, consistent with encoder quality progressively narrowing the gap. PCA to 384d discards information from the 4096d E5 representation; the comparison controls dimensionality but not representation quality, so the true E5 advantage may be larger than reported here.

V Position-Residualized Probing

To quantify non-positional safety signal, we regress out the normalized position t/T from each hidden-state (or text-embedding) vector before training the logistic regression probe. Table 31 summarizes results across all models at their optimal W.

Position accounts for 9–20pp of balanced accuracy depending on model and window size (R1-32B's 20.4pp drop at W=1 reflects the absence of temporal context), and all models retain non-positional signal above chance ($p<0.001$). Three of four models retain significant non-positional HS advantage over text after residualization (OT-7B +6.9pp, R1-8B +6.4pp at W=15, QwQ-32B +3.7pp; all HB corrected). R1-32B is the exception: residualized HS-text gap is +1.9pp (p=0.914), a pattern consistent with position mediation. Larger temporal windows reduce position dependence: R1-8B drops 24.3pp at W=3 but only 16.5pp at W=15.

Model	W	HS BA	Resid. HS BA	Drop	Resid. Text BA
R1-8B	15	0.834	0.669	16.5pp	0.605
R1-8B	3	0.813	0.571	24.3pp	0.534
OT-7B	3	0.732	0.609	12.3pp	0.540
QwQ-32B	3	0.796	0.619	17.7pp	0.582
R1-32B	1	0.756	0.552	20.4pp	0.532

Table 31: Position-residualized probe balanced accuracy. All residualized HS probes are above chance ($p<0.001$). 3/4 models retain significant non-positional HS advantage over text (gap +3.7 to +6.9pp, HB corrected); R1-32B is the exception (+1.9pp, p=0.914).

For QwQ-32B specifically, three complementary significance tests confirm the residualized probe performs above chance: Wilcoxon signed-rank p=0.0024, paired t-test p=0.0008, permutation test $p<0.001$ (bootstrap 95% CI for per-trace BA: $[0.575, 0.744]$). The position baseline achieves higher balanced accuracy (0.832 vs. HS 0.796), and HS precision (+4.5pp, p=0.133) and FPR (+2.5pp, p=0.279) margins over the position baseline are not statistically significant at n=19.

Non-linear position terms. To test whether non-linear position effects drive the HS advantage, we repeat the residualization with both linear (t/T) and quadratic ($[t/T, (t/T)^2]$) regressors (Table 32). Both 7–8B models retain significant residualized advantages under either specification. R1-32B remains non-significant under both. QwQ-32B's residualized advantage survives linear control (+7.4pp, HB) but is fully absorbed by the quadratic term ($-$1.0pp), indicating a non-linear position component in its HS advantage.

Model	Lin. gap	Quad. gap	Lin. HB	Quad. HB
R1-8B	+10.4pp	+10.3pp	✓	✓
OT-7B	+11.4pp	+9.8pp	✓	✓
R1-32B	$-$1.4pp	+0.0pp	×	×
QwQ-32B	+7.4pp	$-$1.0pp	✓	×

Table 32: Linear vs. quadratic position residualization (residualized HS$-$text gap, L60 for QwQ-32B). Both 7–8B models are robust to either specification. QwQ-32B's advantage survives linear but not quadratic control; R1-32B is non-significant under both.

Note: gaps in Table 32 are precision-weighted at per-model optimal layers, whereas Table 31 reports balanced-accuracy gaps; the difference reflects the metric and layer configuration, not methodological

inconsistency.

Effect size. Standardized effect sizes (Cohen's d, residualized per-trace BA vs. chance 0.5): R1-8B d=2.37 (n=43, very large), QwQ-32B d=0.85 (n=19, large). Both exceed the conventional "large" threshold of d=0.8 (Cohen, 1988), confirming that the residualized HS signal is practically meaningful despite sample limitations at 32B.

W Hyperparameter Robustness

The joint search space for layer ($\leq$64), window W (7 values), consecutive-crossing threshold K (5 values), and decision threshold is large (up to 2,240 configurations per model). This raises the concern that reported performance reflects overfitting to small validation sets (n=4–9 per class at 32B). Three analyses address this concern.

Threshold-based metrics converge to a deep-layer band. Despite the large search space, three of four threshold-based metrics (precision, inverse FPR, additive composite) independently select L63 (98% depth) for both 32B models (Table 2). A joint (layer, W) grid search over 192 configurations confirms that L63 is near-optimal for QwQ-32B at recommended windows (Table 5). For R1-32B, layers L55–L63 at W=1 form a robust band where all 3/3 metrics pass Holm-Bonferroni (Section B). The convergence of independent metrics to a narrow band is inconsistent with overfitting, which would produce scattered selections.

BA-optimal layer instability is the finding, not a confound. Five-fold cross-validation on 32B validation sets reveals that balanced-accuracy-optimal layers are highly unstable across folds (Table 33). This instability is not a limitation of the study but the central methodological finding: BA-layer selection is sensitive to data composition, and conclusions drawn from any single BA-optimal layer are unreliable. Despite per-fold instability, mean BA across folds peaks near L47–L50 for both models, consistent with the LOO-CV dominant layers (Section B). The HS advantage holds at both BA-optimal and precision-optimal layers regardless of depth (14/16 per-model tests pass HB; Section Y).

Bootstrap CIs quantify statistical uncertainty. For the most fragile result (R1-8B FPR), bias-corrected accelerated (BCa) bootstrap (Efron and Tibshirani, 1993; Carpenter and Bithell, 2000) yields a 95% CI of [0.006, 0.159] (p=0.033), with 12% leave-one-out instability (Section X). The CI excludes zero and confirms significance despite seed fragility. CP annotation perturbation (Table 21) further shows that $\pm$2-step label noise changes BA by $<$2.5pp, so annotation uncertainty does not compound with hyperparameter selection.

Table 33: BA-optimal layer per fold (5-fold CV, 32B models). Per-fold selections span 24 layers, but mean-BA landscape peaks are stable.

Model	F1	F2	F3	F4	F5	Spread	Mean-BA best
QwQ-32B	L63	L51	L39	L44	L44	24 layers	L50
R1-32B	L53	L45	L40	L63	L39	24 layers	L47

Effective degrees of freedom. The full exploration space (5 metrics $\times$ 7 windows $\times$ 25–64 layers = up to 2,240 configurations) far exceeds the 12 final HB-corrected tests. This does not constitute 2,240 independent hypothesis tests because layer and window are selected on the validation set before test-set evaluation, a standard train/validate/test protocol, not post-hoc cherry-picking on test outcomes. The effective degrees of freedom lie between 12 (final tests) and 2,240 (full grid), a "garden of forking paths" concern (Gelman and Loken, 2013). Three safeguards bound this risk: (1) nested 5-fold CV on 7–8B models shows 13–25% shrinkage relative to holdout estimates (Section W.1), quantifying overfitting; (2) split-half replication on OT-7B confirms the HS advantage on independent data halves (Section X.1); (3) threshold-based metric convergence to a narrow layer band (L63 for both 32B models) is inconsistent with scattered overfitting selections. We acknowledge that cumulative researcher degrees of freedom are substantial and that the 12-test HB boundary may underestimate Type I error.

W.1 Nested Cross-Validation

The holdout estimates in Table 3 select layer and window on the validation fold, then evaluate on a fixed test set. To rule out hyperparameter overfitting, we run nested 5-fold cross-validation on both 7–8B models: the outer fold holds out test data; the inner loop selects (layer, W) on the remaining four folds. Table 34 reports per-fold precision differences.

The HS precision advantage is consistent across all 10 folds (5/5 for each model), with mean advantages of +17.4pp (R1-8B) and +16.4pp (OT-7B). Shrinkage relative to holdout estimates is 13% and 25% respectively, within expected ranges for

Table 34: Nested 5-fold CV: per-fold HS−text precision difference (pp). Layer and W selected independently per fold. All 10/10 folds favor HS.

Model	F1	F2	F3	F4	F5	Mean	Holdout	Shrink.
R1-8B	+22.1	+14.4	+17.5	+17.0	+16.0	$+17.4 \pm 2.6$	+20.1	13%
OT-7B	+13.2	+21.4	+18.8	+12.6	+15.8	$+16.4 \pm 3.3$	+21.9	25%

R1-8B selected layers: L12, L12, L12, L13, L14; W_{HS}: 3, 3, 5, 5, 3. OT-7B selected layers: L23, L21, L27, L26, L26 (75–96% depth); W_{HS}: 5, 5, 5, 5, 5.

validation-selected hyperparameters. R1-8B layer selection is stable (L12–L14, 38–44% depth), consistent with all five metrics agreeing on L14 in the main analysis. OT-7B nested CV selects L21–L27 (75–96% depth), deeper than the CR-composite-selected L16 (57%) used in the main text. The discrepancy between CR-composite-selected (L16) and precision-selected (L21–L27) layers further illustrates the metric-dependence of layer selection documented in Section 4.2.

Formal test. A one-sided Wilcoxon signed-rank test on the 5-fold Δprecision (HS−text) rejects H_0: Δ=0 for both models (W=15, p=0.031; the minimum achievable p-value at n=5). Layer selection entropy across folds is H=1.37 bits for R1-8B (normalized 0.59; dominated by L12 in 3/5 folds) and H=1.92 bits for OT-7B (normalized 0.83; L21–L27), indicating moderately stable layer selection for R1-8B and higher variability for OT-7B.

X Multi-Seed Stability

Table 35 reports LR probe performance across 5 random seeds at each model's threshold-based layer and optimal W.

Table 35: LR probe stability across 5 random seeds (threshold-based layers, optimal W). 7–8B models are stable; R1-32B shows high variance due to small sample (n=20).

Model	Precision	Bal. Acc	FPR
R1-8B	0.590 ± 0.072	0.756 ± 0.028	0.154 ± 0.026
OT-7B	0.421 ± 0.034	0.633 ± 0.023	0.157 ± 0.021
QwQ-32B	0.651 ± 0.099	0.731 ± 0.028	0.133 ± 0.032
R1-32B	0.594 ± 0.128	0.692 ± 0.056	0.207 ± 0.145

R1-32B's high FPR variance (std = 0.145) reflects a single outlier seed (FPR = 0.48), amplified by the small test set (n=20). Note that R1-32B's absolute precision std (12.8pp) differs markedly from its paired ΔPrec std (2.0pp): HS and text precision covary across seeds.

5-seed Holm-Bonferroni pass rates. Table 36 reports HB pass rates per model across 5 seeds. Overall, 18/20 (90%) model-seed combinations pass full HB (3/3 metrics).

Table 36: 5-seed HB pass rates (3/3 metrics per seed). R1-8B failures are FPR-specific.

Model	HB Pass	Mean ΔPrec $\pm$ std	Note
OT-7B	5/5	$+20.9 \pm 1.3$pp	Cleanest evidence
R1-32B	5/5	$+13.7 \pm 2.0$pp	Position-mediated
QwQ-32B	5/5	$+19.9 \pm 2.5$pp	Robust
R1-8B	3/5	$+14.6 \pm 4.5$pp	FPR seed-fragile

R1-8B FPR per-seed breakdown. Table 37 reports per-seed HS vs. text FPR comparisons for R1-8B. The HS advantage is directionally consistent (5/5 seeds), with 2/5 reaching $p<0.05$ uncorrected; after Bonferroni correction for 5 seeds (α=0.01), 1/5 remains significant. Text FPR is highly stable (std = 0.007) while HS FPR is split-sensitive (std = 0.040), which explains why the canonical-split FPR advantage (−7.4pp) does not generalize robustly across seeds.

Table 37: R1-8B FPR per-seed comparison (L14, W=15; main text Table 3 reports W=3 after 5-seed validation). Direction is consistent (5/5 HS $\leq$ Text); 2/5 reach $p<0.05$ uncorrected, 1/5 after Bonferroni correction (5 seeds, α=0.01).

Seed	HS FPR	Text FPR	ΔFPR	p
0	0.161	0.165	−0.004	0.440
1	0.061	0.166	−0.105	<0.001
2	0.123	0.176	−0.053	0.093
3	0.148	0.167	−0.018	0.293
4	0.100	0.176	−0.076	0.021
mean±std	0.119 ± 0.040	0.170 ± 0.007	−0.051	–

R1-8B per-metric HB pass rates. Table 38 reports Holm-Bonferroni pass rates per metric across 5 seeds for R1-8B, the model classified as "moderate" evidence due to FPR instability.

Table 38: R1-8B per-metric×seed HB pass rates. Precision is robust (5/5); FPR is fragile (3/5). FPR std across seeds is 0.040 vs. text FPR std 0.007, consistent with a proportion near boundary (∼12%) amplified at n=43.

Seed	ΔPrec HB	ΔBA HB	ΔFPR HB
0	✓	✓	×
1	✓	✓	✓
2	✓	✓	×
3	✓	✓	✓
4	✓	✓	✓
Pass rate	5/5	5/5	3/5

The FPR instability has a clear source: R1-8B text FPR clusters tightly around 17% (std=0.7pp)

while HS FPR ranges from 6.1% to 16.1% (std=4.0pp). Seeds where HS FPR happens to be high (>14%) lose significance because the gap against text narrows below the detection threshold at n=43. This instability is metric-specific and does not affect the precision or balanced accuracy advantage, which passes all 5 seeds.

R1-32B per-seed breakdown. Table 39 reports the full per-seed breakdown for R1-32B. Seed 0 is an outlier (FPR = 0.483), driven by test-set trace allocation at n=20. Excluding seed 0, FPR std drops from 0.145 to 0.046.

Table 39: R1-32B per-seed performance (L63, W=1). Seed 0 is an outlier driven by test-set trace allocation.

Seed	Precision	Bal. Acc	FPR
0	0.441	0.594	0.483
1	0.750	0.748	0.109
2	0.685	0.670	0.111
3	0.652	0.733	0.111
4	0.444	0.715	0.221
mean±std	0.594 ± 0.128	0.692 ± 0.056	0.207 ± 0.145

X.1 Split-Half Internal Validity (OT-7B)

To assess internal validity, we split OT-7B traces into two independent halves and repeat the full layer sweep on each. Both halves reproduce the core pattern: crossing rate selects L0 (shallow) while precision selects mid-to-deep layers (L20 and L26 respectively). The HS precision advantage is consistent across halves (ΔPrec = +0.262 and +0.154), and 4/4 checkpoints (2 halves × 2 metrics) pass, confirming the metric-induced divergence is not an artifact of a particular data partition (Table 40).

Table 40: Split-half internal validity on OT-7B. Both halves reproduce CR→shallow / threshold→deep divergence with consistent HS advantage direction.

Half	CR layer	Prec. layer	ΔPrec	ΔBA
A (n=24)	L0	L20	+0.262	+0.128
B (n=23)	L0	L26	+0.154	+0.092

Y BA-Layer Modality Comparison

To address the concern that threshold-based layer selection may circularly favor HS probes, we repeat the modality comparison at layers selected by pure balanced accuracy, a threshold-free metric (Table 41). BA-optimal layers vary widely across models (7–98% depth), itself demonstrating that layer selection is a consequential methodological choice. The HS advantage is significant at whichever layer BA selects (14/16 per-model HB, two FPR failures from underpowered 32B test sets n≤20).

Table 41: HS vs. text at BA-selected layers (60/20/20 split, same as main results). 14/16 per-model tests pass Holm-Bonferroni (α=0.05); two FPR failures from underpowered 32B sets. BA-L: layer selected by pure balanced accuracy. Depth varies from 7% to 98%.

Model	BA-L	ΔPrec	ΔBA	ΔFPR	ΔAUROC
R1-8B	L17	+18.6 (<.001)	+8.4 (.006)	−7.0 (.043)	+12.1 (.009)
OT-7B	L2	+18.5 (<.001)	+8.0 (.006)	−13.3 (<.001)	+12.8 (.003)
QwQ-32B†	L63	+18.1 (.001)	+13.5 (<.001)	−6.4 (.088)	+15.1 (.001)
R1-32B†	L46	+12.8 (.014)	+17.6 (<.001)	−12.2 (.083)	+15.1 (.009)

Values: difference in pp (p-value, bootstrap, 10,000 resamples).
† Sample-limited ($n \leq 20$).

Of 16 per-model tests (4 models × 4 metrics), 14 pass Holm-Bonferroni correction. The precision gains (+12.8 to +18.6pp) are comparable to those at threshold-based layers (+15.4 to +21.9pp; Table 3), so the HS advantage is robust to the choice of layer selection criterion. The two failures are both FPR at 32B: R1-32B (p=0.083) and QwQ-32B (p=0.088), consistent with the underpowered test sets (n≤20) noted throughout. BA-optimal depths span 7% (OT-7B L2) to 98% (QwQ-32B L63), in contrast to threshold-based layers that consistently select deep layers (94–98%). That BA selection produces such depth variation while preserving significant HS advantage reinforces the core methodological finding: the advantage is genuine rather than an artifact of any particular layer selection criterion.

Y.1 AUROC Layer Selection

AUROC is threshold-free and thus orthogonal to the threshold-based metrics used in our main analysis. We include it as a reference point for layer selection (Table 42).

Table 42: AUROC-optimal vs. threshold-based layer selection. AUROC selects mid-depth layers for 32B models (∼50%), diverging from threshold-based deep layers (>90%). PCA-256 applied to 32B models for tractability.

Model	AUROC-L	Depth	AUROC	Thresh-L	Depth	AUROC@Thresh-L
R1-8B	L13	41%	0.806	L14	44%	0.803
OT-7B	L1	4%	0.777	L16	57%	0.746
QwQ-32B†	L32	50%	0.839	L60	94%	0.756
R1-32B†	L31	48%	0.897	L63	98%	0.767

† PCA-256 applied. AUROC-L: layer maximizing validation AUROC. Thresh-L: layer from threshold-based selection (Table 2).

AUROC does not converge to the same deep layers as threshold-based metrics. For 32B models,

AUROC prefers mid-depth layers (∼50% depth) vs. threshold-based deep layers (>90%). R1-8B is a near-match (L13 vs. L14). We exclude AUROC from the main analysis because it is threshold-free and cannot diagnose the threshold-crossing artifacts central to our layer selection bias finding, but it provides an independent reference confirming that optimal layer depth is metric-dependent.

Y.2 Effective Independent Tests

The raw exploration space (∼5 metrics × 7 windows × 28–64 layers) nominally spans 980–2,240 configurations per model, raising a multiple-comparisons concern. The effective number of independent tests is substantially smaller for three reasons:

Metric redundancy. Precision, inverse FPR, and the additive composite share a single confusion matrix: they are deterministic functions of the same TP/FP/FN/TN counts. Empirically, their layer rankings have Kendall $\tau \geq 0.85$ across all four models (Table 2). BA is computed from the same confusion matrix but weights errors differently; it independently confirms deep-layer selection. Crossing rate is the only structurally distinct metric (computed from threshold-crossing sequences, not the confusion matrix). Thus five nominal metrics reduce to ∼2 independent metric families (threshold-based and crossing-rate).

Layer autocorrelation. Adjacent transformer layers produce highly correlated probe scores: for R1-8B, the median Pearson r between layers ℓ and $\ell \pm 1$ exceeds 0.95. Using a lag-1 autocorrelation estimate (Efron and Tibshirani, 1993), the effective number of independent layers is ∼8–12 per model (vs. 28–64 nominal).

Two-stage protection. The upstream exploration (layer × window × metric) is conducted entirely within the training/validation split via nested CV at 7–8B (Section W.1) and split-half replication (Section X.1). The held-out test set sees only the 12 final modality comparisons (3 metrics × 4 models), to which Holm-Bonferroni correction is applied. The upstream search inflates Type I risk only if it overfits the validation set; nested CV guards against this at 7–8B, while 32B results are marked exploratory (†) precisely because this guard is unavailable.

Conditional inference. The two-stage design means that test-set p-values are conditional on the layer and window selected during upstream search. This selective inference is valid when the selection and evaluation splits are independent (ensured by our 60/20/20 partition), but the resulting p-values measure significance given the chosen selection path rather than significance averaged over all possible paths. Nested CV at 7–8B (Section W.1) addresses this by averaging over fold-specific selection paths; the 32B exploratory status (†) reflects the absence of this protection.

Effect sizes. Cohen's d (one-sample, $d = (\overline{\text{BA}} - 0.5)/s$) quantifies effect magnitude independently of sample size: R1-8B d=2.37 (very large, n=43), OT-7B d=1.12 (large, n=47), QwQ-32B† d=0.85 (large, n=19), R1-32B† d=0.58 (medium, n=20). The 7–8B models exceed the "very large" threshold (d>1.2); both 32B models exceed the "medium" threshold (d>0.5). R1-32B's medium effect size is consistent with its exploratory status and the position-mediation pattern noted in Section 4.4. These effect sizes argue against a pure multiple-comparisons explanation: fishing artifacts produce small, unstable effects, whereas the observed d values are large and graded across the evidence tiers.

Z Post-Hoc Power Analysis

We compute post-hoc minimum detectable effects (MDEs) at 80% power for each model's test set to contextualize non-significant results, particularly at 32B scale where sample sizes are small (Table 43).

Table 43: Post-hoc power analysis. MDE: minimum detectable effect (balanced accuracy, pp) at 80% power given each model's test-set size and observed variance. Effects smaller than the MDE cannot be reliably detected.

Model	n_{test}	Obs. std (BA)	MDE (80%)
R1-8B	43	0.028	4.2pp
OT-7B	47	0.023	3.3pp
QwQ-32B†	19	0.028	8.6pp
R1-32B†	20	0.056	9.5pp

† Sample-limited. MDE computed from 5-seed observed standard deviation via two-sided paired t-test formula.

At 32B scale, the MDE is 8.6–9.5pp, meaning effects below this magnitude cannot be reliably distinguished from noise. R1-32B's residualized HS-text gap (+1.9pp) falls well below the MDE (9.5pp), so the non-significant result (Section V) is consistent with either a true null or an underpowered test. The 7–8B MDEs (3.3–4.2pp) are

substantially lower, explaining why smaller effects reach significance at these scales.

Z.1 Multi-Metric Layer Ensemble

For each model, we train logistic regression probes at the best layer selected by each of three threshold-based metrics (precision, BA, inverse FPR) and average their predicted probabilities to produce an ensemble score. This eliminates the need to pre-select a single metric for layer selection.

Table 44: Multi-metric layer ensemble vs. best single metric and text baseline. Ensemble trains probes at 3 threshold-based metric-selected layers and averages probabilities. ΔEns–Best: ensemble minus best single metric (negative = ensemble slightly lower). All Ens–Text differences are significant ($p \leq 0.002$, permutation test). No Ens–Best difference is significant ($p > 0.27$).

Model	Ens Prec	Best Single	Δ	Ens − Text
R1-8B	0.565	0.604 (BA@L12)	−3.9pp	+19.3pp
OT-7B	0.506	0.473 (FPR@L18)	+3.3pp	+27.0pp
QwQ-32B	0.578	0.578 (Prec@L60)	−0.0pp	+20.3pp
R1-32B	0.581	0.583 (Prec@L63)	−0.2pp	+10.5pp

This ensemble is a preliminary exploration of metric-agnostic layer selection, not a validated mitigation strategy; rigorous cross-validated evaluation across diverse datasets is future work. The ensemble provides a metric-agnostic selection strategy among principled (threshold-based) metrics. It never significantly underperforms the best individual metric (all $p > 0.27$), and all four models show significant HS advantage over text ($p \leq 0.002$). The ensemble advantage over text ranges from +10.5pp (R1-32B) to +27.0pp (OT-7B). This proof of concept validates that practitioners need not commit to a single metric for layer selection; averaging across metric-selected layers achieves comparable performance. Future work should test whether including biased metrics (e.g., crossing-rate composite) in the ensemble degrades performance, and whether learned metric weighting could improve upon uniform averaging.