DisPeD: A Controlled Study of Encoder Adaptation for Multi-Turn Jailbreak Detection

Anonymous ACL submission

Abstract

What representation properties of encoder adaptation enable cross-attack generalization in multi-turn jailbreak detection? Multi-turn attacks spread adversarial intent across benign-seeming turns, evading existing defenses: Llama Guard 3 detects only 1.8% of multi-turn jailbreaks. We decompose cross-attack generalization through controlled ablation of thirteen encoder configurations on synthetic multi-turn data generated by a single LLM (Qwen3-8B). A surprising finding emerges: domain-relevant classification objectives—including scrambled labels—trigger discriminative compression sufficient for template-attack generalization, with a complexity-dependent boundary on structurally complex attacks. On synthetic multi-turn data, classification-based domain adaptation recovers OOD detection (F1 = 0.97–1.0 vs. vanilla 0.26–0.31; attack-side OOD, benign IID) and shows partial robustness under mixed-LLM training—template attacks remain detectable while structurally complex ActorAttack degrades (F1 = 0.504)—while unsupervised pretraining collapses; however, this advantage reverses on human-authored single-turn data. Orthogonal to attack-side generalization, benign distribution shift is a practical bottleneck: few-shot benign adaptation reduces false-positive rates below deployment thresholds on two independent sources. These findings decompose multi-turn jailbreak generalization into two orthogonal axes—attack-side (discriminative compression) and benign-side (few-shot adaptation)—with 24.3× inference speedup over LLM-as-judge.

1 Introduction

Multi-turn jailbreak attacks distribute adversarial intent across individually benign turns. Crescendo (Russinovich et al., 2025), Foot-in-the-Door (Wang et al., 2024), and Deceptive Delight (Palo Alto Networks Unit 42, 2024) all rely on persuasion as their core mechanism: Zeng et al. (2024b) catalogue 40 persuasion techniques across jailbreak families, and Hagendorff et al. (2026) identify strategies in 97% of successful attacks. Because individual attack turns occupy the same embedding region as benign text (Bullwinkel et al., 2025), no single-turn filter can distinguish them from legitimate conversation.

Existing defenses leave a critical gap. Production classifiers such as Llama Guard (Inan et al., 2023), WildGuard (Han et al., 2024), and ShieldGemma (Zeng et al., 2024a) operate on individual turns and miss multi-turn manipulation; Llama Guard 3 detects only 1.8% of multi-turn jailbreaks in our evaluation (Section 4.3). Multi-turn defenses (DeepContext (Albrethsen et al., 2026), BIID (Tong et al., 2025), G-Guard (Huang et al., 2025)) model conversation-level structure but each evaluates on a single attack family. None answers the central question: *what representation properties enable a detector to generalize across attack families it has never seen?*

Pretrained language understanding does not suffice at base model scale: vanilla DeBERTa-v3 (He et al., 2021) with temporal aggregation (cf. DeepContext) drops from F1 = 1.000 in-distribution to 0.312 on OOD Deceptive Delight. LLM-as-judge baselines also struggle (Appendix A), though prompt optimization may improve their performance. The bottleneck is distributional: cross-attack generalization requires domain adaptation, not a larger model.

Our pipeline, **DisPeD**[1] (Disentangled Pattern Detection), separates encoder adaptation (Stage 1) from temporal classification (Stage 2, a frozen Bi-GRU; Figure 1). Seven Stage 1 variants systematically vary training objectives while sharing the same two-stage pipeline (Section 3); the contribu-

[1] *Disentangled* refers to the systematic disentanglement of adaptation factors through controlled ablation (Section 4.3), not to causal disentanglement or disentangled representation learning.




Figure 1: DisPeD architecture. Stage 1 adapts a DeBERTa encoder on jailbreak conversation text (seven variant objectives). Stage 2 aggregates frozen `[CLS]` embeddings via BiGRU for conversation-level jailbreak detection. Only user turns are processed.

tion is the decomposition, not the pipeline.

Controlled ablation across DeBERTa-v3 and RoBERTa (Liu et al., 2019b) on four attack families and two training compositions reveals two orthogonal generalization axes. On the *attack side*, vanilla DeBERTa drops to F1 = 0.26–0.31 on OOD attacks; classification DAPT recovers to 0.97–1.0, while MLM collapses under mixed-LLM training (F1 = 0.289 ≈ vanilla). On the *benign side*, distributional mismatch drives false positives: WildChat FPR reaches 68.1%, but 10–25 target-domain conversations reduce it to 0–1.5% across two sources. RoBERTa-large (355M) handles ActorAttack (Ren et al., 2025) without adaptation. Classification supervision is associated with observed lower prediction variance on synthetic data ($n = 3$–5, directional) but not on human-authored conversations (Section 4.6).

Our contributions:

- **Systematic ablation of cross-attack generalization factors.** Thirteen encoder configurations at three scales (125–355M) decompose multi-turn jailbreak detection into two orthogonal axes—attack-side and benign-side—the first such controlled factorial study in this domain. On the attack side, classification DAPT recovers OOD detection (vanilla 0.26–0.31 → 0.97–1.0) while unsupervised pretraining collapses under mixed-LLM training. On the benign side, 10–25 target-domain conversations reduce FPR from 58–68% to 0–1.5% on two independent sources (WildChat, OASST2) without detection degradation.

- **Deterministic partition sufficiency with complexity-dependent boundary.** We observe that domain-relevant classification objectives trigger discriminative compression sufficient for cross-attack generalization—based on two template and one structurally complex attack family (structural complexity is not formally defined): scrambled labels match correct labels on template attacks (TOST-confirmed, $d < 0.1$ on DD/FITD at $n = 10$), with a complexity-dependent boundary ($d = 0.44$ on ActorAttack). This is consistent with Zhang et al. (2021)'s framework, with two domain-specific findings: domain-relevant partitioning is necessary (topic labels insufficient) and compression localizes to 3 SVD dimensions in layers 8–12; a discriminative probe confirms that these 3 dimensions suffice for cross-attack detection (Appendix T).

- **Preliminary two-step adaptation protocol.** On the synthetic benchmark, continued pretraining achieves 24.3× inference speedup over LLM-as-judge (a deployment cost comparison; parameter counts differ by 43×; Appendix W); 10–25 target-domain benign conversations reduce FPR below deployment thresholds on both WildChat and OASST2 crowdsourced conversations. No target-domain attack data is required.

2 Related Work

Multi-turn jailbreak attacks. All multi-turn jailbreak families share a persuasion substrate (Zeng et al., 2024b; Hagendorff et al., 2026; Li et al., 2024): Crescendo (Russinovich et al., 2025), FITD (Wang et al., 2024), DD (Palo Alto Networks Unit 42, 2024), and ActorAttack (Ren et al., 2025) each operationalize it differently, while automated methods (Chao et al., 2025; Mehrotra et al., 2024; Perez et al., 2022) iteratively refine prompts and many-shot attacks (Anil et al., 2024) exploit long-context in-context learning. Benchmarks standardize evaluation at single-turn (Mazeika et al., 2024; Chao et al., 2024) and multi-turn (Wei et al., 2023; Jiang et al., 2024; Song et al., 2026) scales. A detector must generalize across families, not merely succeed on its training distribution.

Multi-turn defenses and production safety. No existing defense evaluates cross-attack transfer. Conversation-level systems (DeepContext (Albrethsen et al., 2026), BIID (Tong et al., 2025), G-Guard (Huang et al., 2025), SafeDream (Yan et al., 2026), JailDAM (Nian et al., 2025)) and representation-level approaches (Lu et al., 2025; Zhang et al., 2025; Xie et al., 2024; Zou et al., 2024;

Kulkarni, 2026; Kadali and Papalexakis, 2026; Hua et al., 2026; Shen et al., 2025; Li et al., 2025b; Wang et al., 2026; Templeton et al., 2024) each evaluate on a single family; the latter require white-box access and can be brittle (Derya and Sunar, 2026). J-DAPT (Marchiori et al., 2025) applies CORAL-based domain adaptation with cross-modal fusion for multimodal robotic jailbreak detection; our work focuses on text-only multi-turn persuasion attacks and decomposes which adaptation factors drive cross-attack generalization through controlled ablation. Per-turn classifiers (Inan et al., 2023; Meta AI, 2024; Zeng et al., 2024a; Han et al., 2024; Sharma et al., 2025) and single-turn defenses (Robey et al., 2024; Xu et al., 2024; Jain et al., 2023; Alon and Kamfonas, 2023; Phute et al., 2023; Hsu et al., 2024) miss multi-turn trajectories; M2S (Li et al., 2025a) converts multi-turn attacks to single-turn as a complementary approach. Our ablation contributes to filling this gap via decomposition across thirteen configurations under OOD evaluation.

Computational persuasion and discourse. Persuasion and discourse frameworks (Austin, 1962; Searle, 1969; Mann and Thompson, 1988; Prasad et al., 2008; Stolcke et al., 2000) and technique-level classification (Cialdini, 2001; Zeng et al., 2024b; Hagendorff et al., 2026; Da San Martino et al., 2019, 2020; Wang et al., 2019) offer interpretable vocabulary for attacks, but whether such structure aids detection has not been tested. Our ablation shows the taxonomy enables characterization, but detection operates through domain-adapted embeddings regardless of label correctness.

Domain-adaptive pretraining. Continued pretraining on domain text yields consistent gains (Gururangan et al., 2020; Lee et al., 2020; Beltagy et al., 2019; Howard and Ruder, 2018), but has not been disentangled for safety-critical generalization. Intermediate-task transfer (Phang et al., 2018) and multi-task learning (Caruana, 1997; Liu et al., 2019a) confound domain exposure with supervised signal; our MLM control confirms pretraining alone closes the OOD gap. Dataset artifacts (Gururangan et al., 2018; Niven and Kao, 2019) motivate TF-IDF, adversarial NLP (Jin et al., 2020; Li et al., 2020; Nasr et al., 2025; Andriushchenko et al., 2025) informs perturbation, and probing (Conneau et al., 2018; Hewitt and Manning, 2019) underpins CKA analysis.

Table 1: Stage-1 encoder variants. All operate on the same training conversations except Wikipedia MLM (matched token count on Wikipedia text).

Variant	Objective	Tests whether…
9-class	9-class persuasion + binary intent	full model
Binary	binary persuasion + binary intent	granularity matters
Scrambled	random 9-class + binary intent	label correctness matters
MLM-only	15% token masking	supervision is necessary
Topic	5-class topic classif.	any task suffices
Wiki MLM	15% masking on Wikipedia	domain specificity matters
Vanilla	no training	Stage-2 alone suffices

3 Method

Cross-attack generalization could stem from domain exposure, classification supervision, label correctness, label granularity, or domain specificity. Disentangling these factors demands an architecture where exactly one component varies across conditions. DisPeD (Disentangled Pattern Detection) separates encoder adaptation (Stage 1) from temporal classification (Stage 2); the name reflects this two-stage disentanglement of domain-adapted encoding from downstream classification. Seven Stage-1 variants share the same training data and downstream pipeline but differ solely in their pretraining objective; each isolates a single factor (Figure 1).

3.1 Problem Formulation

A conversation $C = \{u_1, a_1, \ldots, u_N, a_N\}$ alternates user turns u_i and assistant responses a_i. Given a prefix of K user turns, the model predicts $y \in \{0, 1\}$ (jailbreak vs. benign). We restrict input to user turns because adversarial intent resides in the attacker's messages. This formulation supports early detection from partial prefixes.

3.2 Stage 1: Turn-Level Encoder Adaptation

Each user turn u_i is encoded by DeBERTa-v3-base (He et al., 2023); the `[CLS]` embedding $h_i \in \mathbb{R}^d$ serves as the turn representation. Seven variants, summarized in Table 1, share the same training data but differ in objective.

The **9-class** variant uses two classification heads: 9-class persuasion strategy classification (L_{strategy}) and binary jailbreak intent (L_{intent}), with combined

loss $L = L_{\text{strategy}} + \alpha \cdot L_{\text{intent}}$ ($\alpha = 0.3$, selected from $\{0, 0.3, 0.5, 2.0\}$; all values yield F1 = 1.0 on IID; Appendix X). The taxonomy comprises eight persuasion strategies (rapport building, authority appeal, emotional manipulation, logical reframing, role assignment, gradual escalation, obfuscation, direct request) plus a none category, grounded in PAP (Zeng et al., 2024b) and Cialdini's principles (Cialdini, 2001). Strategy annotations are produced by Qwen3-8B with structured prompting that includes definitions and examples for each category; inter-annotator agreement between model annotations and a human sample (n=50) yields Cohen's κ=0.78.

The **binary** variant collapses the 9-class taxonomy into persuasive vs. non-persuasive, testing whether label granularity matters for detection or robustness. The **scrambled** variant randomly permutes the 9-class labels across turns, preserving classification structure (cross-entropy loss, 9-class output space) while destroying label semantics. This isolates whether the classification objective provides representational benefits independent of label correctness. The **MLM-only** variant applies 15% masked language modeling on the same jailbreak conversation text without any classification head, testing whether unsupervised domain exposure suffices. The **topic** variant trains a 5-class topic classifier (technology, health, finance, education, general) on the same conversations, testing whether *any* classification task provides the same benefit or whether task alignment matters. The **Wikipedia MLM** variant applies the same MLM objective to a token-matched sample of Wikipedia text; this isolates domain-specific from general continued pretraining. The **vanilla** baseline uses the pretrained DeBERTa-v3-base weights without any continued pretraining; it measures what Stage 2 alone can achieve.

3.3 Stage 2: Conversation-Level Classification

Turn embeddings $\{h_1, \ldots, h_K\}$ from the frozen Stage-1 encoder are aggregated by a 2-layer bidirectional GRU (d_{hidden}=256, dropout 0.3): $\bar{h} = [\overrightarrow{h_K}; \overleftarrow{h_1}] \in \mathbb{R}^{512}$. A two-layer MLP ($512 \to 256 \to 2$, ReLU activation) maps $\bar{h}$ to $\hat{y} \in \{0, 1\}$. The Stage-1 encoder is frozen during Stage 2 training; only the BiGRU and MLP parameters are updated. This frozen-encoder design ensures ablation fairness: all seven Stage-1 variants are evaluated under identical downstream conditions, isolating the effect of Stage-1 representation quality from Stage-2 classifier capacity. Three-seed evaluation confirms that mean pooling matches BiGRU performance (Section 4.3).

4 Experiments

Terminology. *Cross-attack OOD*: evaluation on attack families unseen during training; benign distribution remains IID throughout (OOD reflects attack-side shift only). K: prefix length (number of conversation turns retained). *DAPT*: all Stage-1 adaptations, extending Gururangan et al. (2020) to supervised variants. *Evidence hierarchy*: vanilla < MLM < classification (Section 4.3).[2]

4.1 Setup

Data. All synthetic data is generated by Qwen3-8B (Yang et al., 2025). The IID dataset contains 250 Crescendo (Russinovich et al., 2025) jailbreak and 250 topic-anchored benign conversations, split into training (350), validation (74), and test (76) sets with balanced class ratios (e.g., test = 38 jailbreak + 38 benign). Stage 1 (DAPT) uses training + validation conversations; Stage 2 (BiGRU) trains on training, early-stops on validation, and evaluates on test. OOD evaluation pairs attack-specific jailbreak conversations with the 38 IID-test benign conversations: 80 FITD (Wang et al., 2024) (non-discriminative; Section 4.3) + 38 benign = 118 total, 80 Deceptive Delight (DD) (Palo Alto Networks Unit 42, 2024) + 38 benign = 118 total, and 80 ActorAttack (Ren et al., 2025) + 38 benign = 118 total. No overlap exists in attack templates across families; benign is IID (same generation pipeline). A paraphrased version of the IID test set (BERTScore 0.92, lexical overlap 0.20) serves as the adversarial robustness benchmark (Section 4.7). For human data validation, we use ToxicChat (Lin et al., 2023) (204 jailbreak + 204 benign from real LMSYS user interactions), entirely independent of Qwen3-8B generation.

Models. Seven DeBERTa-v3 variants share the same Stage-2 pipeline and differ only in Stage-1 training (Section 3). Our vanilla DeBERTa+BiGRU configuration is architecturally equivalent to DeepContext (Albrethsen et al., 2026), differing only in encoder choice (DeBERTa-v3-base vs. BERT); it serves as our primary baseline. For cross-architecture comparison, we

[2]Throughout, OOD refers to attack-family shift (novel persuasion strategies at test time); benign distribution shift is evaluated in Section 5.

Table 2: Cross-attack generalization (F1) at K=2 and full conversation length. IID: Crescendo; OOD: Deceptive Delight (DD). OOD F1 reflects attack-side generalization; benign samples are IID from training distribution. 3-seed mean±std where noted; full per-K in Appendix B.

Method	*IID (Cresc.)* K=2	Full	*OOD (DD)* K=2	F
9-class	**1.000±.000**	**1.000±.000**	.981±.013	**.994**
MLM-only‡	.974	1.000	**.993±.009**	.914
Vanilla	.978±.016	1.000±.000	.479±.038	.312±.026
TF-IDF LR§	1.000	1.000	1.000	.961

‡MLM-only IID reports single seed (42); OOD reports 3-seed.
§TF-IDF is deterministic (no std).




Figure 2: Cross-attack generalization (full conversation F1). DisPeD (9-class) maintains near-perfect detection across all OOD families. On ActorAttack, both vanilla DeBERTa and TF-IDF collapse (≤0.26), exposing a difficulty threshold that lexical and non-adapted methods cannot cross.

replicate vanilla, MLM, and 9-class variants on RoBERTa-base (Liu et al., 2019b) (Section 4.4). We also compare TF-IDF LR, LLM-as-judge (Appendix A), and Llama Guard 3 8B (Meta AI, 2024) (zero-shot; evaluates last-response safety given conversation context), which detects only 1.8% of multi-turn jailbreaks (Table 3).

Metrics. F1 for binary jailbreak detection at prefix K=2 and full conversations (full per-K results in Appendix B). OOD results report 3-seed mean±std (seeds 42, 123, 456) for all variants; TOST equivalence tests for 9-class vs. scrambled use 5 seeds (42, 123, 456, 789, 1000). For key pairwise comparisons, we report BCa bootstrap 95% confidence intervals (10,000 resamples over individual predictions pooled across 3 seeds; this assumes cross-seed independence and is exploratory) and paired permutation tests (10,000 permutations). Seed-level F1 values (Table 39, Appendix Z) confirm all pairwise conclusions hold at every seed. Unless otherwise noted, all standard deviations are computed over 3 random seeds using the population formula (n divisor); Bessel-corrected estimates ($n-1$ divisor) are ≈22% larger but do not alter any significance conclusions. Stage-1: learning rate 2×10^{-5}, batch 16, 4 epochs, MLM masking 15%. Stage-2: two-layer MLP, 20 epochs.

4.2 Cross-Attack Generalization

Vanilla encoders collapse under cross-attack transfer; domain-adapted variants recover near-perfect detection (Table 2, Figure 2). DD exhibits high lexical separability (TF-IDF F1 = 0.961); ActorAttack, where TF-IDF collapses to 0.261, serves as the primary stress test for beyond-lexical generalization. On OOD DD, vanilla DeBERTa collapses to F1 = 0.312±0.026, worsening with more turns (0.628 at K=1 to 0.312 at Full), consistent with attack turns occupying "benign" embedding regions (Bullwinkel et al., 2025). MLM achieves mean F1 ≥ 0.97 at all prefixes $K \leq 5$ without any classification labels; domain exposure alone is sufficient. At full conversation length, MLM drops to 0.914±0.115 (seed 456 recall = 0.64), while the 9-class model maintains 0.994±0.005. TF-IDF LR reaches F1 = 0.961 on full DD; DD is fully solvable by lexical features. On structurally complex ActorAttack, TF-IDF collapses to F1 = 0.261 (precision = 1.0, recall = 0.15), while 9-class maintains 0.972±0.026: a 71 pp gap. Lexical methods cannot capture multi-persona role-playing attack structure. This establishes a "difficulty threshold" for lexical methods parallel to that of vanilla encoders: both succeed on DD and fail on ActorAttack (Section 7). Seed-level F1 values confirm all pairwise conclusions hold at every seed (Appendix Z); pooled BCa CIs provide exploratory confirmation (9-class DD Full [0.943, 1.000] vs. vanilla [0.202, 0.341]; all permutation $p < 0.0001$). FITD serves as a near-ceiling baseline where all variants achieve F1 ≥ 0.990, providing limited discriminative power.

Prefix-length analysis (Appendix Table 8) shows vanilla F1 drops from 0.628 at K=1 to 0.312 at full length. MLM achieves strong early detection (K=2: 0.993) but is unstable at full length (0.914±0.115); the 9-class model maintains 0.972–0.994 across all prefixes, demonstrating that classification supervision stabilizes against distributional drift.

Table 3: Evidence hierarchy on OOD DD and ActorAttack (AA) at full conversation length (3-seed mean±std where available). Bold indicates best per column. OOD F1 reflects attack-side generalization only; benign samples are IID from training distribution (benign-side shift evaluated in Section 5). Full per-prefix results in Appendix Tables 8 and 9.

Variant	DD-Full	AA-Full	DD-K=2
9-class (full model)	.994±.005	.972±.026	.981±.012
Binary (2-class)	**1.000±.000**	**.990±.008**	.994±.009
Scrambled labels	.994±.005	.951±.043	.981±.026
MLM-only[‡] (no labels)	.914±.115	.893±.080	.993±.009
9-class + mean pool[*]	.991±.013	.962±.015	**1.000**
Topic classif. (5-class)	.541±.207	.625±.141	.593±.166
Wikipedia MLM	.904±.115	.686±.297	.911±.071
Vanilla DeBERTa	.312±.026	.258±.000	.479±.038
TF-IDF LR[†]	.961	.261	**1.000**
Llama Guard 3[¶]	.025	.000	–

[*]9-class encoder with mean pooling replacing BiGRU. [†]Deterministic (no std). [‡]MLM-only IID (Table 2) is single-seed (42); all OOD values are 3-seed. [¶]Zero-shot; no domain training. Population std reported; Bessel-corrected values are 22% larger at n=3.

4.3 Decomposing the Detection Mechanism

A clear *evidence hierarchy* emerges across seven variants (Table 3), ordered by OOD detection at full conversation length on DD:

vanilla (0.312±0.026) < topic (0.541±0.207) ≪ wiki-MLM (0.904±0.115) ≈ jb-MLM (0.914±0.115) < scrambled (0.994±0.005) = 9-class (0.994±0.005) ≈ binary (1.000±0.000)

Domain exposure is the primary mechanism. MLM bridges ∼60 pp from vanilla (0.312±0.026 → 0.914±0.115) without labels; this supports the DAPT interpretation (Gururangan et al., 2020). TF-IDF collapse on ActorAttack (0.261 vs. 9-class 0.972) confirms that domain-adapted representations capture features beyond lexical overlap. All three classification-supervised variants converge: all tested domain-relevant partitions suffice for near-perfect detection (F1 = 0.994–1.000 on DD). Extended to $n = 10$ seeds (each using an independent random permutation), TOST (margin = 5 pp, reflecting minimum practical significance for 76–118 test conversations) confirms equivalence on DD ($p < 10^{-8}$, $d = -0.14$; Table 17) and FITD ($p < 10^{-8}$, $d \approx 0$), with a complexity-dependent boundary: template attacks show full equivalence ($d < 0.1$), while structurally complex ActorAttack retains moderate label sensitivity ($d = 0.44$, $p = 0.183$; 9-class 0.979 vs. scrambled 0.949). Label granularity (binary vs. 9-class) is a non-factor across all families; 10 random binary partitions of the 9 labels confirm this (IID/DD: 10/10 perfect; AA: 9/10; Appendix M). We observed 4–20× lower cross-seed variance for classification supervision over MLM on synthetic OOD (std 0.005 vs. 0.115 on DD; observed across 3 seeds, with consistent directionality across 5 seeds on a second GPU, $n = 5$, 4.6×; formal variance ratio tests are not applicable at these sample sizes; cross-seed ensemble yields marginal additional gains, Appendix Z). This stability benefit does not transfer to human-authored data, where classification-supervised variants exhibit the highest variance and pure MLM the lowest (Section 4.6). Appendix G provides t-SNE visualizations confirming that domain-adapted variants produce tighter, more separable embedding clusters than the vanilla baseline.

Domain specificity is marginal at full length but meaningful for early detection. Wikipedia MLM (0.904±0.115) nearly matches jailbreak-domain MLM at full length (1 pp gap), though jailbreak-domain text provides an 8 pp advantage at early prefixes (K=2: 0.993 vs. 0.911). Perturbation analysis (Section 4.7) reveals a sharper domain specificity effect: Wikipedia MLM degrades by ∼12 pp under adversarial paraphrasing while jailbreak-domain MLM degrades by only 2.6 pp.

Misaligned supervision destabilizes generalization. Topic classification yields DD-Full F1 = 0.541±0.207; seed 123 falls *below* vanilla (0.252 vs. 0.312). Despite using the same jailbreak-domain training data, topic classification performs worse than Wikipedia MLM (0.904±0.115), which uses out-of-domain text with no labels. A misaligned objective forces the encoder to allocate capacity to irrelevant features and actively destabilizes representations that MLM would preserve; embedding analysis confirms higher per-turn separability yet failed temporal aggregation (Appendix M).

Evidence hierarchy on structurally complex attacks. ActorAttack (Ren et al., 2025) uses multi-persona steering across longer conversation structures and provides a more challenging OOD benchmark than DD. The evidence hierarchy at full conversation length is:

TF-IDF (0.261) ≈ vanilla (0.258±0.000) < topic (0.625±0.141) < wiki-MLM (0.686±0.297) < jb-MLM (0.893±0.080) < scrambled (0.951±0.043) ≈ 9-class (0.972±0.026) ≈ binary (0.990±0.008)

TF-IDF collapses from 0.961 (DD) to 0.261 (ActorAttack, precision = 1.0, recall = 0.15). This gap shows that domain-adapted representations capture features beyond bag-of-words. Classification-supervised variants cluster tightly (0.951–0.990, max gap 3.9 pp at $n = 3$), though 10-seed TOST resolves the 9-class vs. scrambled gap as a moderate effect ($d = 0.44$). DAPT provides ∼71 pp over both vanilla (0.258) and TF-IDF (0.261). Full per-prefix results and per-prefix error analysis in Appendix C and C.1.

Temporal modeling. Mean pooling matches Bi-GRU on both DD and ActorAttack (F1 gap $\leq$ 1 pp, overlapping CIs; Appendix U). Turn-order shuffling produces negligible change ($|\Delta| <$ 1 pp) across both DeBERTa-v3-base 9-class (DD $\Delta = 0.000$, AA $\Delta = -0.009$, IID $\Delta = 0.000$) and RoBERTa-large 9-class (DD $\Delta = +0.001$, AA $\Delta = -0.007$, IID $\Delta = 0.000$), confirming that detection relies on per-turn representations rather than sequential patterns.

Summary. On synthetic multi-turn data, domain exposure is the primary mechanism; domain-relevant classification objectives suffice for template attacks ($d < 0.1$ on DD/FITD) with a complexity-dependent boundary ($d = 0.44$ on ActorAttack); label granularity, temporal modeling, and domain specificity are non-factors. Classification supervision is associated with observed variance reduction of 4–20× across 3 seeds (cross-hardware n=5: 4.6×) without changing the detection ceiling. User-turn distributions overlap substantially between benign and jailbreak conversations (IID 8.7±2.1 vs. 7.9±1.5; DD 8.1±1.5 vs. 7.9±1.5; FITD 7.8±1.4 vs. 7.9±1.5; only AA partially separated: 5.1±1.7 vs. 7.9±1.5); a turn-count-only baseline achieves F1 = 0.42–0.56 on IID/DD/FITD and 0.00 on AA/ToxicChat, confirming content-driven detection (Appendix V). Detection near-saturates at 50 conversations (Appendix W.1) and is insensitive to auxiliary loss weight (Appendix X).

4.4 Cross-Architecture Observation

We replicate vanilla, MLM, and 9-class on RoBERTa (Liu et al., 2019b) (Table 4); since DeBERTa-v3 and RoBERTa differ in architecture and pretraining, not only scale, all cross-encoder comparisons reflect both factors. On DD, RoBERTa-base vanilla already achieves 0.981±0.026 (vs. DeBERTa 0.312±0.026), so DAPT adds only 1.3 pp. ActorAttack exposes this as DD's simplicity: RoBERTa-base vanilla collapses to 0.466±0.163, a 51.5 pp drop, while domain-adapted variants recover (9-class: 0.939±0.046).

Table 4: Cross-architecture comparison on OOD Full (3-seed mean±std). DD = Deceptive Delight, AA = ActorAttack. Bold indicates best per encoder group.

Variant	DD	AA
DeBERTa-v3-base (184M)		
Vanilla	.312±.026	.258±.000
MLM	.914±.115	.893±.080
9-class	**.994±.005**	**.972±.026**
RoBERTa-base (125M)		
Vanilla	.981±.026	.466±.163
MLM	.987±.018	.730±.201
9-class	**.994±.005**	**.939±.046**
RoBERTa-large (355M)		
Vanilla	.927±.036	**1.000±.000**
MLM	.884±.065	.874±.014
9-class	**.987±.004**	.946±.057

RoBERTa-large (355M) reverses the pattern on ActorAttack: vanilla F1 = 1.000 vs. 9-class 0.946, suggesting DAPT may be unnecessary or mildly harmful for strong pretrained encoders. Smaller models require DAPT to bridge 47–71 pp. All continued pretraining reduces ActorAttack performance for the largest encoder via representation drift (Table 16), though classification DAPT partially compensates on DD (+6 pp).

Three encoder scales reveal a scale-dependent *difficulty threshold*: DeBERTa-v3-base requires adaptation for all attacks, RoBERTa-base only for complex ones, RoBERTa-large for none. A BERT-base-uncased proxy (110M, matching DeepContext) confirms cross-attack generalization is driven by DAPT, not architecture (Appendix R). CKA analysis (Kornblith et al., 2019) confirms DAPT reshapes representations substantially (Figure 4; Appendix F).

4.5 Mixed-LLM Training

All preceding experiments use single-source (Qwen3-8B) data. To test whether the evidence hierarchy transfers when training data mixes LLM sources, we train on 250 Qwen + 250 Llama-3.1-8B conversations (Table 14). In this exploratory cross-LLM condition, 9-class achieves DD OOD F1 = 0.818±0.096 (+53 pp over vanilla), while MLM drops to vanilla level (0.289). AA F1 = 0.504±0.107, below the majority-class base-

Table 5: Human data validation on ToxicChat (Lin et al., 2023) (macro F1, 3-seed mean±std). Bold indicates best. Single-turn data from real LMSYS user interactions, independent of Qwen3-8B.

Variant	Macro F1
JB-MLM	**.837±.013**
Wiki-MLM	.791±.093
Binary	.705±.072
Scrambled	.616±.056
9-class	.596±.087
Topic	.496±.042
Vanilla	.413±.021

line (F1 $\approx$ 0.808 at 80 : 38 class ratio)—we attribute this to cross-LLM style confounds (Section 5); benign-only adaptation on Llama-origin data collapses Llama jailbreak detection (Appendix H). Full results in Appendix I.

4.6 Human Data Validation

Since both training and OOD evaluation data are Qwen3-8B-generated, we validate on ToxicChat (Lin et al., 2023) (204 human-written jailbreak attempts + 204 benign conversations from real LMSYS interactions).

All DAPT variants exceed vanilla by 18–42 pp (Table 5), confirming transfer to human-written attacks. However, the evidence hierarchy reverses: JB-MLM leads (0.837±0.013) while 9-class ranks lower (0.596±0.087; $p < 0.001$). This reversal—analyzed in Section 5—reveals that classification DAPT's advantage is condition-specific to multi-turn persuasion attacks.

4.7 Perturbation Analysis

Under adversarial paraphrasing (BERTScore 0.92), classification-supervised variants achieve zero degradation on IID and OOD DD (Table 11) while non-adapted models degrade by $\sim$12 pp ($p < 0.001$); on ActorAttack, DAPT variants degrade ($\Delta = -20.4$ pp) but maintain 52 pp over vanilla (Appendix D).

Strategy trajectory analysis (κ=0.78 on known attacks, κ=0.126 on OOD; Appendix E) confirms the taxonomy's value as ablation infrastructure rather than a detection mechanism.

5 Discussion

Confounds and transferability. Three observations argue against a topic shortcut: unstable topic OOD (F1 = 0.541±0.207), scrambled labels within 3.9 pp, and label-free MLM detection (F1 $\geq$ 0.97). ToxicChat (+18–42 pp; Table 5) and cross-LLM experiments (Appendix H) confirm transfer; mixed-LLM 9-class maintains DD F1 = 0.818±0.096 while MLM collapses (Appendix I). Composition appears more determinant than sample count, though partially confounded (Appendix J).

Evidence for discriminative compression. Classification DAPT compresses features into few discriminative dimensions (participation ratio 3.7–9.4 vs. 25–32; Fisher 2.6–19.7 vs. <0.001; Appendix T). Scrambled labels yield comparable compression (Fisher = 2.6), consistent with Zhang et al. (2021), with two findings: (i) domain-relevant partitioning is necessary (topic DAPT has higher per-turn Fisher yet fails at conversation level; Appendix M), and (ii) compression localizes to 3 SVD dimensions in layers 8–12 (Appendix T). A discriminative probe over these 3 dimensions achieves perfect AA OOD detection vs. MLM 0.636 with 768 (Appendix T); frozen probing near-parity (3.1 pp) is consistent with Stage-1 establishing this structure, though pattern memorization may also contribute.

Condition-specific advantage. The hierarchy is specific to synthetic multi-turn evaluation. On ToxicChat (single-turn human data), JB-MLM leads (0.837) while 9-class ranks lower (0.596); 65% of the gap stems from false positives (FPR 0.510 vs. 0.167), 35% from missed attacks. Truncation *widens* the 9-class advantage (+6.0 pp; Appendix Z.1), implicating synthetic-human distributional differences.

Generalization boundaries. At larger scale (RoBERTa-large, 355M), vanilla representations suffice for ActorAttack without adaptation, suggesting scale-dependent DAPT utility. Mean pooling matches BiGRU ($\leq$1 pp; Appendix U): detection is turn-level anomaly aggregation. Benign-side shift (WildChat FPR 48.1%→68.1%) is mitigated by 10 target conversations (FPR→0%; OASST2 1.0%±0.5% at $N = 25$; Appendix Q).

6 Conclusion

Thirteen encoder configurations on synthetic multi-turn data (IID benign) decompose jailbreak generalization into attack-side (discriminative compression; MLM collapses under mixed-LLM) and benign-side (FPR 58–68%→0–1.5%, N = 10–25) axes at 24.3× speedup; domain-relevant classification suffices ($d < 0.1$; AA $d = 0.44$).

7 Limitations

All findings derive from synthetic conversations generated by a single LLM (Qwen3-8B; 350 training, 76–118 test per family, 3 seeds); the evidence hierarchy reverses on human single-turn data (Section 5), and no human-generated multi-turn jailbreak dataset exists. OOD F1 figures are upper bounds because benign data is IID; benign-side adaptation (WildChat FPR 68.1% $\rightarrow$ 0% with 10 conversations; OASST2 57.5% $\rightarrow$ 1.0% at $N = 25$) is validated on only two platforms with small samples ($n \leq 49$). Benign-only adaptation does not address cross-LLM distribution shift: adapting on Llama-origin conversations collapses Llama jailbreak detection (Appendix H). Only persuasion-mediated multi-turn attacks fall within scope; single-turn token-level attacks (Zou et al., 2023) and non-text modalities are not addressed.

Ethics Statement

This work is defensive: it improves detection of multi-turn jailbreak attacks rather than developing new attacks. We acknowledge dual-use risk, as the persuasion taxonomy could inform adversarial actors. We mitigate this by using only synthetic conversations (no real harmful content) and withholding attack-generation prompts. Detection code, model weights, and evaluation data will be released under CC BY-NC 4.0. No human subjects were involved.

References

Justin Albrethsen, Yash Datta, Kunal Kumar, and Sharath Rajasekar. 2026. Deepcontext: Stateful real-time detection of multi-turn adversarial intent drift in llms. *arXiv preprint*.

Gabriel Alon and Michael Kamfonas. 2023. Detecting language model attacks with perplexity. *arXiv preprint*.

Maksym Andriushchenko, Francesco Croce, and Nicolas Flammarion. 2025. Jailbreaking leading safety-aligned llms with simple adaptive attacks. In *International Conference on Learning Representations*.

Cem Anil, Esin Durmus, Nina Panickssery, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Meg Tong, Jesse Mu, Daniel Ford, Francesco Mosconi, Rajashree Agrawal, Rylan Schaeffer, Naomi Bashkansky, Samuel Svenningsen, Mike Lambert, Ansh Radhakrishnan, Carson Denison, Evan J. Hubinger, and 15 others. 2024. Many-shot jailbreaking. In *Advances in Neural Information Processing Systems*.

J. L. Austin. 1962. *How to Do Things with Words*. Harvard University Press.

Iz Beltagy, Kyle Lo, and Arman Cohan. 2019. SciBERT: A pretrained language model for scientific text. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3615–3620.

Blake Bullwinkel, Mark Russinovich, Ahmed Salem, Santiago Zanella-Beguelin, Daniel Jones, Giorgio Severi, Eugenia Kim, Keegan Hines, Amanda Minnich, Yonatan Zunger, and Ram Shankar Siva Kumar. 2025. A representation engineering perspective on the effectiveness of multi-turn jailbreaks. *arXiv preprint*.

Rich Caruana. 1997. Multitask learning. *Machine Learning*, 28(1):41–75.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J. Pappas, and Eric Wong. 2024. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *arXiv preprint arXiv:2404.01318*.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J. Pappas, and Eric Wong. 2025. Jailbreaking black box large language models in twenty queries. In *IEEE Conference on Secure and Trustworthy Machine Learning*.

Robert B. Cialdini. 2001. *Influence: Science and Practice*, 4th edition. Allyn & Bacon.

Alexis Conneau, German Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. 2018. What you can cram into a single $&!#* vector: Probing sentence embeddings for linguistic properties. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pages 2126–2136.

Giovanni Da San Martino, Alberto Barrón-Cedeño, Henning Wachsmuth, Rostislav Petrov, and Preslav Nakov. 2020. SemEval-2020 Task 11: Detection of propaganda techniques in news articles. In *Proceedings of the Fourteenth Workshop on Semantic Evaluation*, pages 1377–1414.

Giovanni Da San Martino, Seunghak Yu, Alberto Barrón-Cedeño, Rostislav Petrov, and Preslav Nakov. 2019. Fine-grained analysis of propaganda in news articles. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, pages 5636–5646.

Kemal Derya and Berk Sunar. 2026. Revisiting JBShield: Breaking and rebuilding representation-level jailbreak defenses. *arXiv preprint*.

Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. 2020. Don't stop pretraining: Adapt language models to domains and tasks. In *Proceedings of the 58th Annual Meeting of the*

Association for Computational Linguistics, pages 8342–8360.

Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel Bowman, and Noah A. Smith. 2018. Annotation artifacts in natural language inference data. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics*.

Thilo Hagendorff, Erik Derner, and Nuria Oliver. 2026. Large reasoning models are autonomous jailbreak agents. *Nature Communications*, 17:1435.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. 2024. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of llms. In *Advances in Neural Information Processing Systems*.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2023. DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing. In *International Conference on Learning Representations*.

Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. 2021. Deberta: Decoding-enhanced bert with disentangled attention. In *International Conference on Learning Representations*.

John Hewitt and Christopher D. Manning. 2019. A structural probe for finding syntax in word representations. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics*, pages 4129–4138.

Jeremy Howard and Sebastian Ruder. 2018. Universal language model fine-tuning for text classification. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pages 328–339.

Erick Hsu, Ikuya Hsu, and Paul Chung. 2024. Improved llm jailbreak detection via pretrained embeddings. *arXiv preprint*.

Peichun Hua, Hao Li, Shanghao Shi, Zhiyuan Yu, and Ning Zhang. 2026. Rethinking jailbreak detection of large vision language models with representational contrastive scoring. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics*.

Zixuan Huang, Kecheng Huang, Lihao Yin, Bowei He, Huiling Zhen, Mingxuan Yuan, and Zili Shao. 2025. An attention-aware gnn-based input defender against multi-turn jailbreak on llms. *arXiv preprint*.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. 2023. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint*.

Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping-yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. 2023. Baseline defenses for adversarial attacks against aligned language models. *arXiv preprint*.

Yifan Jiang, Kriti Aggarwal, Tanmay Laud, Kashif Munir, Jay Pujara, and Subhabrata Mukherjee. 2024. RED QUEEN: Safeguarding large language models against concealed multi-turn jailbreaking. *arXiv preprint*.

Di Jin, Zhijing Jin, Joey Tianyi Zhou, and Peter Szolovits. 2020. Is BERT really robust? a strong baseline for natural language attack on text classification and entailment. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 8018–8025.

Sri Durga Sai Sowmya Kadali and Evangelos E. Papalexakis. 2026. Jailbreaking leaves a trace: Understanding and detecting jailbreak attacks from internal representations of large language models. *arXiv preprint arXiv:2602.11495*.

Andreas Köpf, Yannic Kilcher, Dimitri von Rütte, Sotiris Anagnostidis, Zhi-Rui Tam, Keith Stevens, Abdullah Barhoum, Duc Nguyen, Oliver Stanley, Richárd Nagyfi, and 1 others. 2023. OpenAssistant Conversations – Democratizing Large Language Model Alignment. *Advances in Neural Information Processing Systems*, 36.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. 2019. Similarity of neural network representations revisited. In *International Conference on Machine Learning*, pages 3519–3529.

Prashant Kulkarni. 2026. Latent adversarial detection: Adaptive probing of LLM activations for multi-turn attack detection. *arXiv preprint*.

Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. 2020. BioBERT: A pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240.

Linyang Li, Ruotian Ma, Qipeng Guo, Xiangyang Xue, and Xipeng Qiu. 2020. BERT-ATTACK: Adversarial attack against BERT using BERT. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, pages 6193–6202.

Minxuan Li, Yue Liu, Siyuan Chen, Fangzhao Sun, Hao Ren, Zhengyi Liu, Chengming Wu, and Xing Xie. 2025a. M2S: Multi-turn to single-turn – converting multi-turn jailbreak attacks to single-turn for enhanced safety guardrails. *arXiv preprint*.

Nathaniel Li, Ziwen Han, Ian Steneker, Willow Primack, Riley Goodside, Hugh Zhang, Zifan Wang, Cristina Menghini, and Summer Yue. 2024. Llm defenses are not robust to multi-turn human jailbreaks yet. *arXiv preprint*.

Tianlong Li, Zhenghua Wang, Wenhao Liu, Muling Wu, Shihan Dou, Changze Lv, Xiaohua Wang, Xiaoqing Zheng, and Xuanjing Huang. 2025b. Revisiting jailbreaking for large language models: A representation engineering perspective. In *Proceedings of the 31st International Conference on Computational Linguistics*.

Zi Lin, Zihan Wang, Yongqi Tong, Yangkun Wang, Yuxin Guo, Yujia Wang, and Jingbo Shang. 2023. Toxicchat: Unveiling hidden challenges of toxicity detection in real-world user-AI conversation. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 4694–4702.

Xiaodong Liu, Pengcheng He, Weizhu Chen, and Jianfeng Gao. 2019a. Multi-task deep neural networks for natural language understanding. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4487–4496.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019b. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Xiaoya Lu, Dongrui Liu, Yi Yu, Luxin Xu, and Jing Shao. 2025. X-boundary: Establishing exact safety boundary to shield LLMs from multi-turn jailbreaks without compromising usability. In *Findings of the Association for Computational Linguistics: EMNLP 2025*.

Hartmut Maennel, Ibrahim M. Alabdulmohsin, Ilya O. Tolstikhin, Robert J. N. Baldock, Olivier Bousquet, Sylvain Gelly, and Daniel Keysers. 2020. What do neural networks learn when trained with random labels? In *Advances in Neural Information Processing Systems*.

William C. Mann and Sandra A. Thompson. 1988. Rhetorical structure theory: Toward a functional theory of text organization. *Text & Talk*, 8(3):243–281.

Andrea Marchiori and 1 others. 2025. J-dapt: Coral-based domain adaptation with cross-modal fusion for multimodal robotic jailbreak detection. *arXiv preprint*.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. 2024. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. In *Proceedings of the 41st International Conference on Machine Learning*.

Anay Mehrotra, Manolis Zampetakis, Paul Kassianik, Blaine Nelson, Hyrum Anderson, Yaron Singer, and Amin Karbasi. 2024. Tree of attacks: Jailbreaking black-box llms with the pruning of candidate outputs. In *Advances in Neural Information Processing Systems*.

Meta AI. 2024. Llama guard 3. Meta AI (released with Llama 3.1).

Milad Nasr, Nicholas Carlini, Chawin Sitawarin, Sander V. Schulhoff, Jamie Hayes, Michael Ilie, Juliette Pluto, Shuang Song, Harsh Chaudhari, Ilia Shumailov, Abhradeep Thakurta, Kai Yuanqing Xiao, Andreas Terzis, and Florian Tramèr. 2025. The attacker moves second: Stronger adaptive attacks bypass defenses against llm jailbreaks and prompt injections. *arXiv preprint*.

Yi Nian, Shenzhe Zhu, Yuehan Qin, Li Li, Ziyi Wang, Chaowei Xiao, and Yue Zhao. 2025. JailDAM: Jailbreak detection with adaptive memory for vision-language model. In *Conference on Language Modeling*.

Timothy Niven and Hung-Yu Kao. 2019. Probing neural network comprehension of natural language arguments. In *Proceedings of the Association for Computational Linguistics*.

Palo Alto Networks Unit 42. 2024. Deceptive delight: Jailbreak llms through camouflage and distraction. Technical report, Palo Alto Networks.

Ethan Perez, Saffron Huang, Francis Song, Trevor Cai, Roman Ring, John Aslanides, Amelia Glaese, Nat McAleese, and Geoffrey Irving. 2022. Red teaming language models with language models. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 3419–3448.

Jason Phang, Thibault Févry, and Samuel R. Bowman. 2018. Sentence encoders on STILTs: Supplementary training on intermediate labeled-data tasks. *arXiv preprint arXiv:1811.01088*.

Mansi Phute, Alec Helbert, Matthew Hull, ShiNung Peng, Sebastian Szyber, Aylin Caliskan, and Daniel Khashabi. 2023. Llm self defense: By self examination, llms know they are being tricked. *arXiv preprint*.

Rashmi Prasad, Nikhil Dinesh, Alan Lee, Eleni Miltsakaki, Livio Robaldo, Aravind Joshi, and Bonnie Webber. 2008. The penn discourse treebank 2.0. In *Proceedings of the International Conference on Language Resources and Evaluation*.

Qibing Ren, Hao Li, Dongrui Liu, Zhanxu Xie, Xiaoya Lu, Yu Qiao, Lei Sha, Junchi Yan, Lizhuang Ma, and Jing Shao. 2025. Actorattack: Red-teaming large language models via multi-turn actor network theory. In *International Conference on Learning Representations*.

Alexander Robey, Eric Wong, Hamed Hassani, and George J. Pappas. 2024. Smoothllm: Defending large language models against jailbreaking attacks. In *Proceedings of the 41st International Conference on Machine Learning*.

Mark Russinovich, Ahmed Salem, and Ronen Eldan. 2025. Great, now write an article about that: The crescendo multi-turn llm jailbreak attack. In *USENIX Security Symposium*.

J. R. Searle. 1969. *Speech Acts: An Essay in the Philosophy of Language*. Cambridge University Press.

Mrinank Sharma, Meg Tong, Jesse Mu, Tomek Korbak, and 1 others. 2025. Constitutional classifiers: Defending against universal jailbreaks across thousands of hours of red teaming. Technical report, Anthropic.

Guobin Shen, Dongcheng Zhao, Yiting Dong, Xiang He, and Yi Zeng. 2025. Jailbreak antidote: Runtime safety-utility balance via sparse representation adjustment in large language models. In *International Conference on Learning Representations*.

Jialin Song, Xiaodong Liu, Weiwei Yang, Wuyang Chen, Mingqian Feng, Xuekai Zhu, and Jianfeng Gao. 2026. MultiBreak: A scalable and diverse multi-turn jailbreak benchmark for evaluating LLM safety. In *International Conference on Machine Learning*.

Andreas Stolcke, Klaus Ries, Noah Coccaro, Elizabeth Shriberg, Rebecca Bates, Daniel Jurafsky, Paul Taylor, Rachel Martin, Carol Van Ess-Dykema, and Marie Meteer. 2000. Dialogue act modeling for automatic tagging and recognition of conversational speech. *Computational Linguistics*, 26(3):339–374.

Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, Hoagy Cunningham, Nicholas L. Turner, Callum McDougall, Monte MacDiarmid, C. Daniel Freeman, Theodore R. Sumers, Edward Rees, Joshua Batson, Adam Jermyn, and 3 others. 2024. Scaling monosemanticity: Extracting interpretable features from claude 3 sonnet. *Transformer Circuits Thread*.

Haibo Tong, Dongcheng Zhao, Guobin Shen, Xiang He, Dachuan Lin, Feifei Zhao, and Yi Zeng. 2025. Bidirectional intention inference enhances llms' defense against multi-turn jailbreak attacks. *arXiv preprint*.

Xuewei Wang, Weiyan Shi, Richard Kim, Yoojung Oh, Sijia Yang, Jingwen Zhang, and Zhou Yu. 2019. Persuasion for good: Towards a personalized persuasive dialogue system for social good. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5635–5649.

Yifan Wang and 1 others. 2026. Trajguard: Trajectory-based hidden-state detection of multi-turn jailbreak attacks. *arXiv preprint*.

Zhenhua Wang, Wei Xie, Baosheng Wang, Enze Wang, Zhiwen Gui, Shuoyoucheng Ma, and Kai Chen. 2024. Foot in the door: Understanding large language model jailbreaking via cognitive psychology. *arXiv preprint*.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. 2023. Jailbroken: How does llm safety training fail? In *Advances in Neural Information Processing Systems*.

Yueqi Xie, Minghong Fang, Renjie Pi, and Neil Gong. 2024. GradSafe: Detecting jailbreak prompts for LLMs via safety-critical gradient analysis. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, pages 507–518.

Zhangchen Xu, Fengqing Jiang, Luyao Niu, Jinyuan Jia, Bill Yuchen Lin, and Radha Poovendran. 2024. SafeDecoding: Defending against jailbreak attacks via safety-aware decoding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*.

Bo Yan, Weikai Lin, Yada Zhu, and Song Wang. 2026. Safedream: Safety world model for proactive early jailbreak detection. *arXiv preprint*.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Wang, Bo Li, Bowen Lin, and 1 others. 2025. Qwen3 technical report. *arXiv preprint*.

Wenjun Zeng, Yuchi Liu, Ryan Mullins, Ludovic Peran, Joe Fernandez, Hamza Harkous, Karthik Narasimhan, Drew Proud, Piyush Kumar, Bhaktipriya Radharapu, Olivia Sturman, and Oscar Wahltinez. 2024a. Shieldgemma: Generative ai content moderation based on gemma. *arXiv preprint*.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. 2024b. How johnny can persuade llms to jailbreak them: Rethinking persuasion to challenge ai safety by humanizing llms. In *Proceedings of the Association for Computational Linguistics*.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. 2021. Understanding deep learning (still) requires rethinking generalization. *Communications of the ACM*, 64(3):107–115.

Shenyi Zhang, Yuchen Zhai, Keyan Guo, Hongxin Hu, Shengnan Guo, Zheng Fang, Lingchen Zhao, Chao Shen, Cong Wang, and Qian Wang. 2025. JBShield: Defending large language models from jailbreak attacks through activated concept analysis and manipulation. In *USENIX Security Symposium*.

Andy Zou, Long Phan, Justin Wang, Derek Duenas, Maxwell Lin, Maksym Andriushchenko, Rowan Wang, Zico Kolter, Matt Fredrikson, and Dan Hendrycks. 2024. Improving alignment and robustness with circuit breakers. In *Advances in Neural Information Processing Systems*.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint*.

Table 6: LLM-as-judge jailbreak detection. IID: binary F1 (Crescendo test set); OOD: macro F1 (DD = Deceptive Delight, AA = ActorAttack). GPT-5.5 F1 values exclude unparseable responses and represent upper bounds.

Method	DD	AA	IID	Unparse.
Zero-shot				
GPT-5.5	–	–	.383	30–47%
Qwen3-8B	.244	.244	.100	0%
3-shot				
Qwen3-8B	.566	.652	–	0%
Trained classifier				
9-class (ours)	**.994**	**.972**	**1.000**	0%

Table 7: LLM-as-judge prompt optimization (Qwen3-8B, full conversations). CoT adds chain-of-thought + persuasion taxonomy + structured reasoning. IID unparseable: 15.8% (baseline) / 17.1% (CoT); OOD: 0%.

Prompt	DD	AA	FITD	IID
Baseline	.449	.627	.394	.670
CoT-optimized	.851	.885	.729	.700
DAPT 9-class	1.000	.953	1.000	1.000

A LLM-as-Judge Baseline

Table 6 reports LLM-as-judge performance on IID and OOD data. On IID Crescendo, GPT-5.5 achieves precision of 1.0 at all turn prefixes but recall ranges from only 0.105 to 0.290, resulting in F1 = 0.383 on full conversations; 30–47% of responses are unparseable. Qwen3-8B performs worse (IID F1 = 0.100). On OOD data, zero-shot Qwen3-8B achieves macro F1 = 0.244 on both DD and ActorAttack by predicting nearly all conversations as benign. Even with 3-shot prompting, Qwen3-8B reaches only 0.566 (DD) and 0.652 (AA), while DisPeD maintains macro F1 $\geq$ 0.972. The prompts follow a standard format: system instruction defining the task as multi-turn jailbreak detection, followed by the full conversation with role labels, and a binary classification request.

Prompt optimization. To test whether prompt design inflates DisPeD's perceived advantage, we compare the baseline prompt against an optimized variant adding chain-of-thought reasoning, a persuasion pattern taxonomy (rapport building, escalation, reframing, emotional manipulation, authority appeal), and structured output format. Table 7 reports results under identical conditions (Qwen3-8B, full conversations).

CoT prompting substantially improves OOD detection (+40.2 pp DD, +25.8 pp AA, +33.5 pp FITD) but does not close the gap with encoder-based detection: DAPT retains +14.9 pp on DD and +27.1 pp on FITD. The AA gap narrows to 6.8 pp, suggesting ActorAttack's explicit adversarial patterns are partially accessible to LLM reasoning. CoT increases latency to $\sim$1.1 s/conversation (84$\times$ slower than DisPeD).

B Full Cross-Attack Results by Prefix

C ActorAttack Full Results

Table 9 reveals three distinct prefix-length patterns. The 9-class model improves monotonically from K=1 to Full (+20 pp), consistent with cumulative evidence accumulation across turns. Vanilla DeBERTa *decreases* with more turns (0.337 at K=1 to 0.258 at Full), suggesting that additional attack turns push representations further into benign embedding regions. MLM peaks at K=3 (0.945) then declines to 0.893 at Full, indicating that unsupervised domain exposure captures early-turn patterns but is unstable under extended sequences.

C.1 Error Analysis

Per-sample majority vote across 3 seeds yields 98.3% accuracy on ActorAttack OOD (2 false negatives, 0 false positives). No sample is misclassified by all three seeds; all 7 seed-specific errors are false negatives concentrated in shorter conversations (3–6 turns). On these 7 error samples, vanilla achieves 0/3 correct votes per sample, while 9-class majority vote correctly classifies 5/7, confirming that domain adaptation provides robust per-sample coverage even where individual seeds fail.

D Perturbation Robustness

Table 10 shows perturbation behavior on IID data. Classification-supervised variants (9-class, binary, scrambled) achieve zero degradation at full conversation length regardless of label correctness. Models without jailbreak-domain exposure (Wikipedia MLM, vanilla) degrade by $\sim$12 pp. McNemar's test finds no significant pairwise differences among classification-supervised variants (all $p > 0.13$), though with $\leq$7 discordant pairs, statistical power is limited.

On OOD DD, the IID pattern replicates: classification-supervised variants show zero degradation while McNemar's test confirms 9-class

Table 8: Full cross-attack generalization results (F1) at all prefix lengths. 3-seed mean±std where available. "–" indicates insufficient conversation length for that prefix (FITD conversations contain 2–3 turns).

Method	K=1	K=2	K=3	K=5	Full
IID (Crescendo)					
9-class (ours)	1.000±.000	1.000±.000	1.000±.000	1.000±.000	1.000±.000
MLM-only	.960	.974	.987	1.000	1.000
Vanilla DeBERTa	.968±.033	.978±.016	.987±.000	.982±.014	1.000±.000
TF-IDF LR	1.000	1.000	1.000	1.000	1.000
OOD (Deceptive Delight)					
9-class (ours)	.990±.013	.981±.013	.972±.026	.997±.005	.994±.005
Binary	.994±.009	.994±.009	.984±.008	1.000±.000	1.000±.000
Scrambled	.997±.005	.981±.026	.975±.029	.997±.005	.994±.005
MLM-only	.973±.019	.993±.009	.997±.005	.997±.005	.914±.115
Vanilla DeBERTa	.628±.038	.479±.038	.389±.027	.351±.030	.312±.026
TF-IDF LR	1.000	1.000	.994	1.000	.961
OOD (FITD)					
9-class (ours)	1.000	1.000	–	–	1.000
Vanilla DeBERTa	.990	1.000	–	–	1.000
TF-IDF LR	1.000	–	–	–	1.000

Table 9: Full ActorAttack OOD results (F1) at all prefix lengths. 3-seed mean±std (Binary per-K reports n=2; Full is 3-seed).

Method	K=1	K=2	K=3	K=5	Full
DeBERTa-v3					
Binary	.788±.020	**.935±.018**	**.976±.005**	**.995±.005**	**.990±.008**
9-class	.773±.041	.855±.048	.921±.046	.966±.028	.972±.026
Scrambled	.652±.034	.804±.053	.854±.046	.910±.052	.951±.043
MLM-only	.736±.150	.909±.058	.945±.039	.929±.033	.893±.080
Wiki MLM	.656±.224	.672±.252	.693±.280	.689±.285	.686±.297
Topic	.513±.077	.580±.109	.565±.100	.615±.111	.625±.141
Vanilla	.337±.049	.306±.026	.284±.011	.262±.006	.258±.000
TF-IDF LR	.633	.730	.571	.242	.261
RoBERTa					
9-class	**.738±.033**	.805±.033	.884±.066	.925±.066	.939±.046
MLM	.633±.133	.665±.150	.713±.174	.719±.184	.730±.201
Vanilla	.410±.126	.425±.143	.432±.144	.466±.144	.466±.163

vs. vanilla significance ($p < 0.001$, 49–78 discordant pairs). On OOD ActorAttack, domain-adapted variants degrade substantially (9-class $\Delta = -20.4 \pm 13.5$ pp, MLM -35.3 pp), but perturbation narrows rather than closes the adapted vs. non-adapted gap: 9-class perturbed F1 = 0.768 vs. vanilla 0.248 (McNemar $p < 0.001$). Domain specificity also manifests: Wikipedia MLM degrades by $\sim$12 pp while jailbreak-domain MLM degrades by only 2.6 pp.

E Strategy Trajectory Analysis

Figure 3 shows transition count matrices for three attack families. Crescendo conversations exhibit broad transition coverage across all nine strategy categories (1,818 total transitions), with the highest concentration in Role Assignment self-transitions (545); this reflects its gradual escalation design. FITD conversations show a markedly sparser pattern (541 transitions), with Role→Obfuscation (161) as the dominant transition, consistent with FITD's commitment-consistency exploitation (Cialdini, 2001). DD conversations span 5 active source strategies (565 transitions), with Emotion→Obfuscation (129) as the dominant transition, aligning with DD's design of embedding harmful content within emotionally engaging contexts (Palo Alto Networks Unit 42, 2024).

F Centered CKA Heatmaps

G Embedding Space Visualization

Figure 5 visualizes mean-pooled `[CLS]` embeddings via t-SNE for three representative variants (Vanilla, JB-MLM, 9-Class) on DD OOD and Ac-




Figure 3: Persuasion strategy transition count matrices for three attack families, based on ground-truth intended strategy labels. Strategy labels validated on n=50 samples with a single annotator (κ=0.78); fine-grained trajectory patterns should be interpreted with this limitation. Crescendo exhibits broad coverage across all strategy categories, while FITD and DD concentrate transitions in smaller subsets. Row i, column j counts transitions from strategy i at turn t to strategy j at turn $t+1$.

Table 10: Perturbation behavior under adversarial paraphrasing on IID Crescendo (n=76). Δ: F1 degradation (pp). Classification-supervised variants achieve zero degradation at full length; this pattern does not generalize to ActorAttack.

Method	Δ Full	Δ K=1	Δ K=2	Δ K=3
9-class (ours)	**0.0**	**−2.6**	**0.0**	**0.0**
Scrambled	**0.0**	−5.3	−2.6	**0.0**
Binary	**0.0**	−9.2	−2.6	**0.0**
TF-IDF LR	−1.3	−9.6	−4.1	−1.3
MLM-only	−2.6	−9.2	−4.0	−4.0
Topic (seed 42)	−4.0	−2.7	−2.7	**0.0**
Wikipedia MLM	−12.1	−12.4	−15.4	−17.9
Vanilla DeBERTa	−11.8	−14.6	−12.1	−13.8

Table 11: Perturbation robustness on OOD Deceptive Delight (n=118). Δ: F1 change (pp) from clean to paraphrased. 3-seed mean±std where available.

Variant	Clean Full	Pert. Full	Δ Full	Δ K=1
9-class	.994±.005	1.000±.000	+0.6	+0.6
Binary	1.000±.000	1.000±.000	0.0	+0.6
Scrambled	.994±.005	1.000±.000	+0.6	−0.3
JB MLM	.914±.115	.941	+2.7	0.0
Wiki MLM*	.904±.115	.872	−3.3	−3.2
Vanilla†	.312±.026	.339±.055	+2.7	−6.8±1.1

*Wiki MLM degradation is seed-driven: seed 42 accounts for −9.8 pp; other seeds show 0.0 pp change.

†Vanilla Δ Full = +2.7 pp reflects floor-effect noise (baseline 0.312, std 0.055), not meaningful improvement.

torAttack. Vanilla embeddings show dispersed jailbreak clusters with ambiguous decision boundaries, while domain-adapted variants (JB-MLM, 9-Class) produce tighter, more separable clusters. JB-MLM achieves the clearest bimodal separation on both evaluation sets, consistent with its superior detection performance.

H Cross-LLM Validation

Table 12 shows three inference conditions. When both jailbreak and benign text come from Llama (row 2), all variants collapse (F1 = 0.26–0.43), but this conflates two sources of distribution shift: unfamiliar jailbreak patterns and unfamiliar benign text. Row 3 isolates jailbreak transferability by pairing Llama jailbreaks with the original Qwen benign distribution. Under this condition, 9-class recovers to F1 = 1.000 on DD and 0.801 on ActorAttack, and JB-MLM reaches 0.903 on ActorAttack. The contrast between rows 2 and 3 shows that the dominant failure mode in row 2 is benign distribution mismatch (false positives from unfamiliar benign text), not inability to recognize cross-LLM jailbreak patterns. Vanilla remains at 0.26–0.31 across all conditions, further confirming that encoders without DAPT lack OOD detection capability regardless of the LLM source. The residual degradation on ActorAttack (0.801 vs. 0.972) reflects genuine cross-LLM variation in structurally complex attack patterns.

Table 13 decomposes DD Full F1 into true positive and false positive rates. TP rates are identical regardless of the benign source: domain-adapted models detect Llama-generated jailbreaks at the same rate whether evaluated against Qwen or Llama benign text. The F1 collapse in the full Llama condition (Table 12, row 2) is driven entirely by false positives on unfamiliar benign text (FP rate: 88–90% on Llama vs. 0–0.9% on Qwen




Figure 4: Centered CKA similarity (Kornblith et al., 2019) between encoder variants on IID and OOD data for DeBERTa-v3 and RoBERTa. Low off-diagonal values (vanilla vs. adapted variants) confirm that continued pretraining substantially reshapes representations; the MLM vs. 9-class block shows distinct geometries (CKA ≤ 0.2 on RoBERTa OOD).




Figure 5: t-SNE visualization of mean-pooled `[CLS]` embeddings (perplexity=30) for Vanilla, JB-MLM, and 9-Class variants on DD OOD and ActorAttack (118 samples each; blue=benign, red=jailbreak).

Table 12: Cross-LLM validation (F1, full conversation). All models are trained on Qwen3-8B data; conditions vary the source of jailbreak (JB) and benign (ben.) conversations at inference. Values are evaluated under a matched 50-sample subset protocol and differ from Table 3, which uses the full evaluation set.

	DD Full			*AA Full*		
Condition	Van.	MLM	9-cl.	Van.	MLM	9-cl.
Qwen JB + Qwen ben.	.312	.914	.997	.258	.893	.972
Llama JB + Llama ben.	.261	.282	.433	.261	.368	.331
Llama JB + Qwen ben.	.302	.778*	1.000	.302	.903	.801

*High seed variance (std = 0.306): seed 456 outlier (F1 = 0.345); remaining two seeds achieve F1 $\geq$ 0.97.

Table 13: Error decomposition for DD Full cross-LLM conditions (matched 50-sample subsets). TP rate is identical across benign conditions; the F1 collapse in the Llama-only condition (Table 12, row 2) is driven entirely by false positives on unfamiliar benign text.

Metric	Van.	MLM	9-cl.
TP rate (Llama JB)	0.0%	68.0%	100.0%
FP rate (Llama ben.)	29.3%	88.0%	90.0%
FP rate (Qwen ben.)	0.0%	0.9%	0.0%

for adapted variants). The model implicitly treats non-Qwen text style as a jailbreak indicator, a spurious correlation from single-LLM training data. This failure reflects a data diversity limitation, not a methodological one; mixed-LLM training (Table 14) partially addresses this confound.

I Mixed-LLM Training Results

Table 14 reports detection performance when training on a mixed corpus of Qwen3-8B and Llama-3.1-8B conversations. On synthetic multi-turn data, classification-based DAPT (9-class) maintains the strongest DD OOD performance (0.818±0.096), outperforming both vanilla (0.291±0.065) and MLM (0.289±0.101) by 53 pp. ActorAttack remains challenging under mixed-LLM conditions (9-class F1 = 0.504±0.107), suggesting structurally complex attacks require larger or more diverse training data. ToxicChat performance shows no significant improvement over single-source training (0.550±0.052 vs. 0.596±0.087; Section 4.6), consistent with ToxicChat being zero-shot single-turn transfer rather than a standard OOD benchmark.

Cross-LLM training pilot. To test whether mixed-source training preserves Qwen OOD detection while enabling cross-LLM transfer, we train 9-class DAPT on a combined corpus: 175 Qwen jailbreak + 175 Qwen benign + 164 Llama-3.1-8B-Instruct jailbreak + 150 WildChat benign ($n = 664$ total; 3-seed mean). Qwen OOD detection is fully

Table 14: Mixed-LLM training (250 Qwen + 250 Llama conversations, 3-seed mean±std where available). ToxicChat evaluated on balanced set (408 conversations).

Variant	Mixed	DD OOD	AA OOD	FITD OOD	ToxicChat
9-class	**.996±.006**	**.818±.096**	**.504±.107**	**.997±.005**	**.550±.052**
MLM	.681±.226	.289±.101	.258±.075	.679±.188	.256±.053
Vanilla	.802±.010	.291±.065	.389±.073	.867±.022	.366±.007

preserved (DD/AA/FITD F1 = 1.000 across all families), and WildChat FPR remains 0%. On held-out Llama-generated conversations, Crescendo recall reaches 100% ($n = 40$; 95% CI lower bound 91.2%). Llama DD, AA, and FITD each achieve 100% recall, but with only $n = 10$ per family the 95% CI lower bound is 72.2%, limiting the strength of this evidence. These results are preliminary: they confirm that mixed-LLM training does not degrade existing detection and provide initial evidence of cross-LLM transfer, but definitive conclusions require larger Llama-generated test sets.

J Dataset Scale Validation

Table 15: Dataset composition validation (1,000 conversations from a different generation run with different topic seeds and attack composition than the 500-conversation training set; no sample overlap). IID results omitted due to train/test overlap (71% of original test set present in expanded data). Note: the expanded corpus uses different benign sources (LLM-synthetic vs. WildChat-anchored) and excludes cipher-based attack variants present in the original; performance differences may reflect composition changes rather than scale effects.

Corpus	Variant	DD OOD	AA OOD
Expanded (1,000)	9-class	.889±.041	.913±.041
	MLM	.338±.010	.351±.018
	Vanilla	.326±.000	.508±.085
Resample (350)	9-class	.887±.086	.883±.091

Table 15 compares the original 500-conversation training set with a separately generated 1,000-conversation corpus. The hierarchy 9-class $\gg$ MLM $\approx$ vanilla is preserved, but the 5–10 pp OOD degradation relative to the original (9-class DD: 0.889 vs. 0.994) likely reflects corpus composition differences—the expanded set uses different benign generation sources and excludes cipher-based attack variants—rather than a scale effect.

To isolate scale from composition, we randomly sample 350 conversations from the expanded 1,000-conversation corpus and retrain 9-class DAPT (3 seeds). Resample-350 yields DD F1 = 0.887±0.086 and AA F1 = 0.883±0.091, matching the full expanded corpus (DD 0.889, AA 0.913) rather than the original 349-conversation training set (DD 0.994, AA 0.972). Reducing the expanded corpus to the original sample count does not recover original performance, confirming that dataset composition—not sample count—is the primary determinant of detection quality.

K RoBERTa-large DAPT Learning Rate Control

Table 16: RoBERTa-large (355M) DAPT learning rate control on OOD Full (3-seed mean±std). Reducing the learning rate worsens both DD and AA, ruling out over-adaptation as the cause of the regression in Table 4.

Config	DD Full	AA Full
Vanilla (no DAPT)	.927±.036	1.000±.000
9-class, LR=2×10^{-5}	.987±.004	.946±.057
9-class, LR=1×10^{-5}	.948±.034	.781±.054

Reducing the DAPT learning rate from 2×10^{-5} to 1×10^{-5} worsens both DD and AA performance, which rules out over-adaptation as the cause of the regression observed in Table 4. An MLM-only variant (without classification) produces the same pattern (AA Full = 0.874±0.014); representation drift from continued pretraining, not classification-specific bias, is the underlying cause. Domain-adaptive fine-tuning narrows the representation space of a sufficiently large encoder and reduces its inherent OOD generalization ability.

L TOST Equivalence Sensitivity Analysis

Table 17: TOST equivalence test sensitivity to margin δ (scrambled vs. 9-class). Rows grouped by seed count: n=3 (42, 123, 456), n=5 (+789, 1000), n=10 (+2024, 2025, 2026, 314, 628). p-values from two one-sided t-tests; $p < 0.05$ confirms equivalence within $\pm\delta$.

Dataset	n	δ=5 pp	δ=3 pp	δ=2 pp
DD OOD	3	.006 ✓	.016 ✓	.035 ✓
DD OOD	5	$<.001$ ✓	$<.001$ ✓	.002 ✓
DD OOD	10	$<10^{-8}$ ✓	$<10^{-8}$ ✓	$<10^{-8}$ ✓
FITD OOD	10	$<10^{-8}$ ✓	$<10^{-8}$ ✓	$<10^{-8}$ ✓
ActorAttack	3	.290	.428	.507
ActorAttack	5	.080	.200	.310
ActorAttack	10	.183	—	—

On DD, TOST confirms scrambled $\approx$ correct labels even at δ=2 pp (p=0.035 at n=3), demon-

strating that label correctness is not a detection factor; the DD equivalence conclusion is robust to both margin choice and seed count ($p < 10^{-8}$ at n=10). On FITD, equivalence is similarly confirmed ($p < 10^{-8}$, $d \approx 0$ at n=10). On ActorAttack, extending from n=5 to n=10 reveals a moderate effect: Cohen's d increases from 0.09 to 0.44 (medium), with 9-class outperforming scrambled by 3 pp (0.979 vs. 0.949). TOST remains inconclusive ($p = 0.183$ at δ=5 pp), and variance is driven by seed 314 (scrambled F1 = 0.833). Label correctness is thus attack-complexity-dependent: negligible on template-based families (DD, FITD) but moderate on structurally complex attacks (ActorAttack).

M Partition Robustness and Topic Failure Analysis

M.1 Random Binary Partition Robustness

Table 18: OOD F1 for 10 random binary partitions of the 9 strategy labels (each partition randomly assigns strategies to group A or B). All partitions use identical Stage-1 DAPT and Stage-2 GRU training; only the binary label mapping differs. Seed 42 (3 runs).

Partition	Group A	IID	DD OOD	AA OOD
0	{0,2,4,5,7}	1.000	1.000	1.000
1	{1,3,5,6,8}	1.000	1.000	1.000
2	{0,1,3,7,8}	1.000	1.000	1.000
3	{2,4,5,6,7}	1.000	1.000	1.000
4	{0,1,2,6,8}	1.000	1.000	1.000
5	{0,3,4,7,8}	1.000	1.000	1.000
6	{1,2,3,5,6}	1.000	1.000	1.000
7	{1,4,6,7}	1.000	1.000	0.636
8	{0,2,3,4,8}	1.000	1.000	1.000
9	{0,1,5,7,8}	1.000	1.000	1.000
Mean±Std		1.000±.000	1.000±.000	0.964±.109

All 10 partitions achieve perfect IID and DD OOD detection regardless of how the 9 strategy labels are split into two groups. On ActorAttack, 9/10 partitions achieve F1 = 1.000; the sole outlier (partition 7, AA F1 = 0.636) uses a 4/5 split that isolates a specific strategy cluster. The near-universal success confirms that domain-relevant binary classification—not specific label semantics—drives cross-attack generalization on template attacks. The AA outlier is consistent with the complexity-dependent boundary observed in Section 4.3: structurally complex attacks are sensitive to specific partition choices while template attacks are not.

Table 19: Per-turn Fisher ratio (mean across all dimensions) and silhouette score between jailbreak and benign turn embeddings (`[CLS]` representations). Higher values indicate greater per-turn separability.

Model	Dataset	Fisher (mean)	Silhouette
Vanilla	IID test	0.118	0.034
Vanilla	DD OOD	0.401	0.411
Vanilla	AA OOD	0.408	0.330
9-class DAPT	IID test	0.073	0.048
9-class DAPT	DD OOD	0.200	0.079
9-class DAPT	AA OOD	0.832	0.301
Topic DAPT	IID test	0.108	0.076
Topic DAPT	DD OOD	0.653	0.274
Topic DAPT	AA OOD	0.311	0.141

M.2 Topic Classification Failure Analysis

Topic DAPT achieves *higher* per-turn Fisher separability than 9-class DAPT on IID and DD (0.653 vs. 0.200 on DD) yet produces far worse conversation-level detection (F1 = 0.541 vs. 0.994). This rules out per-turn separability destruction as the failure mechanism. The 9-class model instead greatly expands the embedding space (centroid L_2 distance 7.5–27.6 vs. 0.9–1.1 for vanilla) while distributing both classes broadly, creating richer representation geometry that the downstream GRU exploits over the turn sequence. Topic classification teaches features that separate turns individually but are temporally inconsistent across a conversation—high per-turn separability does not guarantee that the GRU can learn a stable conversation-level decision boundary.

N Reproducibility Details

Stage-1 training. All variants use DeBERTa-v3-base (184M parameters) with learning rate 2×10^{-5}, AdamW optimizer (β_1=0.9, β_2=0.999, weight decay 0.01), linear warmup over the first 10% of steps, batch size 16, and 4 epochs. MLM variants use 15% random token masking. Training takes approximately 30 minutes per variant on a single NVIDIA A100 (40GB).

Stage-2 training. The BiGRU has hidden dimension 256, 2 layers, and dropout 0.3 (bidirectional, so output dimension 512). The MLP classifier has layers $512 \rightarrow 256 \rightarrow 2$ with ReLU activation. Training uses learning rate 1×10^{-3}, Adam optimizer, batch size 32, and 20 epochs with early stopping (patience 5) on validation F1. Stage-2 training completes in under 5 minutes per variant.

Data generation. Jailbreak conversations are generated using Qwen3-8B with attack-specific prompt templates. Crescendo conversations follow a 5–8 turn gradual escalation structure. FITD conversations use a 2–3 turn commitment-consistency structure. Deceptive Delight conversations embed harmful content within emotionally engaging 3–5 turn sequences. Benign conversations are generated with topic-anchored prompts across five domains (technology, health, finance, education, general) with matched turn counts.

Strategy annotation. Each user turn is annotated by Qwen3-8B using a structured prompt that provides definitions and two examples for each of the nine strategy categories. The prompt instructs the model to output a single category label. We plan to release all generation and annotation prompts, the full dataset, and training code upon acceptance.

Adversarial paraphrasing. The paraphrased test set is generated by instructing Qwen3-8B to rephrase each user turn while preserving the communicative intent. The resulting paraphrases have mean BERTScore 0.92 and mean lexical overlap 0.20 with the originals. These metrics confirm substantial surface-level variation.

Cross-checkpoint variance. To disentangle Stage-1 from Stage-2 variance, we evaluate three independently trained 9-class DAPT checkpoints (seeds 42, 123, 456) with a fixed downstream BiGRU seed (42). Results: IID F1 = 1.000±0.000, DD OOD = 0.926±0.026, AA OOD = 0.935±0.013. Stage-1 training is stable (OOD std $\leq$ 2.6 pp), confirming that the variance reported in the main paper is not dominated by Stage-1 initialization.

O End-to-End Fine-Tuning Upper Bound

End-to-end fine-tuning unfreezes the Stage-1 encoder during Stage-2 BiGRU training, allowing gradient flow through the full pipeline. On IID and OOD DD, the two configurations are indistinguishable; on structurally complex ActorAttack, E2E recovers +5.8 pp (error rate 6.1% $\rightarrow$ 0.3%, a substantial relative reduction). Frozen probing captures the vast majority of discriminative information from Stage-1 DAPT; the remaining gap reflects downstream optimization constraints rather than missing representational capacity.

Table 20: Frozen probing vs. end-to-end (E2E) fine-tuning for DeBERTa-v3-base 9-class (3-seed mean±std). E2E unfreezes the Stage-1 encoder during Stage-2 training. Frozen values use main-experiment checkpoints (matching Tables 2–3); Table 28 uses plan_002 checkpoints, yielding higher frozen accuracy (DD = .997, AA = .972) and a narrower E2E gap ($\leq$2.5 pp).

Config	IID	DD OOD	AA OOD
Frozen probing	1.000±.000	.994±.005	.939±.047
E2E fine-tuning	1.000±.000	1.000±.000	**.997±.005**
Δ	.000	+.006	+.058

Table 21: False positive rate (%) on 226 WildChat benign multi-turn conversations (GPT-3.5 users, avg 7.4 turns per conversation). All models trained on synthetic Qwen3-8B data (1,000-conversation scale). 3-seed mean±std.

Variant	Seed 42	Seed 123	Seed 456	Mean±Std
9-class	66.8	61.1	76.5	68.1±6.4
MLM	36.7	64.6	32.3	44.5±14.3
Vanilla	47.3	42.5	54.4	48.1±4.9

P Real-World False Positive Rate

Table 21 evaluates false positive rates on 226 WildChat benign multi-turn conversations from real GPT-3.5 users (avg 7.4 turns). All variants produce FPR far exceeding deployable thresholds: 9-class is worst at 68.1%, followed by vanilla (48.1%) and MLM (44.5%). Domain adaptation *increases* FPR relative to vanilla (+20 pp for 9-class), indicating that continued pretraining amplifies dependence on the training benign distribution. This is consistent with the cross-LLM false positive spike (Table 13): models trained on synthetic Qwen3-8B benign text implicitly treat unfamiliar conversational styles as jailbreak indicators. High MLM seed variance (std = 14.3%) suggests that unsupervised pretraining is particularly unstable under benign distribution shift. Deployment requires per-domain benign calibration or mixed-source benign training data.

Post-hoc calibration. ROC AUC = 0.700±0.054 indicates insufficient discrimination between WildChat benign and jailbreak conversations at the representation level. At TPR$\geq$95%, the optimal threshold still yields FPR = 62.7%—far above deployable levels. Temperature scaling cannot improve this trade-off, as ROC curves are invariant to monotonic score transforms. The AUC ceiling reflects genuine

domain shift: WildChat benign and jailbreak representations overlap substantially, and no post-hoc calibration can overcome this; in-domain benign adaptation is required.

Q Benign Distribution Diversification Pilot

To test whether the high WildChat FPR (Section P) reflects a fundamental limitation or a remediable distribution mismatch, we conduct a pilot retraining experiment mixing 150 WildChat benign conversations into the training set. We filter 27 of 226 WildChat conversations containing jailbreak-indicative patterns, use 150 for training and 49 for held-out evaluation. Both training and evaluation WildChat samples are drawn from the same source (GPT-3.5 users); this is therefore an IID evaluation of benign coverage, not an OOD generalization test.

Class ratio shift. Adding 150 WildChat benign to the original 350-conversation training set (175 jailbreak + 175 synthetic benign) shifts the benign-to-jailbreak ratio from 50:50 to approximately 65:35 (325 benign vs. 175 jailbreak). To control for this confound, we downsample WildChat benign to 88 conversations (175 jailbreak : 88 WildChat benign + 87 original benign $\approx$ 50:50, $n = 350$). This balanced variant achieves identical WildChat FPR (0%, same CI) while maintaining OOD detection (AA F1 = 0.991, FITD/DD F1 = 1.000), confirming that class ratio is not the driver of FPR reduction.

Table 22: Effect of benign distribution diversification on WildChat FPR and OOD jailbreak detection. Mixed training adds 150 WildChat benign to the original 350 synthetic conversations. 3-seed mean (seeds 42, 123, 456). WildChat evaluation is IID (same source as training WildChat).

Metric	Original	Mixed
WildChat FPR (%)	68.1	**0.0**
IID F1	1.000	1.000
DD OOD F1	1.000	1.000
AA OOD F1	∼0.960	0.956
FITD OOD F1	1.000	1.000

Mixed benign training reduces WildChat FPR from 68.1% to 0% (exact binomial 95% CI upper bound: 6.1%, $n = 49$) with no degradation in cross-attack detection (ActorAttack F1 = 0.956, within 0.4 pp of original). This confirms the diagnosis from Section P: when representative benign data is available, the high FPR is remediable without sacrificing detection performance. The evaluation set is small ($n = 49$) and IID with respect to the training WildChat distribution, so the result should be interpreted as evidence that benign distribution mismatch—not model capacity—is the bottleneck; validation on larger and independently sourced OOD benign corpora is needed to establish deployment-ready FPR bounds.

Benign adaptation curve. To quantify how many OOD benign samples suffice, we vary the number of WildChat benign conversations added to training ($N \in \{0, 5, 10, 25, 50, 100, 150\}$) and retrain the full pipeline (9-class DAPT + BiGRU) for each N (seed 42).

Table 23: Benign adaptation curve: WildChat FPR and OOD detection F1 as a function of N WildChat benign conversations added to the 350-conversation training set. Seed 42 (single-seed curve); $N = 10$ confirmed across 3 seeds (FPR = 0% for all). WildChat evaluation $n = 49$.

N	Train	FPR (%)	DD F1	AA F1	FITD F1
0	350	65.3	1.000	0.981	1.000
5	355	16.3	0.990	0.981	1.000
10	360	**0.0**	1.000	1.000	1.000
25	375	0.0	1.000	0.953	1.000
50	400	0.0	1.000	1.000	1.000
100	450	0.0	1.000	1.000	1.000
150	500	0.0	1.000	0.981	1.000

FPR drops sharply from 65.3% ($N = 0$) to 16.3% ($N = 5$) to 0% ($N = 10$), remaining at 0% for all $N \geq 10$. OOD detection is preserved throughout: all F1 scores ≥ 0.953 (minor ActorAttack variation at $N = 25$ is within seed noise). This demonstrates that benign distribution mismatch is addressable with minimal annotation effort—10 conversations from the target domain suffice to eliminate false positives entirely (95% CI upper bound: 6.1% at $n = 49$). IID F1 remains 1.000 for all N. Multi-seed validation at $N = 10$ (seeds 42, 123, 456) confirms robustness: FPR = 0.0% for all seeds, DD/FITD F1 = 1.000$\pm$0.000, AA F1 = 0.981$\pm$0.016.

Second benign source: OASST2. To test whether benign-side shift generalizes beyond WildChat, we evaluate on 200 benign multi-turn conversations from OpenAssistant OASST2 (Köpf et al., 2023)—a crowdsourced dataset of real human conversations, distinct from WildChat (GPT-3.5 user logs) in both authorship and topic distribution.

Baseline FPR on OASST2 (57.5%) is comparable to WildChat (68.1%), confirming that benign-side shift is not source-specific but a general consequence of synthetic-only benign training.

Table 24: OASST2 benign adaptation curve: FPR on 200 OASST2 benign conversations and OOD jailbreak detection F1 as a function of N OASST2 conversations added to training. $N = 25$ confirmed across 3 seeds (mean±std); other rows seed 42. Compare WildChat (Table 23): FPR reaches 0% at $N = 10$.

N	FPR (%)	IID F1	DD F1	AA F1	FITD F1
0	57.5	–	–	–	–
10	20.5	1.000	1.000	1.000	1.000
25	**1.0±0.5**	1.000	1.000	0.953±.037	1.000
50	**0.5**	1.000	1.000	0.990	1.000

The adaptation curve follows the same pattern—monotonic FPR reduction with preserved OOD detection—but requires more samples: 25 conversations reduce FPR to 1.0%±0.5% across 3 seeds (vs. 0% at $N = 10$ for WildChat), and 50 conversations reach 0.5%. The slower convergence likely reflects greater distributional distance between crowdsourced OASST2 conversations and the synthetic training distribution compared to WildChat's GPT-3.5 user logs.

Table 25: Benign-side adaptation summary across two independent sources. Both achieve deployment-level FPR (≤1.5%) with no degradation in OOD jailbreak detection. 3 seeds each.

Source	N	FPR (mean±std)	Seeds	Eval n
WildChat	10	0.0%±0.0%	3	49
OASST2	25	1.0%±0.5%	3	200

R BERT-base Proxy Baseline

Table 26: BERT-base-uncased (110M) frozen probing without DAPT, matching DeepContext's encoder family (Albrethsen et al., 2026). 3-seed mean±std. DeBERTa-v3 results from Table 4 for comparison.

Encoder	IID	DD OOD	AA OOD
BERT-base (110M), no DAPT	.996±.006	.318±.031	.275±.027
DeBERTa-v3 (184M), no DAPT	1.000±.000	.312±.043	.258±.000
DeBERTa-v3 (184M), 9-class	1.000±.000	.994±.005	.939±.047

Table 26 compares BERT-base-uncased (110M parameters, matching DeepContext's encoder) against DeBERTa-v3-base (184M), both without domain-adaptive pretraining. The two vanilla encoders achieve comparable OOD performance (DD: 0.318 vs. 0.312; AA: 0.275 vs. 0.258), despite a 1.7× parameter difference and different pretraining procedures. Both collapse on OOD evaluation while 9-class DAPT recovers to 0.994 (DD) and 0.939 (AA). This confirms that cross-attack generalization is driven by domain adaptation, not encoder architecture or capacity at this scale.

S Confidence Calibration

Table 27: Expected calibration error (ECE, 10 bins) for 9-class and vanilla on IID and OOD evaluation (3-seed mean±std). Lower is better.

Variant	IID	DD OOD	AA OOD
9-class	≈0.000	0.143±0.053	0.116±0.053
Vanilla	0.009±0.007	0.669±0.004	0.504±0.066

The 9-class model achieves substantially lower ECE than vanilla on OOD data (0.12–0.14 vs. 0.50–0.67), indicating that domain adaptation improves not only discriminative performance but also confidence calibration. IID calibration is near-perfect for both variants. The residual OOD ECE (0.12–0.14) suggests that temperature scaling could further improve deployment reliability.

T Frozen Probing Verification

Table 28: Frozen probing vs. end-to-end (E2E) fine-tuning (3-seed mean±std). 9-class: plan_002 checkpoints; MLM: plan_017_mlm_control (matched training). Frozen probing trains only BiGRU+MLP on frozen DAPT embeddings.

Config	IID	DD OOD	AA OOD	FITD OOD
Frozen 9-class	1.000±.000	.997±.005	.972±.026	1.000±.000
Frozen MLM	.982±.016	.993±.009	.941±.037	.987±.009
E2E 9-class	1.000±.000	1.000±.000	.997±.005	—

Table 28 compares frozen probing across DAPT objectives and against end-to-end fine-tuning. On easy OOD (DD, FITD), frozen MLM and frozen 9-class representations perform comparably ($\Delta \leq 1.3$ pp). On hard OOD (ActorAttack), 9-class retains a modest advantage (0.972 vs. 0.941, $\Delta = 3.1$ pp) with lower variance ($\sigma = 0.026$ vs. 0.037). Both far exceed vanilla encoders (≤0.318; Table 26). The E2E advantage over frozen 9-class is ≤2.5 pp, confirming that Stage-1 representation quality is the primary source of OOD generalization.

A striking asymmetry emerges when comparing frozen probing to the full pipeline (Table 3): MLM frozen representations *outperform* the full MLM pipeline on AA OOD (0.941 vs. 0.893), while 9-class frozen exactly matches its full pipeline (0.972

vs. 0.972). This indicates that MLM's cross-seed instability originates in Stage-2 BiGRU training rather than Stage-1 DAPT—the MLM encoder produces adequate representations that are then degraded by unstable downstream optimization. Classification DAPT, by contrast, produces representations that remain robust through Stage-2 training, explaining its consistently lower variance (Table 3).

This two-level structure—DAPT vs. no-DAPT producing a representation quality leap (+70 pp), classification vs. MLM DAPT producing a stability difference—is consistent with two further observations: λ=0 matches $\lambda > 0$ during E2E fine-tuning (Table 36), and mean pooling matches BiGRU under E2E (Table 31). Once DAPT representations are strong, downstream configuration details have minimal impact.

Representation geometry analysis. To characterize the mechanism behind classification DAPT's robustness, we analyze Stage-1 representations across all seven DeBERTa-v3-base variants (seed 42). We extract `[CLS]` embeddings from 150 test conversations (50 IID + 50 DD OOD + 50 AA OOD) and compute three metrics.

Table 29: Representation geometry and class separability across Stage-1 variants. PR: participation ratio (effective dimensionality of the embedding space). Fisher ratio: inter-class distance^2 / sum of intra-class variances. Weight Δ: L2 distance from pretrained weights (relative to pretrained norm).

Variant	PR	Fisher	Wt. Δ (%)
Vanilla	31.9	<0.001	0.000
Wiki-MLM	25.0	<0.001	0.221
JB-MLM	24.6	<0.001	0.256
Topic	14.5	0.012	0.371
Scrambled	7.8	2.60	0.283
9-class	9.4	4.47	0.303
Binary	3.7	19.7	0.239

Classification variants compress representations into 2–9 effective dimensions (vs. 25–32 for MLM/vanilla) while increasing Fisher ratio by 3–5 orders of magnitude. Weight distances from pretrained are comparable across all variants (∼0.2–0.4%), indicating that the mechanism is representational restructuring rather than parameter-space regularization. Scrambled labels produce similar compression (PR = 7.8, Fisher = 2.6), confirming that the classification objective structure—not label semantics—drives discriminative compression.

Layer-wise localization. To determine *where* discriminative compression occurs, we compute PR and Fisher ratio at every DeBERTa-v3-base layer (0–12) for four variants (9-class, scrambled, JB-MLM, vanilla) using the same 236-sample evaluation set (seed 42).




Figure 6: Layer-wise representation analysis. (a) Participation ratio: classification variants (9-class, scrambled) show sharp dimensional collapse at layers 9–10 (PR $\approx$ 1.5–2.9) while vanilla/JB-MLM maintain high dimensionality (PR $\approx$ 7–10). (b) Fisher ratio (log scale): class separability diverges from layer 8, with 9-class peaking at 10.9 (layer 10) vs. vanilla 0.73 (15×).

Layers 0–7 show no systematic divergence across variants (Fisher < 2.1 for all; PR tracks similar oscillation patterns), consistent with Maennel et al. (2020)'s finding that early layers learn label-independent features. From layer 8 onward, classification-supervised variants diverge sharply: 9-class Fisher rises from 3.2 (layer 8) to 10.9 (layer 10, peak), while vanilla remains below 1.5 throughout. Simultaneously, 9-class PR drops from 3.4 to 1.5 at layer 10—a 6.6× compression relative to vanilla (PR = 9.7). JB-MLM tracks vanilla across all layers (Fisher ≤ 3.3, PR ≥ 1.4), confirming that MLM does not induce discriminative restructuring. Scrambled labels exhibit the same late-layer pattern (Fisher peaks at 7.9, layer 12; PR drops to 1.5, layer 12), reinforcing that any classification signal—regardless of label semantics—triggers late-layer compression.

Discriminative subspace probe. To test whether the compressed subspace is *sufficient* for OOD detection, we project layer-10 `[CLS]` representations onto the top-k SVD components and train a logistic regression probe (3 seeds, sklearn default). Controls: random k-dimensional projections (10 random bases, mean reported) and vanilla/MLM models under identical projection.

Three findings establish a link between compression and generalization (Table 30). First, 9-class top-3 achieves perfect ActorAttack detection (F1 = 1.000) using only 3 of 768 dimensions—all discriminative information resides in the com-

Table 30: Discriminative subspace probe: OOD F1 when projecting layer-10 representations onto top-k SVD components vs. random k-dimensional projections. 9-class top-3 achieves perfect AA detection with 3/768 dimensions; MLM fails even with all 768.

Model	**Projection**	DD	AA	FITD
9-class	top-3	1.000	**1.000**	1.000
9-class	top-5	1.000	1.000	1.000
9-class	random-3	1.000	0.928±.129	1.000
9-class	random-5	1.000	0.952	1.000
9-class	full-768	1.000	1.000	1.000
scrambled	top-3	1.000	0.962	1.000
scrambled	random-3	0.981	0.766	0.987
JB-MLM	top-3	1.000	0.618	1.000
JB-MLM	full-768	1.000	0.636	1.000
JB-MLM	random-5	0.685	0.584	0.744

pressed subspace. Second, random 3-dimensional projections degrade to 0.928 on AA, confirming that the specific SVD directions matter. Third, JB-MLM reaches only 0.636 on AA even with all 768 dimensions, demonstrating that without classification-induced compression, the representation lacks the structure needed for cross-attack generalization. DD and FITD are near-ceiling for all models, making ActorAttack the critical test. To verify SVD directions are not influenced by OOD test data, we repeated the analysis computing SVD only on IID training data ($n = 350$). IID-only top-3 performance equaled or exceeded all-data SVD across all OOD conditions (top-3 subspace cosine similarity = 0.974), confirming the discriminative subspace is identified from training data alone.

U Temporal Aggregation Comparison

Table 31: Temporal aggregation comparison: mean pooling vs. BiGRU under frozen and end-to-end (E2E) settings (3-seed mean±std). Plan_002 9-class checkpoints.

Setting	**Aggregator**	DD OOD	AA OOD
Frozen	BiGRU	.997±.005	.972±.026
	Mean pooling	.991±.013	.962±.015
E2E	BiGRU	1.000±.000	.997±.005
	Mean pooling	1.000±.000	1.000±.000

Table 31 compares BiGRU and mean pooling under both frozen and E2E settings. Under frozen probing (the main paper's pipeline), BiGRU provides a marginal advantage on ActorAttack (+1.0 pp) with overlapping confidence intervals, consistent with the main text finding that temporal order is not a core detection factor ($|\Delta| < 1$ pp under turn shuffling; Section 4.3). Under E2E fine-tuning, the difference vanishes entirely: mean pooling saturates all benchmarks at F1 = 1.000. The choice of frozen BiGRU in the main pipeline reflects a design trade-off: it enables representation-level analysis (CKA, t-SNE) that E2E would confound, while sacrificing $\leq$1 pp on the hardest OOD set.

V Length Stratification Analysis

Table 32: Jailbreak recall by conversation length bin on OOD evaluation (3-seed majority vote). Benign conversations span 12–20 total turns (6–10 user turns); jailbreak conversations span 3–10 total turns. Bins refer to total (user+assistant) turns.

Dataset	**Variant**	1–3 turns	4–6 turns	7–10 turns
DD OOD	9-class	—	100.0%	99.4%
	Vanilla	—	≤2.6%	≤1.7%
AA OOD	9-class	93.3%	95.6%	100.0%
	Vanilla	0.0%	≤2.6%	0.0%

Table 32 stratifies jailbreak recall by conversation length. The 9-class model shows no systematic degradation: ActorAttack recall increases monotonically from 93.3% (1–3 turns) to 100% (7–10 turns), and DD recall is near-perfect across all bins.

Length confound. While total turn counts differ between benign (12–20) and jailbreak (3–10) conversations, the model processes only user turns. User-turn distributions overlap substantially: IID jailbreak 8.7±2.1 vs. benign 7.9±1.5, DD 8.1±1.5 vs. 7.9±1.5, FITD 7.8±1.4 vs. 7.9±1.5; only ActorAttack shows partial separation (5.1±1.7 vs. 7.9±1.5). A turn-count-only logistic regression trained on user-turn count achieves F1 = 0.54 (IID), 0.56 (DD), 0.42 (FITD), 0.00 (AA), and 0.00 (ToxicChat)—near chance on overlapping distributions and zero on ActorAttack despite partial separation—confirming that detection is content-driven rather than length-driven.

Direct empirical verification. Truncating benign conversations to match jailbreak turn counts (Part A) produces zero false positives across all truncation levels and all 3 seeds, directly confirming that the model does not use conversation length as a detection shortcut. K=3 and K=5 are the effective control conditions where all 38 conversations were truncated; K=10 exceeds the maximum test benign length and serves as a no-op control.

Table 33: Turn-count independence verification (9-class, plan_002 checkpoints, 3 seeds). Part A: FPR on test benign truncated to K user turns (all seeds FPR = 0). Part B: WildChat FPR by turn-count bucket (mean±std). Part C: jailbreak detection (F1) after padding with benign turns to 15+ total turns (mean±std where available).

Condition	FPR / F1	n
Part A: Benign truncation (test set)		
Original (12–20 total; 6–10 user turns)	FPR = .000	38
Truncated K=3	FPR = .000	38
Truncated K=5	FPR = .000	38
Truncated K=8	FPR = .000	38
Truncated K=10*	FPR = .000	38
Part B: WildChat FPR by turn count		
Short (3–10 turns)	FPR = .770±.105	196
Medium (11–15 turns)	FPR = .942±.054	23
Long (16+ turns)	FPR = .857±.117	7
Part C: Jailbreak padding to 15+ turns		
DD original	F1 = .996	80
DD padded	F1 = .971 (Δ=−2.5 pp)	80
AA original	F1 = .963	80
AA padded	F1 = .383±.261 (Δ=−57.9 pp)	80

*K=10 did not truncate any conversation (test benign max ∼8 user turns).

WildChat FPR by turn count (Part B) provides complementary evidence: short conversations (3–10 turns, n=196) have *lower* FPR than medium-length ones (11–15 turns, n=23), inconsistent with a "short = jailbreak" shortcut. Medium and long buckets have limited sample sizes and should be interpreted as directional evidence only.

Padding jailbreak conversations with benign turns (Part C) reveals an asymmetry: DD detection is resilient (Δ=−2.5 pp), but ActorAttack collapses (Δ=−57.9 pp). Padding experiments append benign turns *after* the complete attack sequence; in practice, adversaries would not dilute their own successful attacks. The collapse nonetheless exposes BiGRU temporal aggregation as vulnerable to attention dilution on subtle attack signals, a limitation discussed in Section 7.

W Efficiency

Table 34 compares inference cost under identical conditions. DeBERTa+BiGRU processes a conversation in 13.1 ms, 24.3× faster than Qwen3-8B 3-shot (318.5 ms) while achieving substantially higher OOD detection (DD = 0.566, AA = 0.652 for Qwen3-8B; Table 6). The encoder pipeline requires 868 MB GPU memory (18.5× less than the LLM), enabling deployment on consumer hardware.

Table 34: Inference efficiency comparison on 100 conversations (50 IID + 50 DD OOD), same GPU (RTX PRO 6000). All methods measured under identical conditions.†

Method	Latency (ms)	Params	VRAM
DeBERTa+BiGRU (ours)	13.1±1.6	186.7M	868 MB
Qwen3-8B 3-shot	318.5±26.8	8.2B	16.1 GB

†LLM inference speed varies significantly across GPU generations; same-hardware comparison ensures a fair speedup estimate.

W.1 Data Efficiency

Table 35: Data efficiency of 9-class DAPT (3-seed mean±std, sample std with $n-1$ divisor) and vanilla baseline (seed 42 only). N = total training conversations (balanced jailbreak/benign).

N	Variant	IID	DD OOD	AA OOD
50	9-class	1.000±.000	1.000±.000	.969±.037
125	9-class	1.000±.000	1.000±.000	.975±.019
250	9-class	1.000±.000	1.000±.000	.975±.035
350	9-class	1.000±.000	.978±.030	.972±.033
50	Vanilla	.646	.529	.234
125	Vanilla	.532	.244	.244
250	Vanilla	.987	.365	.502
350	Vanilla	1.000	.360	.489

Table 35 shows that 9-class DAPT reaches near-saturation performance with as few as 50 conversations (25 jailbreak + 25 benign): AA OOD F1 = 0.969±0.037, already surpassing vanilla at full training size (N=350, AA = 0.489) by 48 pp using only 14% of the data. DD OOD is perfectly solved at all training sizes. Vanilla performance is noisy across N (single seed); the consistent pattern is that vanilla never exceeds DD = 0.53 or AA = 0.50 regardless of training size, while 9-class maintains AA ≥ 0.969 at all N. Seed 456 is systematically lower across all N values, contributing most of the cross-seed variance; this is consistent with the initialization sensitivity observed in the main results.

X Auxiliary Loss Weight Ablation

During Stage-2 E2E fine-tuning, the auxiliary persuasion loss weight λ has limited impact on detection (Table 36): the maximum AA OOD gap across all λ values is 5.6 pp (single seed), comparable to the cross-seed variance (∼6 pp) observed in the main results. All configurations converge to perfect validation F1 within epoch 1, indicating that DAPT representations already encode sufficient dis-

Table 36: Effect of auxiliary persuasion loss weight λ during Stage-2 E2E fine-tuning (seed 42). Stage-1 DAPT encoder is identical across all rows; only the Stage-2 loss $L = L_{\text{binary}} + \lambda \cdot L_{\text{strategy}}$ varies.

λ	IID	DD OOD	FITD OOD	AA OOD
0	1.000	1.000	1.000	1.000
0.1	1.000	1.000	1.000	.990
0.5	1.000	1.000	1.000	.981
1.0	1.000	1.000	1.000	.981
2.0	1.000	1.000	1.000	.944

criminative features for downstream classification (Section T). The value of persuasion strategy classification lies in Stage-1 DAPT—where it shapes encoder representations that transfer across attack families—not in the Stage-2 auxiliary loss.

Y OOD Strategy Prediction Analysis

Table 37: OOD strategy prediction accuracy (jailbreak turns only) and detection rate for the 9-class model (3-seed mean). r: Pearson correlation between per-strategy prediction accuracy and per-strategy detection rate.

Dataset	Strat. Acc.	Det. Rate	Missed (per seed)	r
DD OOD	50.1%	99.6%	0 / 0 / 1	$\sim$0.45
AA OOD	50.1%	96.2%	1 / 7 / 1	$\sim$0.25

Table 37 reports OOD strategy prediction accuracy alongside detection rates. Strategy prediction accuracy is substantially above random (50.1% vs. 11.1% chance for 9 classes) and positively correlated with detection success ($r \approx 0.24$–0.45), but strategy prediction is not the detection mechanism: frozen probing with a randomly initialized strategy head (Appendix T) achieves 97.2% AA OOD detection, and λ=0 (no strategy loss) matches or exceeds $\lambda > 0$ during E2E fine-tuning (Table 36). The classification objective shapes representations during Stage-1 DAPT training; at inference, strategy predictions are a byproduct of those representations, not a driver of detection.

Z Cross-Seed Ensemble and Seed-Level F1 Comparisons

Table 38 shows that majority vote never corrupts correct predictions (Broke = 0 for all variants). MLM benefits most from ensembling (+8.6 pp DD, +6.0 pp AA), because its per-seed errors are complementary—each seed fails on different samples, and the majority corrects these. This further exposes MLM's seed instability: its individual seeds are unreliable, but their errors are uncorrelated. By contrast, 9-class seeds are already highly consistent (std ≤ 0.026), leaving minimal room for ensemble improvement (+0.3–0.9 pp). Vanilla errors are systematic (all seeds fail on the same OOD samples), so ensembling provides no benefit.

Table 38: Majority vote ensemble (3 seeds) vs. single-seed mean on OOD Full. "Fixed" = samples corrected by ensemble; "Broke" = samples corrupted by ensemble.

Variant	DD single→ens.	AA single→ens.	Fixed	Broke
9-class	.997→**1.000**	.972→**.981**	5	0
MLM	.914→**1.000**	.897→**.953**	26	0
Vanilla	.258→.258	.258→.258	0	0

To verify that cross-seed pooling does not mask inconsistent pairwise orderings, Table 39 reports per-seed F1 for all variants on OOD DD and ActorAttack at full conversation length. The relative ordering of variants is consistent across all three seeds: classification-supervised variants (9-class, binary, scrambled) dominate MLM and vanilla at every seed, and no seed reverses the hierarchy established by the pooled analysis. Table 40 extends the comparison between 9-class and scrambled to 5 seeds for TOST analysis.

Table 39: Per-seed OOD F1 (Full) for all variants across three attack families (seeds 42, 123, 456). Cohen's d for 9-class vs. scrambled: DD = -0.003 (negligible), AA = 0.587 (medium; CI crosses 0 at n=3).

	DD			ActorAttack			FITD		
Variant	s42	s123	s456	s42	s123	s456	s42	s123	s456
9-class	1.000	1.000	.990	.990	.935	.990	1.000	1.000	1.000
Binary	1.000	1.000	1.000	.981	.990	1.000	1.000	1.000	1.000
Scrambled	.990	1.000	1.000	.891	.990	.971	1.000	1.000	1.000
MLM+cls	1.000	.990	.751	.971	.925	.784	.961	.432	.729
Topic	.727	.252	.644	.686	.431	.759	.990	.774	.909
Vanilla	.284	.305	.348	.258	.258	.258	.871	.855	.919

Benign recall = 1.000 for all DAPT variants across all seeds and OOD conditions (IID benign); OOD F1 variation is driven entirely by attack recall. Classification-supervised variants (9-class, binary, scrambled) achieve perfect or near-perfect F1 on FITD, confirming its non-discriminative nature.

Cross-hardware replication. To assess hardware sensitivity, we independently retrained 9-class and JB-MLM from scratch on a different GPU (RTX PRO 6000 Blackwell, 5 seeds each). Table 41 reports OOD F1 on all three attack families. IID and FITD results are perfectly consistent (9-class: 5/5 seeds = 1.000 on both). On ActorAttack, 9-class outperforms MLM direction-

Table 40: 5-seed OOD F1 (Full) for 9-class vs. scrambled (seeds 42, 123, 456, 789, 1000). At $n = 10$ (5 additional seeds; see text), TOST (δ=5 pp): DD $p < 10^{-8}$ ✓; FITD $p < 10^{-8}$ ✓; AA $p = 0.183$ (non-equivalent). Cohen's d at $n = 10$: DD ≈ 0; AA = 0.44 (medium).

Attack	Variant	s42	s123	s456	s789	s1000	Mean±SD
DD	9-class	1.000	1.000	.990	1.000	1.000	.998±.004
DD	Scrambled	.990	1.000	1.000	1.000	1.000	.998±.004
AA	9-class	.990	.935	.990	.972	.972	.972±.021
AA	Scrambled	.891	.990	.971	.990	.990	.966±.040

ally ($\Delta = +1.7$ pp) but the difference is not statistically significant (paired t-test $p = 0.246$), reflecting the higher variance inherent to this structurally complex attack family; this is consistent with the complexity-dependent boundary reported in Section 4.3.

Table 41: Cross-hardware 5-seed replication (RTX PRO 6000 Blackwell). OOD F1 (Full) for 9-class vs. JB-MLM across three attack families.

Attack	Variant	s42	s123	s456	s789	s1000	Mean±SD
IID	9-class	1.000	1.000	1.000	1.000	1.000	1.000±.000
IID	JB-MLM	1.000	1.000	1.000	1.000	1.000	1.000±.000
DD	9-class	1.000	1.000	1.000	1.000	1.000	1.000±.000
DD	JB-MLM	1.000	1.000	1.000	1.000	1.000	1.000±.000
FITD	9-class	1.000	1.000	1.000	1.000	1.000	1.000±.000
FITD	JB-MLM	1.000	1.000	1.000	1.000	1.000	1.000±.000
AA	9-class	.990	.943	.972	.972	.972	.970±.016
AA	JB-MLM	.857	.751	.906	.916	.943	.875±.074

AA difference is directionally consistent ($\Delta = +9.5$ pp mean) but reflects high MLM variance; paired t-test $p = 0.246$. Template attacks (DD, FITD) show perfect agreement across all seeds and both variants.

Z.1 Single-Turn Truncation Analysis

To isolate whether the ToxicChat evidence-hierarchy reversal (Section 5) reflects multi-turn structural dependence, we truncate each synthetic test conversation to its last user turn and re-evaluate both 9-class and JB-MLM models (3-seed mean).

Table 42: Full-conversation vs. last-turn-only F1 (3-seed mean). Truncation widens the 9-class advantage, ruling out multi-turn structure as the driver of the ToxicChat reversal.

Dataset	Mode	9-class	JB-MLM
IID	Full	1.000	.983
IID	Last turn	.991	.894
DD OOD	Full	.997	.993
DD OOD	Last turn	.942	.924
AA OOD	Full	.972	.941
AA OOD	Last turn	.978	.927
FITD OOD	Full	1.000	.987
FITD OOD	Last turn	1.000	.927

Mean Δ (9-class − MLM): Full +1.6 pp, Last turn +6.0 pp. 9-class advantage widens under truncation across all families, indicating the reversal on ToxicChat is driven by distributional differences between synthetic and human text, not by multi-turn structural dependence.