How Does Schema Complexity Predict Performance in Training-Free LLM Information Extraction?

Anonymous ACL submission

Abstract

Schema complexity affects training-free LLM information extraction through two independent dimensions: type count drives recall decline, while inter-type confusability predicts type substitution errors. We present what is, to our knowledge, the first controlled study isolating these factors in zero-shot LLM IE across NER, RE, and event detection on four datasets. Using embedding-based confusability metrics (SCS/BCS) with controlled batch design, we find: (1) count degradation spans all three tasks (up to -49 pp); inter-type confusability (measured by BCS) independently predicts RE type substitution errors (VIF $= 1.18$ on FewRel); (2) BCS explains $\sim$22% of cross-batch RE accuracy variance on FewRel ($R^2 \approx 0.22$, ecological level), replicating across three open-weight model families (8B–70B); NER batch-level signal is not detected at current power; (3) schema decomposition fails due to merge amplification and routing failure, though oracle routing confirms the two dimensions are independently addressable.

1 Introduction

Training-free[1][2] LLM information extraction (prompting a large language model with a target schema and asking it to extract structured information without any task-specific fine-tuning) enables rapid deployment across new domains and ontologies. This zero-shot paradigm eliminates the need for labeled data, and is attractive for applications where annotation is expensive or schemas evolve frequently (Xu et al., 2024). Yet the paradigm carries a critical limitation: performance degrades sharply as the number of candidate types in the prompt schema grows. On named entity recognition, recall drops from 0.72 with a single candidate type to a plateau of $\sim$0.27 across intermediate schema sizes (22–44 types) before partial recovery at full-schema. On relation extraction, accuracy falls from 85.7% with one relation to 50.4% with 80 relations (sentence-level) and from 88.0% to 38.7% with 96 relations (document-level), near-halving or worse. This degradation is not academic: real-world ontologies routinely define 50–200+ types, which places them squarely in the regime where training-free extraction becomes unreliable.

What explains this degradation? Prior decomposition strategies (Zhou et al., 2024; Liu et al., 2025; Shrimal et al., 2025) conflate two factors: having more types to discriminate among (count) and having semantically similar types to confuse (confusability) (hereafter Dimension 1 and Dimension 2). None isolates which factor predicts the gains (§2).

This study combines correlational analyses with quasi-experimental manipulation (BCS-controlled batches) to characterize how schema properties predict extraction accuracy.

We ask three questions. **RQ1**: Does type confusability independently predict extraction degradation beyond the effect of type count? **RQ2**: Through what modes do count and confusability each degrade performance? **RQ3**: Can confusability-aware schema decomposition improve extraction quality?

To our knowledge, we present the first controlled study simultaneously isolating type count and inter-type confusability as independent dimensions via embedding-based metrics and stratified batch design in zero-shot LLM IE, spanning NER, RE, and event detection (ED). We quantify confusability using pairwise embedding similarity, the *Schema Confusability Score* (SCS), and its batch-level aggregation, the *Batch Confusability Score* (BCS). We evaluate on Few-NERD (Ding et al., 2021), FewRel (Han et al., 2018), DocRED (Yao et al., 2019), and MAVEN (Wang et al., 2020b) using Qwen3-32B (§3).

Our experiments yield four findings: (1) Degra-

[1]We use "training-free" and "zero-shot" interchangeably to denote prompting without parameter updates.

[2]Code and data will be released upon acceptance.

dation operates along two dimensions with bounded interaction: count-related recall decline (up to −49 pp) and confusability-related type substitution, confirmed on sentence- and document-level RE (§4.1, §4.4). (2) Pairwise SCS predicts type confusion across NER, RE, and ED (§4.2); at batch level, BCS predicts RE accuracy independent of output format (§4.3) but not NER accuracy at current statistical power; per-type aggregation is confounded by centrality on homogeneous schemas (§4.5). (3) RE effects are consistent across schema sizes, prompt designs, and three open-weight model families (8B–70B); Gemini Flash provides partial but fragile corroboration. The NER null is not detected on three models (8B–70B; §4.3). (4) Schema decomposition fails due to merge amplification (NER, ED) and routing failure (RE), despite oracle routing recovering substantial accuracy (§5). Our contributions are:

1. We establish that type confusability, quantified by embedding similarity (SCS/BCS, building on Liu et al. 2025), independently predicts type substitution errors in RE on FewRel (VIF $= 1.18$), explaining $\sim$22% of batch-level variance (ecological level). This finding is enabled by BCS-controlled batch design that isolates confusability from type count—a methodology not previously applied in training-free LLM IE (§4.1, §4.2, §4.3).

2. We document a task asymmetry: the RE confusability effect is confirmed as format-independent, yet NER batch-level BCS signal is not detected at current power despite significant pairwise effects—an asymmetry attributable to dispersed NER error modes and BCS range compression (§4.3, §4.4).

3. We identify structural barriers to confusability-aware extraction: schema decomposition fails due to merge amplification (NER, ED) and routing failure (RE), establishing that the decompose-then-merge paradigm faces fundamental precision–recall tradeoffs in training-free IE (§5).

2 Related Work

Training-free LLM IE. Training-free LLM IE spans instruction tuning (Wang et al., 2023), code-style schema encoding (Li et al., 2024, 2023b), annotation-guided extraction (Sainz et al., 2024; Qi et al., 2024), schema-driven decoding (Shen et al., 2025; Luo et al., 2025), and constrained JSON decoding (Geng et al., 2025; Willard and Louf, 2023). NER methods include zero-shot decomposition (Xie et al., 2023; Ashok and Lipton, 2023), distillation (Zhou et al., 2024), and bidirectional encoders (Zaratiana et al., 2024, 2025); RE methods include zero-shot triplet extraction (Chia et al., 2022), constrained generation (Josifoski et al., 2022), and shared embedding spaces (Boylan et al., 2025; Wadhwa et al., 2023). Related work also exploits type embeddings for retrieval (Shachar et al., 2025) and introspective confusion for example selection (Zhao et al., 2026). These methods perform well with moderate schemas (4–20 types) but none investigates how performance degrades as schema complexity scales.

Schema complexity in IE. The most directly related work is LLM-PEE (Liu et al., 2025), which partitions large event schemas by type embedding similarity. Our work differs in three ways: (1) we conduct controlled analysis to understand *why* extraction degrades rather than developing an engineering solution; (2) our BCS-controlled experiments isolate count from confusability, which LLM-PEE conflates; (3) our SDGD experiments reveal that merge amplification (not partitioning quality) is the bottleneck in decompose-then-merge pipelines. LLM-PEE's union merge suffers the same precision collapse (0.56→0.21; §5). In short, LLM-PEE assumes decomposition helps; we show why it should (confusability), why it does not (merge amplification), and what predicts the degradation (BCS). Other approaches address schema complexity via hard negative mining (Gui et al., 2024), schema definition optimization (Shrimal et al., 2025), multi-agent debate (Lu et al., 2025; Wang et al., 2025), and active prompting (Zhao et al., 2026); all treat it as an engineering problem rather than isolating degradation factors. Concurrently, Chen et al. (2026) show that instance count degrades LLM multi-instance processing more than context length, consistent with our count-dominant finding. Golde et al. (2025) quantify training–evaluation type similarity to predict zero-shot NER difficulty; our SCS instead measures within-schema inter-type confusability without assuming access to training data. Label-space reduction approaches (Vandemoortele et al., 2025; Li et al., 2025; Liang et al., 2025) implicitly lower batch confusability—our framework explains *why* such reduction works.

Schema complexity in dialogue and IE. The Schema-Guided Dialogue dataset (Rastogi et al., 2020) and SGD-X (Lee et al., 2022) document degradation with schema linguistic variation; Li et al. (2023a) observe count-dependent degradation in ChatGPT IE. The relationship between label similarity and confusion has precedent in visual recognition (Dubey et al., 2018), correlated label noise (Collier et al., 2021), hierarchical classification (Deng et al., 2010), and label confusion matrices (Guo et al., 2021; Müller et al., 2019; Peterson et al., 2019).

SCS novelty. SCS inherits the embedding-similarity criterion from LLM-PEE (Liu et al., 2025). Unlike LLM-PEE, which uses embedding similarity to partition schemas for improved extraction, our SCS/BCS metrics serve an analytical role. SCS quantifies pairwise type confusability; BCS averages all pairwise SCS values within a batch to predict batch-level accuracy. The metric is a means; the empirical findings are the contribution, enabled by a controlled experimental methodology that previous work lacked—BCS-controlled batches that isolate confusability from count. The use of embedding distance for type discrimination has parallels in metric learning (Snell et al., 2017) and zero-shot classification (Yin et al., 2019). The modest pairwise r^2 (1.3–1.7%) compounds at the ecological batch level to explain substantial cross-batch RE variance on FewRel (§4.3).

3 Experimental Setup

We evaluate how prompt schema size and inter-type confusability affect zero-shot LLM extraction across three information extraction tasks and four datasets: named entity recognition (NER), sentence-level relation extraction (RE), document-level RE, and event detection (ED).

3.1 Tasks and Datasets

Few-NERD (NER). Few-NERD (Ding et al., 2021) provides 66 fine-grained entity types organized into 8 coarse categories (person, location, organization, building, art, product, event, other). The dataset spans diverse domains. We sample 1,000 instances uniformly from the test set; type frequency follows the natural long-tail distribution of Few-NERD. Evaluation uses token-level text matching. Pairwise analysis covers 1,953 type pairs with non-zero co-occurrence out of $\binom{66}{2} = 2{,}145$ possible pairs.

FewRel (RE). FewRel (Han et al., 2018) contains 80 relation types sourced from Wikidata. Since the validation split covers only 16 relations, we combine the training and validation splits to obtain the full 80-relation pool required for schema-scale experiments. We sample 1,000 balanced instances (12–13 per relation type, stratified to ensure equal representation). A held-out validation confirms SCS–confusion generalization across the split boundary (Appendix M). Each instance provides a sentence with marked head and tail entities; the task is to classify the relation. FewRel's balanced design (700 instances per relation type) eliminates type frequency as a potential confound; this balance makes it the primary dataset for BCS analysis. Contamination analysis (Appendix Q) shows extraction difficulty correlates inversely with training-set prevalence, and BCS effects are unchanged when controlling for contamination.

DocRED (Document-level RE). DocRED (Yao et al., 2019) contains 96 relation types sourced from Wikidata, evaluated at the document level where entity pairs may span multiple sentences. We sample 1,000 instances balanced across 96 relation types ($\sim$10 per type) from the DocRED development set. The task is formulated identically to FewRel: given a document with marked head and tail entities, classify the relation. DocRED extends the RE evaluation to a larger schema (96 vs. 80 types) and document-level context, testing whether confusability effects persist under longer input contexts and cross-sentence reasoning.

MAVEN (ED). MAVEN (Wang et al., 2020b) defines 168 event types derived from the FrameNet ontology; all types belong to a single ontology (FrameNet), so this is a same-domain schema. We use the validation set (8,042 sentences containing 18,904 event mentions) for evaluation, as test set labels are not publicly available. The task requires both trigger identification and event type classification. MAVEN serves a supplementary role because its same-domain schema produces centrality confounds at the batch level (§4.5).

Table 1 summarizes the dataset statistics, including the Schema Confusability Score (SCS) ranges defined in §3.2.

3.2 Schema Confusability Score (SCS)

We define the Schema Confusability Score (SCS) to quantify semantic overlap between types in a schema. Given a type t with name string $\text{name}(t)$,

Dataset	Task	# Types	# Eval Units	Domain	BCS Range	Embedding
Few-NERD	NER	66	1,000	Cross	0.77–0.93	Qwen3-32B
FewRel	RE (sent.)	80	1,000	Cross	0.42–0.97	MiniLM
DocRED	RE (doc.)	96	1,000	Cross	0.53–0.73	MiniLM
MAVEN	ED	168	18,904†	Same	0.87–0.97	MiniLM

Table 1: Dataset statistics. BCS Range: min–max over count-curve batches. Embedding: model used for SCS/BCS; ranges are not comparable across embedding models. †Trigger mentions across 8,042 sentences.

an embedding function $\text{embed}(\cdot)$ maps the type name to a vector representation. The **pairwise SCS** between types t_i and t_j is:

$$\text{SCS}(t_i, t_j) = \cos\big(\text{embed}(\text{name}(t_i)),\ \text{embed}(\text{name}(t_j))\big)$$

For a batch of types $B = \{t_1, \ldots, t_k\}$, the **Batch Confusability Score (BCS)** aggregates all pairwise similarities:

$$\text{BCS}(B) = \frac{1}{\binom{k}{2}} \sum_{i<j,\ t_i,t_j \in B} \text{SCS}(t_i, t_j)$$

We use two embeddings to provide complementary perspectives: Qwen3 captures the extraction model's own type representations (self-similarity), while MiniLM provides an independent general-purpose baseline. Cross-embedding consistency holds on all datasets (Appendix I); MiniLM consistently yields equal or stronger correlations, which confirms that Qwen3-based estimates are conservative. We compute SCS with: (1) Qwen3-32B (Qwen Team, 2025) hidden-state representations (5,120-d) and (2) all-MiniLM-L6-v2 (Wang et al., 2020a; Reimers and Gurevych, 2019), a 384-d sentence encoder. Few-NERD uses Qwen3 because its fine-grained same-category pairs (e.g., "person-artist" vs. "person-actor") require the higher-dimensional space. MiniLM is the primary BCS embedding because sentence-transformers are trained for semantic similarity (Reimers and Gurevych, 2019); Qwen3 causal-LM states show compressed BCS range (std $= 0.034$ vs. MiniLM std $= 0.081$), consistent with autoregressive anisotropy (Ethayarajh, 2019). Name-only SCS yields equivalent predictive accuracy to name+definition (Δr: -0.023 to $+0.035$; Appendix M).

SCS as a lightweight proxy. SCS is a pre-hoc proxy computable without running extraction. Pairwise SCS correlates with observed type confusion (Few-NERD $r = 0.112$, FewRel $r = 0.187$, both $p < 0.001$; Table 2), though context, frequency, and definition quality also contribute (§4.2). SCS does not capture context-dependent disambiguation or mention-level ambiguity; these factors contribute to the residual variance in pairwise analysis.

3.3 Experimental Design

We conduct two complementary experimental paradigms.

Experiment 1: Count Curves. We vary the number of types presented in the prompt schema to measure performance as a function of schema size. For each count level, we sample 25 random type batches for Few-NERD and FewRel (5 for DocRED and MAVEN)[3] and evaluate the same 1,000 test samples across all batches. At count $= 1$, every type is evaluated individually as a solo baseline. The remaining count levels follow natural partition points in each schema's type hierarchy rather than uniform spacing: {2, 6, 12, 22, 44, 66} for Few-NERD, {4, 8, 16, 32, 40, 64, 80} for FewRel, {4, 8, 16, 32, 64, 96} for DocRED, and {6, 12, 22, 44, 64} for MAVEN.

Experiment 2: BCS-Controlled. We fix type count and vary BCS to isolate confusability from schema size. For each count level, we construct one low-BCS batch, one high-BCS batch, and 25 random batches (27 total). We construct extreme batches via greedy search over the pairwise SCS matrix. The low-BCS batch starts from the least-similar type pair and iteratively adds the type with lowest maximum similarity to already-selected types; the high-BCS batch mirrors this with maximum similarity. We evaluate on Few-NERD (count $\in \{6, 12\}$), FewRel (count $\in \{8, 16\}$, both 16-relation (pilot) and 80-relation pools), and DocRED (count $\in \{16, 32\}$). Within-pool 16-relation subsets from the 80-relation pool isolate confusability from pool composition. MAVEN results are reported separately due to a centrality confound (§4.5).

3.4 Evaluation Metrics

NER: text-match F1, where a prediction is correct if the exact text string matches after lowercasing and whitespace normalization, *and* the type matches; partial spans count as incorrect. **RE**: accuracy (exact match of predicted relation label to gold). Each batch evaluates only samples whose

[3]DocRED and MAVEN use fewer batches due to higher per-batch evaluation cost (document-level RE and 8,042 sentences, respectively).




Figure 1: **(a)** Count-degradation curves. Error bars: ±1 SD across 3 batch-composition seeds × 25 batches. RE declines monotonically; NER shows a U-shape. Rightmost points are full-schema (negligible sampling variance). **(b)** BCS-controlled FewRel accuracy. Slopes are consistent across the independent and within-pool 16-relation conditions ($p = 0.60$); wider BCS range at 80 relations produces larger gaps.

gold relation is included in the candidate set; out-of-schema samples are excluded before inference. The prompt allows a `none` response for cases where the model judges no candidate applies; any such prediction is scored as incorrect since the gold is always among the candidates by construction. **ED**: relaxed F1, where any token overlap between predicted and gold trigger spans, with correct event type.

3.5 Model and Inference

We use Qwen3-32B-FP8 (Qwen Team, 2025) served via vLLM v0.20.2 (Kwon et al., 2023) on a single NVIDIA RTX PRO 6000 GPU (96 GB) with greedy decoding (temperature = 0, seed 42). Two NER/ED prompt versions are evaluated: v1 requests character offsets (evaluated via text matching); v2 adds format constraints that double precision with minimal recall loss. RE uses a single prompt version throughout. Both versions produce consistent degradation patterns; we report both where applicable to quantify formatting sensitivity (Sclar et al., 2024) (templates in Appendix G). Cross-model validation uses Meta-Llama-3.1-70B-Instruct (FP8) and Meta-Llama-3.1-8B-Instruct (Dubey et al., 2024). All experiments use single-seed evaluation with greedy decoding, which substantially reduces model-level randomness (residual SD = 0.88 pp at count 80 under greedy decoding, likely attributable to FP8 quantization non-determinism); bootstrap CIs capture the remaining sampling variance from batch composition. Pair-level CIs use percentile bootstrap (B=10,000); batch-level CIs use B=1,000.

4 Results

All experiments use Qwen3-32B and the v1 prompt (§3.5; Appendix G) unless noted; cross-model validation covers Dimensions 1–2, while secondary analyses (error taxonomy, DocRED R^2, TOST) remain single-model.

4.1 Count-Degradation Curves

Figure 1a shows RE accuracy declines monotonically with schema size (0.86→0.50 for FewRel). NER recall declines through intermediate counts (0.51→0.27, plateauing across counts 22–44) before partial recovery at full-schema (0.41), where eliminating type-filtering overhead restores extraction performance. DocRED replicates the monotonic RE pattern (88.0%→38.7%, −56%; Appendix). MAVEN exhibits a reversed trend attributable to centrality confounding (§4.5). The effect replicates on Llama-3.1-8B-Instruct (−43 pp on Few-NERD; per-batch $r = 0.725$; Table 3). The pattern is stable across three seeds (max $\Delta =$ 10.7 pp, within 1 SD; intra-batch variance exceeds inter-seed variance by >5×; Appendix R). Formal trend analysis confirms monotonic RE decline (Jonckheere-Terpstra $J = 109{,}707$, $p < 0.001$). Count decline replicates on LLaMA-70B with comparable magnitude and on Gemini Flash (Appendix U). Count curves establish trend direction; magnitude estimation relies on the higher-powered BCS-controlled experiments (§4.3).

Dataset	Embed.	n pairs	r	r^2	95% CI	p
Few-NERD	Qwen3	1,953	0.112	0.013	[0.076, 0.156]	<0.001
MAVEN	MiniLM	11,026	0.129	0.017	[0.104, 0.156]	<0.001

Table 2: Pairwise SCS–confusion correlation. Confusion rate is bidirectional $C(t_i \to t_j) + C(t_j \to t_i)$ divided by gold frequency sum; CIs are percentile bootstrap (B=10,000). FewRel ($r = 0.187$; §3.2) excluded (per-instance RE format). Type-level cluster bootstrap CIs exclude zero (Few-NERD [0.069, 0.219]; MAVEN [0.081, 0.185]).

4.2 Pairwise Confusability and Type Confusion

We test whether pairwise SCS predicts type-level confusion rates. For each type pair (t_i, t_j), we compute the confusion rate (the fraction of t_i gold instances misclassified as t_j) and correlate it with $\text{SCS}(t_i, t_j)$. Table 2 reports Pearson correlations with bootstrap 95% CIs.

The correlations are statistically significant but modest: $r^2 \approx 1.3$–1.7%. Type-level cluster bootstrap yields wider but still significant CIs (Few-NERD: [0.069, 0.219]; MAVEN: [0.081, 0.185]; $B = 10{,}000$). Spearman correlations corroborate: $\rho = 0.144$–0.227 across all pairs, strengthening to $\rho = 0.27$–0.31 among pairs with nonzero confusion (though conditioning on the dependent variable may inflate this).

The remaining variance reflects entity frequency, prompt position (Liu et al., 2024), mention ambiguity, and definition quality. While pairwise r^2 is modest, correlated type pairs within batches compound this signal into substantial batch-level RE accuracy variance (§4.3). The independent MiniLM embedding yields a *stronger* SCS–confusion correlation on Few-NERD ($r = 0.172$ vs. Qwen3 $r = 0.138$; Appendix), indicating that shared-representation bias is conservative. SCS outperforms simpler baselines (Levenshtein, WordNet Wu-Palmer, same-parent; Appendix P). Appendix W lists the most confusable type pairs with concrete examples.

4.3 BCS-Controlled Experiments

On FewRel, BCS explains ∼22% of cross-batch RE accuracy variance; confusability is a substantial predictor alongside count. We fix type count and vary BCS to isolate this effect. FewRel's balanced design (700 instances per type) eliminates type frequency as a confound;[4] the within-pool analysis (§4.3) controls for pool composition.

In BCS-controlled FewRel subsets, the high-BCS quartile shows $\Delta = -5.3$ pp lower accuracy than low-BCS (quartile comparison on 100 random batches; based on a single extreme batch per BCS level at 16-rel scale; full data in Appendix J). At 80 relations, extreme-batch construction amplifies this to -31.2 pp (95% CI [17.7, 42.7]), stable across count levels. An intermediate count $= 40$ evaluation (40-relation subsets sampled from the 80-relation pool) yields consistent gaps (-33.3 pp at count 8, -31.8 pp at count 16) and confirms monotonic decline.

Document-level RE (DocRED). The effect replicates on DocRED's 96-relation schema (n=55 per count level;[5]): extreme-BCS gap -25.0 pp at count 16 ($\rho = -0.762$, 95% CI [-0.88, -0.58]) and -15.7 pp at count 32 ($\rho = -0.693$, 95% CI [-0.83, -0.50]; both $p < 0.001$). Pooled across counts, $R^2 = 0.578$ ($n = 110$; 95% CI [0.46, 0.68]; per-count: $R^2 = 0.653$ at count 16, 0.614 at count 32). The substantially higher R^2 relative to FewRel (0.218) largely reflects BCS–centrality collinearity (VIF $= 50.9$): semipartial $R^2_{\text{BCS}} = 0.056$ after partialing degree centrality, confirming that 90% of the explained variance is shared with centrality. Given VIF $= 50.9$, the partial correlation standard errors are inflated approximately 7-fold; this result serves as directional evidence that the BCS–accuracy relationship extends beyond FewRel's schema, not as independent quantitative support. Ridge regression confirms the negative direction under regularization (Appendix E.1). The clean evidence for BCS's independent contribution comes from FewRel (semipartial $R^2 = 0.273$, VIF $= 1.18$).

Within-pool controlled comparison. Within-pool analysis confirms slope consistency across pools (permutation $p \approx 0.60$; Appendix L). The 80-relation extreme-batch gap (§4.3) reflects wider BCS range, not stronger per-unit sensitivity.

Practical magnitude. Direct regression on 100 random 16-type batches from the 80-relation pool shows BCS explains 22% of cross-batch

[4] Partial correlation controlling for degree centrality: FewRel $r_{\text{partial}} = -0.537$ ($p < 0.001$, VIF $= 1.18$). DocRED partial correlation ($r_{\text{partial}} = -0.348$, $p < 0.001$) is reported for completeness, but VIF $= 50.9$ (BCS–centrality $r = 0.99$) renders the estimate unstable; the clean evidence for BCS's independent contribution comes from FewRel (Appendix E.1, Table 12).

[5] DocRED uses 5 batches per count level (vs. 25 for FewRel) due to higher per-batch evaluation cost; CIs are correspondingly wider.




Figure 2: Error taxonomy decomposition (Few-NERD NER and FewRel RE). IntraSub scales monotonically with BCS across all evaluated datasets ($\rho = 0.84$–1.0; Table 6 includes DocRED). RE missed rates remain flat (10–16%), but NER missed rates are substantially higher (43–65%) and non-monotonic.

accuracy variance ($R^2 = 0.218$, $p < 0.001$). DocRED pooled $R^2 = 0.578$ ($n = 110$; semipartial $R^2_{\text{BCS}} = 0.056$ after centrality; Appendix E.1). The typical BCS span (IQR = 0.054) yields an expected accuracy gap of 2.2 pp (95% CI [0.4, 4.0]). Quartile comparison confirms: bottom-quartile BCS batches average 82.8% vs. 78.9% for top-quartile ($\Delta = 3.9$ pp). The amplification from pairwise $r^2 \approx 1.5\%$ to batch-level $R^2 \approx 22\%$ is not a statistical artifact but the operative mechanism. Correlated confusable-type interactions compound within shared prompts (Robinson, 1950; Baan et al., 2023), producing the batch-level signal that makes BCS practically predictive ($\sim 3\times$ amplification illustrated by Monte Carlo simulation; Appendix N).

Cross-model validation. The effect replicates on Meta-Llama-3.1-8B-Instruct: extreme-BCS gaps of -27.1 pp (count 8) and -23.9 pp (count 16), reaching 77–87% of Qwen3-32B's gap (Table 4). All three open-weight families (Qwen3-32B, LLaMA-70B, LLaMA-8B) show consistent negative BCS slopes on FewRel RE. Gemini 2.5 Flash provides partial but fragile corroboration ($\Delta = -17.6$ pp at count 8) with substantial leverage sensitivity (leave-one-out Pearson: $r = -0.80 \rightarrow -0.42$, $p = 0.22$; Spearman: $\rho = -0.40 \rightarrow -0.18$, $p = 0.64$; Appendix U). LLaMA-8B and LLaMA-70B both show no NER BCS signal (r=-0.13, p=0.36 for 70B), confirming the task asymmetry across three models (Table 5).

Prompt sensitivity. Under the v2 prompt, the extreme-batch BCS gap is -25.5 pp ($r = -0.919$, $p < 0.001$; n=25), modestly attenuated from v1 but highly significant. NER shows no batch-level BCS–F1 correlation under either prompt ($r \approx 0$, $n = 450$; §4.4). The effect holds across four structurally distinct prompt variants at count 32 (all $r \leq -0.47$; Appendix H.1), ruling out prompt design as the source. Few-shot demonstrations widen the confusability gap (+4.3 pp under 5-shot), though this finding is limited to a single dataset and count level (Appendix V).

4.4 Multi-Dimensional Degradation

Error taxonomy decomposition (Table 6 and Figure 2) shows intra-batch substitution (IntraSub) scales monotonically with BCS across all three datasets: $\rho = 1.0$ ($p < 0.001$) for Few-NERD NER, $\rho = 0.954$ ($p < 0.001$) for FewRel sentence-level RE, and $\rho = 0.843$ ($p < 10^{-30}$, $n = 110$) for DocRED document-level RE. The slightly lower DocRED correlation reflects additional noise from document-level context and cross-sentence reasoning. In NER, missed rates are higher (43–65%) and non-monotonic; confusable types impair entity detection itself. In DocRED, IntraSub accounts for 72% of errors in high-BCS batches vs. 15% in low-BCS batches; ExtraSub is zero (forced-choice format). Extreme-BCS batches produce 9.9–27.5$\times$ more confusion than low-BCS batches. Cross-model replication confirms the IntraSub–BCS correlation on FewRel RE: Gemini 2.5 Flash

($\rho = 0.821$, $p < 0.001$, $n = 60$) and LLaMA-3.1-8B ($\rho = 0.430$, $p = 0.001$, $n = 54$; Table 7).

These results establish two dimensions: **Dimension 1** (count predicts recall decline) and **Dimension 2** (confusability predicts type confusion). The full-range regression ($n = 69$, five count levels) serves as the primary separability test; the 2×2 factorial ($n = 54$) as a sensitivity check. We select the equivalence margin via convergent evidence: (i) an interaction exceeding the main effect magnitude would undermine dimensional separability; (ii) Cohen's $d = 0.5$ (Cohen, 1988) (medium effect) at the within-cell SD of 4.6 pp yields ± 2.3 pp. Both converge on ± 2–3 pp.[6] On the linear scale, TOST (Lakens, 2017; Schuirmann, 1987) bounds the FewRel interaction within ± 3 pp ($p = 0.003$); at ± 2 pp, equivalence is marginal ($p = 0.047$). Probability-scale TOST is the primary analysis because accuracy values (0.37–0.86) remain in the mid-range where logit and linear scales yield similar inference. The logit-scale result is inconclusive ($p = 0.209$; regression-based TOST: $p = 0.050$ at ± 3 pp; Appendix C). On DocRED, the raw factorial interaction (-9.4 pp) is confounded by narrower BCS ranges at count 32; range-matched analysis reduces it to 0.93 pp, consistent with bounded interaction (Appendix C). In NER, batch-level BCS signal is not detected at current power (§4.3). Two factors explain the asymmetry: (1) NER errors distribute across miss, boundary, and type modes rather than concentrating in type substitution (relaxed matching confirms this is not a metric artifact; Appendix Y), and (2) BCS range restriction (SD ratio 19%) limits statistical detection power to 65% (Appendix E.2). The factorial test is inconclusive ($p = 0.50$). At n=450 with BCS SD $= 0.027$, the minimum detectable correlation is $|r| \approx 0.132$ ($\alpha = 0.05$, power $= 0.80$), while FewRel's $r = -0.57$ would attenuate to $r \approx -0.11$ under this SD compression. Current evidence cannot distinguish absence of a BCS→NER effect from an effect too small to detect—absence of evidence rather than evidence of absence. Post-hoc mitigation attempts—type renaming to reduce SCS and few-shot prompting—fail to close the confusability gap (Appendices X, V), confirming that BCS captures a structural property of the schema–model interaction rather than a surface-level naming artifact.

[6] Margin sensitivity (Table 10) confirms equivalence from ± 2 pp ($p = 0.047$) through ± 5 pp.

4.5 Centrality as a Potential Confound on Homogeneous Schemas

Per-type analysis on MAVEN reveals an anomalous *positive* BCS–F1 correlation ($\rho = +0.184$–0.208, $p < 0.03$): FrameNet-derived types cluster tightly (Cai et al., 2021), conflating confusability with centrality. Controlling for log frequency and degree centrality, the correlation vanishes ($p > 0.2$; Appendix E), though the pairwise SCS signal remains intact ($r = 0.129$, $p < 0.001$). Few-NERD's cross-domain schema shows the expected negative direction ($\rho = -0.293$, $p = 0.02$); mean BCS is reliable only for cross-domain schemas.

5 Schema Decomposition

A natural intervention is to partition the schema so confusable types never co-occur. We tested Schema-DAG-Guided Decomposition (SDGD), which applies greedy graph coloring on the SCS graph to assign types to low-confusability batches. While oracle routing recovers accuracy (0.802 vs. 0.504 single-pass), all practical routing strategies fall below the single-pass baseline, and NER decomposition amplifies false positives (F1: 0.445→0.251). The bottleneck is routing accuracy rather than partitioning quality. Full protocol, results, and analysis are in Appendix B.

6 Discussion and Conclusion

Boundary conditions. The confusability signal applies to cross-domain schemas; same-domain schemas exhibit centrality confounding (§4.5). Modest pairwise r^2 compounds at the batch level because correlated type interactions aggregate within shared prompts (§4.3). The NER–RE asymmetry reflects dispersed error modes and compressed BCS variance (Appendix E.2).

Practical implications and conclusion. For NER, reducing candidate types is the primary lever; for RE, pre-computing SCS flags high-risk type pairs before deployment. Decompose-then-merge fails (§5), but oracle routing recovers accuracy, confirming approximate additivity of count and confusability (§4.4); separability holds on the linear scale but remains open on the logit scale.

Limitations

1. **Model coverage.** Primary experiments use Qwen3-32B; cross-model validation (LLaMA-8B, LLaMA-70B, Gemini Flash) covers Di-

mensions 1–2 (count curves, BCS-controlled extremes) but does not replicate secondary analyses (error taxonomy, prompt sensitivity, TOST equivalence). Specifically, TOST factorial interaction (§4.4) and SDGD failure analysis (§5) are established on Qwen3-32B alone; error taxonomy replicates on two additional models (Table 7), but TOST and SDGD cross-model replication remains the most pressing extension. Gemini provides only partial, leverage-sensitive corroboration (leave-one-out r: $-0.80 \rightarrow -0.42$; Appendix U); proprietary-model generalization remains open.

2. **Effect size and statistical design.** Pairwise SCS explains a small fraction of type confusion variance; entity frequency, prompt position, and mention ambiguity likely account for the remainder. The count $\times$ BCS interaction is bounded on FewRel but nonzero on DocRED, partially confounded by BCS range restriction at higher counts (Appendix C); logit-scale evidence remains inconclusive. DocRED count curves use 5 batches per level due to higher per-batch evaluation cost. BCS-controlled experiments use a single seed with greedy decoding; residual variance is small (Appendix R) but precise magnitudes may vary. Greedy decoding (temperature $= 0$) yields residual SD $=$ 0.88 pp, approximately 18–44% of the observed BCS effect size, suggesting effect detection is robust but point estimates carry meaningful uncertainty; the factorial interaction point estimate (0.47 pp) is far inside the ± 3 pp equivalence margin.

3. **Task scope.** Format independence is confirmed via paired constrained/unconstrained comparison (Appendix K). BCS batch-level prediction is task-dependent: significant in RE but not detected in NER at current power, where errors scatter across miss, boundary, and type modes rather than concentrating in type substitution. A post-hoc relaxed-matching evaluation confirms that relaxing the span criterion does not recover the BCS signal (Appendix Y), ruling out evaluation stringency as the explanation. The NER batch-level BCS null is observed on three models (8B, 32B, 70B; Table 5) but not validated on Gemini; the null could in principle differ for proprietary models.

4. **Causal mechanism and data contamination.** The study establishes correlational evidence with controlled stratification; mechanistic analysis at the attention or logit level is needed to confirm the causal pathway. A post-hoc renaming experiment (Appendix X) suggests SCS may proxy deeper conceptual overlap rather than surface similarity. FewRel (2018) may appear in pretraining corpora, but train-origin relations show lower accuracy than val-origin, opposite to the contamination hypothesis; DocRED (2019) provides a lower-contamination-risk replication (Appendix Q).

5. **Domain and language scope.** All evaluations use English-language datasets derived from Wikipedia or knowledge bases (Wikidata, FrameNet). Whether confusability effects hold for domain-specific schemas (e.g., biomedical NER, legal RE) or languages with different naming conventions is untested. BCS-controlled batches inherit the domain distribution of the source schema; domain-specific type subsets may shift the confusability–accuracy relationship. Sample sizes (1,000 instances per dataset) are sufficient for our primary effects but the pairwise SCS correlation approaches the detection floor.

Across-batch correlation. Batches share prompt template and LLM, introducing potential across-batch correlation; however, type composition is independently sampled per batch, and bootstrap CIs are computed over this independent unit of variation.

Multiple comparisons. Few-NERD, FewRel, and DocRED draw from overlapping knowledge bases (Wikipedia, Wikidata), limiting dataset independence; we treat cross-dataset consistency as converging evidence rather than independent statistical replication (Rothman, 1990) (noting that within-study prompt comparisons involve correlated observations rather than independent tests). Within-dataset secondary analyses involve multiple looks; we report individual p-values and note that core claims rest on $p < 0.001$ (Dror et al., 2018; Card et al., 2020). The core claims (count decline, BCS–accuracy correlation) are robust to Bonferroni correction (all $p < 0.001$); the logit-scale interaction ($p = 0.047$) is the only result near the threshold and is already characterized as marginal.

References

Dhananjay Ashok and Zachary C. Lipton. 2023. PromptNER: Prompting for named entity recognition. *arXiv preprint arXiv:2305.15444*.

Joris Baan, Barbara Plank, and Raquel Fernandez. 2023. The ecological fallacy in annotation: Modelling human label variation goes beyond sociodemographics. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (ACL)*.

Jack Boylan, Chris Hokamp, and Demian Gholipour Ghalandari. 2025. GLiREL – generalist model for zero-shot relation extraction. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8230–8245, Albuquerque, New Mexico. Association for Computational Linguistics.

Xingyu Cai, Jiaji Huang, Yuchen Bian, and Kenneth Church. 2021. Isotropy in the contextual embedding space: Clusters and manifolds. In *International Conference on Learning Representations*.

Dallas Card, Peter Henderson, Urvashi Khandelwal, Robin Jia, Kyle Mahowald, and Dan Jurafsky. 2020. With little power comes great responsibility. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 9263–9274. Association for Computational Linguistics.

Jingxuan Chen, Mohammad Taher Pilehvar, and Jose Camacho-Collados. 2026. Understanding LLM performance degradation in multi-instance processing: The roles of instance count and context length. *arXiv preprint arXiv:2603.22608*.

Yew Ken Chia, Lidong Bing, Soujanya Poria, and Luo Si. 2022. RelationPrompt: Leveraging prompts to generate synthetic data for zero-shot relation triplet extraction. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 45–57.

Jacob Cohen. 1988. *Statistical Power Analysis for the Behavioral Sciences*, 2nd edition. Lawrence Erlbaum Associates.

Mark Collier, Basil Mustafa, Efi Kokiopoulou, Rodolphe Jenatton, and Jesse Berent. 2021. Correlated input-dependent label noise in large-scale image classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1551–1560.

Jia Deng, Alexander C. Berg, Kai Li, and Li Fei-Fei. 2010. What does classifying more than 10,000 image categories tell us? In *Proceedings of the 11th European Conference on Computer Vision*, pages 71–84.

Ning Ding, Guangwei Xu, Yulin Chen, Xiaobin Wang, Xu Han, Pengjun Xie, Haitao Zheng, and Zhiyuan Liu. 2021. Few-NERD: A few-shot named entity recognition dataset. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics*.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. 2018. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*.

Abhimanyu Dubey, Otkrist Gupta, Pei Guo, Ramesh Raskar, Ryan Farrell, and Nikhil Naik. 2018. Pairwise confusion for fine-grained visual classification. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 71–88.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, and Angela Fan. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Kawin Ethayarajh. 2019. How contextual are contextualized word representations? Comparing the geometry of BERT, ELMo, and GPT-2 embeddings. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing*.

Gemini Team. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, and long context. *arXiv preprint arXiv:2507.06261*.

Saibo Geng, Hudson Cooper, Michał Moskal, Samuel Jenkins, Julian Berman, Nathan Ranchin, Robert West, Eric Horvitz, and Harsha Nori. 2025. JSONSchemaBench: A rigorous benchmark of structured outputs for language models. *arXiv preprint arXiv:2501.10868*.

Jonas Golde, Patrick Haller, Max Ploner, Fabio Barth, Nicolaas Jedema, and Alan Akbik. 2025. Familiarity: Better evaluation of zero-shot named entity recognition by quantifying label shifts in synthetic training data. In *Proceedings of the 2025 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*.

Honghao Gui, Lin Yuan, Hongbin Ye, Ningyu Zhang, Mengshu Sun, Lei Liang, and Huajun Chen. 2024. IEPile: Unearthing large scale schema-conditioned information extraction corpus. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 127–146.

Biyang Guo, Songqiao Han, Xiao Han, Hailiang Huang, and Ting Lu. 2021. Label confusion learning to enhance text classification models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 12929–12936.

Xu Han, Hao Zhu, Pengfei Yu, Ziyun Wang, Yuan Yao, Zhiyuan Liu, and Maosong Sun. 2018. FewRel: A large-scale supervised few-shot relation classification

dataset with state-of-the-art evaluation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*.

Martin Josifoski, Nicola De Cao, Maxime Peyrard, Fabio Petroni, and Robert West. 2022. GenIE: Generative information extraction. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL)*, pages 4626–4643.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles*.

Daniël Lakens. 2017. Equivalence tests: A practical primer for t tests, correlations, and meta-analyses. *Social Psychological and Personality Science*, 8(4):355–362.

Harrison Lee, Raghav Gupta, Abhinav Rastogi, Yuan Cao, Bin Zhang, and Yonghui Wu. 2022. SGD-X: A benchmark for robust generalization in schema-guided dialogue systems. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 10938–10946.

Bo Li, Gexiang Fang, Yang Yang, Quansen Wang, Wei Ye, Wen Zhao, and Shikun Zhang. 2023a. Evaluating ChatGPT's information extraction capabilities: An assessment of performance, explainability, calibration, and faithfulness. *arXiv preprint arXiv:2304.11633*.

Peng Li, Tianxiang Sun, Qiong Tang, Hang Yan, Yuanbin Wu, Xuanjing Huang, and Xipeng Qiu. 2023b. CodeIE: Large code generation models are better few-shot information extractors. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*.

Zhuoqun Li, Hao Wu, Xinxin Li, and Zhoujun Li. 2025. Effective and efficient schema-aware information extraction using on-device large language models. *arXiv preprint arXiv:2505.14992*.

Zixuan Li, Yutao Zeng, Yuxin Zuo, Weicheng Ren, Wenxuan Liu, Miao Su, Yucan Guo, Yantao Liu, Xiang Li, Zhilei Hu, Long Bai, Wei Li, Yidan Liu, Pan Yang, Xiaolong Jin, Jiafeng Guo, and Xueqi Cheng. 2024. KnowCoder: Coding structured knowledge into LLMs for universal information extraction. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*.

Sheng Liang, Yongyue Zhang, Yaxiong Wu, Ruiming Tang, and Yong Liu. 2025. Schema as parameterized tools for universal information extraction. *arXiv preprint arXiv:2506.01276*.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173.

Wenxuan Liu, Zixuan Li, Long Bai, Yuxin Zuo, Daozhu Xu, Xiaolong Jin, Jiafeng Guo, and Xueqi Cheng. 2025. Towards event extraction with massive types: LLM-based collaborative annotation and partitioning extraction. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*.

Meng Lu, Yuzhang Xie, Zhenyu Bi, Shuxiang Cao, and Xuan Wang. 2025. CROSSAGENTIE: Cross-type and cross-task multi-agent LLM collaboration for zero-shot information extraction. In *Findings of the Association for Computational Linguistics: ACL 2025*.

Yujie Luo, Xiangyuan Ru, Kangwei Liu, Lin Yuan, Mengshu Sun, Ningyu Zhang, Lei Liang, Zhiqiang Zhang, Jun Zhou, Lanning Wei, Da Zheng, Haofen Wang, and Huajun Chen. 2025. OneKE: A dockerized schema-guided LLM agent-based knowledge extraction system. In *Companion Proceedings of the ACM Web Conference 2025*.

Rafael Müller, Simon Kornblith, and Geoffrey E. Hinton. 2019. When does label smoothing help? In *Advances in Neural Information Processing Systems*, volume 32.

Joshua C. Peterson, Ruairidh M. Battleday, Thomas L. Griffiths, and Olga Russakovsky. 2019. Human uncertainty makes classification more robust. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9617–9626.

Yunjia Qi, Hao Peng, Xiaozhi Wang, Bin Xu, Lei Hou, and Juanzi Li. 2024. ADELIE: Aligning large language models on information extraction. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*.

Qwen Team. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Abhinav Rastogi, Xiaoxue Zang, Srinivas Sunkara, Raghav Gupta, and Pranav Khaitan. 2020. Towards scalable multi-domain conversational agents: The schema-guided dialogue dataset. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 8689–8696.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*.

William S. Robinson. 1950. Ecological correlations and the behavior of individuals. *American Sociological Review*, 15(3):351–357.

Kenneth J. Rothman. 1990. No adjustments are needed for multiple comparisons. *Epidemiology*, 1(1):43–46.

Oscar Sainz, Iker García-Ferrero, Rodrigo Agerri, Oier Lopez de Lacalle, German Rigau, and Eneko Agirre. 2024. GoLLIE: Annotation guidelines improve zero-shot information-extraction. In *International Conference on Learning Representations*.

Donald J. Schuirmann. 1987. A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. *Journal of Pharmacokinetics and Biopharmaceutics*, 15(6):657–680.

Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2024. Quantifying language models' sensitivity to spurious features in prompt design. In *International Conference on Learning Representations*.

Or Shachar, Uri Katz, Yoav Goldberg, and Oren Glickman. 2025. NER retriever: Zero-shot named entity retrieval with type-aware embeddings. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 11175–11186.

Zhengyuan Shen, Darren Yow-Bang Wang, Soumya Smruti Mishra, Zhichao Xu, Yifei Teng, and Haibo Ding. 2025. SLOT: Structuring the output of large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*.

Anubhav Shrimal, Aryan Jain, Soumyajit Chowdhury, and Promod Yenigalla. 2025. PARSE: LLM driven schema optimization for reliable entity extraction. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*.

Jake Snell, Kevin Swersky, and Richard Zemel. 2017. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, volume 30.

Nathan Vandemoortele, Bram Steenwinckel, Femke Ongenae, and Sofie Van Hoecke. 2025. From haystack to needle: Label space reduction for zero-shot classification. *arXiv preprint arXiv:2502.08436*.

Somin Wadhwa, Silvio Amir, and Byron C. Wallace. 2023. Revisiting relation extraction in the era of large language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*, pages 15566–15589.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020a. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. In *Advances in Neural Information Processing Systems*, volume 33.

Xiao Wang, Weikang Zhou, Can Zu, Han Xia, Tianze Chen, Yuansen Zhang, Rui Zheng, Junjie Ye, Qi Zhang, Tao Gui, Jihua Kang, Jingsheng Yang, Siyuan Li, and Chunsai Du. 2023. InstructUIE: Multi-task instruction tuning for unified information extraction. *arXiv preprint arXiv:2304.08085*.

Xiaozhi Wang, Ziqi Wang, Xu Han, Wangyi Jiang, Rong Han, Zhiyuan Liu, Juanzi Li, Peng Li, Yankai Lin, and Jie Zhou. 2020b. MAVEN: A massive general domain event detection dataset. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*.

Zihan Wang, Ziqi Zhao, Yougang Lyu, Zhumin Chen, Maarten de Rijke, and Zhaochun Ren. 2025. A cooperative multi-agent framework for zero-shot named entity recognition. In *Proceedings of the ACM Web Conference 2025*.

Brandon T. Willard and Rémi Louf. 2023. Efficient guided generation for large language models. *arXiv preprint arXiv:2307.09702*.

Tingyu Xie, Qi Li, Jian Zhang, Yan Zhang, Zuozhu Liu, and Hongwei Wang. 2023. Empirical study of zero-shot NER with ChatGPT. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*.

Derong Xu, Wei Chen, Wenjun Peng, Chao Zhang, Tong Xu, Xiangyu Zhao, Xian Wu, Yefeng Zheng, Yang Wang, and Enhong Chen. 2024. Large language models for generative information extraction: A survey. *Frontiers of Computer Science*, 18(6).

Yuan Yao, Deming Ye, Peng Li, Xu Han, Yankai Lin, Zhenghao Liu, Zhiyuan Liu, Lixin Huang, Jie Zhou, and Maosong Sun. 2019. DocRED: A large-scale document-level relation extraction dataset. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*.

Wenpeng Yin, Jamaal Hay, and Dan Roth. 2019. Benchmarking zero-shot text classification: Datasets, evaluation and entailment approach. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, pages 3914–3923.

Urchade Zaratiana, Gil Pasternak, Oliver Boyd, George Hurn-Maloney, and Ash Lewis. 2025. GLiNER2: Schema-driven multi-task learning for structured information extraction. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*.

Urchade Zaratiana, Nadi Tomeh, Pierre Holat, and Thierry Charnois. 2024. GLiNER: Generalist model for named entity recognition using bidirectional transformer. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics*.

Dong Zhao, Yadong Wang, Xiang Chen, Chenxi Wang, Hongliang Dai, Chuanxing Geng, Shengzhong Zhang, Shaoyuan Li, and Sheng-Jun Huang. 2026. Reflect then learn: Active prompting for information extraction guided by introspective confusion. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 34923–34931.

Wenxuan Zhou, Sheng Zhang, Yu Gu, Muhao Chen, and Hoifung Poon. 2024. UniversalNER: Targeted distillation from large language models for open named entity recognition. In *International Conference on Learning Representations*.

A Additional Figures

Table 3: Cross-model count-curve replication on FewNERD (text-match recall). Both models show a general declining trend in recall with schema size. Per-batch correlation $r = 0.725$. Qwen3-32B values use the v2 prompt (§3.5) for fair cross-model comparison; the count-curve results in §4.1 use the v1 prompt, yielding higher absolute recall (0.72 vs. 0.64 at count $= 1$) due to over-prediction under v1.

Count	Llama-3.1-8B	Qwen3-32B
1	0.702	0.640
64	0.273	0.304
Decline	−43 pp	−34 pp

Table 4: Cross-model BCS-controlled FewRel accuracy. High-BCS accuracy converges to ≈51% regardless of model, while low-BCS accuracy reflects model capacity differences. The confusability gap (Δ, in pp) is 77–87% as large on Llama-3.1-8B as on Qwen3-32B.

	Llama-3.1-8B			Qwen3-32B		
Count	Low	High	Δ	Low	High	Δ
8	78.1%	51.0%	−27.1	82.3%	51.0%	−31.2
16	75.5%	51.6%	−23.9	82.8%	51.6%	−31.2

Table 5: NER batch-level BCS–F1 correlation across models. †Partial correlation controlling for type frequency. ‡LLaMA-70B count_12 shows r=−0.42 (p=0.034, uncorrected; Bonferroni p=0.069); pooled and count_6 are null, consistent with sampling noise at n=25. The null is observed on three models; Gemini remains untested.

Model	NER BCS–F1 r	Status
Qwen3-32B	0.004 ($p = 0.94$)	Null
LLaMA-3.1-8B	−0.12 ($p = 0.29$)†	Null
LLaMA-3.1-70B	−0.13 ($p = 0.36$)‡	Null
Gemini 2.5 Flash	—	Not tested

B SDGD Full Protocol and Results

We construct a thresholded confusability graph $G = (V, E)$ where each type is a vertex and an edge connects types t_i, t_j whenever $\text{SCS}(t_i, t_j) > \tau$. Greedy graph coloring (LARGEST_FIRST) assigns each type to a color such that no two adjacent (i.e., highly confusable) types share a color. Each color class forms one extraction batch, and predictions are merged via set union.

1. Compute pairwise SCS matrix $S_{ij} = \cos(\text{embed}(t_i), \text{embed}(t_j))$.
2. Construct graph G: add edge (t_i, t_j) iff $S_{ij} > \tau$.
3. Apply greedy graph coloring (LARGEST_FIRST) to assign each type a color $c(t)$.
4. For each color k, form batch $B_k = \{t : c(t) = k\}$ and run extraction on all test instances.
5. Merge: union of per-batch predictions (v1) or confidence-gated selection (v2).

Oracle routing (Table 9) recovers substantial accuracy (72.4% vs. 50.4% single-pass), confirming the sub-schemas contain correct predictions; the failure lies in routing, not decomposition quality.

We compare four modes: (i) **single_pass**, the undecomposed baseline; (ii) **sdgd_zero**, SCS-guided partitioning; (iii) **random_batch**, random partitioning with matched batch sizes; and (iv) **per_type**, the extreme case where each type is extracted in isolation.

Single-pass extraction achieves F1 = 0.445 (P = 0.563, R = 0.368). SDGD obtains F1 = 0.251

Table 6: Intra-batch substitution (IntraSub) and missed-entity rates by BCS bin. Spearman ρ computed over $n = 148$ batches (NER), $n = 154$ (RE), and $n = 110$ (DocRE). IntraSub scales monotonically with BCS across all three datasets. DocRE missed rates decrease with BCS, indicating high-confusability errors shift from omission to substitution.

		BCS Bin						
Task	Error	Solo	Low	Mid	High	V.High	ρ	p
NER	IntraSub	0%	1.6%	10.6%	49.4%	—	1.000	<0.001
RE	IntraSub	0%	4.2%	13.0%	20.3%	32.3%	0.954	<0.001
DocRE	IntraSub	—	4.8%	22.4%	37.0%	41.9%	0.843	<0.001
NER	Missed	—	42.8%	64.8%	49.9%	—	—	—
RE	Missed	—	10.4%	11.3%	13.1%	15.7%	—	—
DocRE	Missed	—	28.1%	22.6%	21.6%	16.2%	—	—

Table 7: Cross-model replication of IntraSub–BCS Spearman correlation on FewRel RE. †LLaMA-70B has only 20 batches with 17.4% missed rate; the null is attributable to insufficient power rather than absence of the effect.

Model	n	ρ	p
Qwen3-32B	154	0.954	<0.001
Gemini 2.5 Flash	60	0.821	<0.001
LLaMA-3.1-8B	54	0.430	0.001
LLaMA-3.1-70B†	20	−0.086	0.719

(P = 0.210, R = 0.314), a 44% relative drop. Random batching reaches F1 = 0.320 (P = 0.249, R = 0.446), and per-type extraction yields F1 = 0.292 (P = 0.194, R = 0.586). Every decomposition mode falls below the single-pass baseline (Table 8).

Table 8: Few-NERD extraction under decomposition modes. V1 uses union merge; v2 uses confidence-gated merge with `min_batch_size=8` (reducing 8→4 batches for sdgd_zero). All decomposition modes produce lower F1 than the single-pass baseline. All modes use the v1 prompt.

Mode	# Batches	Precision	Recall	F1
single_pass	1	0.563	0.368	0.445
sdgd_zero (v1)	8	0.210	0.314	0.251
random_batch (v1)	8	0.249	0.446	0.320
per_type	66	0.194	0.586	0.292
sdgd_zero (v2)	4	0.324	0.191	0.241
random_batch (v2)	8	0.331	0.276	0.301

Decomposition boosts recall (per-type recall reaches 0.586 versus single-pass 0.368) but devastates precision (0.194 versus 0.563). When the same text is presented to the model k times with different type subsets, each pass independently generates entity predictions. Because LLM outputs are not calibrated across passes, the union merge step accumulates overlapping and contradictory predictions and inflates false positives.

Our v2 merge ranks competing predictions by the LLM's self-reported confidence and retains only the highest-scoring candidate for each span. Confidence gating improves precision (sdgd_zero: 0.210→0.324; random_batch: 0.249→0.331), but at the cost of disproportionate recall loss (0.314→0.191; 0.446→0.276), and both modes produce lower F1 (sdgd_zero: 0.251→0.241; random_batch: 0.320→0.301).

B.1 Practical Routing Strategies on RE

We evaluate five non-oracle routing strategies on FewRel 80-relation RE using graph-coloring sub-schema decomposition (same grouping as Table 13). Each strategy selects a single sub-schema for each test instance and returns that sub-schema's prediction.

C Factorial Analysis and Separability Test

To formally test whether count and confusability effects are additive, we fit a multiple regression (accuracy $\sim \log_2$ count + BCS + count×BCS) across 69 batches from FewRel spanning five count levels ($k \in \{4, 8, 16, 32, 40\}$). Both main effects are significant (count: $p = 0.008$; BCS: $p = 0.0002$; $R^2 = 0.52$), but the interaction term is negligible (0.47 pp). A TOST equivalence test with a ± 3 pp margin confirms that the interaction is bounded well below practical significance ($p_{\text{TOST}} = 0.003$); this supports bounded interaction between count and confusability effects.

Table 9: Routing strategy comparison on FewRel 80-relation RE with graph-coloring sub-schema decomposition. Oracle requires gold labels. All practical (non-oracle) strategies perform below the single-pass baseline. The failure stems from constrained decoding (enum constraint), which forces confident predictions in every sub-schema: 73.4% of instances receive positive predictions from 3–5 sub-schemas simultaneously, with per-sub-schema none-rates of only 20–40%.

Strategy	Accuracy	Δ vs. Single-Pass
Oracle (gold label)	72.4%	+22.0 pp
Max-conf (positive only)	36.5%	−14.0 pp
None-aware	36.5%	−14.0 pp
Margin (positive only)	35.9%	−14.5 pp
Max-conf (all)	27.7%	−22.7 pp
Random	14.7%	−35.7 pp
Single-pass (no decomposition)	50.4%	—

A 2×2 factorial sensitivity check on FewRel (count $\in \{8, 16\}$, BCS low/high; $n = 54$) was inconclusive ($p_{\text{TOST}} = 0.56$) due to limited power; this does not contradict the primary finding but limits its generalization beyond the regression framework. The Few-NERD factorial (§4.4) similarly did not reach significance ($p = 0.50$). The regression approach provides the stronger test by leveraging the full count range.

Equivalence margin justification. We set the ± 3 pp margin based on three converging anchors. *External*: evaluation variance in IE benchmarks typically spans 2–5 pp across random seeds, prompt variations, and data splits (Card et al., 2020; Dror et al., 2018); a within-margin interaction would be indistinguishable from routine evaluation noise. *Internal*: $0.5\times$ within-cell SD ($= 2.3$ pp) corresponds to Cohen's $d \approx 0.5$ (medium effect threshold; Lakens 2017), cross-validated against the IQR-predicted confusability main effect of 2.2 pp (§4.3)—an interaction exceeding 3 pp would represent $>130\%$ amplification. *Sensitivity*: Table 10 shows equivalence holds from ± 2 pp ($p = 0.047$) through ± 5 pp ($p < 0.001$) on the probability scale; the conclusion is not margin-dependent.

Table 10: TOST sensitivity analysis across equivalence margins. The interaction effect (0.47 pp, 90% CI [−1.0, 2.0] pp) is bounded below 2 pp at marginal significance ($p = 0.047$); the ±3 pp choice does not drive the equivalence conclusion. At ±1 pp, equivalence is inconclusive ($p = 0.278$), meaning interaction could reach approximately half the main effect magnitude.

Margin (pp)	t_{upper}	p_{TOST}	Conclusion
±1	−0.59	0.278	Inconclusive
±2	−1.70	0.047	Equivalent
±3	−2.81	0.003	Equivalent
±5	−5.02	< 0.001	Equivalent

Logit-scale sensitivity. Because accuracy near 50% compresses interaction effects on the linear scale, we refit the regression on logit-transformed accuracy. The logit-scale interaction (0.111 logit units, $p = 0.047$, 90% CI [0.019, 0.203]) is marginally significant, and TOST at the equivalent ±3 pp margin (±0.156 logit at median accuracy) is inconclusive ($p_{\text{TOST}} = 0.209$). However, back-transforming the interaction to the probability scale at the observed floor ($p = 0.51$) yields 2.78 pp, still within the ±3 pp margin; at the median baseline ($p = 0.65$), the back-transformed effect is 2.53 pp. The logit TOST is inconclusive due to limited power ($n = 69$, wide CI) rather than a large effect size: the point estimate remains below the equivalence bound at all observed baselines. We retain the linear-scale TOST as the primary test and report this logit analysis as a sensitivity check. A regression-based TOST ($n = 375$, five count levels with continuous BCS) yields $p = 0.050$ at ±3 pp and $p = 0.026$ at ±3.5 pp on the logit scale, confirming the borderline status with substantially greater power than the factorial design.

DocRED factorial (expanded). With expanded batches (n=55 per count level, up from n=5), the DocRED 2 × 2 factorial (count ∈ {16, 32}, BCS median split) yields an apparent interaction (−9.4 pp, 95% CI [−12.9, −6.0]): the BCS effect is −25.0 pp at count 16 but −15.7 pp at count 32. However, this attenuation is confounded by BCS range restriction: higher-count batches have narrower BCS ranges (spread 0.26 vs. 0.38), limiting achievable extremes.

Range-matched robustness check. To control for the BCS range confound, we restrict both count levels to the overlapping BCS range [0.43, 0.70]. This retains 29 of 55 batches at count 16 (all 55 at count 32 fall within the range). Within this matched range, the BCS effect at count 16 shrinks from 15.95 pp to 9.37 pp (reflecting the narrower BCS span), while count 32 remains at 8.44 pp. The interaction drops from 7.52 pp (95% CI [1.49, 12.83]) to 0.93 pp (95% CI [−7.13, 7.44])—the CI spans zero, consistent with no interaction. Spearman correlations remain comparable ($\rho = -0.65$ at count 16, $\rho = -0.69$ at count 32), confirming that the underlying BCS–accuracy relationship is robust across counts while the raw interaction magnitude was an artifact of differing achievable BCS ranges. This result aligns with the FewRel TOST equivalence finding and supports bounded association as the cross-dataset pattern. The reduced sample ($n = 29{+}55$) yields a minimum detectable effect of 5.5 pp at 80% power, consistent with insufficient power to distinguish a true null from a small (<5 pp) interaction.

D Within-Pool CI Details

The quartile Δ for 80-pool 16-relation subsets (−3.92 pp, 95% CI [−8.17, +0.38]) crosses zero, reflecting the compressed BCS range within that pool (0.46–0.68 vs. 0.48–0.71 for the independent pool). Within this narrow band, the quartile contrast lacks statistical power to detect the effect that the regression identifies. The full 80-relation condition ($n = 25$) is underpowered for both the slope (95% CI [−1.303, +1.695]) and quartile analyses; we include it in Table 19 for completeness but do not draw inferential conclusions from it.

E Controlling for Centrality Confounds in MAVEN Per-Type Analysis

Section 4.5 identifies a centrality confound in MAVEN's per-type BCS–F1 correlation: both embeddings show a *positive* raw correlation, opposite to the expected direction. Here we formalize this analysis by identifying specific confounders for each embedding and testing whether the BCS–F1 relationship survives partial correlation controlling for these confounders.

Confound identification. For each embedding, we computed the correlation between mean BCS and candidate confounders (type frequency, degree centrality at threshold 0.7) across MAVEN's 149 active event types. The dominant confound differs by embedding:

- **MiniLM**: BCS correlates with log type frequency ($r = 0.201$). Frequent types have more

training signal and are extracted more reliably, which produces the positive BCS–F1 association.

- **Qwen3**: BCS correlates strongly with degree centrality ($r = 0.854$). In the Qwen3 embedding space, high-BCS types are those with many semantic neighbors, central, well-represented types that the model extracts well.

Partial correlation results. Table 11 reports raw Spearman ρ and partial Pearson r after controlling for the identified confounders. Under single-variable control, both correlations weaken to non-significance. Under joint control (log frequency + degree centrality simultaneously), neither embedding retains a significant BCS–F1 association.

Table 11: MAVEN per-type BCS–F1 correlation before and after controlling for centrality confounders. Raw correlations are Spearman ρ; partial correlations are Pearson r from residualized regression. Degree centrality is computed on the SCS graph at threshold 0.7. All values from experiment `exp_maven_residualized_bcs`.

Embedding	Control	Raw ρ	Raw p	Partial r	Partial p
MiniLM	—	+0.208	0.011	—	—
MiniLM	log freq	—	—	+0.133	0.11
MiniLM	log freq + degree	—	—	—	0.23
Qwen3	—	+0.184	0.025	—	—
Qwen3	degree centrality	—	—	+0.063	0.44
Qwen3	log freq + degree	—	—	—	0.44

Interpretation. The two embeddings encode different aspects of the same underlying confound. MiniLM, a smaller sentence encoder, produces a tighter embedding cluster for MAVEN's FrameNet-derived types; here, type frequency is the primary confounder because frequent types accumulate higher mean similarity to the dense cluster. Qwen3, with a larger representation space, differentiates types enough that frequency is not the dominant factor, but degree centrality (the count of strong semantic neighbors) becomes the confound instead. In both cases, the positive raw correlation reflects a centrality artifact: types that are semantically central are both high-BCS and easy to extract.

Under joint control, both embeddings yield $p > 0.2$; the raw positive BCS–F1 correlation on MAVEN is thus fully attributable to centrality-related confounders. This does not invalidate the confusability hypothesis; the pairwise SCS–confusion correlation on MAVEN remains significant (MiniLM $r = 0.129$, $p < 0.001$; Table 2). Rather, it demonstrates that per-type aggregation (mean BCS) conflates confusability with centrality in semantically homogeneous schemas, and that pairwise analysis or explicit confound adjustment is required in such settings.

E.1 Partial Correlation: Controlling for Degree Centrality

To rule out degree centrality as a confound in cross-domain datasets, we compute partial correlations between BCS and accuracy controlling for batch mean degree centrality (mean off-diagonal SCS per type, averaged across batch members).

Table 12: BCS–accuracy partial correlation controlling for degree centrality. FewRel shows minimal attenuation (VIF $= 1.18$, low collinearity). DocRED shows high BCS–centrality collinearity (VIF $= 50.9$, $r = 0.99$), but the partial correlation remains highly significant.

Dataset	n	r_{zero}	r_{partial}	p_{partial}	VIF
FewRel	204	-0.570	-0.537	< 0.001	1.18
DocRED	110	-0.760	-0.348	< 0.001	50.9

As Table 12 shows, on FewRel, BCS and degree centrality are only moderately correlated ($r = 0.39$), and the BCS effect survives nearly intact after partialling ($r_{\text{partial}} = -0.537$ vs. $r_{\text{zero}} = -0.570$; semipartial $R^2 = 0.273$). On DocRED, the near-perfect BCS–centrality correlation ($r = 0.99$) makes it impossible to fully separate the two predictors; the significant partial correlation ($p < 0.001$) indicates BCS retains predictive value but does not uniquely identify the causal channel. This contrasts with MAVEN (§E), where the BCS signal vanishes after controlling for centrality.

Ridge regression under multicollinearity. Ridge regression (GCV, $\lambda = 0.001$) on the 110 DocRED batches confirms the negative direction of the BCS–accuracy relationship even after regularizing for the severe BCS–centrality multicollinearity (VIF ≈ 50.9). The standardized BCS coefficient is $\hat{\beta}_{\text{BCS}} = -1.53$ ($\hat{\beta}_{\text{centrality}} = 0.78$, $R^2 = 0.594$). An analytic derivation shows that $\hat{\beta}_{\text{BCS}} < 0$ for *all* $\lambda \geq 0$: the numerator of the closed-form ridge solution, $-(1+\lambda) \times 0.760 + 0.727$, is negative at $\lambda{=}0$ and monotonically decreasing thereafter. Given the shrinkage bias inherent to ridge estimation, we interpret only the sign—not the magnitude—of the BCS coefficient as directional evidence that higher schema confusability degrades extraction accuracy, independent of degree centrality.

E.2 NER BCS-Null Power Analysis

The Few-NERD BCS-null may reflect insufficient BCS variance rather than a genuine absence of the BCS–accuracy relationship. Few-NERD's BCS standard deviation (0.027) is only 19% of FewRel's (0.141); FewRel's observed $r = -0.570$ would attenuate to $r = -0.111$ under this restricted range, yielding 65% power at $n = 450$ (below the conventional 80% threshold). The minimum detectable $|r|$ at 80% power is 0.132. This analysis characterizes the NER result as absence of evidence (insufficient power at the attenuated effect size) rather than evidence of absence.

E.3 Bootstrap CI Robustness

Because batches in the FewRel experiments are constructed by sampling relation types from a shared pool, different batches may share text instances of the same type, potentially inducing residual dependence that makes standard bootstrap CIs anti-conservative. We assess this concern via cluster-robust inference. We cluster the $n = 164$ FewRel batches by instance-weighted type overlap (hierarchical clustering, complete linkage) and compute cluster-robust standard errors. Across six overlap thresholds (Jaccard distance $\in \{0.1, \ldots, 0.9\}$, yielding 80–83 clusters), the cluster-robust SE for the BCS regression slope is 0.96–0.97$\times$ the OLS SE, and the slope remains highly significant ($p < 10^{-11}$). Cluster bootstrap CIs for R^2 show width changes of -6% to $+6\%$ relative to standard bootstrap CIs ($[0.14, 0.42]$ vs. $[0.15, 0.41]$). We conclude that the reported CIs are robust to the non-independence induced by shared text instances.

E.4 Domain Distribution in Extreme-BCS Batches

We classify the 80 FewRel relation types into six semantic domains (geography, creative work, person, organization, event/temporal, science/taxonomy) and compare domain composition between the 25 highest-BCS and 25 lowest-BCS batches from our 8-type schema pool. The distributions differ significantly ($\chi^2 = 230.74$, $p < 0.001$, $df = 5$): low-BCS batches draw heavily from geography (45.5%) and creative work (25.5%), while high-BCS batches concentrate on science/taxonomy (49.5%) and event/temporal (26.0%) domains. Normalized Shannon entropy is higher for low-BCS batches ($H' = 0.79$) than high-BCS ($H' = 0.67$), confirming that low-BCS schemas span more diverse domains. Crucially, this domain concentration is an *expected* property of embedding-based confusability: relation types within the same domain naturally share semantic features, producing higher pairwise cosine similarity and thus higher BCS. Domain composition therefore acts as a mediator—it is *part of* the mechanism through which BCS captures schema difficulty—rather than an independent confounding variable. The BCS metric intentionally aggregates such semantic overlap into a single predictive score.

F Batch Composition Results

Table 13: Batch composition on FewRel 80-relation RE with oracle routing. †Mean ± SD across 15 random seeds.

Condition	Accuracy	Mean BCS
Single-pass (80 types)	0.504	0.557
Random batching (15 seeds)†	0.788 ± 0.018	0.559
Confus.-aware (graph coloring)	**0.802**	0.552

See the accompanying discussion in §5.

G Prompt Templates

This appendix reproduces the complete prompt templates used for all three extraction tasks. All prompts are injected into a single `user` message (no system prompt); the model's chat template adds the system/assistant framing. Both versions provide a JSON-formatted type schema to the vLLM constrained-decoding engine; the schema is *not* included in the natural-language prompt itself. We use greedy decoding (`temperature=0`, `seed=42`) throughout.

Notation. Placeholders are shown in `{braces}`. Text **added in v2** (relative to v1) is marked with ▷. Text **removed in v2** is marked with ~~strikethrough~~.

G.1 Named Entity Recognition (Few-NERD)

```
Extract all named entities from the
    following text.
Only extract entities of the following
    types:
- {type_1}: {definition_1}
- {type_2}: {definition_2}
  ...

Text: {input_text}

Output as JSON: [{"text": "...",
    "type": "...",
              "start": ..., "end": ...}]
```

v1 constrained-decoding schema:

```
{"type": "array",
 "items": {"type": "object",
   "properties": {
     "text": {"type": "string"},
     "type": {"type": "string",
              "enum": [<sorted_types>]},
     "start": {"type": "integer"},
     "end": {"type": "integer"}},
   "required":
      ["text","type","start","end"]}}
```

```
Extract all named entities from the
    following text.
Only extract entities of the following
    types:
- {type_1}: {definition_1}
- {type_2}: {definition_2}
  ...

Text: {input_text}
```

▷ **Added in v2:**

```
Only extract entities that clearly
    match one of the
given types. If no entities of these
    types exist in
the text, output an empty list [].

Output as JSON: [{"text": "...",
    "type": "..."}]
```

v2 constrained-decoding schema:

```
{"type": "array",
 "items": {"type": "object",
   "properties": {
     "text": {"type": "string"},
     "type": {"type": "string",
              "enum": [<sorted_types>]}},
   "required": ["text","type"]}}
```

v1 → v2 differences (NER).

1. **Offset fields removed.** The `start`/`end` integer fields are dropped from both the natural-language instruction and the JSON schema. In v1, 96.5% of predicted offsets were hallucinated (§3.5).
2. **Format constraints added.** Two sentences are appended: (a) "Only extract entities that clearly match one of the given types" suppresses spurious predictions; (b) "If no entities . . . output an empty list `[]`" provides an explicit empty-output path.

G.2 Event Detection (MAVEN)

```
Extract all event triggers from the
    following text.
A trigger is the word or phrase that
    most clearly
expresses the event occurrence. Only
    extract triggers
of the following event types:
- {type_1}: {definition_1}
- {type_2}: {definition_2}
  ...

Text: {input_text}

Output as JSON: [{"text": "...",
    "type": "...",
              "start": ..., "end": ...}]
```

```
Extract all event triggers from the
    following text.
A trigger is the word or phrase that
    most clearly
expresses the event occurrence. Only
    extract triggers
of the following event types:
- {type_1}: {definition_1}
- {type_2}: {definition_2}
  ...

Text: {input_text}
```

▷ **Added in v2:**

```
Only extract triggers that clearly
    match one of the
given event types. If no events of
    these types exist
in the text, output an empty list [].

Output as JSON: [{"text": "...",
    "type": "..."}]
```

The JSON schemas for ED are identical to the NER schemas above; only the natural-language framing differs ("event triggers" instead of "named entities").

v1 → v2 differences (ED). Same two changes as NER: offset fields removed, format constraints added.

G.3 Relation Extraction (FewRel)

RE uses only a v2-style prompt (no offset fields are applicable to classification).

```
Given the following sentence and two
    entities,
classify the relation between them.

Sentence: "{sentence}"
Head entity: "{head_entity}"
Tail entity: "{tail_entity}"

Candidate relations: {type_1},
    {type_2}, ...

Output a single JSON object:
  {"relation": "<relation_type>"}
If none of the candidate relations
    apply, output:
  {"relation": "none"}
```

Constrained-decoding schema:

```
{"type": "object",
 "properties": {
   "relation": {"type": "string",
     "enum": [<sorted_types>, "none"]}},
 "required": ["relation"]}
```

G.4 Type Definitions

All prompts include per-type natural-language definitions sourced from the respective dataset documentation:

- **Few-NERD:** 66 fine-grained entity types with definitions derived from the Few-NERD type ontology (Ding et al., 2021).
- **MAVEN:** 168 event types with FrameNet-based definitions (Wang et al., 2020b).
- **FewRel:** 80 relation types with Wikidata property descriptions (Han et al., 2018).

Type definitions are injected as "– `{type_name}: {definition}`" lines in alphabetical order. The number of types per prompt varies by experimental condition (count = 1 to full schema; §3.3).

H Prompt Version Sensitivity Analysis

We assess whether the confusability effects reported in §4.3–4.4 are robust to prompt design by replicating key experiments under the v2 prompt (§3.5; full templates in Appendix G).

RE (FewRel). Under the v1 prompt, the extreme-batch BCS gap (Table 16) is substantial. Under v2, with n=25 batches per group and wider BCS contrast (low-BCS range [0.356, 0.367]; high-BCS range [0.791, 0.811]), the gap is -25.5 pp (low-BCS 85.2% vs. high-BCS 59.7%; 95% CI [22.4, 28.6]; $p < 0.001$; Pearson $r = -0.919$). The effect is significant, directionally consistent with v1, and only modestly attenuated in magnitude (-5.7 pp reduction). An earlier n=5 evaluation with narrower BCS contrast (0.21) yielded a smaller gap of -7.9 pp (95% CI [-5.2, $+21.5$]), illustrating how limited statistical power and restricted BCS range can obscure the underlying signal, a cautionary note for small-sample prompt sensitivity studies.

NER (Few-NERD). The batch-level BCS–F1 correlation is null under both prompt versions. Pooling across three seeds and all count levels ($n = 450$), the correlation is $r = 0.004$ ($p = 0.94$). An earlier small-sample analysis ($n = 27$, single seed) had reported positive correlations ($r = +0.50/+0.58$), but these were driven by an accidental BCS–type-frequency confound: those 27 batches exhibited $r(\text{BCS}, \text{freq}) = 0.53$, creating a spurious path through frequency to F1. After controlling for type frequency, the partial correlation is non-significant in both the small ($r = 0.28$, $p = 0.16$) and large ($r = -0.12$, $p = 0.29$) samples. The pairwise SCS–confusion analysis (§4.2), which is immune to this batch-level aggregation artifact, remains the primary evidence for the NER confusability dimension.

Interpretation. The n=25 v2 result confirms that the confusability effect is directionally consistent across prompt designs, with attenuated magnitude: the gap narrows (-5.7 pp) but remains highly significant ($p < 0.001$, $r = -0.919$). The earlier n=5 non-significance reflected insufficient power and narrow BCS contrast, not absence of the effect. V2's stricter format constraints raise the baseline accuracy (low-BCS 85.2% vs. 82.3%), but type confusion under high confusability persists (59.7% vs. 51.0%). Prompt design modulates the practical magnitude of the confusability effect but does not eliminate it, ruling out prompt-specific confounding as the primary source. The underlying confusability signal (pairwise SCS–confusion correlation and the directional BCS–accuracy relationship) persists across both prompt versions.

H.1 Cross-Prompt-Variant BCS Correlation

To verify that the BCS–accuracy relationship is not an artifact of a specific prompt template, we evaluate four structurally distinct prompt variants on FewRel 80-relation RE at two count levels (8 and 32), with 10 random batches per condition (Table 14).

At count 32, all four variants produce negative BCS–accuracy correlations (r ranges from -0.47 to -0.77), with V2 ($p = 0.043$) and Minimal ($p = 0.009$) reaching significance and Chain-of-thought approaching it ($p = 0.088$). At count 8, correlations are weaker and nonsignificant across all variants, consistent with the narrower BCS range at lower schema complexity reducing the detectable effect size. Rather than applying Bon-

Table 14: BCS–accuracy Pearson correlation across four prompt variants. At count 32, all four variants show negative BCS–accuracy correlations ($r \leq -0.47$), with two reaching $p < 0.05$. At count 8, the narrower BCS range reduces statistical power.

Variant	Count	Mean Acc	r	p
V2 (definition-first)	8	0.769	−0.333	0.348
V2 (definition-first)	32	0.564	−0.648	0.043
Instruction-rewrite	8	0.847	−0.223	0.536
Instruction-rewrite	32	0.662	−0.469	0.171
Chain-of-thought	8	0.749	+0.254	0.478
Chain-of-thought	32	0.617	−0.566	0.088
Minimal	8	0.852	−0.170	0.638
Minimal	32	0.615	−0.771	0.009

ferroni correction, which assumes independent hypotheses inappropriate for correlated prompt variants testing the same underlying signal, we note directional consistency: 7 of 8 conditions show negative BCS–accuracy slopes, consistent with the primary finding (Rothman, 1990). These results confirm that the confusability effect arises from schema composition, not prompt-specific phrasing.

I BCS Aggregation Sensitivity

We define Batch Confusability Score (BCS) as the *mean* pairwise SCS across all type pairs in a batch (§4.3). An alternative definition takes the *maximum* pairwise SCS within each batch to capture the single most confusable pair. Here we compare both aggregation methods to verify that core conclusions are robust to this choice (Table 15).

Table 15: BCS–accuracy regression under mean vs. max pairwise SCS aggregation (FewRel, 16-relation batches). Permutation test for slope equivalence across pools: MEAN $p \approx 0.60$; MAX $p \approx 0.44$. The 80-pool row is identical under both definitions because these batches were collected using mean-aggregated BCS; the MAX column reflects the same data for completeness.

Aggregation	Condition	Slope	95% CI	r	p
MEAN (primary)	16-rel	−0.509	[−0.686, −0.336]	−0.467	< 0.001
MEAN	80-pool 16-sub	−0.401	[−0.701, −0.069]	−0.221	0.027
MAX	16-rel	−0.449	[−0.552, −0.346]	−0.637	< 0.001
MAX	80-pool 16-sub	−0.401	[−0.701, −0.069]	−0.221	0.027

MAX aggregation yields stronger correlations ($r = -0.637$ vs. -0.467 for 16-rel), consistent with the hypothesis that the single most confusable pair in a batch predicts substitution errors. Both definitions produce significant negative slopes across all conditions, and the permutation tests confirm no significant difference between independent and sampled pools under either definition. We adopt MEAN as the primary definition because it better represents average pairwise difficulty across all schema combinations, while MAX may overweight a single outlier pair. The choice does not affect any paper conclusion.

J BCS-Controlled Detailed Results

Table 16: BCS-controlled FewRel accuracy. Low-BCS batches contain maximally dissimilar types; high-BCS batches contain maximally similar types. The 80-relation extreme-batch gap reflects the wider BCS range; regression slopes are consistent across pools ($p = 0.60$; Table 19; see §4.3 for typical-batch magnitudes). The 16-relation condition used a single extreme batch per BCS level; bootstrap CIs require multiple batches.

Schema	Count	Low-BCS	High-BCS	Δ (pp)	95% CI
16-rel	8	88.9%	79.8%	−9.1	—
80-rel	8	82.3%	51.0%	−31.2	[17.7, 42.7]
80-rel	16	82.8%	51.6%	−31.2	[22.9, 39.6]

Adjusted R^2 and confidence intervals. DocRED regressions (§4.3) use OLS on $n = 55$ batches (15 high-BCS + 15 low-BCS + 25 random) per count level, with one predictor. At count 16, adjusted $R^2 = 0.646$ (unadjusted: 0.653; 95% CI [0.53, 0.77]); at count 32, adjusted $R^2 = 0.606$ (unadjusted: 0.614; 95% CI [0.47, 0.75]). The small shrinkage ($\Delta R^2 \leq 0.01$) indicates the unadjusted values are not inflated by the predictor-to-sample ratio.

K Format Independence: Paired Constrained vs. Unconstrained Comparison

To test whether the BCS–accuracy relationship depends on the output format, we run both constrained (enum-based) and unconstrained (free-text) decoding on the same 25 batch type sets from the FewRel 80-relation pool (13 low-BCS, 12 high-BCS; count 8). Each batch uses identical instances and type sets; only the decoding format differs (Table 17).

The near-zero Fisher z statistics ($|z| < 0.05$, $p > 0.96$) confirm that the BCS–accuracy correlation is indistinguishable between formats. Both Pearson r values are significant ($p < 0.03$), reflecting the bimodal BCS distribution of extreme batches (13 low + 12 high); the monotonic Spearman ρ is modest and non-significant under both formats, consistent with the typical-batch BCS effect size (∼2 pp; §4.3). This result establishes that the

Table 17: Paired comparison of constrained vs. unconstrained decoding on 25 identical FewRel batch type sets. Both formats yield virtually identical BCS–accuracy correlations (Fisher $z \approx 0$), confirming the confusability effect is format-independent. Mean accuracy is also unchanged ($\Delta = -0.08$ pp), ruling out a format-driven accuracy shift.

Metric	Constrained	Unconstrained
Mean accuracy	79.5%	79.6%
Pearson r (BCS vs. acc)	-0.448 ($p = 0.025$)	-0.439 ($p = 0.028$)
Spearman ρ (BCS vs. acc)	-0.157 ($p = 0.455$)	-0.144 ($p = 0.492$)
Paired Fisher z-test for correlation equality		
Pearson z	-0.04 ($p = 0.97$)	
Spearman z	-0.04 ($p = 0.97$)	

confusability-associated degradation pattern is robust across output formats, not an artifact of forced-choice decoding.

Per-batch paired results. Table 18 reports per-batch accuracy under both formats. Of 25 batches, 23 yield *identical* accuracy; the two exceptions (high_5, high_11) differ by a single sample (1/96 $\approx$ 1.04 pp). Only 2 out-of-vocabulary predictions occur in unconstrained decoding (OOV rate 0.08%), confirming that the model generates valid type labels even without format constraints.

L Within-Pool Analysis Methodology

A potential confound in the cross-scale comparison is that the 16-relation and 80-relation pools contain different types, so the observed gap could reflect pool composition rather than confusability. To control for this, we draw 100 random 16-relation subsets from the 80-relation pool and evaluate under the same BCS-controlled protocol.

The within-pool slope (-0.401, CI excludes zero) is statistically indistinguishable from the independent 16-relation pool (-0.509; permutation $p \approx 0.60$). The smaller quartile gap (-3.92 pp vs. -5.31 pp) reflects the narrower BCS range within the 80-relation pool (Appendix D).

In the full 80-relation condition, natural BCS variation is insufficient (IQR $= 0.033$) to yield a detectable effect ($n = 25$, slope $= +0.221$, $p \approx 0.76$). This does not invalidate the confusability effect; the within-pool slope is significant ($p = 0.027$) when BCS is deliberately varied, but establishes that natural schema sampling at this scale does not produce sufficient BCS contrast for detection.

Table 18: Per-batch accuracy (%) under constrained and unconstrained decoding on 25 identical FewRel batch type sets (count 8, 96 instances each). 23/25 batches yield identical accuracy; the two exceptions differ by exactly one sample ($\Delta = -1.04$ pp). L = low-BCS, H = high-BCS.

Batch	Group	BCS	Constr.	Unconstr.	Δ
low_0	L	0.472	83.3	83.3	0.0
low_1	L	0.647	81.3	81.3	0.0
low_2	L	0.665	87.5	87.5	0.0
low_3	L	0.672	82.3	82.3	0.0
low_4	L	0.674	67.7	67.7	0.0
low_5	L	0.678	72.9	72.9	0.0
low_6	L	0.679	80.2	80.2	0.0
low_7	L	0.687	87.5	87.5	0.0
low_8	L	0.692	77.1	77.1	0.0
low_9	L	0.692	91.7	91.7	0.0
low_10	L	0.692	87.5	87.5	0.0
low_11	L	0.709	84.4	84.4	0.0
low_12	L	0.709	68.8	68.8	0.0
high_0	H	0.712	91.7	91.7	0.0
high_1	H	0.724	77.1	77.1	0.0
high_2	H	0.735	67.7	67.7	0.0
high_3	H	0.742	86.5	86.5	0.0
high_4	H	0.742	86.5	86.5	0.0
high_5	H	0.747	81.3	82.3	-1.0
high_6	H	0.768	83.3	83.3	0.0
high_7	H	0.778	77.1	77.1	0.0
high_8	H	0.791	71.9	71.9	0.0
high_9	H	0.820	70.8	70.8	0.0
high_10	H	0.823	92.7	92.7	0.0
high_11	H	0.971	49.0	50.0	-1.0

Table 19: Three-way BCS–accuracy analysis on FewRel. Slope: OLS of batch accuracy on BCS (bootstrap CIs, B=10,000). Δ: accuracy gap between top- and bottom-quartile BCS batches. See Appendix D for CI interpretation.

	Regression (BCS → Accuracy)				Quartile Δ	
Setting	Slope	95% CI	r	p	Δ (pp)	95% CI
Independent 16-rel (n=100)	-0.509	[-0.686, -0.336]	-0.467	< 0.001	-5.31	[-7.44, -3.19]
80-pool → 16-sub (n=100)	-0.401	[-0.701, -0.069]	-0.221	0.027	-3.92	[-8.17, $+0.38$]
Full 80-rel (n=25)†	$+0.221$	[-1.303, $+1.695$]	$+0.064$	0.76	-1.04	[-10.12, $+8.04$]

Permutation test (16-rel vs. 80-pool slopes): $p \approx 0.60$ (5,000 permutations)
†BCS range (IQR = 0.033) insufficient for regression; slope not interpretable.

M SCS Embedding Ablation: Name-Only vs. Name+Definition

Table 20 compares predictive accuracy of name-only SCS against name+definition SCS across three datasets.

Few-NERD is the only dataset whose prompts include type definitions; for MAVEN and FewRel, prompts use type names alone, so name-only SCS directly matches model input. The high matrix correlation (0.66–0.89) confirms that type names capture the dominant semantic structure.

Held-out validation. From the 80-type confusion matrix, we extract the $\binom{16}{2} = 120$ pairs among the 16 validation-origin types (fully disjoint from

Table 20: Pearson correlation between SCS and empirical confusion rate. "Def" concatenates type name with definition before embedding. All correlations significant ($p < 0.001$). The inconsistent direction of Δr indicates that definitions provide no systematic benefit.

Dataset	SCS_{name} r	SCS_{def} r	Δr	Matrix corr.
Few-NERD	0.172	0.149	−0.023	0.894
MAVEN	0.129	0.164	+0.035	0.656
FewRel	0.178	0.193	+0.015	0.848

the 64 training-pool types). The SCS–confusion Spearman correlation remains positive and significant ($\rho = 0.216$, $p = 0.018$), nearly identical to the full 80-type pool ($\rho = 0.218$, $p < 0.001$, $n = 3{,}160$ pairs), ruling out training-set contamination as the driver of the observed relationship.

N Pair-to-Batch Aggregation Simulation

The following simulation provides an illustrative explanatory model for how pair-level effects aggregate to batch-level variance. It is not the evidence base for our claims; the observed batch-level $R^2 = 0.218$ (§4.3) is a direct empirical measurement independent of this simulation.

Setup. We examine whether the pair-level $R^2 \approx 7\%$ (computed over non-zero confusion pairs) can aggregate to the observed batch-level $R^2 \approx 22\%$ via a Monte Carlo simulation. From the FewRel 16-relation experiment, we estimate the inter-pair SCS correlation for pairs sharing a common type ($\rho_{\text{SCS}} = 0.35$). For batches of $k = 8$ types ($\binom{8}{2} = 28$ pairs), we simulate 10,000 iterations: (1) generate 28 correlated pair-level effects with individual $R^2 = 0.074$; (2) average to obtain batch-level signals; (3) compute batch-level R^2.

Results. Simulated batch $R^2 = 0.219$ (95% CI [0.092, 0.361]), matching the observed value of 0.218. The effective amplification factor is $\sim 3\times$, explained by signal correlation within batches preserving variance while independent noise averages out (effective degrees of freedom ≈ 3.4, not 28).

Unconditional baseline. When the simulation uses the unconditional pairwise $r^2 = 0.013$ (computed over all type pairs including zero-confusion pairs; Table 2), the simulated batch-level R^2 drops to 0.044 (95% CI [0.001, 0.151]), well below the observed $R^2 = 0.218$. The analytical formula confirms: $\text{SNR} \times \text{EF}/(\text{SNR} \times \text{EF} + 1) = 0.042$ with the same effective factor EF $= 3.35$. This $\sim 5\times$ gap reflects the dilution from zero-confusion pairs: approximately 89% of type pairs never exhibit mutual confusion, contributing only noise to the unconditional correlation. The conditional model ($R^2 = 0.074 \rightarrow 0.219$) matches the observed value because it isolates the minority of semantically proximate pairs that actually compete during type resolution; BCS predicts batch accuracy through the density of *active* confusable pairs, not uniform contributions from all pairs.

Sensitivity to ρ. The inter-pair SCS correlation $\rho = 0.35$ is estimated from pairs sharing a common type. At $\rho = 0.20$ (halved correlation), a parallel simulation yields batch $R^2 \approx 0.22$, still matching the observed value; at $\rho = 0.50$, the correlation structure approaches the positive-definiteness boundary; $\rho = 0.35$ thus sits in a stable regime. The simulation is illustrative; the observed batch $R^2 = 0.218$ is the primary evidence.

Non-independence and ecological inference. Types within a batch share prompt context, so their extraction outcomes are not independent—a form of ecological correlation (Robinson, 1950). This non-independence is built into the design: BCS measures batch-level confusability precisely because co-present types interact during type resolution. The core batch-level $R^2 = 0.218$–0.578 (§4.3) is a direct empirical observation from regressing batch accuracy on BCS, not derived from the simulation above. The inter-pair SCS correlation $\rho = 0.35$ used in the simulation was estimated from the SCS correlation matrix independently of batch-level accuracy data.

O BCS Independence from Type Composition

FewRel's balanced design (700 instances per type) makes type frequency invariant across batches, ruling out frequency-driven confounding. To test whether BCS captures information beyond type composition effects, we decompose the explained variance in a joint model (accuracy $\sim$ BCS + mean type difficulty), where type difficulty is the per-type solo-baseline accuracy averaged across batch members. On 100 random 8-type batches from the 16-relation pool, the joint model explains $R^2 = 0.704$. Variance decomposition yields: BCS unique $R^2 = 0.259$ (36.8% of explained variance), composition unique $R^2 = 0.298$ (42.3%), and shared $R^2 = 0.147$ (20.9%). The near-orthogonality of predictors (VIF $= 1.06$,

$r(\text{BCS}, \text{difficulty}) = -0.21$) confirms that BCS captures confusability-specific signal rather than a proxy for type difficulty.

P SCS vs. Simple Baselines

Table 21 compares SCS against simple baselines for pairwise confusion prediction.

Table 21: Pairwise confusion prediction: SCS vs. simple baselines. Spearman ρ between each metric and the empirical confusion rate. SCS outperforms all baselines on FewRel; the margin is smaller on Few-NERD, where hierarchical naming conventions provide partial signal to string-based metrics. †42% of pairs lack WordNet coverage.

Dataset	Metric	Spearman ρ	p
FewRel (3,160 pairs)	SCS (embedding)	**0.218**	< 0.001
	Same-parent (WordNet)	0.097	< 0.001
	WordNet Wu-Palmer	0.073	< 0.001
	Levenshtein	0.016	0.363 (n.s.)
Few-NERD (1,953 pairs)	SCS (embedding)	**0.166**	< 0.001
	Levenshtein	0.152	< 0.001
	Same-parent (prefix)	0.146	< 0.001
	WordNet Wu-Palmer	0.054	0.070 (n.s.)†

Q Split-Origin Covariate Analysis

FewRel combines 64 train-split and 16 val-split relation types into a single 80-type pool. Train-origin types show numerically lower accuracy (-8.8 pp, $p = 0.06$; see Limitations), raising the question of whether differential pre-training exposure confounds the BCS–accuracy relationship. We test this by adding a per-batch *train-origin ratio* (fraction of relation types drawn from the train split) as a covariate in the BCS–accuracy regression.

Method. Across 213 multi-type batches ($k \geq 2$) from the batch-composition experiment (§5) and the factorial design (§4.3), we compute $\texttt{train_origin_ratio} = n_{\text{train}}/k$ for each batch. The ratio ranges from 0.40 to 1.00 (mean 0.80, consistent with the 64/80 base rate). We fit:

$$\text{acc} = \beta_0 + \beta_{\text{BCS}} \cdot \text{BCS} + \beta_{\text{orig}} \cdot \text{train_origin_ratio} + \varepsilon$$

Results. The BCS partial effect is unchanged after controlling for split-origin: $\beta_{\text{BCS}} = -0.416$, $p < 0.001$ (vs. $\beta = -0.412$, $p < 0.001$ without the covariate). Train-origin ratio is not independently significant ($\beta_{\text{origin}} = -0.057$, $p = 0.245$), and $\Delta R^2 = 0.005$. The BCS–accuracy relationship is therefore not confounded by differential pre-training exposure at the batch level.

Pairwise SCS distributions do not differ significantly between train-origin (64 types, mean = 0.880) and val-origin (16 types, mean = 0.874) subsets (Mann-Whitney $p = 0.754$, Cohen's $d = 0.081$); the train/val split does not introduce systematic confusability bias.

R Cross-Seed Variance Decomposition

Table 22: Variance decomposition on FewRel (3 seeds × 25 batches per count level). Batch SD: root-mean intra-seed variance averaged over seeds. Seed SD: standard deviation of per-seed means. Ratio = batch variance / seed variance. At count 80, only one batch composition exists, so batch variance vanishes by construction.

Count	Batch SD	Seed SD	Ratio
4	0.0889	0.0122	53.5
8	0.0820	0.0098	70.0
16	0.0626	0.0270	5.4
32	0.0462	0.0091	26.0
40	0.0421	0.0019	474.4
64	0.0245	0.0022	119.8
80	0.0001	0.0088	<0.1

Table 22 shows that intra-batch variance dominates inter-seed variance by 5–474× across count levels 4–64 (mean 125×); random batch composition is the primary source of performance variability. Under greedy decoding (temperature = 0), model inference is nearly deterministic; the inter-seed variance reflects differences in which random batch compositions each seed generates, not inference stochasticity. At count 80, the full schema admits only one composition, leaving residual model-level noise as the sole variance source (seed SD = 0.88 pp, likely attributable to FP8 quantization non-determinism).

S Cross-Domain Connections

The schema-associated degradation documented here is not unique to information extraction. Schema-Guided Dialogue systems (SGD/SGD-X; Rastogi et al. 2020) face an analogous challenge: as the number of intent and slot types grows, dialogue state tracking accuracy declines. Li et al. (2023a) observed count-dependent degradation in ChatGPT-based IE, attributing it to prompt overload. Our two-dimensional decomposition offers a more refined explanation: schema size per se is not the sole predictor; rather, larger schemas increase the probability of including high-SCS pairs, which contribute disproportionately to confusion. This distinction has practical implications: a schema of 80 types with low mutual confusability may outperform a 40-type schema with clustered semantics,

and suggests that confusability-aware design principles may generalize to any task where an LLM must discriminate among a prompt-specified label inventory.

T Cross-Model Validation with LLaMA-3.1-70B-Instruct (FP8)

To test whether the two-dimensional degradation pattern generalizes across models, we replicate the count-curve and BCS-controlled experiments on Meta-LLaMA-3.1-70B-Instruct (FP8 quantization). All batch compositions, type pools, and test samples are identical to those used for Qwen3-32B (§4.1, §4.3).

Table 23: Cross-model count curves for LLaMA-3.1-70B-Instruct (FP8) and Qwen3-32B. RE decline (count 8→80): −30.7 pp (70B) vs. −30.1 pp (32B). NER decline (count 2→22): −7.1 pp (70B) vs. −23.6 pp (32B); both models exhibit a U-shaped rebound at higher counts. 25 batches per count level, same samples and batch compositions across models (seed 42). All metrics are micro-averaged across batches.

Count	LLaMA-70B	Qwen3-32B
RE (FewRel, Classification Accuracy)		
8	0.757	0.805
16	0.685	0.719
32	0.601	0.652
64	0.504	0.539
80	0.450	0.504
NER (Few-NERD, Text+Type Match Recall)		
2	0.323	0.515
6	0.300	0.399
12	0.278	0.318
22	0.252	0.279
44	0.297	0.309
66	0.273	0.407

Table 23 shows that RE degradation slopes are near-identical: −30.7 pp (70B) versus −30.1 pp (32B) from count 8 to count 80, with the 70B model approximately 4 pp lower in absolute accuracy at each count level. This quantitative match provides strong evidence that Dimension 1 (count-related decline) is directionally consistent across architectures for RE.

On NER, the count-related decline direction is consistent across models: both 70B and Qwen3 show a recall decline from count 2 to count 22 (70B: 0.323→0.252, −7.1 pp; Qwen3: 0.515→0.279, −23.6 pp). Both models also exhibit a U-shaped rebound at higher counts (70B: 0.252 at count 22 → 0.297 at count 44; Qwen3: 0.279 at count 22 → 0.407 at count 66), which cross-validates the U-shape phenomenon. The magnitude difference reflects a precision-recall tradeoff: 70B operates more conservatively (higher precision, lower recall), while Qwen3 over-predicts (higher recall, lower precision, especially at low counts).

For the confusability dimension (Dimension 2), at count 16 on FewRel, LLaMA-70B achieves low-BCS accuracy of 0.708 versus high-BCS accuracy of 0.599 ($\Delta = +10.9$ pp, 95% CI [+3.0, +20.1]). The confidence interval excludes zero; the confusability effect is thus confirmed at the 70B scale.

In summary, FewRel RE provides a quantitative match across models (near-identical slopes for Dimension 1 and a significant Dimension 2 effect). NER provides directional consistency: the count-related decline direction is preserved and the U-shaped rebound replicates, though magnitudes vary with each model's precision-recall operating point. Together, these results indicate that the degradation pattern is directionally consistent across architectures.

U Cross-Model Validation with Gemini 2.5 Flash (API)

We validate both dimensions on a proprietary model, Gemini 2.5 Flash (Gemini Team, 2025), accessed via API. This extends the cross-model evidence from open-weight families (Qwen, LLaMA) to a proprietary architecture with unknown training details. We replicate the FewRel count-curve and BCS-controlled experiments using the same 960 balanced samples, batch compositions, and evaluation protocol as Qwen3-32B.

Table 24: Cross-model count curves for Gemini 2.5 Flash (API) and Qwen3-32B on FewRel RE (classification accuracy). 25 batches per count level, same samples and batch compositions (seed 42). Gemini's count-1 result is included for completeness; Qwen3 count-1 was not collected. Both models show monotonic decline from count 4 onward ($\rho = -1.0$ for both on counts 4–32). †Count 64: Gemini based on 11/25 batches (partial).

Count	Gemini Flash	Qwen3-32B
1	0.827	—
4	0.873	0.870
8	0.820	0.805
16	0.787	0.719
32	0.739	0.652
64†	0.637	0.539

Table 24 confirms that the count-related accuracy decline replicates on Gemini 2.5 Flash. From count

4 to count 32, both models show perfectly monotonic decline (Spearman $\rho = -1.0$). Including count 1, the Gemini count curve yields $\rho = -0.900$ ($p = 0.037$); including partial count-64 data (11/25 batches), $\rho = -0.943$ ($p = 0.005$). The decline magnitude is smaller for Gemini (-13.3 pp from count 4 to 32) than for Qwen3 (-21.8 pp), consistent with Gemini's higher absolute accuracy providing more headroom before degradation saturates. At each count level, Gemini matches or exceeds Qwen3, with the gap widening at higher counts (0.3 pp at count 4 vs. 8.7 pp at count 32, 9.8 pp at partial count 64); Gemini appears more robust to schema scaling but not immune.

Dimension 2: BCS-controlled confusability. We replicate the BCS-controlled experiment on Gemini 2.5 Flash using extreme-BCS batches at count 8 ($n = 50$; 25 low-BCS, 25 high-BCS) and count 16 ($n = 10$; 5+5).

At count 8, low-BCS batches achieve 90.5% vs. high-BCS 72.9% ($\Delta = -17.6$ pp, 95% CI [15.1, 20.1]). At count 16, the gap narrows to -8.7 pp, but one high-BCS outlier (BCS $= 0.97$, accuracy 59.9%) inflates Pearson r; leave-one-out excluding this point drops r from -0.80 to -0.42 ($p = 0.22$) and ρ from -0.40 to -0.18 ($p = 0.64$), confirming the count-16 correlation is driven by this single leverage point. The count-8 gap is smaller than Qwen3-32B's (-31.2 pp), consistent with ceiling compression: Gemini's higher baseline (90.5% vs. 82.3%) leaves less room for degradation.

Table 25 summarizes BCS-controlled results across all validated models. Both dimensions thus replicate on a proprietary architecture with unknown training details.

Table 25: Cross-model BCS-controlled FewRel RE summary. All models show significant low-vs-high BCS accuracy gaps. Gap magnitude varies with model capacity (ceiling compression), but the direction is consistent across open-weight (8B–70B) and proprietary architectures.

Model	Count	Low BCS	High BCS	Δ	95% CI
Qwen3-32B	8	82.3%	51.0%	-31.2 pp	—
Qwen3-32B	16	82.8%	51.6%	-31.2 pp	—
Llama-8B	8	78.1%	51.0%	-27.1 pp	—
Llama-70B FP8	16	—	—	-10.9 pp	[3.0, 20.1]
Gemini Flash	8	90.5%	72.9%	-17.6 pp	[15.1, 20.1]

V Few-Shot Prompting and Confusability

To test whether in-context demonstrations mitigate the BCS-associated confusability effect, we evaluate 0-shot, 1-shot, and 5-shot prompting on FewRel 80-relation RE at count 8 using the same extreme-BCS batch design as §4.3. Each condition uses 50 batches (25 low-BCS, mean ≈ 0.36; 25 high-BCS, mean ≈ 0.80), drawn from the pre-constructed batch pool of §4.3. Few-shot examples are sampled from the FewRel training split for each target type (Table 26).

Table 26: BCS gap under few-shot prompting (FewRel, count 8). Demonstrations improve absolute accuracy on low-BCS batches (+3.3–7.2 pp over 0-shot) but provide inconsistent benefit on high-BCS batches (+5.6 pp at 1-shot, -1.0 pp at 5-shot). The confusability gap widens from +18.5 pp (0-shot) to +22.8 pp (5-shot). All metrics are micro-averaged across batches.

Condition	Low-BCS	High-BCS	Δ (pp)	95% CI
0-shot	0.682	0.498	+18.5	[+14.3, +22.7]
1-shot	0.754	0.554	+20.0	[+16.3, +23.5]
5-shot	0.715	0.488	+22.8	[+18.9, +26.8]

Demonstrations improve absolute accuracy primarily on low-BCS (easy) batches, where type boundaries are already distinct and examples reinforce correct mappings. On high-BCS batches, where types are semantically confusable, demonstrations provide inconsistent benefit (+5.6 pp at 1-shot, -1.0 pp at 5-shot): the model still substitutes similar types at comparable rates. The net effect is that the confusability gap widens under few-shot prompting (+4.3 pp from 0-shot to 5-shot, bootstrap $p = 0.014$), with all three confidence intervals excluding zero. This indicates that BCS-associated type confusion is a structural property of the schema composition rather than a deficit addressable through prompt engineering. The non-monotonic low-BCS pattern (0.754 at 1-shot vs. 0.715 at 5-shot) may reflect lost-in-middle effects from increased prompt length (Liu et al., 2024).

The 0-shot gap (+18.5 pp) is smaller than the extreme-batch gap reported in §4.3 (+25.5 pp) because the two experiments use different test splits and batch sampling seeds; direct magnitude comparison across experiments is not appropriate.

W Qualitative Error Analysis

Tables 27 and 28 list the ten most frequently confused type pairs on FewRel 80-relation RE and Few-NERD NER. Confusion counts are aggregated

bidirectionally across three random seeds (72,000 predictions per seed for RE; single-seed 66-type extraction for NER). Table 29 provides illustrative confusion instances with SCS values.

Table 27: Top-10 confused relation pairs on FewRel 80-relation RE. N: bidirectional confusion count aggregated over 3 seeds $\times$ 25 batches. SCS: pairwise Schema Confusability Score (Qwen3 embedding cosine similarity). High-SCS pairs (e.g., *followed by*/*follows*, SCS = 0.90) and family-relation pairs (*child*/*father*, *child*/*mother*) dominate. Some low-SCS pairs (*instance of*/*taxon rank*, SCS = 0.53) reflect domain-specific co-occurrence rather than semantic similarity.

#	Type A	Type B	SCS	N
1	instance of	taxon rank	0.53	875
2	child	father	0.84	700
3	participant of	participating team	0.75	675
4	mountain range	part of	0.57	575
5	mouth of watercourse	tributary	0.65	549
6	child	mother	0.84	500
7	league	member of	0.66	450
8	country of citizenship	country of origin	0.76	400
9	followed by	follows	0.90	400
10	occupation	voice type	0.57	400

Table 28: Top-10 confused entity type pairs on Few-NERD NER. N: bidirectional confusion count from 66-type full-schema extraction. SCS: pairwise Schema Confusability Score (Qwen3 embedding cosine similarity). Intra-category confusions (e.g., *person-other*/*person-politician*, SCS = 0.93) and cross-category pairs sharing referent overlap (*building-other*/*location-GPE*, SCS = 0.85) are most frequent. The "other" subtypes absorb diverse entities and confuse with more specific siblings.

#	Type A	Type B	SCS	N
1	person-other	person-politician	0.93	121
2	location-GPE	organization-other	0.83	81
3	art-film	location-GPE	0.69	57
4	building-other	location-GPE	0.85	56
5	building-other	person-other	0.90	43
6	location-GPE	product-other	0.69	39
7	org-gov/agency	person-other	0.85	34
8	person-actor	person-other	0.90	34
9	building-other	location-road/transit	0.76	32
10	location-GPE	org-sportsleague	0.81	30

X Schema Label Renaming Experiment

To test whether reducing pairwise SCS through label renaming improves accuracy, we conducted a controlled intervention on FewRel 80-relation RE (count 8, Qwen3-32B). We identified 14 high-SCS relation pairs (covering 12 unique relation types, as two types each appear in multiple pairs; mean SCS = 0.87) and replaced one label in each pair with a semantically distinct paraphrase chosen to minimize embedding cosine similarity (all-MiniLM-L6-v2). Examples: *participant of* $\rightarrow$ *event involvement* (SCS: 0.97 $\rightarrow$ 0.72), *follows* $\rightarrow$ *prior entry* (0.90 $\rightarrow$ 0.69), *part of* $\rightarrow$ *integral segment of* (0.90 $\rightarrow$ 0.64). The renaming reduced mean pairwise SCS from 0.87 to 0.67 ($\Delta = -0.20$). We ran the same 50 BCS-controlled batches (25 low-BCS, 25 high-BCS; 96 samples each) under both original (control) and renamed (treatment) label sets (Table 30).

Renaming hurt accuracy uniformly: both groups showed significant declines (paired t-test, both $p < 0.001$). The number of renamed types per batch correlated negatively with accuracy change ($r = -0.625$, $p < 0.001$). A solo sanity check confirmed that 11 of 12 renamed labels were individually recognizable (accuracy $\geq$ original -5 pp). The results indicate that replacing familiar Wikidata labels with unfamiliar paraphrases disrupts the model's type semantics; this label unfamiliarity effect outweighs any benefit from reduced confusability.

Y Relaxed Matching Evaluation (NER)

To test whether exact-match F1 masks the BCS signal in NER by conflating boundary errors with type errors, we evaluate three progressively relaxed matching criteria on the full Few-NERD NER dataset ($n = 450$ batches: 6 count levels $\times$ 25 batches $\times$ 3 seeds; Table 31).

A per-error-mode analysis confirms this null extends to all individual categories: miss ($\rho = 0.017$), boundary ($\rho = -0.043$), and type substitution ($\rho = -0.010$) rates show no BCS association (all $p > 0.3$, $n = 450$). The null holds within each count level (count 2: $r = 0.022$; count 6: $r = 0.110$; count 12: $r = 0.028$; all $p > 0.3$), ruling out count as a confound.

Table 29: Illustrative confusion instances from FewRel 80-rel RE. All gold-predicted pairs have SCS > 0.90: *participant* vs. *participant of* reverses directionality; *contains* vs. *located in* inverts containment; *part of* vs. *member of* conflates meronymy with membership. a.t.e. = admin. territorial entity.

Sentence	**Gold**	**Pred.**	**SCS**
… played for **Valencia** … [**EuroLeague**]	participant	participant of	0.97
Pilões is a municipality in **Rio Grande do Norte** …	contains a.t.e.	located in a.t.e.	0.92
Davies … appointed to **Cabinet** as **Sec. of State**	part of	member of	0.90

Table 30: Accuracy (%) under original vs. renamed labels on FewRel count-8 batches. Renaming reduced embedding similarity but decreased accuracy in both groups, with a larger drop on high-BCS batches (Cohen's $d = -2.92$) than low-BCS ($d = -1.09$). Interaction: $\Delta_{\text{high}} - \Delta_{\text{low}} = -5.9$ pp ($t = -7.23$, $p < 0.001$).

	Control	**Treatment**	**Δ (pp)**
Low-BCS ($n = 25$)	90.1	87.1	−3.0
High-BCS ($n = 25$)	69.3	60.5	−8.8

Table 31: BCS–F1 correlation under progressively relaxed NER matching. Relaxed span credits a match if the predicted span overlaps the gold span and the type is correct; token overlap uses token-level intersection; type-ignored drops the type constraint entirely. Relaxed matching improves mean F1 by 4.2 pp (98.4% of batches improve), but Pearson r remains near zero across all modes (bootstrap 95% CI crosses zero in all cases). Boundary errors affect all batches uniformly and do not mask a BCS signal.

Match mode	r	p	ρ	p	**F1**
Exact	0.014	0.760	−0.101	0.033	0.304
Relaxed span	0.003	0.946	−0.110	0.020	0.346
Token overlap	0.004	0.936	−0.113	0.017	0.349
Type-ignored	0.023	0.621	−0.097	0.039	0.425