

Overview

Provides data logging and SDLC-to-Ethernet protocol translation to enable next generation vehicle detection technologies in the traffic signals cabinet.

Features

- TS2 Port 1 SDLC compatible on BIU 1-4
- Tested with numerous 2070 and ATC controllers
- Static and dynamic IP addressing support
- Low power consumption
- Wide voltage range
- Onboard screen for system status
- Web based configuration
- Onboard option switches
- Bootloader for field upgradeable firmware
- 100Mb Ethernet with PoE 802.3af PD
- Coming July 2026 - BIU rack/shelf alternative
- Coming Sept 2026 - (8) SPDT Solid-State Relay output

Technical Specifications

Supply voltage

12-24 VDC or PoE

Temp range

-34 C to +74 C (operating and storage)

Humidity

95% non-condensing

Power consumption

3.2W operating (7.5W peak startup)

Construction

Extruded Aluminum

OS

Debian 13 (Kernel 6.12)

Computing

Quadcore 64-bit Cortex-A76 @ 2.4GHz

RAM

2GB DDR4

Storage

128GB Removable microSDHC

Dimensions

125 x 125 x 88 mm (4.9 x 4.9 x 3.5in)

Weight

719g (25oz)

(DIN Rail Mount)

GET IN TOUCH

