

Overview

Provides data logging and SDLC-to-Ethernet protocol translation to enable next generation vehicle detection technologies in the traffic signals cabinet.



Features

- TS2 Port 1 SDLC compatible on BIU 1-4
- Tested with numerous 2070 and ATC controllers
- Static and dynamic IP addressing support
- Low power consumption
- Wide voltage range
- Onboard screen for system status
- Web based configuration
- Onboard option switches
- Bootloader for field upgradeable firmware
- 100Mb Ethernet with PoE 802.3af PD
- Coming Soon - BIU rack/shelf alternative
- Coming Soon - (8) SPDT Solid-State Relay output



(DIN Rail Mount)

Technical Specifications

Supply voltage
Temp range
Humidity
Power consumption
Construction
OS
Computing
RAM
Storage
Dimensions
Weight

12-24 VDC or PoE
-34 C to +74 C (operating and storage)
95% non-condensing
3.2W operating (7.5W peak startup)
Extruded Aluminum
Debian 13 (Kernel 6.12)
Quadcore 64-bit Cortex-A76 @ 2.4GHz
2GB DDR4
128GB Removable microSDHC
125 x 125 x 88 mm (4.9 x 4.9 x 3.5in)
719g (25oz)

GET IN TOUCH

