Asymptotic Dictionary Correction Discovery: A Deterministic, Identifiability-Aware Framework for Recovering Physical Corrections from Observational Data

Muhammad Afif Erdita
Independent Researcher
Indonesia
maeapip10@gmail.com

Abstract

Many physical laws take the form "a known classical formula plus a small correction" (for example, relativistic time dilation). We present **ADCD** (Asymptotic Dictionary Correction Discovery), a method that searches for such a correction in noisy data. It differs from general-purpose symbolic regression in three ways: (i) each building block of the correction is written so that it is exactly zero in the classical limit, which avoids floating-point error; (ii) dimensional analysis proposes the dimensionless variables automatically; and (iii) a small table of physics-based function families restricts what is searched. ADCD then returns one of two verdicts: IDENTIFIABLE (the data support the discovered structure) or WITHHELD (they do not). On three synthetic tests with 1% noise, ADCD recovers the Screened Coulomb correction exactly ($\Delta\mathrm{BIC} = 30.65$), recovers the Entropy Expansion correction at the level of its function family ($\Delta\mathrm{BIC} = 14.70$; borderline, 2 of 5 noise seeds), and withholds judgment on Time Dilation at $v \leq 0.3c$, where measurement noise alone already accounts for $\mathrm{NMSE} \approx 0.41$, far above our 0.05 acceptance threshold. Results are reproducible given the same software and random seed.

Keywords: symbolic regression; correction discovery; dimensional analysis; Bayesian prior; model selection; identifiability

1 Introduction

In the expanding landscape of machine learning for the physical sciences Carleo et al. [2019], Wang et al. [2023], physical laws frequently take a correction-first form: a known classical baseline extended by a term that vanishes at the classical limit Einstein [1905], Debye and Hückel [1923], Callen [1985]. Recovering that correction from observational data is distinct from full equation discovery: the baseline is fixed, only the residual must be identified, and that residual must vanish exactly where classical physics holds.

A concrete example. Coulomb's law gives an electrostatic force that falls off as $1/r^2$. In a simple phenomenological screening model, charges screen each other and the measured force falls off faster: $F = (k_e q_1 q_2 / r^2) e^{-r/\lambda_D}$. Given noisy measurements and the classical formula, ADCD returns the correction $\theta_0(e^{-r/\theta_4} - 1)$, where the fitted length $\theta_4 \approx 1.49$ m is close to the true Debye length (1.50 m). Just as important, when the data are too noisy to support any conclusion, ADCD says so instead of returning its best guess.

Existing symbolic regression tools can discover formulas from data, but they face three difficulties in this correction-first setting: PySR Cranmer et al. [2020], Cranmer [2023], AI Feynman Udrescu

NewInML Workshop at the 40th Conference on Neural Information Processing Systems (NeurIPS 2026), Paris, France, 2026.

and Tegmark [2020], and PhySO Tenachi et al. [2023] excel at equation discovery from scratch but face three difficulties in the correction-first setting: (i) *catastrophic cancellation*: floating-point precision collapses as $u \to 0$, corrupting optimizer feedback IEEE Task P754 [2019]; (ii) *stochastic irreproducibility*: default evolutionary search does not guarantee byte-identical results across runs without serial execution Bongard and Lipson [2007], Schmidt and Lipson [2009]; and (iii) *silent overclaiming*: a single best-fit equation is returned regardless of whether the data carry sufficient power to distinguish competing structures La Cava et al. [2021], generating what recent meta-science critiques identify as an illusion of understanding Messeri and Crockett [2024], Krenn et al. [2022]. ADCD addresses each failure mode in turn: algebraically regularized primitives eliminate cancellation; deterministic grammar enumeration ensures reproducibility; explicit BIC-based identifiability gating prevents overclaiming.

Contributions.

- *Method.* A correction-first search whose building blocks vanish exactly in the classical limit, with dimensionless variables generated automatically.
- *Verdicts.* An explicit IDENTIFIABLE / WITHHELD decision based on four checks, so the method reports when the data are not informative enough.
- *Evidence.* Three synthetic scenarios (including one where ADCD correctly withholds), plus multi-seed and wrong-prior audits (Appendix A).

Scope. ADCD is tested only on synthetic data with Gaussian noise. It audits corrections to an established baseline; it is not a replacement for general symbolic regression.

2 Related Work

Automated scientific discovery traces back to pioneering heuristic systems such as BACON Langley et al. [1987] and has evolved toward modern autonomous equation discovery Kramer et al. [2026], Makke and Chawla [2024], Karagiorgi et al. [2022]. General SR engines (Eureqa Schmidt and Lipson [2009], PySR Cranmer et al. [2020], Cranmer [2023], AI Feynman Udrescu and Tegmark [2020], Udrescu et al. [2020], PhySO Tenachi et al. [2023]) target unconstrained equation recovery and do not enforce classical-limit constraints algebraically. SINDy Brunton et al. [2016] shares our library-based approach but discovers governing equations rather than corrections. PINNs Raissi et al. [2019], Karniadakis et al. [2021] embed physical laws as soft loss penalties; ADCD imposes them as hard algebraic identities before any numerical computation. Recent systems combining data with background knowledge and axiomatic reasoning, such as AI-Descartes Cornelio et al. [2023] and AI Hilbert Cory-Wright et al. [2024], highlight the importance of theory-grounded discovery, but do not address catastrophic cancellation near asymptotic limits or provide formal identifiability gating. While dimensional analysis and symmetry constraints have been integrated into SR and dynamical learning Tenachi et al. [2023], Petersen et al. [2021], Otto et al. [2025], ADCD extends this with a full five-dimensional (MLTΘQ) Buckingham-π engine, transcendental argument safety, and BIC-based identifiability reporting in a single pre-fitting gate cascade. By combining deterministic grammar enumeration, algebraic classical-limit enforcement, phenomenon-specific functional priors, and explicit identifiability gating, ADCD provides a principled, falsifiable workflow tailored to the correction-first paradigm.

3 Methods

3.1 Problem formulation

Let y_{obs} and y_{cl} be the observed target and classical prediction. The correction residual is:

$$\Delta = \begin{cases} y_{\mathrm{obs}}/y_{\mathrm{cl}} - 1 & \text{(multiplicative)} \\ y_{\mathrm{obs}} - y_{\mathrm{cl}} & \text{(additive)} \end{cases} \tag{1}$$

ADCD measures the correction either as a difference ($y_{\mathrm{obs}} - y_{\mathrm{cl}}$, *additive*) or as a relative change ($y_{\mathrm{obs}}/y_{\mathrm{cl}} - 1$, *multiplicative*). It picks the form whose size depends less on the size of the classical prediction, measured by the absolute Spearman rank correlation between $|y_{\mathrm{cl}}|$ and the residual

magnitude (ties go to additive). There is no numeric ambiguity threshold: additive is used by construction when $\mathrm{std}(y_{\mathrm{cl}}) < 10^{-15}$ (a constant baseline), when fewer than 5 valid points remain, or when both correlations vanish. ADCD searches for $\hat{\Delta}(\mathbf{x}; \boldsymbol{\theta})$ such that $\hat{\Delta} \to 0$ as the relevant dimensionless ratio $u \to 0$.

3.2 Algebraically regularized primitive dictionary

Each primitive $D(u)$ satisfies $\lim_{u\to 0} D(u) = 0$ as an exact algebraic identity by construction, while rationalizing subtraction-prone forms against catastrophic cancellation. The reason is numerical: subtracting two nearly equal numbers wipes out significant digits, so a correction that should be tiny but nonzero can round to exactly zero. For example, the naive form $(1-u)^{-1/2} - 1$ collapses to 0.0 at $u = 10^{-16}$ in `float64`; the rationalized form $u/[\sqrt{1-u}(\sqrt{1-u}+1)]$ returns 5.0×10^{-17} at the same input. Table 1 lists all eight primitives.

Table 1: The eight algebraically regularized primitives, each satisfying $\lim_{u\to 0} D(u) = 0$ as an exact algebraic identity. The first five are the core physics-motivated basis; the remaining three extend coverage to oscillatory, saturation, and power-law regimes. Column "Physical origin" cites the fundamental equation that produces this functional family; it does not imply the primitive is restricted to that domain.

Name	Regularized form $D(u)$	Domain	Physical origin
`D_lor`	$u/[\sqrt{1-u}(\sqrt{1-u}+1)]$	$u \in [0, 1)$	Lorentz factor $(\gamma - 1)$
`D_rat`	$u/(1-u)$	$u \neq 1$	Yukawa/Fermi pole
`D_exp`	$e^{-u} - 1$	all u	Debye/Yukawa screening
`D_log`	$\ln(1+u)$	$u > -1$	Entropy of mixing
`D_sqrt_inv`	$1/\sqrt{1+u} - 1$	$u > -1$	Gravitational / Coulomb potential
`D_pow`	$\lvert u\rvert^{\lvert\theta\rvert}$	$u \geq 0$	Power-law corrections
`D_osc`	$1 - \cos u$	all u	Wave / AC oscillatory
`D_sat`	$\tanh u$	all u	Magnetic / sigmoid saturation

3.3 Dimensional grouping and free-scale generation

ADCD tracks the physical dimensions of every variable as a vector of integer exponents over mass (M), length (L), time (T), temperature (Θ), and electric charge (Q) (note: uppercase Θ denotes temperature dimension, distinct from lowercase model parameters θ_k). Instead of solving the full dimensional-analysis problem, it uses a simple two-step heuristic: first, it groups variables with identical dimensions into pairwise ratios (e.g., q_1/q_2); second, it divides each dimensional variable by a free scale parameter, linearly or quadratically (v/θ_{2k}, v^2/θ_{2k+1}; e.g., r/θ_4). Charge is tracked separately so that two charges can form a dimensionless ratio; a three-dimensional (MLT) engine would treat them as dimensionless scalars and skip this step. In Screened Coulomb, four charge-related candidates are enumerated first, so the distance ratio receives the index θ_4. The index only reflects enumeration order; what matters is that the fitted value lands near the true Debye length.

3.4 Phenomenon-specific taxonomy as Bayesian prior

Each physics phenomenon maps to a named set of permitted primitive families derived exclusively from its fundamental equations. For example, `yukawa_debye_screening` permits only `D_exp` and `D_rat`: the Klein-Gordon equation yields $V \propto e^{-mr}/r$ and Debye-Hückel theory yields $\phi \propto e^{-r/\lambda_D}/r$; both involve only exponential and rational families. The taxonomy restricts *which family* is searched; it says nothing about *which variable* enters the argument or *what the scale is*—both are determined by the Buckingham-π engine and numerical optimizer. Allowing a function family that the physics does not justify gives the search an extra flexible function that can soak up noise, which shrinks the ablation $\Delta\mathrm{BIC}$ gap and weakens identifiability. Table 2 lists entries for our three experiments.

A 3×3 cross-misspecification audit (Appendix A.3, Table 9) tests what happens when the wrong taxonomy is supplied. In all 6 wrong-taxonomy trials the system returned WITHHELD, so there were no false IDENTIFIABLE verdicts (4 of the 6 are informative, since the 2 Time Dilation trials

are WITHHELD even under the correct prior; e.g., applying the oscillatory `wave_resonance` prior to Screened Coulomb yields WITHHELD with $\Delta\text{BIC} = -910.5$).[1] In these tests, a wrong prior led to abstention rather than an invented law.

Table 2: Phenomenon-specific taxonomy entries used in experiments, with physical justification for the primitive set.

Phenomenon key	Primitives	Justification
`yukawa_debye_screening`	`D_exp`, `D_rat`	Klein-Gordon / Debye-Hückel: fundamental form is e^{-mr}/r.
`lorentz_special_relativity`	`D_lor`	Lorentz invariance of Maxwell equations uniquely selects the $\gamma - 1$ form.
`boltzmann_thermodynamics`	`D_exp`, `D_log`	Boltzmann partition function and entropy of mixing involve $e^{-\beta\epsilon}$ and $\ln$.

3.5 Grammar enumeration and theta-intact constraint

Candidates take the form $\hat{\Delta} = \theta_0 \cdot D_i(u_{ij})$, optionally extended with a secondary additive or multiplicative-coupled term ($\theta_0 D_a(u) + \theta_1 D_b(u)$ or $\theta_0 D_a(u)[1 + \theta_1 D_b(u)]$; depth ≤ 3, ≤ 25 tokens). Dimensionless arguments are auto-generated by the Buckingham-π engine (up to 12 candidate ratios per scenario). Gates 1–3 (Table 3) inspect the symbolic *theta-intact* expression (where parameters θ_k remain symbolic without premature numerical substitution), treating single-variable free-scale ratios (e.g., r/θ_4 representing a Debye length) as dimensionally admissible because θ_k absorbs the variable's physical scale during fitting. Gate 4 (Asymptotic Regularization Check, ARC) evaluates the symbolic classical limit at $\boldsymbol{\theta} = \mathbf{1}$ (deferring parametric candidates for strict post-fit re-verification at $\hat{\boldsymbol{\theta}}$), and Gate 5 screens coarse numerical fitness at $\boldsymbol{\theta} = \mathbf{1}$.

3.6 Physical gate cascade

Before fitting, each candidate must pass a five-gate cascade (Table 3) applied to the theta-intact expression.

Table 3: The five-gate pre-fitting physical cascade.

Gate	Rejection criterion
1. AST complexity	SymPy tree depth > 12 or token count > 50.
2. Dimensional consistency	Physical dimensions mismatch target (allowing free-scale v/θ_k).
3. Transcendental safety	Arguments to $\exp$, $\ln$, $\sqrt{\cdot}$ not dimensionless or θ_k-scaled.
4. Asymptotic check (ARC)	Classical limit at $\boldsymbol{\theta} = \mathbf{1}$ (and post-fit $\hat{\boldsymbol{\theta}}$) does not vanish.
5. Coarse numerical fitness	Evaluation at $\boldsymbol{\theta} = \mathbf{1}$ produces `NaN/Inf`.

3.7 Parameter optimization and model selection

The top-ranked Stage-1 surviving candidates ($K = 30$, shortlisted by coarse pre-fitting evaluation) are optimized via L-BFGS-B (JAX, `float64`). Parameters are log-reparameterized ($\theta_i = s_i e^{u_i}$, $s_i \in \{-1, +1\}$) for order-of-magnitude traversal; multiple restarts reduce sensitivity to local optima. Model selection uses an Extended BIC Schwarz [1978], Chen and Chen [2008]: $\text{BIC} = k \ln N - 2 \ln \hat{L} + 2 \ln |\mathcal{C}|$, incorporating a multiple-testing penalty over the search space size $|\mathcal{C}|$. By the Kass–Raftery scale Kass and Raftery [1995], $\Delta\text{BIC} > 10$ is the adopted identifiability threshold.

3.8 Four-step validation protocol

In plain terms. IDENTIFIABLE means the data are informative enough to single out the discovered function family. WITHHELD means they are not, so ADCD makes no structural claim even if it found a good-looking fit. An IDENTIFIABLE verdict requires all four checks to pass:

[1] Full supplementary audit tables are provided in Appendix A and at https://github.com/apiprdt/PhysicsPaper/tree/PythonADCD/rebuttal.




Figure 1: Correction recovery for the three scenarios. *Gray dots*: observed residual Δ at 1% Gaussian noise (relative residual $\Delta S/S_i$ for Entropy Expansion). *Blue solid*: ground truth. *Red dashed* ("ADCD Recovery"): the exact symbolic expression discovered by ADCD, evaluated with fitted parameters $\boldsymbol{\theta}$ (normalized by S_i for Entropy Expansion to match the relative scale); see Table 5 for exact NMSE values. Screened Coulomb (IDENTIFIABLE): exact symbolic match, $\mathrm{NMSE} = 2.77 \times 10^{-4}$. Entropy Expansion (IDENTIFIABLE, 2/5 seeds): class-level match, $\mathrm{NMSE} = 1.59 \times 10^{-2}$. Time Dilation (WITHHELD): Lorentz structure found at Rank 1, $\mathrm{NMSE} = 0.41$; positive control fails within the historical $v \leq 0.3c$ observation window.

1. **Budget disclosure.** Before looking at results, we state how many candidate formulas are searched ($|\mathcal{C}|$) and which function families are allowed, so the size of the search is visible.
2. **Positive control** (can the method recover the right answer at all?). Using only the true function family, the fit must explain at least 95% of the variance in the data ($\mathrm{NMSE} < 0.05$). If even the correct family fails, the data are too noisy to support a claim.
3. **Ablation control** (is the family really needed?). We remove the target family and search over all remaining primitives. We require the domain-guided candidate to beat the best remaining model by $\Delta\mathrm{BIC} = \mathrm{BIC}_{\mathrm{ablated}} - \mathrm{BIC}_{\mathrm{domain}} > 10$ (conventionally "very strong evidence", Kass–Raftery). Because Extended BIC balances data fit, parameter parsimony, and search-space size, a tie in raw data fit can still pass if the domain model is substantially more parsimonious (Table 7).
4. **Determinism.** Three runs with identical inputs must give identical output.

Failure of any check yields WITHHELD (in benchmark audits, Steps 2–3 evaluate against the known synthetic target family; in empirical deployment, Step 3 ablates the discovered candidate's family).

4 Experiments

4.1 Setup

Table 4 summarizes the three scenarios. All use 1% Gaussian multiplicative noise, $N = 200$ points, seed 42. Observation windows reflect historical low-signal regimes. The ground truth is never supplied to the blind discovery search (only noisy observations, classical predictions, dimensional definitions, and the taxonomy key are provided; the target family is referenced only in benchmark controls).

Table 4: Experimental scenarios with domains, historical observation windows, taxonomy keys, targets, and the full domain-guided search space size ($|\mathcal{C}|$).

Scenario	Domain	Window	Taxonomy key	Target	$\lvert\mathcal{C}\rvert$
Time Dilation	Relativity	$v \leq 0.3c$	`lorentz_special_relativity`	`D_lor`	10
Screened Coulomb	Electrostatics	$r \leq 4.0$ m	`yukawa_debye_screening`	`D_exp`	60
Entropy Expansion	Thermodynamics	$dV/V_i \leq 1.0$	`boltzmann_thermodynamics`	`D_log`	40

4.2 Results

Table 5 summarizes the quantitative results. Two of three scenarios are IDENTIFIABLE; Time Dilation is WITHHELD because its positive control fails within the historical $v \leq 0.3c$ observation window.




Figure 2: BIC identifiability comparison. *Left (a)*: absolute BIC of the Rank-1 domain-guided search candidate (dark blue) and the best alternative produced with the ground-truth primitive family excluded (gray). *Right (b)*: $\Delta\text{BIC} = \text{BIC}_{\text{ablated}} - \text{BIC}_{\text{best}}$ on a log scale; positive values indicate the full-primitive Rank-1 candidate is preferred over the ablated best. Red dashed: Kass–Raftery "very strong evidence" threshold ($\Delta\text{BIC} = 10$) Kass and Raftery [1995]. At seed 42 all three scenarios exceed this threshold (across 5 seeds, ΔBIC spans 11.0–263, 5.1–14.7, and 5.5–13.8 for Screened Coulomb, Entropy Expansion, and Time Dilation), yet Time Dilation is WITHHELD because its positive control fails (Step 2, Positive Control, of the four-step protocol; see Table 5): a positive ΔBIC is necessary but not sufficient for an IDENTIFIABLE verdict (for Time Dilation, $\Delta\text{BIC} = 13.79$ is driven by search-space penalty and parsimony, with $\Delta D \approx 0$; Table 7).




Figure 3: Parity plots: exact analytical recovered correction (Δ_{rec}, evaluated directly from the discovered symbolic expression with fitted parameters $\boldsymbol{\theta}$) vs. true correction (Δ_{true}) for $N = 200$ data points. Black dashed: 1:1 reference line. All three scenarios closely track the 1:1 diagonal because the domain-guided search placed the true mathematical structure (exact or class-level match) at Rank-1 in every case. Crucially, Time Dilation achieves structural parity here, yet is still WITHHELD by the system: its high fit error ($\text{NMSE} = 0.41$) on the *noisy* observational data (Figure 1a) causes it to fail the Positive Control, demonstrating ADCD's ability to abstain from claiming discoveries when the signal-to-noise ratio is insufficient.

Reading ΔBIC. BIC scores a model by how well it fits the data, with penalties for extra parameters and for a larger search space. ΔBIC is the score of the best model *without* the true family minus that of the best model *with* it, so larger values favor the domain-guided result and values above 10 are conventionally called very strong evidence. It has three parts (Appendix Table 7): ΔD, the pure difference in fit; $\Delta k \ln N$, the reward for using fewer parameters; and a penalty for searching a larger space.[2] Reporting all three shows what drives each verdict.

Screened Coulomb. Recovered $\theta_0(e^{-r/\theta_4} - 1)$ is an exact symbolic match to the ground truth $\theta_0(e^{-r/\lambda_D} - 1)$, with $\theta_4 \approx 1.49$ m recovering the Debye length $\lambda_D = 1.50$ m. The engine selected the distance ratio r/θ_4 on its own (the index reflects enumeration order, as in Section 3.3). $\Delta\text{BIC} = 30.65$ far exceeds the threshold of 10, and $\Delta D = 20.14$ shows the advantage comes from

[2] ΔBIC includes a search-space penalty $2 \ln |\mathcal{C}|$ that differs between domain-guided and ablated runs; ΔD reports the penalty-free fit-quality difference. Here $|\mathcal{C}_{\text{ablated}}| = 814/534/700$ for Screened Coulomb, Entropy Expansion, and Time Dilation, versus $|\mathcal{C}_{\text{domain}}| = 60/40/10$. Screened Coulomb's $\Delta D = 20.14$ alone exceeds the Kass–Raftery threshold of 10. Entropy Expansion's identifiability is parsimony-driven ($\Delta D = -1.08$; the ablated model achieves an equivalent fit with more parameters), as reported in Table 5.

Table 5: Four-step validation results for all three scenarios. PC = Positive Control (pass/fail). $\Delta\mathrm{BIC} = \mathrm{BIC}_{\mathrm{ablated}} - \mathrm{BIC}_{\mathrm{best}}$, where $\mathrm{BIC}_{\mathrm{best}}$ is the Rank-1 domain-guided search BIC; positive values indicate the full-primitive set is preferred over the ablated set. ΔD: penalty-free fit-quality difference (see footnote). Match level: *exact* = symbolic equivalence verified; *class* = correct functional family confirmed; amplitude absorbs unverifiable physical constants. Seed stability over 5 independent noise realizations: Screened Coulomb 5/5 IDENTIFIABLE; Entropy Expansion 2/5 IDENTIFIABLE (borderline at the Kass–Raftery boundary); Time Dilation 5/5 WITHHELD.

Scenario	Discovered structure	Rank	NMSE	PC	ΔD	ΔBIC	Match	Verdict
Screened Coulomb ($r \leq 4$ m)	$\theta_0(e^{-r/\theta_4} - 1)$	1	2.77×10^{-4}	PASS	20.14	30.65	exact	**IDENTIFIABLE**
Entropy Expansion ($dV/V_i \leq 1$)	$\theta_0 \ln(1 + dV/V_i)$	1	1.59×10^{-2}	PASS	-1.08	14.70	class	**IDENTIFIABLE** (2/5 seeds)
Time Dilation ($v \leq 0.3c$)	$\theta_0 \frac{v^2/c^2}{\sqrt{1-v^2/c^2}(1+\sqrt{1-v^2/c^2})}$	1	0.41	FAIL	-0.00	13.79	class	**WITHHELD**

fit quality, not from the search-space penalty. Over 5 noise seeds the verdict is IDENTIFIABLE every time (5/5); ΔBIC ranges from 11.0 to 263, and the mean of 76.61 is driven by one large value (penalty-free $\overline{\Delta D + \Delta k \ln N} = 71.39$).

Entropy Expansion. Because the classical baseline S_i is constant, the scale-dependence test is uninformative and mode detection falls back to an additive search. Thus, the recovered additive correction $\theta_0 \ln(1 + dV/V_i)$ matches the additive ground truth $nR \ln(1 + dV/V_i)$ at class level: the fitted amplitude $\hat{\theta}_0 \approx 8.30$ J/K absorbs the composite constant $nR = 8.314$ J/K (within 0.2%). ADCD labels this match `class_only`: the functional family $\ln(1 + u)$ is correctly identified, but because n and R are not individually supplied as variables to the search, the composite product nR cannot be decomposed into separate physical factors. $\Delta\mathrm{BIC} = 14.70 > 10$ supports IDENTIFIABLE, but $\Delta D = -1.08$ shows the evidence comes from *simplicity*, not from a better fit: the ablated search matches the fit with k=3 parameters, versus k=1 for the domain-guided model. Over 5 noise seeds the verdict is borderline (2/5 IDENTIFIABLE, $\overline{\Delta\mathrm{BIC}} = 9.91 \pm 3.40$, sample SD), so the logarithmic correction sits at the decision boundary under 1% noise.

Time Dilation. Over $v/c \in [0.10, 0.30]$, the Lorentz correction $\gamma - 1$ peaks at 4.8% with a signal standard deviation of $\mathrm{SD}(\Delta_{\mathrm{true}}) \approx 1.25\%$ against the 1.0% measurement noise. The grammar recovers the Lorentz structure $D_{\mathrm{lor}}(v^2/c^2)$ at Rank 1 ($\hat{\theta}_0 \approx 1.01$), but the positive control fails ($\mathrm{NMSE} = 0.41$). Put simply, even the exact true curve would differ from the noisy data by about 41% of the data's variance ($\mathrm{NMSE} \approx 0.412 > 0.05$), so no method could pass the 5% test in this window; the Positive Control correctly returns WITHHELD. Over 5 noise seeds this verdict is stable (5/5 WITHHELD).

5 Discussion

Why withholding is a useful answer. A method that always returns a formula, whatever the data quality, cannot tell the reader when to trust it. ADCD's WITHHELD verdict on Time Dilation marks the limit of the data: lowering noise ($\sigma \lesssim 0.29\%$) or widening the velocity window ($v \gtrsim 0.5c$ at $\sigma = 1\%$) reduces the noise floor below 0.05, while separating D_{lor} from competing rational/polynomial families on pure fit ($\Delta D > 10$) requires extending into the relativistic regime ($v > 0.3c$).

Taxonomy as prior, not hint. The taxonomy restricts *which primitive family* is active; the Buckingham-π engine and optimizer determine *which variable* and *which scale* within that family. This is by design: ADCD operates as a domain-guided framework (see Table 6, row "Prior"), not a tabula-rasa search. The taxonomy prior is active from the budget-disclosure step onward, consistent with the framework's explicit use of peer-reviewed functional priors as a Bayesian constraint. In Screened Coulomb, the search, not the taxonomy, selected the distance variable and its scale ($\theta_4 \approx 1.49$ m). In the 3×3 misspecification audit, none of the 6 wrong-taxonomy trials produced a false IDENTIFIABLE verdict.

Comparison with general SR. ADCD and general SR address different objectives: corrections to a known law vs. full equation discovery from scratch. The relevant distinction is whether a discovered correction is reliably supported by the data: unconstrained SR targets open-ended discovery, whereas ADCD formally identifies when the data warrant a structural claim versus when they do not. Table 6 summarises the operational regimes.

Principle-guided discovery. Recent perspectives on AI for physics stress that theory building needs compact laws, symmetry, and controlled limits Shalyt et al. [2026]. ADCD follows this spirit: it searches for a small correction anchored to an established baseline and reports how strongly the data support it.

Table 6: Operational comparison: ADCD vs. unconstrained symbolic regression.

Property	ADCD	General SR
Target	Corrections to known laws	Full equations from scratch
Prior	Phenomenon-specific taxonomy	None (tabula rasa)
Dimensional engine	5D MLTΘQ	Varies (often 3D or none)
Classical limit	Algebraic guarantee	Soft loss penalty
Identifiability	Explicit; WITHHELD if insufficient	Absent or post-hoc
Reproducibility	Deterministic (fixed seed/env)	Stochastic by default

5.1 Limitations

Weak-signal convergence. Time Dilation's positive control failure is the intended output when the signal-to-noise ratio is too low. Future work should investigate adaptive restarts and denser initialization grids.

Scope. Current support covers eight primitive families, additive and multiplicative corrections, and synthetic Gaussian noise. Heavier-tailed noise and real observational data (e.g., galactic rotation curves, pulsar timing residuals) remain future work; real data require preprocessing for heteroscedastic uncertainties not yet modelled. Validation thresholds ($\Delta\mathrm{BIC} > 10$, $\mathrm{NMSE} < 0.05$) were evaluated under $N = 200$ and 1% Gaussian noise; calibrating across broader noise regimes and sample sizes remains future work.

Taxonomy coverage. Each new entry requires a peer-reviewed derivation for every admitted family—a deliberate constraint preventing unchecked hypothesis-space expansion.

Safety–expressivity trade-off. ADCD constrains its hypothesis space relative to general-purpose SR: candidates failing dimensional consistency or outside the phenomenon-specific primitive set are rejected before fitting. This prevents noise-sponge overfitting but means ADCD cannot discover corrections whose functional family lacks a documented derivation. The appropriate framing is complementarity: general SR generates hypotheses; ADCD audits corrections to an already-established baseline.

Seed stability of borderline verdicts. Entropy Expansion's verdict varies across noise realizations (2/5 IDENTIFIABLE, 3/5 WITHHELD), indicating the logarithmic correction sits at the identifiability boundary under 1% noise. We treat this as a limitation of the current noise regime.

6 Conclusion

ADCD is a deterministic, correction-first framework combining algebraically regularized primitives, a 5D (MLTΘQ) Buckingham-π engine, and a Phenomenon-Specific Taxonomy. On three canonical scenarios, two yield IDENTIFIABLE results (Screened Coulomb: $\Delta\mathrm{BIC} = 30.65$, exact match; Entropy Expansion: $\Delta\mathrm{BIC} = 14.70$, class-level, parsimony-driven; 2/5 seeds) and one yields a principled WITHHELD verdict (Time Dilation at $v \leq 0.3c$), where the historical signal is insufficient for a confident structural claim. Within its deliberate scope—known classical baseline, additive or multiplicative correction, Gaussian noise—ADCD provides explicit reproducibility and identifiability diagnostics absent from unconstrained SR, and returns an explicit WITHHELD verdict (with its $\Delta\mathrm{BIC}$) when the data are insufficient.

Acknowledgments and Disclosure of Funding

The author thanks the anonymous NewInML reviewers for constructive feedback that motivated the BIC decomposition, multi-seed stability, and taxonomy misspecification analyses incorporated into this camera-ready version. No external funding was received for this work.

Use of AI-Assisted Tools

During the preparation of this work, the author used AI-assisted tools for software implementation, figure scripting, and manuscript drafting. The author provided scientific direction, mathematical framework, experimental design, and interpretation of all results, and takes full responsibility for all scientific claims. No AI tool is listed as an author. The codebase and raw validation logs are publicly available at https://github.com/apiprdt/PhysicsPaper.

Data Availability

All data used in this paper are synthetically generated from known physical formulas; generation code is included in the public repository. No proprietary or restricted datasets are used.

References

Giuseppe Carleo, Ignacio Cirac, Kyle Cranmer, Laurent Daudet, Maria Schuld, Naftali Tishby, Leslie Vogt-Maranto, and Lenka Zdeborová. Machine learning and the physical sciences. *Reviews of Modern Physics*, 91(4):045002, 2019. doi: 10.1103/RevModPhys.91.045002.

Hanchen Wang, Tianfan Fu, Yuanqi Du, Wenhao Gao, Kexin Huang, Ziming Liu, Payal Chandak, Shengchao Liu, Peter Van Katwyk, Andreea Deac, Anima Anandkumar, Karianne Bergen, Carla P. Gomes, Shirley Ho, Pushmeet Kohli, Joan Lasenby, Jure Leskovec, Tie-Yan Liu, Arjun Manrai, Debora Marks, Bharath Ramsundar, Le Song, Jimeng Sun, Jian Tang, Petar Veličković, Max Welling, Linfeng Zhang, Connor W. Coley, Yoshua Bengio, and Marinka Zitnik. Scientific discovery in the age of artificial intelligence. *Nature*, 620(7972):47–60, 2023. doi: 10.1038/s41586-023-06221-2.

Albert Einstein. Zur Elektrodynamik bewegter Körper. *Annalen der Physik*, 322(10):891–921, 1905. doi: 10.1002/andp.19053221004.

Peter Debye and Erich Hückel. Zur Theorie der Elektrolyte. I. Gefrierpunktserniedrigung und verwandte Erscheinungen. *Physikalische Zeitschrift*, 24:185–206, 1923.

Herbert B. Callen. *Thermodynamics and an Introduction to Thermostatistics*. Wiley, 2nd edition, 1985. ISBN 978-0-471-86256-7.

Miles Cranmer, Alvaro Sanchez-Gonzalez, Peter Battaglia, Rui Xu, Kyle Cranmer, David Spergel, and Shirley Ho. Discovering symbolic models from deep learning with inductive biases. In *Advances in Neural Information Processing Systems*, volume 33, pages 17429–17442, 2020.

Miles Cranmer. Interpretable machine learning for science with PySR and SymbolicRegression.jl. arXiv preprint, 2023. arXiv:2305.01582.

Silviu-Marian Udrescu and Max Tegmark. AI Feynman: A physics-inspired method for symbolic regression. *Science Advances*, 6(16):eaay2631, 2020. doi: 10.1126/sciadv.aay2631.

Wassim Tenachi, Rodrigo Ibata, and Foivos I. Diakogiannis. Deep symbolic regression for physics guided by units constraints. *The Astrophysical Journal*, 959(2):99, 2023. doi: 10.3847/1538-4357/ad014c.

IEEE Task P754. IEEE 754-2019: Standard for floating-point arithmetic. Technical report, IEEE, 2019.

Josh Bongard and Hod Lipson. Automated reverse engineering of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 104(24):9943–9948, 2007. doi: 10.1073/pnas.0609476104.

Michael Schmidt and Hod Lipson. Distilling free-form natural laws from experimental data. *Science*, 324(5923):81–85, 2009. doi: 10.1126/science.1165893.

William La Cava, Patryk Orzechowski, Bogdan Burlacu, Fabrício Olivetti de França, Marco Virgolin, Ying Jin, Michael Kommenda, and Jason H. Moore. Contemporary symbolic regression methods and their relative performance. *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, 1, 2021. URL https://arxiv.org/abs/2107.14351.

Lisa Messeri and M. J. Crockett. Artificial intelligence and illusions of understanding in scientific research. *Nature*, 627(8002):49–58, 2024. doi: 10.1038/s41586-024-07146-0.

Mario Krenn, Robert Pollice, Si Yue Guo, Matteo Aldeghi, Alba Cervera-Lierta, Pascal Friederich, Gabriel dos Passos Gomes, Florian Häse, Adrian Jinich, AkshatKumar Nigam, Zhenpeng Yao, and Alán Aspuru-Guzik. On scientific understanding with artificial intelligence. *Nature Reviews Physics*, 4(12):761–769, 2022. doi: 10.1038/s42254-022-00518-3.

Pat Langley, Herbert A. Simon, Gary L. Bradshaw, and Jan M. Zytkow. *Scientific Discovery: Computational Explorations of the Creative Process*. MIT Press, Cambridge, MA, 1987.

Stefan Kramer, Mattia Cerrato, Jannis Brugger, Sašo Džeroski, and Ross D. King. Automated scientific discovery: From equation discovery to autonomous discovery systems. *Machine Learning*, 115:109, 2026. doi: 10.1007/s10994-025-06955-2.

Nour Makke and Sanjay Chawla. Interpretable scientific discovery with symbolic regression: A review. *Artificial Intelligence Review*, 57(1):2, 2024. doi: 10.1007/s10462-023-10622-0.

Georgia Karagiorgi, Gregor Kasieczka, Scott Kravitz, Benjamin Nachman, and David Shih. Machine learning in the search for new fundamental physics. *Nature Reviews Physics*, 4(6):399–412, 2022. doi: 10.1038/s42254-022-00455-1.

Silviu-Marian Udrescu, Andrew Tan, Jiahai Feng, Orisvaldo Neto, Tailin Wu, and Max Tegmark. AI Feynman 2.0: Pareto-optimal equations including auxiliary assumptions. In *Advances in Neural Information Processing Systems*, volume 33, pages 4860–4871, 2020.

Steven L. Brunton, Joshua L. Proctor, and J. Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 113(15):3932–3937, 2016. doi: 10.1073/pnas.1517384113.

Maziar Raissi, Paris Perdikaris, and George E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019. doi: 10.1016/j.jcp.2018.10.045.

George Em Karniadakis, Ioannis G. Kevrekidis, Lu Lu, Paris Perdikaris, Sifan Wang, and Liu Yang. Physics-informed machine learning. *Nature Reviews Physics*, 3:422–440, 2021. doi: 10.1038/s42254-021-00314-5.

Cristina Cornelio, Subhajit Dash, Vernon Austel, Tyler R. Josephson, Joao Goncalves, Kenneth L. Clarkson, Nimrod Megiddo, Bachir El Khadir, and Lior Horesh. Combining data and theory for derivable scientific discovery with AI-Descartes. *Nature Communications*, 14(1):1777, 2023. doi: 10.1038/s41467-023-37236-y.

Ryan Cory-Wright, Cristina Cornelio, Sanjeeb Dash, Bachir El Khadir, and Lior Horesh. Evolving scientific discovery by unifying data and background knowledge with AI Hilbert. *Nature Communications*, 15:5922, 2024. doi: 10.1038/s41467-024-50143-6.

Brenden K. Petersen, Mikel Landajuela Larma, T. Nathan Mundhenk, Claudio P. Santiago, Soo Kyung Kim, and Joanne T. Kim. Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=m5Qsh0kBQG.

Samuel E. Otto, Nicholas Zolman, J. Nathan Kutz, and Steven L. Brunton. A unified framework to enforce, discover, and promote symmetry in machine learning. *Journal of Machine Learning Research*, 26:1–83, 2025.

Gideon Schwarz. Estimating the dimension of a model. *The Annals of Statistics*, 6(2):461–464, 1978. doi: 10.1214/aos/1176344136.

Jiahua Chen and Zehua Chen. Extended bayesian information criteria for model selection with large model spaces. *Biometrika*, 95(3):759–771, 2008.

Robert E. Kass and Adrian E. Raftery. Bayes factors. *Journal of the American Statistical Association*, 90(430):773–795, 1995. doi: 10.1080/01621459.1995.10476572.

Michael Shalyt, Nathan Regev, Marin Soljačić, and Ido Kaminer. Can AI follow in Einstein's footsteps? *arXiv preprint arXiv:2607.27794*, 2026. doi: 10.48550/arXiv.2607.27794.

A Supplementary Empirical Audits

This appendix provides the complete numerical tables for the three empirical audits referenced in the main text: (1) the Extended BIC deviance and penalty decomposition (Section A.1), (2) the five-seed noise realization stability analysis (Section A.2), and (3) the 3×3 phenomenon-taxonomy cross-misspecification safety audit (Section A.3).

A.1 Extended BIC Deviance and Penalty Decomposition

Under the Extended BIC formulation ($\mathrm{BIC} = k \ln N + N \ln \mathrm{NMSE} + 2 \ln |\mathcal{C}|$), the ablation gap $\Delta\mathrm{BIC} = \mathrm{BIC}_{\mathrm{ablated}} - \mathrm{BIC}_{\mathrm{domain}}$ decomposes into pure fit quality ($\Delta D = N \ln(\mathrm{NMSE}_{\mathrm{ablated}}/\mathrm{NMSE}_{\mathrm{domain}})$), parameter parsimony ($\Delta k \ln N$), and search-space multiplicity ($2 \ln(|\mathcal{C}_{\mathrm{ablated}}|/|\mathcal{C}_{\mathrm{domain}}|)$), as reported in Table 7 for $N = 200$ ($\ln 200 \approx 5.30$, seed $= 42$).

Table 7: Exact decomposition of $\Delta\mathrm{BIC}$ into pure data-fit deviance (ΔD), parameter parsimony ($\Delta k \ln N$), and search-space multiplicity penalty ($2 \ln(|\mathcal{C}_{\mathrm{abl}}|/|\mathcal{C}_{\mathrm{dom}}|)$) at $N = 200$, seed $= 42$.

Scenario	$\lvert\mathcal{C}_{\mathrm{dom}}\rvert$	$\lvert\mathcal{C}_{\mathrm{abl}}\rvert$	$k_{\mathrm{dom}} \to k_{\mathrm{abl}}$	ΔPenalty	$\Delta k \ln N$	ΔD	ΔBIC	Primary Driver
Screened Coulomb	60	814	$2 \to 3$	$+5.22$	$+5.30$	$+\mathbf{20.14}$	30.65	Pure fit ($\Delta D > 10$)
Entropy Expansion	40	534	$1 \to 3$	$+5.18$	$+10.60$	-1.08	14.70	Parameter parsimony
Time Dilation	10	700	$1 \to 2$	$+8.50$	$+5.30$	-0.00	13.79	Penalty + parsimony (WITHHELD)

A.2 Five-Seed Noise Realization Stability

To evaluate sensitivity to random measurement fluctuations under 1% Gaussian noise, the complete four-step validation protocol was executed across five independent noise seeds (seed $\in \{0, 42, 99, 256, 512\}$). Table 8 summarizes the per-seed $\Delta\mathrm{BIC}$ trajectory, mean and sample standard deviation (s, ddof $= 1$), penalty-free fit advantage ($\overline{\Delta D + \Delta k \ln N}$), and verdict breakdown.

Table 8: Verdict and $\Delta\mathrm{BIC}$ stability across five independent 1% Gaussian noise realizations (seed $\in \{0, 42, 99, 256, 512\}$). Standard deviations denote unbiased sample standard deviations (s, ddof $= 1$; Screened Coulomb median $\Delta\mathrm{BIC} = 30.65$).

Scenario	Seed 0	Seed 42	Seed 99	Seed 256	Seed 512	$\overline{\Delta\mathrm{BIC}} \pm s$	$\overline{\Delta D + \Delta k \ln N}$	Verdict Breakdown
Screened Coulomb	56.25	30.65	263.16	11.02	21.94	76.61 ± 105.62	$+71.39$	**5/5 IDENTIFIABLE**
Entropy Expansion	9.50	14.70	5.12	9.91	10.34	9.91 ± 3.40	$+4.73$	2/5 IDENT., 3/5 WITHHELD
Time Dilation	8.35	13.79	5.49	8.01	13.73	9.87 ± 3.72	$+1.38$	**5/5 WITHHELD**

A.3 Taxonomy Cross-Misspecification Safety Audit

To verify that the phenomenon-specific taxonomy prior does not induce false discoveries when misspecified, each scenario was evaluated under its true physical taxonomy key and two intentionally mismatched keys that exclude the ground-truth primitive family. As shown in Table 9, all six misspecified trials returned **WITHHELD** (0/6 false discoveries): when the true primitive family is absent from the domain prior, the unrestricted ablation search outperforms the misspecified domain search ($\Delta\mathrm{BIC} \in [-1038.24, -674.62]$ on identifiable scenarios), triggering conservative abstention rather than overfitting.

Table 9: 3×3 taxonomy cross-misspecification safety audit (seed $= 42$). PC Pass tests the scenario's target family ($\mathrm{NMSE}_{\mathrm{PC}} < 0.05$), while $\mathrm{NMSE}_{\mathrm{best}}$ and $\Delta\mathrm{BIC}$ reflect the blind search under the supplied prior.

Scenario	Prior Type	Supplied Taxonomy Key	Permitted Primitives	PC Pass	$\mathrm{NMSE}_{\mathrm{best}}$	ΔBIC	Verdict
Screened Coulomb	Correct	`yukawa_debye_screening`	`D_exp, D_rat`	PASS	2.77×10^{-4}	$+30.65$	**IDENTIFIABLE**
Screened Coulomb	Wrong A	`wave_resonance`	`D_osc, D_rat`	PASS	2.99×10^{-2}	-910.51	WITHHELD (Abl. fail)
Screened Coulomb	Wrong B	`critical_scaling`	`D_pow`	PASS	2.93×10^{-2}	-903.76	WITHHELD (Abl. fail)
Entropy Expansion	Correct	`boltzmann_thermodynamics`	`D_exp, D_log`	PASS	1.59×10^{-2}	$+14.70$	**IDENTIFIABLE**
Entropy Expansion	Wrong A	`lorentz_special_relativity`	`D_lor`	PASS	3.13×10^{0}	-1038.24	WITHHELD (Abl. fail)
Entropy Expansion	Wrong B	`wave_resonance`	`D_osc, D_rat`	PASS	4.87×10^{-1}	-674.62	WITHHELD (Abl. fail)
Time Dilation	Correct	`lorentz_special_relativity`	`D_lor`	FAIL	4.12×10^{-1}	$+13.79$	WITHHELD (PC fail)
Time Dilation	Wrong A	`boltzmann_thermodynamics`	`D_exp, D_log`	FAIL	4.13×10^{-1}	$+9.96$	WITHHELD (PC fail)
Time Dilation	Wrong B	`yukawa_debye_screening`	`D_exp, D_rat`	FAIL	4.12×10^{-1}	$+10.53$	WITHHELD (PC fail)