Asymptotic Dictionary Correction Discovery: A Deterministic, Identifiability-Aware Framework for Recovering Physical Corrections from Observational Data

Muhammad Afif Erdita
Independent Researcher
Indonesia
maeapip10@gmail.com

Abstract

We present **ADCD** (Asymptotic Dictionary Correction Discovery), a deterministic framework for recovering structured corrections to known physical laws from noisy data. Given a classical baseline, ADCD searches for the residual correction that vanishes exactly at the classical limit, using three interlocking mechanisms: algebraically regularized primitives that enforce asymptotic vanishing as an exact algebraic identity; a five-dimensional (MLTΘQ) Buckingham-π engine that auto-derives dimensionless ratio arguments without manual specification; and a Phenomenon-Specific Taxonomy encoding peer-reviewed functional priors for each physics domain. A four-step validation protocol—budget disclosure, positive control, BIC-based ablation control, and determinism check—issues one of two verdicts: IDENTIFIABLE or WITHHELD. On three canonical scenarios at historical low-signal windows, Screened Coulomb ($\Delta\mathrm{BIC} = 30.65$, exact symbolic match) and Entropy Expansion ($\Delta\mathrm{BIC} = 14.70$, class-level match; borderline across noise seeds) are IDENTIFIABLE; Time Dilation at $v \leq 0.3c$ is WITHHELD because the 4.8% correction is indistinguishable from 1% noise—the intended, epistemically honest behavior. All results are byte-exact deterministic.

Keywords: symbolic regression; correction discovery; dimensional analysis; Bayesian prior; model selection; identifiability

1 Introduction

In the expanding landscape of machine learning for the physical sciences Carleo et al. [2019], Wang et al. [2023], physical laws frequently take a correction-first form: a known classical baseline extended by a term that vanishes at the classical limit Einstein [1905], Debye and Hückel [1923], Callen [1985]. Recovering that correction from observational data is distinct from full equation discovery: the baseline is fixed, only the residual must be identified, and that residual must vanish exactly where classical physics holds.

General-purpose symbolic regression (SR) engines such as PySR Cranmer et al. [2020], Cranmer [2023], AI Feynman Udrescu and Tegmark [2020], and PhySO Tenachi et al. [2023] excel at equation discovery from scratch but face three difficulties in the correction-first setting: (i) *catastrophic cancellation*: floating-point precision collapses as $u \to 0$, corrupting optimizer feedback IEEE Task P754 [2019]; (ii) *stochastic irreproducibility*: evolutionary search cannot guarantee byte-identical results across runs Bongard and Lipson [2007], Schmidt and Lipson [2009]; and (iii) *silent overclaiming*: a single best-fit equation is returned regardless of whether the data carry sufficient power to distinguish competing structures La Cava et al. [2021], generating what recent meta-science critiques identify

NewInML Workshop at the 40th Conference on Neural Information Processing Systems (NeurIPS 2026), Paris, France, 2026.

as an illusion of understanding Messeri and Crockett [2024], Krenn et al. [2022]. ADCD addresses each failure mode in turn: algebraically regularized primitives eliminate cancellation; deterministic grammar enumeration ensures reproducibility; explicit BIC-based identifiability gating prevents overclaiming.

2 Related Work

Automated scientific discovery traces back to pioneering heuristic systems such as BACON Langley et al. [1987] and has evolved toward modern autonomous equation discovery Kramer et al. [2026], Makke and Chawla [2024], Karagiorgi et al. [2022]. General SR engines (Eureqa Schmidt and Lipson [2009], PySR Cranmer et al. [2020], Cranmer [2023], AI Feynman Udrescu and Tegmark [2020], Udrescu et al. [2020], PhySO Tenachi et al. [2023]) target unconstrained equation recovery and do not enforce classical-limit constraints algebraically. SINDy Brunton et al. [2016] shares our library-based approach but discovers governing equations rather than corrections. PINNs Raissi et al. [2019], Karniadakis et al. [2021] embed physical laws as soft loss penalties; ADCD imposes them as hard algebraic identities before any numerical computation. Recent systems combining data with background knowledge and axiomatic reasoning, such as AI-Descartes Cornelio et al. [2023] and AI Hilbert Cory-Wright et al. [2024], highlight the importance of theory-grounded discovery, but do not address catastrophic cancellation near asymptotic limits or provide formal identifiability gating. While dimensional analysis and symmetry constraints have been integrated into SR and dynamical learning Tenachi et al. [2023], Petersen et al. [2021], Otto et al. [2025], ADCD extends this with a full five-dimensional (MLTΘQ) Buckingham-π engine, transcendental argument safety, and BIC-based identifiability reporting in a single pre-fitting gate cascade. To our knowledge, ADCD is the first framework to combine deterministic grammar enumeration, algebraic classical-limit enforcement, phenomenon-specific Bayesian priors, and explicit identifiability gating for the correction-first paradigm.

3 Methods

3.1 Problem formulation

Let y_{obs} and y_{cl} be the observed target and classical prediction. The correction residual is:

$$\Delta = \begin{cases} y_{\mathrm{obs}}/y_{\mathrm{cl}} - 1 & \text{(multiplicative)} \\ y_{\mathrm{obs}} - y_{\mathrm{cl}} & \text{(additive)} \end{cases} \tag{1}$$

The mode with the lower scale dependence is selected, measured as the absolute Spearman correlation between $|y_{\mathrm{cl}}|$ and the residual magnitude (ties go to additive). There is no numeric ambiguity threshold: additive is used by construction when $\mathrm{std}(y_{\mathrm{cl}}) < 10^{-15}$, when fewer than 5 valid points remain, or when both correlations vanish. ADCD searches for $\hat{\Delta}(\mathbf{x}; \boldsymbol{\theta})$ such that $\hat{\Delta} \to 0$ as the relevant dimensionless ratio $u \to 0$.

3.2 Algebraically regularized primitive dictionary

Each primitive $D(u)$ is zero-anchored ($\lim_{u\to 0} D(u) = 0$ as an exact algebraic identity), while the rational/radical primitives (`D_lor`, `D_rat`) also rationalize the numerator to prevent catastrophic cancellation. For example, the naive form $(1-u)^{-1/2} - 1$ collapses to 0.0 at $u = 10^{-16}$ in `float64`; the regularized form $u/[\sqrt{1-u}(\sqrt{1-u}+1)]$ returns 5.0×10^{-17} at the same input. Table 1 lists all eight primitives.

3.3 Dimensional grouping and free-scale generation

ADCD employs a 5D (MLTΘQ) dimensional engine representing each variable as $\mathbf{d} \in \mathbb{Z}^5$ over the SI base dimensions M, L, T, Θ, and Q. Rather than computing the full rational nullspace, dimensionless arguments are generated via a two-pass domain heuristic: first, it groups physical variables with identical dimensions into pairwise ratios (e.g., q_1/q_2); second, each dimensional variable is normalized by linear and quadratic free-scale parameters ($v/\theta_{2k}, v^2/\theta_{2k+1}$; e.g., r/θ_4). Extending from the conventional 3D MLT to 5D is essential for correctness: in a 3D engine charges

Table 1: The eight algebraically regularized primitives, each satisfying $\lim_{u\to 0} D(u) = 0$ as an exact algebraic identity. The first five are the core physics-motivated basis; the remaining three extend coverage to oscillatory, saturation, and power-law regimes. Column "Physical origin" cites the fundamental equation that produces this functional family; it does not imply the primitive is restricted to that domain.

Name	Regularized form $D(u)$	Domain	Physical origin
`D_lor`	$u/[\sqrt{1-u}(\sqrt{1-u}+1)]$	$u \in [0, 1)$	Lorentz factor $(\gamma - 1)$
`D_rat`	$u/(1-u)$	$u \neq 1$	Yukawa/Fermi pole
`D_exp`	$e^{-u} - 1$	all u	Debye/Yukawa screening
`D_log`	$\ln(1+u)$	$u > -1$	Entropy of mixing
`D_sqrt_inv`	$1/\sqrt{1+u} - 1$	$u > -1$	Gravitational / Coulomb potential
`D_pow`	$\lvert u\rvert^{\lvert\theta\rvert}$ (probe $u^{3/2}$)	$u \geq 0$	Power-law corrections
`D_osc`	$1 - \cos u$	all u	Wave / AC oscillatory
`D_sat`	$\tanh u$	all u	Magnetic / sigmoid saturation

q_1, q_2 are dimensionless scalars and incorrectly bypass the ratio generation; in the 5D engine, charge carries genuine Charge dimension (Q), ensuring q_1, q_2 form pairwise ratios in Pass 1 and consume four free-scale parameters (θ_0–θ_3) in Pass 2 before distances are indexed. Because four charge-dimensional candidates are enumerated first, that ratio receives subscript θ_4, not θ_0. This subscript is machine-verifiable evidence of automated discovery: a manually supplied ratio would be pinned to θ_0 by convention, not assigned by enumeration.

3.4 Phenomenon-specific taxonomy as Bayesian prior

Each physics phenomenon maps to a named set of permitted primitive families derived exclusively from its fundamental equations. For example, `yukawa_debye_screening` permits only `D_exp` and `D_rat`: the Klein-Gordon equation yields $V \propto e^{-mr}/r$ and Debye-Hückel theory yields $\phi \propto e^{-r/\lambda_D}/r$; both involve only exponential and rational families. The taxonomy restricts *which family* is searched; it says nothing about *which variable* enters the argument or *what the scale is*—both are determined by the Buckingham-π engine and numerical optimizer. Including a physically unjustified primitive acts as a noise sponge, collapsing the Ablation Control BIC gap and destroying identifiability. Table 2 lists entries for our three experiments.

A 3×3 cross-misspecification audit (Appendix, Table R3) confirms the taxonomy is *safe against misspecification*: in all 6 wrong-taxonomy trials the system returned WITHHELD (0% false discovery rate; 4 of the 6 are informative, since the 2 Time Dilation trials are WITHHELD even under the correct prior; e.g., applying the oscillatory `wave_resonance` prior to Screened Coulomb yields WITHHELD with $\Delta\text{BIC} = -910.5$).[1] An incorrect prior causes conservative abstention, not hallucinated laws.

Table 2: Phenomenon-specific taxonomy entries used in experiments, with physical justification for the primitive set.

Phenomenon key	Primitives	Justification
`yukawa_debye_screening`	`D_exp`, `D_rat`	Klein-Gordon / Debye-Hückel: fundamental form is e^{-mr}/r.
`lorentz_special_relativity`	`D_lor`	Lorentz invariance of Maxwell equations uniquely selects the $\gamma - 1$ form.
`boltzmann_thermodynamics`	`D_exp`, `D_log`	Boltzmann partition function and entropy of mixing involve $e^{-\beta\epsilon}$ and ln.

3.5 Grammar enumeration and theta-intact constraint

Candidates take the form $\hat{\Delta} = \theta_0 \cdot D_i(u_{ij})$, optionally extended with a secondary additive or multiplicative-coupled term ($\theta_0 D_a(u) + \theta_1 D_b(u)$ or $\theta_0 D_a(u)[1 + \theta_1 D_b(u)]$; depth ≤ 3, ≤ 25 tokens). Dimensionless arguments are auto-generated by the Buckingham-π engine (up to 12

[1] Full rebuttal tables are available at https://github.com/apiprdt/PhysicsPaper/tree/PythonADCD/rebuttal.

candidate ratios per scenario). All gates (Table 3) are evaluated on the *theta-intact* expression—the fully parameterized symbolic form before any θ_i is assigned the value 1—because early substitution collapses dimensionful scale parameters (e.g., r/θ_4 representing a Debye length) to dimensionless constants, falsifying the dimensional consistency check (single-variable free-scale ratios v/θ_k pass Gate 2 via explicit θ-scaling relaxation, and parameterized candidates defer final ARC verification to post-fit $\hat{\boldsymbol{\theta}}$).

3.6 Physical gate cascade

Before fitting, each candidate must pass a five-gate cascade (Table 3) applied to the theta-intact expression.

Table 3: The five-gate pre-fitting physical cascade.

Gate	Rejection criterion
1. AST complexity	SymPy tree depth > 12 or token count > 50.
2. Dimensional consistency	SI base dimensions of the expression do not match the target.
3. Transcendental safety	Arguments to $\exp$, $\ln$, $\sqrt{\cdot}$ are not dimensionless.
4. Asymptotic check (ARC)	Symbolic limit at the classical boundary does not vanish.
5. Coarse numerical fitness	Evaluation at $\boldsymbol{\theta} = \mathbf{1}$ produces `NaN/Inf`.

3.7 Parameter optimization and model selection

The top-30 Stage-1 surviving candidates (ranked at probe $\boldsymbol{\theta} = \mathbf{1}$) are optimized via L-BFGS-B (JAX, `float64`). Parameters are log-reparameterized ($\theta_i{=}s_i e^{u_i}$, $s_i{\in}\{-1,+1\}$) for order-of-magnitude traversal; multiple restarts reduce sensitivity to local optima. Model selection uses an Extended BIC Schwarz [1978], Chen and Chen [2008]: $\mathrm{BIC} = k\ln N - 2\ln\hat{L} + 2\ln|\mathcal{C}|$, incorporating a multiple-testing penalty over the search space size $|\mathcal{C}|$. By the Kass–Raftery scale Kass and Raftery [1995], $\Delta\mathrm{BIC} > 10$ is the adopted identifiability threshold.

3.8 Four-step validation protocol

The pipeline issues an IDENTIFIABLE verdict only when all four checks pass:

1. **Budget disclosure.** The complete size of the domain-guided search space $|\mathcal{C}|$ and the primitive list are reported before any results are seen.
2. **Positive control.** Restricted to the ground-truth primitive family alone, the system must recover the correct structure (NMSE < 0.05; i.e., less than 5% unexplained variance).
3. **Ablation control.** With the ground-truth family excluded from an otherwise unrestricted search over the full eight-primitive registry, the BIC gap $\Delta\mathrm{BIC} > 10$ (Kass–Raftery "very strong evidence") must hold between the domain-guided Rank-1 candidate from the blind search and the best Rank-1 candidate found under ablation (on synthetic benchmarks, the evaluation harness isolates/ablates the ground-truth family directly; on unlabelled data, ablation removes the Rank-1 family found in Step 1).
4. **Determinism.** Three independent runs with identical inputs produce byte-exact identical results.

Failure of any check yields WITHHELD.

4 Experiments

4.1 Setup

Table 4 summarizes the three scenarios. All use 1% Gaussian multiplicative noise, $N = 200$ points, seed 42. Observation windows reflect historical low-signal regimes. The ground truth is never supplied to the pipeline; only noisy observations, classical predictions, dimensional variable definitions, and the taxonomy key are provided.

Table 4: Experimental scenarios with domains, historical observation windows, taxonomy keys, targets, and the full domain-guided search space size ($|\mathcal{C}|$).

Scenario	Domain	Window	Taxonomy key	Target	$\lvert\mathcal{C}\rvert$
Time Dilation	Relativity	$v \leq 0.3c$	`lorentz_special_relativity`	`D_lor`	10
Screened Coulomb	Electrostatics	$r \leq 4.0$ m	`yukawa_debye_screening`	`D_exp`	60
Entropy Expansion	Thermodynamics	$dV/V_i \leq 1.0$	`boltzmann_thermodynamics`	`D_log`	40




Figure 1: Correction recovery for the three scenarios. *Gray dots*: observed residual Δ at 1% Gaussian noise. *Blue solid*: ground truth. *Red dashed* ("ADCD Recovery"): the exact symbolic expression discovered by ADCD, evaluated with the fitted parameters $\boldsymbol{\theta}$; see Table 5 for exact NMSE values. Screened Coulomb (IDENTIFIABLE): exact symbolic match, $\mathrm{NMSE} = 2.77 \times 10^{-4}$. Entropy Expansion (IDENTIFIABLE): class-level match, $\mathrm{NMSE} = 1.59 \times 10^{-2}$. Time Dilation (WITHHELD): Lorentz structure found at Rank 1, $\mathrm{NMSE} = 0.41$; positive control fails within the historical $v \leq 0.3c$ observation window.

4.2 Results

Table 5 summarizes the quantitative results. Two of three scenarios are IDENTIFIABLE; Time Dilation is WITHHELD because its positive control fails within the historical $v \leq 0.3c$ observation window. ΔD, the change in deviance $D = -2 \ln \hat{L} = N \ln \mathrm{NMSE}$ (twice the unpenalized NLL difference), isolates the pure fit-quality advantage from the multiple-testing penalty, addressing a known asymmetry in Extended BIC when $|\mathcal{C}_{\mathrm{domain}}| \neq |\mathcal{C}_{\mathrm{ablated}}|$.[2]

Table 5: Four-step validation results for all three scenarios. PC = Positive Control (pass/fail). $\Delta\mathrm{BIC} = \mathrm{BIC}_{\mathrm{ablated}} - \mathrm{BIC}_{\mathrm{best}}$, where $\mathrm{BIC}_{\mathrm{best}}$ is the Rank-1 domain-guided search BIC; positive values indicate the full-primitive set is preferred over the ablated set. ΔD: penalty-free fit-quality difference (see footnote). Match level: *exact* = symbolic equivalence verified; *class* = correct functional family confirmed; amplitude absorbs unverifiable physical constants. Seed stability over 5 independent noise realizations: Screened Coulomb 5/5 IDENTIFIABLE; Entropy Expansion 2/5 IDENTIFIABLE (borderline at the Kass–Raftery boundary); Time Dilation 5/5 WITHHELD.

Scenario	Discovered structure	Rank	NMSE	PC	ΔD	ΔBIC	Match	Verdict
Screened Coulomb ($r \leq 4$ m)	$\theta_0(e^{-r/\theta_4} - 1)$	1	2.77×10^{-4}	PASS	20.14	30.65	exact	**IDENTIFIABLE**
Entropy Expansion ($dV/V_i \leq 1$)	$\theta_0 \ln(1 + dV/V_i)$	1	1.59×10^{-2}	PASS	-1.08	14.70	class	**IDENTIFIABLE**
Time Dilation ($v \leq 0.3c$)	$\theta_0 \frac{v^2/c^2}{\sqrt{1-v^2/c^2}(1+\sqrt{1-v^2/c^2})}$	1	0.41	FAIL	-0.00	13.79	class	**WITHHELD**

Screened Coulomb. Recovered $\theta_0(e^{-r/\theta_4} - 1)$ is an exact symbolic match to the ground truth $\theta_0(e^{-r/\lambda_D} - 1)$, with $\theta_4 \approx 1.49$ m recovering the Debye length $\lambda_D = 1.50$ m. Subscript 4 (not 0) is machine-verifiable evidence of automated discovery: the engine assigned this subscript by enumerating four charge-dimensional candidates before reaching the distance-ratio r/θ, which was indexed as the fifth candidate (θ_4). A manually supplied ratio would be pinned to subscript 0 by

[2] ΔBIC includes a search-space penalty $2 \ln |\mathcal{C}|$ that differs between domain-guided and ablated runs; ΔD reports the penalty-free fit-quality difference. Here $|\mathcal{C}_{\mathrm{ablated}}| = 814/534/700$ for Screened Coulomb, Entropy Expansion, and Time Dilation, versus $|\mathcal{C}_{\mathrm{domain}}| = 60/40/10$. Screened Coulomb's $\Delta D = 20.14$ alone exceeds the Kass–Raftery threshold of 10. Entropy Expansion's identifiability is parsimony-driven ($\Delta D = -1.08$; the ablated model achieves an equivalent fit with more parameters), a distinction we report transparently.




Figure 2: BIC identifiability comparison. *Left (a)*: absolute BIC of the Rank-1 domain-guided search candidate (dark blue) and the best alternative produced with the ground-truth primitive family excluded (gray). *Right (b)*: $\Delta\text{BIC} = \text{BIC}_{\text{ablated}} - \text{BIC}_{\text{best}}$ on a log scale; positive values indicate the full-primitive Rank-1 candidate is preferred over the ablated best. Red dashed: Kass–Raftery "very strong evidence" threshold ($\Delta\text{BIC} = 10$) Kass and Raftery [1995]. At seed 42 all three scenarios exceed this threshold (across 5 seeds, ΔBIC spans 11.0–263, 5.1–14.7, and 5.5–13.8 for Screened Coulomb, Entropy Expansion, and Time Dilation), yet Time Dilation is WITHHELD because its positive control fails (Step 2, Positive Control, of the four-step protocol; see Table 5): a positive ΔBIC is necessary but not sufficient for an IDENTIFIABLE verdict.




Figure 3: Parity plots: exact analytical recovered correction (Δ_{rec}, evaluated directly from the discovered symbolic expression with fitted parameters $\boldsymbol{\theta}$) vs. true correction (Δ_{true}) for $N = 200$ data points. Black dashed: 1:1 reference line. All three scenarios form perfect or near-perfect diagonals because the domain-guided search successfully placed the true mathematical structure (exact or class-level match) at Rank-1 in every case. Crucially, Time Dilation achieves structural parity here, yet is still WITHHELD by the system: its high fit error ($\text{NMSE} = 0.41$) on the *noisy* observational data (Figure 1a) causes it to fail the Positive Control, demonstrating ADCD's epistemic safety against claiming discoveries from insufficient signal-to-noise ratios.

convention. $\Delta\text{BIC} = 30.65$ far exceeds the threshold of 10; $\Delta D = 20.14$ confirms the advantage is driven by fit quality, not search-space penalty. Over 5 noise seeds, the verdict is 100% stable (5/5 IDENTIFIABLE, $\overline{\Delta\text{BIC}} = 76.61$, penalty-free $\overline{\Delta D + \Delta k \ln N} = 71.39$).

Entropy Expansion. Because the classical baseline S_i is constant, the scale-dependence test is uninformative and mode detection falls back to an additive search. Thus, the recovered additive correction $\theta_0 \ln(1 + dV/V_i)$ matches the additive ground truth $nR \ln(1 + dV/V_i)$ at class level: θ_0 legitimately absorbs the additive amplitude $nR \approx 8.314$, rather than the multiplicative ratio nR/S_i. ADCD labels this `class_only`—explicit epistemic qualification absent from unconstrained SR outputs. $\Delta\text{BIC} = 14.70 > 10$ supports IDENTIFIABLE; however, $\Delta D = -1.08$ reveals the identifiability is *parsimony-driven*: the ablated search achieves an equivalent raw fit with k=3 parameters versus k=1 for the domain-guided model. Over 5 noise seeds, the verdict is borderline (2/5 IDENTIFIABLE, $\overline{\Delta\text{BIC}} = 9.91 \pm 3.40$, sample SD), confirming the logarithmic correction sits at the decision boundary under 1% noise.

Time Dilation. At $v \leq 0.3c$, the Lorentz correction $\gamma - 1 \approx 4.8\%$ of the classical prediction—a signal-to-noise ratio of approximately $4.8 : 1$ against the 1% noise floor, which is insufficient for

reliable isolation. The grammar recovers the Lorentz structure $D_{\mathrm{lor}}(v^2/c^2)$ at Rank 1 ($\hat{\theta}_0 \approx 1.01$), but the positive control fails (NMSE$= 0.41$): over $v \leq 0.3c$ (RMS correction $\approx 1.6\%$ vs. 1% noise), even the exact ground-truth curve has an intrinsic observational noise floor of $\mathrm{NMSE} \approx \sigma^2_{\mathrm{noise}}/\mathrm{Var}(\Delta_{\mathrm{obs}}) \approx 0.41 > 0.05$. Because $> 40\%$ of residual variance is measurement noise, the Positive Control gate correctly triggers WITHHELD. The system outputs WITHHELD. Over 5 noise seeds, this verdict is 100% stable (5/5 WITHHELD).

5 Discussion

WITHHELD is not failure. A system that always returns a structural claim regardless of data sufficiency is epistemically weaker than one that formally distinguishes *found and confirmed* (IDENTIFIABLE) from *data insufficient for a structural claim* (WITHHELD). ADCD's WITHHELD verdict on Time Dilation is the system correctly locating its own identifiability boundary—a boundary that is quantitative and testable: a wider velocity window ($v > 0.3c$) or lower measurement noise ($\sigma < 1\%$) would lower the observational noise floor below 0.05, yielding IDENTIFIABLE.

Taxonomy as prior, not hint. The taxonomy restricts *which primitive family* is active; the Buckingham-π engine and optimizer determine *which variable* and *which scale* within that family. This is by design: ADCD operates as a domain-guided framework (see Table 6, row "Prior"), not a tabula-rasa search. The taxonomy prior is active from the budget-disclosure step onward, consistent with the framework's explicit use of peer-reviewed functional priors as a Bayesian constraint. The Screened Coulomb subscript θ_4 is machine-verifiable evidence that the optimizer found the correct variable independently: subscript indices are assigned sequentially by the Buckingham-π engine, not by any taxonomy entry. A 3×3 misspecification audit confirms the taxonomy is safe: all 6 wrong-taxonomy trials yielded WITHHELD (0% false discovery).

Comparison with general SR. ADCD and general SR address different objectives: corrections to a known law vs. full equation discovery from scratch. The relevant axis is not search-space flexibility but epistemic certainty—the ability to distinguish confirmed from data-insufficient. Table 6 summarises the operational regimes.

Principle-guided discovery vs. black-box prediction. Recent perspectives on AI for physics highlight a crucial epistemic challenge: while modern AI excels at high-dimensional predictive emulation, true physical theory building requires compact mathematical laws, symmetry invariance, and controlled asymptotic regimes Shalyt et al. [2026]. ADCD explicitly embodies this principle-first paradigm: rather than performing unconstrained curve-fitting, it converts physical correction discovery into an exact, dimensionally consistent perturbation search anchored to established baselines and audited by falsifiable identifiability metrics.

Table 6: Operational comparison: ADCD vs. unconstrained symbolic regression.

Property	ADCD	General SR
Target	Corrections to known laws	Full equations from scratch
Prior	Phenomenon-specific taxonomy	None (tabula rasa)
Dimensional engine	5D MLTΘQ	Varies (often 3D or none)
Classical limit	Algebraic guarantee	Soft loss penalty
Identifiability	Explicit; WITHHELD if insufficient	Absent or post-hoc
Reproducibility	Byte-exact deterministic	Stochastic

5.1 Limitations

Weak-signal convergence. Time Dilation's positive control failure is the correct protocol output for an insufficient signal-to-noise ratio, not an algorithmic defect. Future work should investigate adaptive restarts and denser initialization grids.

Scope. Current support covers eight primitive families, additive and multiplicative corrections, and synthetic Gaussian noise. Heavier-tailed noise and real observational data (e.g., galactic rotation

curves, pulsar timing residuals) remain future work; real data require preprocessing for heteroscedastic uncertainties not yet modelled.

Taxonomy coverage. Each new entry requires a peer-reviewed derivation for every admitted family—a deliberate constraint preventing unchecked hypothesis-space expansion.

Safety–expressivity trade-off. ADCD constrains its hypothesis space relative to general-purpose SR: candidates failing dimensional consistency or outside the phenomenon-specific primitive set are rejected before fitting. This prevents noise-sponge overfitting but means ADCD cannot discover corrections whose functional family lacks a documented derivation. The appropriate framing is complementarity: general SR generates hypotheses; ADCD audits corrections to an already-established baseline.

Seed stability of borderline verdicts. Entropy Expansion's verdict varies across noise realizations (2/5 IDENTIFIABLE, 3/5 WITHHELD), indicating the logarithmic correction sits at the identifiability boundary under 1% noise. We report this transparently as a limitation of the current noise regime.

6 Conclusion

ADCD is a deterministic, correction-first framework combining algebraically regularized primitives, a 5D (MLTΘQ) Buckingham-π engine, and a Phenomenon-Specific Taxonomy. On three canonical scenarios, two yield IDENTIFIABLE results (Screened Coulomb: $\Delta\mathrm{BIC} = 30.65$, exact match; Entropy Expansion: $\Delta\mathrm{BIC} = 14.70$, class-level match, borderline at $2/5$ seeds) and one yields a principled WITHHELD verdict (Time Dilation at $v \leq 0.3c$), where the historical signal is insufficient for a confident structural claim. Within its deliberate scope—known classical baseline, multiplicative correction, Gaussian noise—ADCD provides stronger reproducibility and identifiability guarantees than general-purpose SR, and furnishes an explicit WITHHELD verdict (with associated $\Delta\mathrm{BIC}$) when those guarantees cannot be met.

Acknowledgments and Disclosure of Funding

The author thanks the anonymous NewInML reviewers for constructive feedback that motivated the BIC decomposition, multi-seed stability, and taxonomy misspecification analyses incorporated into this camera-ready version. No external funding was received for this work.

Use of AI-Assisted Tools

During the preparation of this work, the author used AI-assisted tools for software implementation, figure scripting, and manuscript drafting. The author provided scientific direction, mathematical framework, experimental design, and interpretation of all results, and takes full responsibility for all scientific claims. No AI tool is listed as an author. The codebase and raw validation logs are publicly available at https://github.com/apiprdt/PhysicsPaper.

Data Availability

All data used in this paper are synthetically generated from known physical formulas; generation code is included in the public repository. No proprietary or restricted datasets are used.

References

Giuseppe Carleo, Ignacio Cirac, Kyle Cranmer, Laurent Daudet, Maria Schuld, Naftali Tishby, Leslie Vogt-Maranto, and Lenka Zdeborová. Machine learning and the physical sciences. *Reviews of Modern Physics*, 91(4):045002, 2019. doi: 10.1103/RevModPhys.91.045002.

Hanchen Wang, Tianfan Fu, Yuanqi Du, Wenhao Gao, Kexin Huang, Ziming Liu, Payal Chandak, Shengchao Liu, Peter Van Katwyk, Andreea Deac, Anima Anandkumar, Karianne Bergen, Carla P. Gomes, Shirley Ho, Pushmeet Kohli, Joan Lasenby, Jure Leskovec, Tie-Yan Liu, Arjun Manrai, Debora Marks, Bharath Ramsundar, Le Song, Jimeng Sun, Jian Tang, Petar Veličković, Max

Welling, Linfeng Zhang, Connor W. Coley, Yoshua Bengio, and Marinka Zitnik. Scientific discovery in the age of artificial intelligence. *Nature*, 620(7972):47–60, 2023. doi: 10.1038/s41586-023-06221-2.

Albert Einstein. Zur Elektrodynamik bewegter Körper. *Annalen der Physik*, 322(10):891–921, 1905. doi: 10.1002/andp.19053221004.

Peter Debye and Erich Hückel. Zur Theorie der Elektrolyte. I. Gefrierpunktserniedrigung und verwandte Erscheinungen. *Physikalische Zeitschrift*, 24:185–206, 1923.

Herbert B. Callen. *Thermodynamics and an Introduction to Thermostatistics*. Wiley, 2nd edition, 1985. ISBN 978-0-471-86256-7.

Miles Cranmer, Alvaro Sanchez-Gonzalez, Peter Battaglia, Rui Xu, Kyle Cranmer, David Spergel, and Shirley Ho. Discovering symbolic models from deep learning with inductive biases. In *Advances in Neural Information Processing Systems*, volume 33, pages 17429–17442, 2020.

Miles Cranmer. Interpretable machine learning for science with PySR and SymbolicRegression.jl. arXiv preprint, 2023. arXiv:2305.01582.

Silviu-Marian Udrescu and Max Tegmark. AI Feynman: A physics-inspired method for symbolic regression. *Science Advances*, 6(16):eaay2631, 2020. doi: 10.1126/sciadv.aay2631.

Wassim Tenachi, Rodrigo Ibata, and Foivos I. Diakogiannis. Deep symbolic regression for physics guided by units constraints. *The Astrophysical Journal*, 959(2):99, 2023. doi: 10.3847/1538-4357/ad014c.

IEEE Task P754. IEEE 754-2019: Standard for floating-point arithmetic. Technical report, IEEE, 2019.

Josh Bongard and Hod Lipson. Automated reverse engineering of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 104(24):9943–9948, 2007. doi: 10.1073/pnas.0609476104.

Michael Schmidt and Hod Lipson. Distilling free-form natural laws from experimental data. *Science*, 324(5923):81–85, 2009. doi: 10.1126/science.1165893.

William La Cava, Patryk Orzechowski, Bogdan Burlacu, Fabrício Olivetti de França, Marco Virgolin, Ying Jin, Michael Kommenda, and Jason H. Moore. Contemporary symbolic regression methods and their relative performance. *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, 1, 2021. URL https://arxiv.org/abs/2107.14351.

Lisa Messeri and M. J. Crockett. Artificial intelligence and illusions of understanding in scientific research. *Nature*, 627(8002):49–58, 2024. doi: 10.1038/s41586-024-07146-0.

Mario Krenn, Robert Pollice, Si Yue Guo, Matteo Aldeghi, Alba Cervera-Lierta, Pascal Friederich, Gabriel dos Passos Gomes, Florian Häse, Adrian Jinich, AkshatKumar Nigam, Zhenpeng Yao, and Alán Aspuru-Guzik. On scientific understanding with artificial intelligence. *Nature Reviews Physics*, 4(12):761–769, 2022. doi: 10.1038/s42254-022-00518-3.

Pat Langley, Herbert A. Simon, Gary L. Bradshaw, and Jan M. Zytkow. *Scientific Discovery: Computational Explorations of the Creative Process*. MIT Press, Cambridge, MA, 1987.

Stefan Kramer, Marco Cerrato, Jannis Brugger, Sašo Džeroski, and Ross D. King. Automated scientific discovery: From equation discovery to autonomous discovery systems. *Machine Learning*, 115:109, 2026. doi: 10.1007/s10994-025-06721-6.

Nour Makke and Sanjay Chawla. A perspective on symbolic machine learning in physical sciences. In *NeurIPS 2024 Workshop on Machine Learning and the Physical Sciences*, 2024.

Georgia Karagiorgi, Gregor Kasieczka, Scott Kravitz, Benjamin Nachman, and David Shih. Machine learning in the search for new fundamental physics. *Nature Reviews Physics*, 4(6):399–412, 2022. doi: 10.1038/s42254-022-00455-1.

Silviu-Marian Udrescu, Andrew Tan, Jiahai Feng, Orisvaldo Neto, Tailin Wu, and Max Tegmark. AI Feynman 2.0: Pareto-optimal equations including auxiliary assumptions. In *Advances in Neural Information Processing Systems*, volume 33, pages 4860–4871, 2020.

Steven L. Brunton, Joshua L. Proctor, and J. Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 113(15):3932–3937, 2016. doi: 10.1073/pnas.1517384113.

Maziar Raissi, Paris Perdikaris, and George E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019. doi: 10.1016/j.jcp.2018.10.045.

George Em Karniadakis, Ioannis G. Kevrekidis, Lu Lu, Paris Perdikaris, Sifan Wang, and Liu Yang. Physics-informed machine learning. *Nature Reviews Physics*, 3:422–440, 2021. doi: 10.1038/s42254-021-00314-5.

Cristina Cornelio, Subhajit Dash, Vernon Austel, Tyler R. Josephson, Joao Goncalves, Kenneth L. Clarkson, Nimrod Megiddo, Bachir El Khadir, and Lior Horesh. Combining data and theory for derivable scientific discovery with AI-Descartes. *Nature Communications*, 14(1):1777, 2023. doi: 10.1038/s41467-023-37236-y.

Ryan Cory-Wright, Cristina Cornelio, Sanjeeb Dash, Bachir El Khadir, and Lior Horesh. Evolving scientific discovery by unifying data and background knowledge with AI Hilbert. *Nature Communications*, 15:5922, 2024. doi: 10.1038/s41467-024-50143-6.

Brenden K. Petersen, Mikel Landajuela Larma, T. Nathan Mundhenk, Claudio P. Santiago, Soo Kyung Kim, and Joanne T. Kim. Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=m5Qsh0kBQG.

Samuel E. Otto, Nicholas Zolman, J. Nathan Kutz, and Steven L. Brunton. A unified framework to enforce, discover, and promote symmetry in machine learning. *Journal of Machine Learning Research*, 26:1–83, 2025.

Gideon Schwarz. Estimating the dimension of a model. *The Annals of Statistics*, 6(2):461–464, 1978. doi: 10.1214/aos/1176344136.

Jiahua Chen and Zehua Chen. Extended bayesian information criteria for model selection with large model spaces. *Biometrika*, 95(3):759–771, 2008.

Robert E. Kass and Adrian E. Raftery. Bayes factors. *Journal of the American Statistical Association*, 90(430):773–795, 1995. doi: 10.1080/01621459.1995.10476572.

Michael Shalyt, Nathan Regev, Marin Soljačić, and Ido Kaminer. Can AI follow in Einstein's footsteps? *arXiv preprint arXiv:2607.27794*, 2026. doi: 10.48550/arXiv.2607.27794.