

Setup Data Sheet

Rod End Bearing

MACHINE : KS-40081				PART NO : 3ABG5-5-2-T		REV : H	PROCESS : 1041 SPHERICAL GRIND		SETUP DATA SHEET REV.		PREPARED	CHECKED	APPROVED						
CYCLE TIME : 48 sec				C/N : C31-00165			PROGRAM NO :		NC										
CATEGORY : Ball Parts				MAT'L TYPE : 440C (AMSS5630/QQ-S-763)			PROGRAM NAME :												
NOTE :																			
REV.	ECN NO.		DATE		DESCRIPTION				REMARK		SAMPLE NO :								
											REASON OF CHANGE :								
TOOLING & GRINDING CONDITION											SPHERICAL GRINDING AREA								
FEED CONDITION				T01	WORK DRIVER		T02	LOADING CHUTE		T03				SUPPORT BLOCK		T04	PLUG(A)		T05
FAST FEED 0.220-0.240 mm 0.005-0.007 mm/s																			
SLOW FEED 0.020-0.040 mm 0.003-0.005 mm/s																			
DRESS CONDITION																			
DRESS INTERVAL 15-30 pcs																			
COMPESATOR				Tooling No : 4664-01-0013		Tooling No : 4664-02-0017		Tooling No : 4664-03-0017		Tooling No : 4664-21-0070		Tooling No : 4664-22-0070							
R. DRESS 0.020-0.030 mm				Maker :		Maker :		Maker :		Maker :		Maker :							
S. DRESS 0.020-0.030 mm				T06		T07		T08		T09		T10							
WORK 0.020-0.030 mm																			
MACHINE CONDITION																			
MAIN DRESS SPEED 20-40 rpm																			
WORK MOTOR 200-700 rpm																			
MAG. CHUCK 4-6 A																			
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :							
				Maker :		Maker :		Maker :		Maker :		Maker :							
				T11		T12		T13		T14		T15							
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :							
				Maker :		Maker :		Maker :		Maker :		Maker :							
				T16		T17		T18		T19		T20							
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :							
				Maker :		Maker :		Maker :		Maker :		Maker :							