

Setup Data Sheet

Rod End Bearing

MACHINE : KS-40081				PART NO : 3ABG5-5-2-T		REV : H		PROCESS : 1041 SPHERICAL GRIND		SETUP DATA SHEET REV.		PREPARED	CHECKED	APPROVED							
CYCLE TIME : 48 sec				C/N : C31-00165				PROGRAM NO :		NC											
CATEGORY : Ball Parts				MAT'L TYPE : 440C (AMSS5630/QQ-S-763)				PROGRAM NAME :													
NOTE :																					
REV.	ECN NO.		DATE		DESCRIPTION						REMARK		SAMPLE NO :								
													REASON OF CHANGE :								
TOOLING & GRINDING CONDITION															SPHERICAL GRINDING AREA						
FEED CONDITION				T01	SUPPORT BLOCK		T02	LOADING CHUTE		T03	PLUG(B)		T04	PLUG(A)				T05	PLUG(B)		
FAST FEED 0.220-0.240 mm 0.005-0.007 mm/s																					
SLOW FEED 0.020-0.040 mm 0.003-0.005 mm/s																					
DRESS CONDITION																					
DRESS INTERVAL 15-30 pcs																					
COMPESATOR				Tooling No : 4664-03-0017		Tooling No : 4664-02-0017		Tooling No : 4664-22-0070		Tooling No : 4664-06-0070		Tooling No : 4664-07-0070									
R. DRESS 0.020-0.030 mm				Maker :		Maker :		Maker :		Maker :		Maker :									
S. DRESS 0.020-0.030 mm				T06	WORK DRIVER		T07	PLUG(A)		T08			T09					T10			
WORK 0.020-0.030 mm																					
MACHINE CONDITION																					
MAIN DRESS SPEED 20-40 rpm																					
WORK MOTOR 200-700 rpm																					
MAG. CHUCK 4-6 A																					
				Tooling No : 4664-01-0013		Tooling No : 4664-21-0070		Tooling No :		Tooling No :		Tooling No :									
				Maker :		Maker :		Maker :		Maker :		Maker :									
				T11			T12			T13			T14					T15			
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :									
				Maker :		Maker :		Maker :		Maker :		Maker :									
				T16			T17			T18			T19			T20					
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :									
				Maker :		Maker :		Maker :		Maker :		Maker :									