

Setup Data Sheet

Rod End Bearing

MACHINE : KS-400B1				PART NO : 3ABG5-5-2-T		REV : H		PROCESS : 1041 SPHERICAL GRIND		SETUP DATA SHEET REV.		PREPARED	CHECKED	APPROVED						
CYCLE TIME : 48 sec				C/N : C31-00165				PROGRAM NO :		NC										
CATEGORY : Ball Parts				MAT'L TYPE : 440C (AMSS5630/QQ-S-763)				PROGRAM NAME :												
NOTE :																				
REV.	ECN NO.			DATE		DESCRIPTION						REMARK		SAMPLE NO :						
														REASON OF CHANGE :						
TOOLING & GRINDING CONDITION														OD GRINDING AREA						
FEED CONDITION				T01	SUPPORT BLOCK		T02	LOADING CHUTE		T03	PLUG(B)		T04			PLUG(A)		T05	PLUG(B)	
FAST FEED 0.220-0.240 mm 0.005-0.007 mm/s																				
SLOW FEED 0.020-0.040 mm 0.003-0.005 mm/s																				
DRESS CONDITION																				
DRESS INTERVAL 15-30 pcs																				
DRESS CONDITION				Tooling No : 4664-03-0017		Tooling No : 4664-02-0017		Tooling No : 4664-22-0070		Tooling No : 4664-06-0070		Tooling No : 4664-07-0070								
R. DRESS 0.020-0.030 mm				Maker :		Maker :		Maker :		Maker :		Maker :								
S. DRESS 0.020-0.030 mm				T06 WORK DRIVER		T07 PLUG(A)		T08		T09		T10								
WORK 0.020-0.030 mm																				
MACHINE CONDITION																				
MAIN DRESS SPEED 20-40 rpm																				
WORK MOTOR 200-700 rpm																				
MAG. CHUCK 4-6 A																				
				Tooling No : 4664-01-0013		Tooling No : 4664-21-0070		Tooling No :		Tooling No :		Tooling No :								
				Maker :		Maker :		Maker :		Maker :		Maker :								
				T11		T12		T13		T14		T15								
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :								
				Maker :		Maker :		Maker :		Maker :		Maker :								
				T16		T17		T18		T19		T20								
				Tooling No :		Tooling No :		Tooling No :		Tooling No :		Tooling No :								
				Maker :		Maker :		Maker :		Maker :		Maker :								