


Setup Data Sheet

Rod End Bearing

MACHINE : TSG-300W			PART NO : 3ABYT3-T		REV : B	PROCESS : 1021 FACE GRIND		SETUP DATA SHEET REV.	PREPARED	CHECKED	APPROVED	
CYCLE TIME : 0 sec			C/N : C35-00488			PROGRAM NO :		NC				
CATEGORY : Ball Parts			MAT'L TYPE : 440C (AMSS5630/QQ-S-763)			PROGRAM NAME :						
NOTE :												
REV.	ECN NO.	DATE	DESCRIPTION					REMARK	SAMPLE NO :			
									REASON OF CHANGE :			
TOOLING & GRINDING CONDITION												
GRIND CONDITION			T01	CARRIER	T02		T03		T04		T05	
CARRIER AUTO SPEED 40-50 rpm												
CUTTING CONDITION												
1st Time : 0.04-0.08 mm (Control Roundness is not more than 0.8 μm)												
2nd Time : 0.02-0.05 mm (Control Roundness is not more than 0.8 μm)			Tooling No : 4556-01-0002 Maker :									
3rd Time : 0.02-0.05 mm (Control Roundness is not more than 0.8 μm)												
4th Time : 0.01 mm (Control Roundness is not more than 0.8 μm)												
5th Time : 0.005 mm (Control Roundness is not more than 0.8 μm)												
			T06		T07		T08		T09		T10	
			Tooling No : Maker :									
			T11		T12		T13		T14		T15	
			Tooling No : Maker :									
			T16		T17		T18		T19		T20	
			Tooling No : Maker :									