Setup Data Sheet

Rod End Bearing

MACHINE : KS-400B1	**PART NO :** 3ABG5-5-2-T	**REV :** H	**PROCESS :** 1041 SPHERICAL GRIND	**SETUP DATA SHEET REV.**	**PREPARED**	**CHECKED**	**APPROVED**
CYCLE TIME : 38 sec	**C/N :** 310165		**PROGRAM NO :** -	NC			
CATEGORY : Ball Parts	**MAT'L TYPE :** 440C		**PROGRAM NAME :** -				
NOTE :							

REV.	ECN NO.	DATE	DESCRIPTION	REMARK

SAMPLE NO :

REASON OF CHANGE :

TOOLING & GRINDING CONDITION

FEED CONDITION				
FAST FEED	0.220-0.240	mm	0.005-0.007	mm/s
SLOW FEED	0.020-0.040	mm	0.003-0.005	mm/s

DRESS CONDITION		
DRESS INTERVAL	15-30	pcs

DRESS CONDITION		
R. DRESS	0.020-0.030	mm
S. DRESS	0.020-0.030	mm
WORK	0.020-0.030	mm

MACHINE CONDITION		
MAIN DRESS SPEED	20-40	rpm
WORK MOTOR	200-700	rpm
MAG. CHUCK	4-6	A

T01 WORK DRIVER	T02 LOADING CHUTE	T03 SUPPORT BLOCK	T04 PLUG A	T05 PLUG B
				
Tooling No : 4664-01-0013	Tooling No : 4664-02-0017	Tooling No : 4664-03-0017	Tooling No : 4664-06-0070	Tooling No : 4664-07-0070
Maker : -	Maker : -	Maker : -	Maker : -	Maker : -
T06	**T07**	**T08**	**T09**	**T10**
Tooling No :	Tooling No :	Tooling No :	Tooling No :	Tooling No :
Maker :	Maker :	Maker :	Maker :	Maker :

SPHERICAL GRINDING AREA

GRINDING WHEEL DETAILS	
WHEEL SPEC	SH80J8V35S
WHEEL SIZE	405.0x32.0x203.2

NMB Minebea Thai Ltd.