

Setup Data Sheet

Rod End Bearing

MACHINE : TSG300W			PART NO : 3ABG5-5-2-T		REV : H	PROCESS : 1021 FACE GRIND		SETUP DATA SHEET REV.		PREPARED	CHECKED	APPROVED
CYCLE TIME :29 sec			C/N : 310165			PROGRAM NO : -		NC				
CATEGORY : Ball Parts			MAT'L TYPE :440C			PROGRAM NAME : -						
NOTE :												
REV.	ECN NO.	DATE	DESCRIPTION					REMARK	SAMPLE NO :			
									REASON OF CHANGE :			
TOOLING & GRINDING CONDITION GRIND CONDITION CARRIER AUTO SPEED 40-50 rpm CUTTING CONDITION 1st Time : 0.04-0.08 mm (Control Roundness is not more than 0.8 μm) 2nd Time : 0.02-0.05 mm (Control Roundness is not more than 0.8 μm) 3rd Time : 0.02-0.05 mm (Control Roundness is not more than 0.8 μm) 4th Time : 0.01 mm (Control Roundness is not more than 0.8 μm) 5th Time : 0.005 mm (Control Roundness is not more than 0.8 μm) T01 CARRIER T02 T03 T04 T05 Tooling No : Tooling No : Tooling No : Tooling No : Tooling No : Maker : Maker : Maker : Maker : Maker : T06 T07 T08 T09 T10 Tooling No : Tooling No : Tooling No : Tooling No : Tooling No : Maker : Maker : Maker : Maker : Maker :												

FACE GRINDING AREA

GRINDING WHEEL DETAILS

POS.

GRINDING WHEEL SPEC

MAKER

UPPER

UPPER WA320K7B51A

mitsui

LOWER

LOWER WA320K7B51A

mitsui