

Setup Data Sheet

Rod End Bearing

MACHINE : KS-400B1				PART NO : 3ABG5-S-2-T		REV : H	PROCESS : 1041 SPHERICAL GRIND		SETUP DATA SHEET REV.	PREPARED	CHECKED	APPROVED
CYCLE TIME :38 sec				C/N : 310165			PROGRAM NO : -		NC			
CATEGORY : Ball Parts				MAT'L TYPE :440C			PROGRAM NAME : -					
NOTE :												
REV.	ECN NO.		DATE	DESCRIPTION					REMARK	SAMPLE NO :		
										REASON OF CHANGE :		
TOOLING & GRINDING CONDITION FEED CONDITION T01 WORK DRIVER T02 LOADING CHUTE T03 SUPPORT BLOCK T04 PLUG A T05 PLUG B FAST FEED 0.220-0.240 mm 0.005-0.007 mm/s SLOW FEED 0.020-0.040 mm 0.003-0.005 mm/s DRESS CONDITION DRESS INTERVAL 15-30 pcs DRESS CONDITION R. DRESS 0.020-0.030 mm S. DRESS 0.020-0.030 mm WORK 0.020-0.030 mm MACHINE CONDITION MAIN DRESS SPEED 20-40 rpm WORK MOTOR 200-700 rpm MAG. CHUCK 4-6 A Tooling No : 4664-01-0013 Maker : - T06 Tooling No : 4664-02-0017 Maker : - T07 Tooling No : 4664-03-0017 Maker : - T08 Tooling No : 4664-06-0070 Maker : - T09 Tooling No : 4664-07-0070 Maker : - T10 SPHERICAL GRINDING AREA GRINDING WHEEL DETAILS WHEEL SPEC SH80J8V35S WHEEL SIZE 405.0x32.0x203.2 NMB Minebea Thai Ltd. NMB- Minebea Thai Ltd.												