

```

1: #include <stdio.h>
2: #include <stdlib.h>
3:
4: //V2.5 using getNumber() and reusable sum()
5: int getInt(char message[]);
6: int sum(int n1, int n2);
7:
8: int num1, num2, result;
9:
10: int main(int argc, char *argv[]) {
11:     printf ("Programma Add2Numbers Vol2\n");
12:     num1 =getInt("Dose 1o akeraio: ");
13:     num2 =getInt("Dose 2o akeraio: ");
14:     // result = num1+num2;
15:     result=sum(num1, num2);
16:     // printf("result=%d",result);
17:     printf ("%d + %d = %d", num1, num2, result);
18:
19:     return 0;
20: }
21:
22: int sum(int n1, int n2) {
23:     int sum;
24:     sum = n1+n2;
25:     return sum;
26: }
27:
28: /////V2.4 using getNumber() and sum()
29: //int getNumber(void);
30: //void sum(void);
31: //
32: //int num1,num2,result;
33: //
34: //
35: //int main(int argc, char *argv[]) {
36: // printf("Program Add2Numbers Version2\n");
37: // num1=getNumber();
38: // num2=getNumber();
39: ///// result = num1+num2;
40: // sum();
41: ///// printf("result=%d",result);
42: // printf("%d + %d = %d",num1,num2,result);
43: // return 0;
44: //}
45: //
46: //void sum(void){
47: // int result;
48: // result = num1+num2;
49: // return result;
50: //}
51:
52: //V2.3 using getNumber() to create an
53: //experssion and pass it as argument to printf
54: //int getNumber(void);
55: //
56: /////int num1,num2;
57: //

```

```

58: //int main(int argc, char *argv[]) {
59: // printf("Program Add2Numbers Version2\n");
60: // printf("sum is %d",getNumber()+getNumber());
61: // return 0;
62: //}
63:
64: //V2.2
65: //int getNumber(void);
66: ////int num1,num2;
67: //
68: //int main(int argc, char *argv[]) {
69: // printf("Program Add2Numbers Version2\n");
70: // num1=getNumber();
71: // num2=getNumber();
72: // printf("%d + %d = %d",num1,num2,num1+num2);
73: // return 0;
74: //}
75:
76: //V2.1 using getNumber() in assignement statement
77: //int getNumber(void);
78: //
79: //int num1,num2,result;
80: //
81: //int main(int argc, char *argv[]) {
82: // printf("Program Add2Numbers Version2\n");
83: // num1=getNumber();
84: // num2=getNumber();
85: // result = num1+num2;
86: //// printf("result=%d",result);
87: // printf("%d + %d = %d",num1,num2,result);
88: // return 0;
89: //}
90:
91:
92: int getInt(char message[]) {
93:     int num;
94:     printf(message);
95:     scanf ("%d", &num);
96:     return num;
97: }

```