


备注(Remarks):

- ER14505采用品牌包装。
- ER14505 packed with "GEBC" logo PVC .
- 热缩横向透明PVC
- The shrink laterally transparent PVC
- 电池表面平整,外观无划痕、不变形、无污点、无漏液
- The surface of battery is smooth, no scratch, no distortion, no discoloration and leakage on the appearance of the cell
- 黑线要求外露130mm、红线外露100mm
- Red wire length(battery to connector) 100mm and black wire length(battery to connector) 130mm
- Pin 1接红线 (Pin 1 with red wire)
- 满足RoHS (RoHS compliant)
- 日期格式 (DATE) : XXXX-XX-XX (Year - Month - Day)

Cell:	ER14505	Date Code:		 GREEN ENERGY Power Solution Expert GREEN ENERGY BATTERY Co.,Ltd	Drawn:	Fen	Version:	A1
Electrical Characteristics	Open Circuit Voltage@RT	3.6V			Checked:		Page:	1-1
	Operating Voltage@RT	3.4V (at 10mA load)			Approved:		Scale:	1:1
	Ampere hour Rating@RT	2.6Ah			Drawn Date:	2014-8-4	Unite:	mm
	Operating Temperature	-55℃-85℃						
	Storage Temperature	20℃-25℃						
				Part No.:	ER14505-1-C-100(130)-24 -Molex 2510-0200			
				File No.:	E-103-016			
Modification Cause:	Original drawing	Revise the length of wires						
	A0	2014.4.9	A1	2014.8.4				