

Classical Control

We will implement and tune a trajectory following controller for a 2-degree of freedom(DoF) robotic arm, and a race car.

Getting Started

We'll be using OpenAI gym, along with PyBullet, to model the robot's environment.

- [OpenAI gym](#) is a toolkit for developing planning and control algorithms. It provides a standard API that abstracts away the model of the robot's environment. It is primarily used for reinforcement learning agents, but can work with any controller, including the PD controllers you'll build in this assignment.
 - If you've never used gym, be sure to read this short [tutorial](#) before getting started.
- [PyBullet](#) is an open-source physics engine that we'll use to model the robot.
- [pybullet-gym](#) is an open-source library that implements a variety of gym environments using PyBullet as the backend. One of these environments is `ReacherPyBulletEnv-v0`, the robotic arm that you'll be working with.

Installation Instructions

Before running this notebook, you'll need to install `gym` and `pybullet-gym`, like so:

```
~ # install gym
~ pip install gym=0.25.2
~ # install pybullet-gym
~ git clone https://github.com/benelot/pybullet-gym.git
~ cd pybullet-gym
~ pip install -e .
```

Overview: 2-DOF robotic arm

Instruction

1. Sometimes on having two pybullet env active, notebook crashes - Both for Q3 and Q6. This can be overcome by closing one before running another.

2. $K_i=0$ for my controller

```
In [1]: conda info --env
```

```
# conda environments:
#
base                /Users/sbhat/miniconda3
cs593                *  /Users/sbhat/miniconda3/envs/cs593
```

Note: you may need to restart the kernel to use updated packages.

```
In [2]: conda list
```

```
# packages in environment at /Users/sbhat/miniconda3/envs/cs593:
#
# Name                                Version                                Build                                Channel
anyio                                  3.5.0                                py39hca03da5_0
appnope                               0.1.2                                py39hca03da5_1001
argon2-cffi                           21.3.0                                pyhd3eb1b0_0
argon2-cffi-bindings                  21.2.0                                py39h1a28f6b_0
asttokens                             2.0.5                                pyhd3eb1b0_0
attrs                                 22.1.0                                py39hca03da5_0
backcall                              0.2.0                                pyhd3eb1b0_0
beautifulsoup4                        4.11.1                                py39hca03da5_0
blas                                  1.0                                  openblas
bleach                                 4.1.0                                pyhd3eb1b0_0
ca-certificates                       2023.01.10                            hca03da5_0
certifi                               2022.12.7                            py39hca03da5_0
cffi                                  1.15.1                               py39h80987f9_3
cloudpickle                           2.2.1                                pypi_0                                pypi
comm                                  0.1.2                                py39hca03da5_0
contourpy                             1.0.7                                pypi_0                                pypi
cyclor                                0.11.0                               pypi_0                                pypi
debugpy                               1.5.1                                py39hc377ac9_0
decorator                             5.1.1                                pyhd3eb1b0_0
defusedxml                            0.7.1                                pyhd3eb1b0_0
entrypoints                           0.4                                  py39hca03da5_0
executing                             0.8.3                                pyhd3eb1b0_0
flit-core                             3.6.0                                pyhd3eb1b0_0
fonttools                             4.38.0                               pypi_0                                pypi
gym                                    0.21.0                               pypi_0                                pypi
icu                                    68.1                                 hc377ac9_0
idna                                   3.4                                  py39hca03da5_0
ipykernel                             6.19.2                               py39h86d0a89_0
ipython                               8.9.0                                py39hca03da5_0
ipython_genutils                      0.2.0                                pyhd3eb1b0_1
jedi                                   0.18.1                               py39hca03da5_1
jinja2                                 3.1.2                                py39hca03da5_0
jsonschema                            4.16.0                               py39hca03da5_0
jupyter_client                        7.4.9                                py39hca03da5_0
jupyter_core                          5.1.1                                py39hca03da5_0
jupyter_server                        1.23.4                               py39hca03da5_0
jupyterlab_pygments                   0.1.2                                py_0
kiwisolver                            1.4.4                                pypi_0                                pypi
libcxx                                14.0.6                               h848a8c0_0
libffi                                 3.4.2                                hca03da5_6
libgfortran                           5.0.0                                11_3_0_hca03da5_28
libgfortran5                          11.3.0                               h009349e_28
libiconv                              1.16                                 h1a28f6b_2
libopenblas                           0.3.21                               h269037a_0
libsodium                             1.0.18                               h1a28f6b_0
libxml2                               2.9.14                               h8c5e841_0
libxslt                               1.1.35                               h9833966_0
llvm-openmp                           14.0.6                               hc6e5704_0
lxml                                  4.9.1                                py39h2fae87d_0
markupsafe                            2.1.1                                py39h1a28f6b_0
matplotlib                            3.6.3                                pypi_0                                pypi
matplotlib-inline                     0.1.6                                py39hca03da5_0
mistune                               0.8.4                                py39h1a28f6b_1000
nb_conda_kernels                      2.3.1                                py39hca03da5_0
nbclassic                             0.4.8                                py39hca03da5_0
nbclient                              0.5.13                               py39hca03da5_0
```

nbconvert	6.5.4	py39hca03da5_0	
nbformat	5.7.0	py39hca03da5_0	
ncurses	6.4	h313beb8_0	
nest-asyncio	1.5.6	py39hca03da5_0	
notebook	6.5.2	py39hca03da5_0	
notebook-shim	0.2.2	py39hca03da5_0	
numpy	1.23.5	py39h1398885_0	
numpy-base	1.23.5	py39h90707a3_0	
openssl	1.1.1t	h1a28f6b_0	
packaging	23.0	pypi_0	pypi
pandocfilters	1.5.0	pyhd3eb1b0_0	
parso	0.8.3	pyhd3eb1b0_0	
pexpect	4.8.0	pyhd3eb1b0_3	
pickleshare	0.7.5	pyhd3eb1b0_1003	
pillow	9.4.0	pypi_0	pypi
pip	22.3.1	py39hca03da5_0	
platformdirs	2.5.2	py39hca03da5_0	
prometheus_client	0.14.1	py39hca03da5_0	
prompt-toolkit	3.0.36	py39hca03da5_0	
psutil	5.9.0	py39h1a28f6b_0	
ptyprocess	0.7.0	pyhd3eb1b0_2	
pure_eval	0.2.2	pyhd3eb1b0_0	
pybullet	3.2.5	pypi_0	pypi
pybulletgym	0.1	dev_0	<develop>
pycparser	2.21	pyhd3eb1b0_0	
pygments	2.11.2	pyhd3eb1b0_0	
yparsing	3.0.9	pypi_0	pypi
pyrsistent	0.18.0	py39h1a28f6b_0	
python	3.9.16	hc0d8a6c_0	
python-dateutil	2.8.2	pyhd3eb1b0_0	
python-fastjsonschema	2.16.2	py39hca03da5_0	
pyzmq	23.2.0	py39hc377ac9_0	
racecar	0.0.1	dev_0	<develop>
readline	8.2	h1a28f6b_0	
send2trash	1.8.0	pyhd3eb1b0_1	
setuptools	65.6.3	py39hca03da5_0	
six	1.16.0	pyhd3eb1b0_1	
sniffio	1.2.0	py39hca03da5_1	
soupsieve	2.3.2.post1	py39hca03da5_0	
sqlite	3.40.1	h7a7dc30_0	
stack_data	0.2.0	pyhd3eb1b0_0	
terminado	0.17.1	py39hca03da5_0	
tinycss2	1.2.1	py39hca03da5_0	
tk	8.6.12	hb8d0fd4_0	
tornado	6.2	py39h1a28f6b_0	
traitlets	5.7.1	py39hca03da5_0	
typing-extensions	4.4.0	py39hca03da5_0	
typing_extensions	4.4.0	py39hca03da5_0	
tzdata	2022g	h04d1e81_0	
wcwidth	0.2.5	pyhd3eb1b0_0	
webencodings	0.5.1	py39hca03da5_1	
websocket-client	0.58.0	py39hca03da5_4	
wheel	0.37.1	pyhd3eb1b0_0	
xz	5.2.10	h80987f9_1	
zeromq	4.3.4	hc377ac9_0	
zlib	1.2.13	h5a0b063_0	

Note: you may need to restart the kernel to use updated packages.

```
In [3]: %cd pybullet-gym
!ls
!pip install -e .

/Users/sbhat/Documents/Purdue/purduePrivate/assignments/a2/pybullet-gym
LICENSE.md      __init__.py      pybulletgym
README.md       arm_traj.png     pybulletgym.egg-info
RaceCar         arm_traj_error.png requirements.txt
RaceCar0G       pd_arm_traj.png  setup.py
Obtaining file:///Users/sbhat/Documents/Purdue/purduePrivate/assignments/a2/pybullet-gym
Preparing metadata (setup.py) ... done
Requirement already satisfied: pybullet>=1.7.8 in /Users/sbhat/miniconda3/envs/cs593/lib/python3.9/site-packages (from pybulletgym==0.1) (3.2.5)
Installing collected packages: pybulletgym
  Attempting uninstall: pybulletgym
    Found existing installation: pybulletgym 0.1
    Uninstalling pybulletgym-0.1:
      Successfully uninstalled pybulletgym-0.1
  Running setup.py develop for pybulletgym
Successfully installed pybulletgym-0.1
```

```
In [1]: # load libraries (if this fails, see "Installation Instructions")
import gym
import numpy as np
import pybulletgym.envs
import matplotlib.pyplot as plt
import pybullet

import math
```

pybullet build time: Feb 14 2023 21:20:29

```
In [2]: ##-- PARAMS --##
pi=np.pi
l1=0.1
l2=0.11
```

```
In [3]: # initialize the environment

# This try-except is to make sure there is only a single pybullet connection
try:
    env.reset()
except NameError:
    env = gym.make("ReacherPyBulletEnv-v0")

env.render(mode="human")
obs = env.reset()
```

```
/Users/sbhat/miniconda3/envs/cs593/lib/python3.9/site-packages/gym/spaces/box.py:73: UserWarning: WARN: Box bound precision lowered by casting to float32
  logger.warn(
```

```
In [7]: pybullet.resetDebugVisualizerCamera(1, 5, -80, np.array([0,0,0]))
```

The robot arm you will be controlling looks like this:



The base of the robot is at the origin; the links l_0 and l_1 are 0.1 and 0.11 units long respectively.

The action space of environment is $[\tau_0, \tau_1]$, where τ_0 and τ_1 are the torques applied to joints q_0 and q_1 respectively.

Do *not* use the observation space of the environment to get the robot's position. Instead, use the following class methods to obtain the joint angles:

```
# To get the current position and angular velocity of q0
q0, q0_dot = env.unwrapped.robot.central_joint.current_position()
# To get the current position and angular velocity of q1
q1, q1_dot = env.unwrapped.robot.elbow_joint.current_position()


# To set joint q0 to a particular position. (Use only before
running your controller, to initialize the start position)
env.unwrapped.robot.central_joint.reset_position(position, 0)
# To set joint q1 to a particular position. (Use only before
running your controller, to initialize the start position)
env.unwrapped.robot.elbow_joint.reset_position(position, 0)
```

Your job is to implement PD controllers that track the trajectory

$$\begin{bmatrix} x(\theta) \\ y(\theta) \end{bmatrix} = \begin{bmatrix} (0.19 + 0.02 \cos 4\theta) \cos \theta \\ (0.19 + 0.02 \cos 4\theta) \sin \theta \end{bmatrix}, \text{ for } \theta \in [-\pi, \pi]$$

This trajectory is plotted below:

```
In [11]: x = [(0.19 + 0.02 * np.cos(theta * 4)) * np.cos(theta) for theta in np.arange(0, 2*np.pi, 0.01)]
y = [(0.19 + 0.02 * np.cos(theta * 4)) * np.sin(theta) for theta in np.arange(0, 2*np.pi, 0.01)]
plt.plot(x, y, 'b')
plt.axis('equal')
# plt.show()
plt.savefig('arm_traj.png')
traj = list(zip(x,y))
```



1. Forward Model

Derive the forward model for the robot as a closed-form expression expressed in joint angles and link length:

$$f\left(\begin{bmatrix} q_0 \\ q_1 \end{bmatrix}\right) = \begin{bmatrix} l_0 \cos(q_0) + l_1 \cos(q_0 + q_1) \\ l_0 \sin(q_0) + l_1 \sin(q_0 + q_1) \end{bmatrix} = \begin{bmatrix} x \\ y \end{bmatrix}$$

Using the robot model parameters, write a function `getForwardModel` that takes the joint states and returns the end-effector position.

```
In [ ]: def getForwardModel(q0, q1):
        x=l1*np.cos(q0)+l2*np.cos(q0+q1)
        y=l1*np.sin(q0)+l2*np.sin(q0+q1)
        return [x,y]
```

2. Jacobian

Derive the expression for the Jacobian of the robot:

$$J_f(q_0, q_1) = [\text{---}]$$

Derive the expression for the Jacobian of the robot:

$$J_f(q_0, q_1) = \begin{bmatrix} \frac{\partial x}{\partial q_0} & \frac{\partial x}{\partial q_1} \\ \frac{\partial y}{\partial q_0} & \frac{\partial y}{\partial q_1} \end{bmatrix}$$

Also we know that,

$x = l_0 * \cos(q_0) + l_1 * \cos(q_0 + q_1)$ \ $y = l_0 * \sin(q_0) + l_1 * \sin(q_0 + q_1)$ \ So, on pluggin we get,

$$J_f(q_0, q_1) = \begin{bmatrix} -l_0 \sin(q_0) - l_1 \sin(q_0 + q_1) & -l_1 \sin(q_0 + q_1) \\ l_0 \cos(q_0) + l_1 \cos(q_0 + q_1) & l_1 \cos(q_0 + q_1) \end{bmatrix}$$

Write a function `getJacobian` that takes the joint states and returns the Jacobian.

```
In [38]: #for my code l1 is l0 and l2 is l2
def getJacobian(q0, q1):
    jaco=np.array([-l1*np.sin(q0)-l2*np.sin(q0+q1),-l2*np.sin(q0+q1),l1*np.c
    return jaco
```

3. X-Y controller

Background: for reasons beyond the scope of this course, it so happens that, for any robot,

$$\vec{\tau} = J^T \vec{F},$$

where

- $\vec{F} = \langle F_x, F_y \rangle$ is the force vector exerted by the robot at the end effector
- $\vec{\tau} = \langle \tau_0, \tau_1 \rangle$ is the vector of torques exerted by the joints
- J is the Jacobian matrix at the current position.

Use this fact to implement a closed-loop PD controller that controls the robot along the trajectory `traj`, using the error in the end-effector as the input signal. Your controller should compute forces F_x and F_y , and then use `getJacobian` along with the above equation to translate them into joint torques.

Plot the trajectory of the robot juxtaposed over the desired trajectory, and calculate the mean square error between both paths. Also plot the errors with respect to time, and use those plots to tune your controller.

Note: Initialize the robot arm to $q_0 = \pi$ and $q_1 = 0$

```
In [3]: def sq_error(A,B):
    ## mean sq error ##
    return np.square(np.subtract(A, B)).mean()
```



```
In [4]: def mse_error(A,B):  
        ## mse error ##  
        ans= np.square(np.subtract(A, B)).mean()  
        return ans
```

```
In [5]: def resetBody():  
        env.unwrapped.robot.central_joint.reset_position(pi, 0)  
        env.unwrapped.robot.elbow_joint.reset_position(0, 0)
```

```
In [6]: def plot_original_traj(plt):  
        x = [(0.19 + 0.02 * np.cos(theta * 4)) * np.cos(theta) for theta in np.linspace(0, 2*np.pi, 100)]  
        y = [(0.19 + 0.02 * np.cos(theta * 4)) * np.sin(theta) for theta in np.linspace(0, 2*np.pi, 100)]  
        plt.plot(x, y)  
        plt.axis('equal')
```

```

In [7]: def PdController(kp,kd,goalTraj,useSqrtKD=False):
    import math
    #define the pd controllers
    ## I am choosing Kd=sqrt(Kp)
    Kp=kp
    Kd=kd

    if(useSqrtKD==True):
        Kd=sqrt(Kp)

    ## End-effector pos and velocity
    q0, q0_dot = env.unwrapped.robot.central_joint.current_position()
    q1, q1_dot = env.unwrapped.robot.elbow_joint.current_position()

    ## store ee points- used for plotting
    ee_pos_track=[]
    mse_track=[]
    err_track=[]

    ##Previous error
    error_pos_prev=np.zeros(2).reshape(2,1)

    for i in range(len(traj)):
        ## get angle configs
        q0, q0_dot = env.unwrapped.robot.central_joint.current_position()
        q1, q1_dot = env.unwrapped.robot.elbow_joint.current_position()

        J=getJacobian(q0,q1)

        ## get end-effector position
        ee_x,ee_y=getForwardModel(q0,q1)
        ee_pos=np.array([ee_x,ee_y]).reshape(2,1)

        ## goal end-effector position
        ee_goal=np.array(traj[i]).reshape(2,1)

        ## store position for plotting
        ee_pos_track.append([ee_x,ee_y])

        error_pos=ee_goal-ee_pos
        del_error_pos=error_pos-error_pos_prev

        err_track.append(sq_error(ee_goal,ee_pos))

        ## Force for PD controller
        F=Kp*error_pos+Kd*del_error_pos

        ## Calculate and apply torque - Tau = (Transpose(J).F)
        tau=np.dot(J.T,F)
        env.step(tau)

        ## Update last error prev - used for delta error
        error_pos_prev=error_pos

    print("MSE ERROR :{}\n".format(np.mean(err_track)))
    # print("pred len {}".format(len(ee_pos_track)))
    x = [ele[0] for ele in ee_pos_track]
    y = [ele[1] for ele in ee_pos_track]
    plt.plot(x,y,color="r")


```


```
plt.plot(x, y, color='r')
plt.axis('equal')
plot_original_traj(plt)
plt.show()
plt.savefig('pd_arm_traj.png')

plt.plot(range(len(err_track)), err_track, color="y")
plt.show()
```

```
In [19]: resetBody()
PdController(100,math.sqrt(100),traj)
```

MSE ERROR :5.2761670383716196e-08





4. Inverse Kinematics

Using the functions `getForwardModel` and `getJacobian` from parts 1 and 2, write a function `getIK` that takes the current end-effector position, target end-effector position, and current joint states; and returns the target joint-states.

In [20]: `def getIK(current_position, target_position, current_state):`

```

    curr_pos=np.array(current_position).reshape(2,1)
    targ_pos=np.array(target_position).reshape(2,1)
    curr_state=np.array(current_state).reshape(2,1)

    q0=curr_state[0]
    q1=curr_state[1]
    J=getJacobian(q0,q1)
    Jinv=np.linalg.pinv(J)
    GAMMA=0.1

    e=10000;
    THRESHOLD=0.001
    while(e>THRESHOLD):
        q0=curr_state[0]
        q1=curr_state[1]

        ee_pos=getForwardModel(q0,q1)
        curr_pos=np.array(ee_pos).reshape(2,1)

        del_ee_pos=curr_pos-targ_pos

        J=getJacobian(q0,q1)
        Jinv=np.linalg.pinv(J)

        del_q=Jinv@del_ee_pos
        curr_state=curr_state-(GAMMA*del_q)
#         print("\nDEL Q {}".format(del_q))
        e=mse_error(ee_pos,targ_pos)
#         print("IN Error {}\n".format(e))
    return curr_state

```

In [21]: `print(getIK([0,0],[0,0.2],[pi,0]))`

```

[[ 13.41392937]
 [-11.1835432 ]]

```

Now derive the analytical inverse kinematic solution; i.e. solve the problem using a closed-form equation, rather than an iterative method. *Show your work*. Correct answers without derivations will not receive full credit.

$q_0 = \underline{\hspace{1cm}}$

$q_1 = \underline{\hspace{1cm}}$

Explain what challenges there would be to use the analytical IK solution to track trajectories:

<your explanation here>

In []:

$$x = l_0 \cos(q_0) + l_1 \cos(q_0 + q_1)$$

$$y = l_0 \sin(q_1) + l_1 \sin(q_0 + q_1)$$

Use formula of $\cos(x+y)$ and $\sin(x+y)$ here

Now to find the inverse kinematics, we need to solve for θ_1 and θ_2 in terms of x and y .

Using basic Pythagoras theorem to solve for θ_1 :

$$l_0^2 + l_1^2 + 2l_0l_1 \cos(q_1) = x^2 + y^2$$

$$\cos(q_1) = (x^2 + y^2 - l_0^2 - l_1^2) / (2l_0l_1)$$

We can then use the arccosine function to solve for θ_2 :

$$q_1 = \pm \arccos [(x^2 + y^2 - l_0^2 - l_1^2) / (2l_0l_1)]$$

To determine the sign of q_1 , we need to consider the configuration of the robot arm. If the end-effector is on the opposite side of the y -axis compared to the origin, we take the negative of the arccosine. Otherwise, we take the positive arccosine.

Next, we can use the law of cosines to solve for q_0 :

$$\cos(q_0) = (l_0^2 + x^2 + y^2 - l_1^2 - 2l_0(x \cos(q_1) + y \sin(q_1))) / (2l_0\sqrt{x^2 + y^2})$$

Again, we can use the arccosine function to solve for q_0 :

$$q_0 = \text{atan2}(y, x) - \text{atan2}(l_1 \sin(q_1), l_0 + l_1 \cos(q_1))$$

On Consolidating result we get

$$q_1 = \pm \arccos [(x^2 + y^2 - l_0^2 - l_1^2) / (2l_0l_1)]$$

$$q_0 = \text{atan2}(y, x) - \text{atan2}(l_1 \sin(q_1), l_0 + l_1 \cos(q_1))$$

atan is \arctan . \arccos is arccos inverse and likewise

Explain what challenges there would be to use the analytical IK solution to track trajectories:

1. **Solution Uniqueness:** In some cases, like the one shown above (via \pm sign for q_1) there may be multiple solutions to the analytical IK problem. This happens since for a specific end effector position the arm can be positioned in various ways hence with various angles
2. The analytical version doesn't incorporate error sensitivity. In iterative one we iterate until it reaches close to goal with certain specified threshold. This error Threshold helps better tune and incorporate error sensitivity too.

3. since there can be large float point division within the calculations, analytical IK might be computationally expensive or infeasible

5. IK controller

Implement a closed-loop PD controller that controls the robot along the trajectory \mathbf{traj} , using the error in the joint-angles as the input signal.

Plot the trajectory of the robot juxtaposed over the actual trajectory and calculate the mean square error between both paths. Also plot the errors with respect to time, and use those plots to tune your controller.

Note: Initialize the robot arm to $q_0 = \pi$ and $q_1 = 0$

```

In [22]: # Write your script here.
def PdControllerAngle(kp,kd):
    Kp=kp
    Kd=kd

    ## End-effector pos and velocity
    q0, q0_dot = env.unwrapped.robot.central_joint.current_position()
    q1, q1_dot = env.unwrapped.robot.elbow_joint.current_position()

    ## store ee points- used for plotting
    ee_pos_track=[]
    mse_track=[]

    ##Previous error
    error_pos_prev=np.zeros(2).reshape(2,1)
    error_angle_prev=np.zeros(2).reshape(2,1)

    for i in range(len(traj[:6000])):
        # print("-- POINT {} \n --".format(i+1))
        ## get angle configs
        q0, q0_dot = env.unwrapped.robot.central_joint.current_position()
        q1, q1_dot = env.unwrapped.robot.elbow_joint.current_position()

        ## get end-effector position
        ee_x,ee_y=getForwardModel(q0,q1)
        ee_pos=np.array([ee_x,ee_y]).reshape(2,1)

        # print("3 \n")
        ## goal end-effector position
        ee_goal=np.array(traj[i]).reshape(2,1)

        # print("4 \n")
        ## store position for plotting
        ee_pos_track.append([ee_x,ee_y])

        # print("5 \n")
        error_pos=ee_goal-ee_pos
        del_error_pos=error_pos-error_pos_prev

        goal_angle_raw=getIK(ee_pos,traj[i],[q0,q1])

        goal_angle=np.array(goal_angle_raw).reshape(2,1)

        error_angle=goal_angle-np.array([q0,q1]).reshape(2,1)
        del_error_angle=error_angle-error_angle_prev

        ## Force for PD controller
        F=Kp*error_angle+Kd*del_error_angle
        # print("del error angle: {} \n".format(del_error_angle))

        ## Calculate and apply torque - Tau = (Transpose(J).F)
        # tau=np.dot(J.T,F)
        env.step(F)

        ## Update last error prev - used for delta error
        # error_pos_prev=error_pos

        ## Save Error for plot

```



```

    ## Save error for plot
    ee_position_for_updated_angle=getForwardModel(goal_angle_raw[0],goal
    mse_val=mse_error(ee_goal,ee_position_for_updated_angle)
    mse_track.append(mse_val)


    error_angle_prev=error_angle
#     print("\n ** iter:{}\n".format(i))

#     print("MSE ERROR :{}\n".format(mse_error(traj,ee_pos_track)))
# print("pred len {}".format(len(ee_pos_track)))
x = [ele[0] for ele in ee_pos_track]
y = [ele[1] for ele in ee_pos_track]
plt.plot(x, y, color="r")
plt.axis('equal')
plot_original_traj(plt)
plt.show()
plt.savefig('pd_arm_traj.png')


plt.plot(range(len(mse_track)), mse_track, color="y")
print("MSE:{}\n".format(np.mean(mse_track)))
plt.show()

```

In [23]: `resetBody()`
`PdControllerAngle(100,math.sqrt(100))`



MSE:5.1074760112821436e-08



6. Race Car

The objective of the `racecar` environment is to make the race car travel as far as possible on a track within the given time. There are 3 tracks available: `FigureEight`, `Linear`, and `Circle` (default). Each track has a different shape, time limit, and horizon length. To set up an environment with a particular track, you can pass the track name while instantiating the environment. For example, to set up the figure eight trajectory:

```
from racecar.SDRaceCar import SDRaceCar
env = SDRaceCar(render_env=True, track='FigureEight')
```

To install the race car environment, run the following commands:

```
~ git clone https://github.com/ucsdarclab/RaceCar.git
~ cd RaceCar
~ pip install -e .
```

The action space of the environment consists of [wheel angle, thrust]. The range of both these values are normalized to be between ± 1 . The observation space consists of $[x, y, \theta, v_x, v_y, \dot{\theta}, h]$, where (x, y, θ) is the inertial frame position of the car; v_x, v_y are the longitudinal and lateral velocities respectively; and $\dot{\theta}$ is the yaw rate. h is the coordinate on the track the car has to reach.

At each time step, the race car environment gives a reward that is proportional to the speed of the car and its proximity to the track. It terminates (`done = True`) after a fixed amount of time, or if the car gets too far from the track.

Using these observations implement a controller that can traverse all three tracks. You may use different gains for different tracks, but the controller itself must be the same. Record the cumulative reward for each track; these rewards will be summed together to create your controller's score. If your controller has the highest score, you win!

Tip: if you call `env.render()` at each step to visualize the car's path, you may find that Jupyter interprets each step as a separate image. To avoid this, try running

```
%matplotlib tk # others include qt, wx, gtk, osx
```

to load results as animations in a separate window. You may have to experiment with several different backends to find the one that works best with your system.

```
In [26]: !git clone https://github.com/ucsdarclab/RaceCar.git
%pwd
```

```
Cloning into 'RaceCar'...
remote: Enumerating objects: 28, done.
remote: Total 28 (delta 0), reused 0 (delta 0), pack-reused 28
Receiving objects: 100% (28/28), 7.72 KiB | 7.72 MiB/s, done.
Resolving deltas: 100% (7/7), done.
Out[26]: '/Users/sbhat/Documents/Purdue/purduePrivate/assignments/a2/pybullet-gym'
```

```
In [8]: %cd RaceCar
!pip install -e .
%ls
```

```
[Errno 2] No such file or directory: 'RaceCar'
/Users/sbhat/Documents/Purdue/purduePrivate/assignments/a2
Obtaining file:///Users/sbhat/Documents/Purdue/purduePrivate/assignments/a2
ERROR: file:///Users/sbhat/Documents/Purdue/purduePrivate/assignments/a2 do
es not appear to be a Python project: neither 'setup.py' nor 'pyproject.tom
l' found.
Assignment2.ipynb    arm_traj_2.png      pbcopy              robotArm.png
RaceCar0G/          arm_traj_error.png  pd_arm_traj.png     shivam.py
arm_traj.png        conda_list.txt      pybullet-gym/       shivamTest2.py
```

```
In [ ]: # ##### Init #####
# from racecar.SDRaceCar import SDRaceCar
# trk='Circle'
# env = SDRaceCar(render_env=True, track=trk)
# env.reset()
```

```

In [9]: ## Race Car Util Functions ##

def get_rotation_mat(angle):
    ans=np.array([np.cos(angle),-np.sin(angle),np.sin(angle),np.cos(angle)])
    return ans

## returns co-ordinated with h as center
def moveXYtoCarFrame(h,x,y):
    return [h[0]-x,h[1]-y]

## rotates the point by theta
def doRotation(theta,point,h):
    ans=0;
    rot_matrix=get_rotation_mat(theta)
    ans=np.transpose(rot_matrix)@np.array(moveXYtoCarFrame(h,point[0],point[1]))
    return ans

def myAngleController(Kp,Kd,pos,err_prev):
    return Kp*np.arctan2(pos[1],pos[0])+Kd*(pos[1]-err_prev)

def thrustController2(KpThrust,KdThrust,x,y,v_x,v_y,h):
    return KpThrust * np.linalg.norm(h - np.array([x, y])) + KdThrust * (-np

def myAngleController2(Kp,Kd,pos,err_prev):
    return Kp*np.arctan2(pos[1],pos[0])+Kd*(pos[1]-err_prev)

```

```

In [10]: def raceCarPlay(env, kp_angle, kd_angle, kp_thrust, kd_thrust, pathName, steps):
# define your controller here
    trk=pathName
#     from racecar.SDRaceCar import SDRaceCar
#     env = SDRaceCar(render_env=True, track=trk)
    env.reset()

    ### main code ###

    ## show in a animation form - might have to play with 'tk'
    %matplotlib tk
    steps=9999
    err_prev=0
    car_pos = np.zeros((2,steps))
    track_pos = np.zeros((2,steps))
    reward=0;
    isPathComplete=False
    en_ret=[0,0,0,0]
    for step in range(steps):
        isPathComplete=en_ret[-2]
#         print(en_ret[-2])
        if(isPathComplete==True):
            break
        reward+=env.reward()
        env.render()
        x, y, theta, v_x, v_y, omega, h=env.get_observation()
        car_pos[0,step], car_pos[1,step] = x, y
        track_pos[0,step], track_pos[1,step] = h[0], h[1]

        rotatedShiftedPos=doRotation(theta, [x,y],h)
        angle=myAngleController(kp_angle,kd_angle,rotatedShiftedPos,err_prev)

        thrust=thrustController2(kp_thrust,kd_thrust,x,y,v_x,v_y,h)
        car_action=[angle,thrust]
#         print("Action {}\n".format(car_action))
        en_ret=env.step(car_action)
#         print("env ret {}\n".format(len(en_ret)))
        err_prev=rotatedShiftedPos[1]

    ## Print Path
    plt.plot(car_pos[0,:],car_pos[1,:], label = 'car trajectory')
    plt.plot(track_pos[0,:], track_pos[1,:], label = 'reference trajectory')
    plt.title('Car vs Reference Trajectory')
    return reward
# %%

# print(rotation_mat(0.5))

```

```
In [33]: from racecar.SDRaceCar import SDRaceCar
rc_env = SDRaceCar(render_env=True, track='Circle')
##PARAMS
KpAngle=3
KdAngle=0.1
KpThrust=6.5
KdThrust=1.45

steps=1000

track="Circle"

circle_rwd=raceCarPlay(rc_env, KpAngle, KdAngle, KpThrust, KdThrust, None, steps)
print("Reward Car:{}".format(circle_rwd))
# run your controller for the 'Circle' environment
```

Reward Car:211.38460348029358

```
In [13]: from racecar.SDRaceCar import SDRaceCar
rc_env = SDRaceCar(render_env=True, track='Linear')
##PARAMS
KpAngle=3
KdAngle=0.1
KpThrust=6.5
KdThrust=1.45

steps=1000

track="Linear"

linear_rwd=raceCarPlay(rc_env, KpAngle, KdAngle, KpThrust, KdThrust, None, steps)
print("Reward Car:{}".format(linear_rwd))
# run your controller for the 'Circle' environment
```

Reward Car:70.96802949917131

```
In [25]: from racecar.SDRaceCar import SDRaceCar
rc_env = SDRaceCar(render_env=True, track='FigureEight')
##PARAMS
KpAngle=3
KdAngle=1
KpThrust=4
KdThrust=1.9

steps=1000

track="FigureEight"

eight_rwd=raceCarPlay(rc_env, KpAngle, KdAngle, KpThrust, KdThrust, None, steps)
print("Reward Car:{}".format(eight_rwd))
# run your controller for the 'Circle' environment
```

Reward Car:314.5439654137004

```
In [34]: print("Total Reward: {}".format(circle_rwd+linear_rwd+eight_rwd))
```

Total Reward: 596.8965983931653

```
In [ ]: rc_env = SDRaceCar(render_env=True, track='FigureEight')  
        # run your controller for the 'FigureEight' environment
```