

Enrichment Flag Codes

The `flag_codes` vocabulary — 17 codes, defined in `enrichment/flags.py` (ALL_CODES, lines 196–214). Each has exactly one detection rule and one prose template in `_REASONS`. Grouped below by the Issue-Catalogue code they join to.

FLAG CODE	WHAT IT SAYS	ISSUE CODE
G8-VERIFY-001 — ENRICHMENT LEFT THE VALUE UNESTABLISHED		
no-match	No source could identify this organisation — resolve the name manually.	G8-VERIFY-001
low-confidence-unchanged	Left exactly as supplied; the canonical form could not be established with enough confidence to rewrite it.	G8-VERIFY-001
person-unresolved	The field holds a person, and the organisation they belong to could not be resolved.	G8-VERIFY-001
G7-CONFIRM-001 — A VALUE WAS WRITTEN; NOTHING INDEPENDENT BACKS IT		
domain-unverified ADVISORY	The domain was found on the web but nothing independently tied it to this organisation. The candidate <i>ships</i> , at <code>web:{domain}:low</code> .	G7-CONFIRM-001
unverified-inference	Inferred without external evidence — confirm against an authoritative source.	G7-CONFIRM-001
dept-via-lab	The parent department was inferred from the lab's own page, not read from a stated department.	G7-CONFIRM-001
dept-via-contact	The department was inferred from the contact's own affiliation, not read from a stated department.	G7-CONFIRM-001
relocated-unverified	Preprocessing moved the content into this slot and nothing vouched for the placement.	G7-CONFIRM-001
G6-RESOLVE-001 — NO AUTOMATED PATH RESOLVES IT		
opaque-code	A name field holds an internal code rather than an organisation name.	G6-RESOLVE-001
email-conflict	More than one email address, all kept in the column — both are the record's own and there is no basis for choosing.	G6-RESOLVE-001
multiple-contacts	More than one person named, so the department could not be confirmed against a contact's page.	G6-RESOLVE-001
name-states-another-site	A name field named a site the record's own address block contradicts.	G6-RESOLVE-001
DELIBERATELY UNMAPPED — UNMAPPED_FLAG_CODES		
overflow	One value appears to be split across several SAP fields.	— already G1-NAME-001

FLAG CODE	WHAT IT SAYS	ISSUE CODE
name3-not-demoted	The parent department went to Name 2 but every slot below it was populated, so the lab name could not be moved down.	– already G4-NAME-015
registry-location-mismatch ADVISORY	The matched registry record is registered at a different address. The match is <i>kept</i> .	– advisory by design
entity-superseded	The organisation has been dissolved or replaced (Wikidata P576 / P1366). The name is deliberately not rewritten to the successor.	– business decision
source-conflict	Two sources identified this as different organisations; the lower-priority source's fields were removed.	– business decision

Three things worth knowing about the set

- **Two codes are advisory.** `ADVISORY_CODES` (`flags.py:246`) holds `registry-location-mismatch` and `domain-unverified`. They emit code, prose and field scope exactly as any other code — what changes is only whether their presence is enough to make `flag_for_review` true. A row can therefore ship with `flag_for_review` false and a populated `flag_reason`: the finding is on the record for anyone who looks at it, and nobody is asked to look.
- **Low-confidence-unchanged is derived, never raised.** `render` computes it from the record's own provenance (`flag_low_confidence`, in turn derived from the write history); a tier that passes it in `scopes` still gets a `ValueError` (`flags.py:96–110`). An audit of an enriched file re-supplies it from the `Name 1 / Name 2 Provenance` columns when `Flag Codes` does not carry it.
- **Five codes map to no catalogue code, on purpose.** Declared in `UNMAPPED_FLAG_CODES` (`issue_detection.py:1128`) rather than left implicit, so the pairing is a decision a test can hold the vocabulary to: a code added to `ALL_CODES` is either mapped or named there, and never silently neither. Two would double-count a defect already reported from record content, one is advisory, and two ask a business question no catalogue code carries the meaning for.

Not these — two adjacent vocabularies

`dedup/flags.py` holds three Phase 2 *feature* flags, not record flags: environment switches read on every call, all default-false, each gating one v2 change — `DEDUP_V2_BLOCKING` (delivery-point blocking), `DEDUP_V2_NAME2` (Name-2 slot classification) and `DEDUP_V2_ID_CONFLICT` (ROR/LEI conflict routing). With all three off the output is byte-identical to v1.

`ISSUE_CATALOGUE` (`enrichment/issue_detection.py:201`) is the separate 41-entry G1–G8 issue vocabulary — 37 live, 1 unlisted, the rest withdrawn or not deterministically detectable. The `FLAG_CODE_ISSUES` map in the same module is the join between the two, and it is many-to-one on purpose: three flags that all mean “no automated path exists, a human must supply the value” are one queue, not three.