

```

#include <stdio.h>
int main()
{
    int pid[15];
    int bt[15];
    int n;
    printf("Enter the number of processes: ");
    scanf("%d",&n);
    printf("Enter process id of all the processes: ");
    for(int i=0;i<n;i++)
    {
        scanf("%d",&pid[i]);
    }
    printf("Enter burst time of all the processes: ");
    for(int i=0;i<n;i++)
    {
        scanf("%d",&bt[i]);
    }
    int i, wt[n];
    wt[0]=0;
    //for calculating waiting time of each process
    for(i=1; i<n; i++)
    {
        wt[i]= bt[i-1]+ wt[i-1];
    }
}

```

```

    }

    printf("Process ID    Burst Time    Waiting Time\n");
    printf("TurnAround Time\n");

    float twt=0.0;
    float tat= 0.0;
    for(i=0; i<n; i++)
    {
        printf("%d\t\t", pid[i]);
        printf("%d\t\t", bt[i]);
        printf("%d\t\t", wt[i]);

        //calculating and printing turnaround time of each process

        printf("%d\t\t", bt[i]+wt[i]);
        printf("\n");

        //for calculating total waiting time
        twt += wt[i];

        //for calculating total turnaround time
        tat += (wt[i]+bt[i]);
    }

    float att,awt;

    //for calculating average waiting time
    awt = twt/n;

    //for calculating average turnaround time
    att = tat/n;

    printf("Avg. waiting time= %f\n",awt);

```

```
printf("Avg. turnaround time= %f",att);  
}
```