

QuB

A Resource Aware Functional Programming Language

Apoorv Ingle

The University of Kansas

Table of Contents

- 1 Introduction and Motivation
- 2 Background Work
- 3 QuB
- 4 Examples And Extensions
- 5 Conclusion and Future Work

Hard problems in programming

Naming variables

Hard problems in programming

Resource management

in evolving production code

Resources: Files, database connections, entity with a shared state

- Modified File Handling API in Haskell

```
openFile :: FilePath → IO FileHandle
```

```
closeFile :: FileHandle → IO ()
```

```
readLine :: FileHandle → IO (String, FileHandle)
```

```
writeFile :: String      → FileHandle  
           → IO ((), FileHandle)
```

```
upper      :: String      → String
```

- File Handling in Haskell

```
do f <- openFile "sample.txt"  
   (s, f) <- readLine f  
   let c = upper s  
   ((), f) <- writeLine f c  
   .  
   .  
   .  
   () <- closeFile f
```

- File Handling in Haskell Gone Wrong (Part I)

```
do f <- openFile "sample.txt"
    (s, f) <- readLine f
    let c = upper s
    ((), f) <- writeLine f c
    .
    .
    .
    () <- closeFile f
    .
    .
    .
    () <- closeFile f
    return c
```

Resource Management: File Handling

- File Handling in Haskell Gone Wrong (Part I)

```
do f <- openFile "sample.txt"  
    (s, f) <- readLine f  
    let c = upper s  
    ((), f) <- writeLine f c  
    .  
    .  
    .  
    () <- closeFile f  
    .  
    .  
    .  
    () <- closeFile f  
    return c
```

- File is closed twice: Run time crash

- File Handling in Haskell Gone Wrong (Part II)

```
do f <- openFile "sample.txt"
  (s, f) <- readLine f
  let c = upper s
  ((), f) <- writeLine f c
  .
  .
  .
return c
```

- File Handling in Haskell Gone Wrong (Part II)

```
do f <- openFile "sample.txt"
    (s, f) <- readLine f
    let c = upper s
    ((), f) <- writeLine f c
    .
    .
    .
    return c /*File not closed!!*/
```

- File not closed: Memory leak

- `MonadError`[5] in Haskell

```
class Monad m => MonadError e m | m -> e where  
    throwError :: e -> m a  
    catchError :: m a -> (e -> m a) -> m a
```

- `throwError` starts exception processing
- `catchError` exception handler

- Using MonadError in Haskell

```
do f ← openFile "sample.txt"
  ((s, f) ← readLine f
   let c = upper s
   () ← closeFile f
   return $ Right c)
  `catchError` (\_ →
    return $ Left "Error in reading file")
```

- Exception may cause memory leak

Well typed programs do not go wrong.

— R. Milner

Well typed programs do not go wrong.

— R. Milner

~~Lights~~ *Types* will guide you home

— Coldplay

- Design and implement QuB type system
 - Resources as first class citizens
 - Program objects are restricted or unrestricted
 - Functions that share resources with their arguments or are separate.
- Formalizing and proving important properties of QuB
- QuB is logic of **BI** with steroids
 - Environments as graphs
- Working examples

Background Work: Simply Typed Lambda Calculus (STLC)

$$\begin{array}{l} \lambda x.M \left\{ \begin{array}{l} \text{Abstract over computation} \\ \text{Define functions} \end{array} \right. \\ MN \left\{ \begin{array}{l} \text{Do the computation} \\ \text{Use functions} \end{array} \right. \end{array}$$

Background Work: Simply Typed Lambda Calculus (STLC)

$\lambda x.M$ $\left\{ \begin{array}{l} \text{Abstract over computation} \\ \text{Define functions} \end{array} \right.$

MN $\left\{ \begin{array}{l} \text{Do the computation} \\ \text{Use functions} \end{array} \right.$

$$\frac{\Gamma_{x, x:\tau} \vdash M:\tau'}{\Gamma \vdash \lambda x.M:\tau \rightarrow \tau'} [\rightarrow I]$$

$$\frac{\Gamma \vdash M:\tau \rightarrow \tau' \quad \Gamma \vdash N:\tau}{\Gamma \vdash MN:\tau'} [\rightarrow E]$$

Background Work: Simply Typed Lambda Calculus (STLC)

$$\begin{array}{l} \lambda x.M \left\{ \begin{array}{l} \text{Abstract over computation} \\ \text{Define functions} \end{array} \right. \\ MN \left\{ \begin{array}{l} \text{Do the computation} \\ \text{Use functions} \end{array} \right. \end{array}$$

$$\frac{\Gamma_x, x : \tau \vdash M : \tau'}{\Gamma \vdash \lambda x.M : \tau \rightarrow \tau'} [\rightarrow I] \qquad \frac{\Gamma \vdash M : \tau \rightarrow \tau' \quad \Gamma \vdash N : \tau}{\Gamma \vdash MN : \tau'} [\rightarrow E]$$

Hinley-Milner (**HM**) type system ensures sane programs

Background Work: Curry-Howard Correspondence

- Types are Propositions
- Programs are Proofs

HM type system \equiv Second Order Propositional Logic

Background Work: Second Order Propositional Logic

Language:

Propositions & connectives $A, B, C ::= x \mid A \supset B \mid \forall x.B \mid \dots$

Context $\Gamma, \Delta ::= \epsilon \mid \Gamma, A$

Logic Rules:

$$\frac{}{A \vdash A} [Ax]$$

$$\frac{\Gamma \vdash B \quad x \notin \Gamma}{\forall x.B} [\forall I]$$

$$\frac{\Gamma \vdash \forall x.B \quad \Gamma \vdash A}{B[x/A]} [\forall E]$$

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \supset B} [\supset I]$$

$$\frac{\Gamma \vdash A \supset B \quad \Gamma \vdash A}{\Gamma \vdash B} [\supset E]$$

- Two implicit rules in Propositional Calculus

$$\frac{\Gamma \vdash B}{\Gamma, A \vdash B} \text{ [WKN]}$$

$$\frac{\Gamma, A, A \vdash B}{\Gamma, A \vdash B} \text{ [CTR]}$$

- Two implicit rules in Propositional Calculus

$$\frac{\Gamma \vdash B}{\Gamma, A \vdash B} \text{ [WKN]}$$

$$\frac{\Gamma, A, A \vdash B}{\Gamma, A \vdash B} \text{ [CTR]}$$

- Control the use of [WKN] and [CTR]

Background Work: Linear Logic

Certain contexts cannot undergo weakening or contraction[3, 10]

Context $\Gamma, \Delta ::= \epsilon \mid \Gamma, \langle A \rangle \mid \Gamma, [A]$

$\Gamma, \langle A \rangle \not\vdash \Gamma$

$\Gamma, \langle A \rangle \not\vdash \Gamma, \langle A \rangle, \langle A \rangle$

$\Gamma, [A] \vdash \Gamma$

$\Gamma, [A] \vdash \Gamma, [A], [A]$

Background Work: Linear Logic

Language

Context $\Gamma, \Delta ::= \epsilon \mid \Gamma, \langle A \rangle \mid \Gamma, [A]$

Propositions $A, B, C ::= X \mid !A \mid A \multimap B \mid A \& B \mid A \otimes B \mid A \oplus B$

Structural Rules

$$\frac{}{[A] \vdash A} [\text{ID}_{[]}]\qquad \frac{}{\langle A \rangle \vdash A} [\text{ID}_{\langle \rangle}]$$

$$\frac{\Gamma, \Delta \vdash A}{\Delta, \Gamma \vdash A} [\text{EXCH}] \quad \frac{\Gamma, [A], [A] \vdash B}{\Gamma, [A] \vdash B} [\text{CTRN}] \quad \frac{\Gamma \vdash B}{\Gamma, [A] \vdash B} [\text{WKN}]$$

$$\frac{[\Gamma] \vdash A}{[\Gamma] \vdash !A} [!I] \quad \frac{\Gamma \vdash !A \quad \Delta, [A] \vdash B}{\Gamma, \Delta \vdash B} [!E]$$

Background Work: Linear Logic

Connective Rules

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \multimap B} [\multimap I]$$

$$\frac{\Gamma \vdash A \multimap B \quad \Delta \vdash A}{\Gamma, \Delta \vdash B} [\multimap E]$$

Background Work: Linear Logic

Connective Rules

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \multimap B} [\multimap I]$$

$$\frac{\Gamma \vdash A \multimap B \quad \Delta \vdash A}{\Gamma, \Delta \vdash B} [\multimap E]$$

$$\frac{\Gamma \vdash A \quad \Gamma \vdash B}{\Gamma \vdash A \& B} [\& I]$$

$$\frac{\Gamma \vdash A \& B}{\Gamma \vdash A} [\& E_1]$$

$$\frac{\Gamma \vdash A \& B}{\Gamma \vdash B} [\& E_2]$$

Connective Rules

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \multimap B} [\multimap I]$$

$$\frac{\Gamma \vdash A \multimap B \quad \Delta \vdash A}{\Gamma, \Delta \vdash B} [\multimap E]$$

$$\frac{\Gamma \vdash A \quad \Gamma \vdash B}{\Gamma \vdash A \& B} [\& I]$$

$$\frac{\Gamma \vdash A \& B}{\Gamma \vdash A} [\& E_1]$$

$$\frac{\Gamma \vdash A \& B}{\Gamma \vdash B} [\& E_2]$$

$$\frac{\Gamma \vdash A \quad \Delta \vdash B}{\Gamma, \Delta \vdash A \otimes B} [\otimes I]$$

$$\frac{\Gamma \vdash A \otimes B \quad \Delta, A, B \vdash C}{\Gamma, \Delta \vdash C} [\otimes E]$$

Background Work: Linear Logic

Connective Rules

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \multimap B} [\multimap I]$$

$$\frac{\Gamma \vdash A \multimap B \quad \Delta \vdash A}{\Gamma, \Delta \vdash B} [\multimap E]$$

$$\frac{\Gamma \vdash A \quad \Gamma \vdash B}{\Gamma \vdash A \& B} [\& I]$$

$$\frac{\Gamma \vdash A \& B}{\Gamma \vdash A} [\& E_1]$$

$$\frac{\Gamma \vdash A \& B}{\Gamma \vdash B} [\& E_2]$$

$$\frac{\Gamma \vdash A \quad \Delta \vdash B}{\Gamma, \Delta \vdash A \otimes B} [\otimes I]$$

$$\frac{\Gamma \vdash A \otimes B \quad \Delta, A, B \vdash C}{\Gamma, \Delta \vdash C} [\otimes E]$$

$$\frac{\Gamma \vdash A}{\Gamma \vdash A \oplus B} [\oplus I_1]$$

$$\frac{\Delta \vdash B}{\Delta \vdash A \oplus B} [\oplus I_2]$$

$$\frac{\Gamma \vdash A \oplus B \quad \Delta, A \vdash C \quad \Delta, B \vdash C}{\Gamma, \Delta \vdash C} [\oplus E]$$

Background Work: Linear Logic

- Propositions act like Resources

“A consumed to give B” $A, A \multimap B \vdash B$

“Both A and B” $A \otimes B$

“Choice between A and B” $A \& B$

Cannot create new copies $A \not\vdash A \otimes A$

Fall back to intuitionistic logic $!A \multimap B \equiv A \multimap B$

Background Work: Linear Logic

- Propositions act like Resources

“A consumed to give B” $A, A \multimap B \vdash B$

“Both A and B” $A \otimes B$

“Choice between A and B” $A \& B$

Cannot create new copies $A \not\vdash A \otimes A$

Fall back to intuitionistic logic $!A \multimap B \equiv A \multimap B$

- Curry-Howard Correspondence: Type systems based on Linear Logic
- Active Area of research: $L^3[1]$, $F^\circ[6]$, Linear Haskell[2], Quill[7]
- Resources are first class values

Background Work: Linear Logic

Downside: Asymmetry between implication and conjunction

Multiplicative Fragment:

$$A \otimes B \vdash C \text{ iff } A \vdash B \multimap C$$

Additive Fragment:

$$!A \& !B \vdash C \text{ iff } !A \vdash !B \multimap C$$

Modality is necessary to avoid over-restriction

General framework to incorporate predicates into type language

$$P \mid \Gamma \vdash M : \sigma$$

“Type of M is σ when predicates in P are satisfied and free variables in M are specified in Γ ”[4]

Background Work: Typing Rules with Qualified Types

HM system with qualified Types:

$$\frac{x:\sigma \in \Gamma}{P \mid \Gamma \vdash x:\sigma} [\text{VAR}] \quad \frac{P \mid \Gamma \vdash M:\sigma \quad Q \mid \Gamma_x, x:\sigma \vdash N:\tau}{P, Q \mid \Gamma \vdash (\text{let } x = M \text{ in } N):\tau} [\text{LET}]$$

$$\frac{P \mid \Gamma \vdash M:\sigma \quad t \notin \text{fvs}(\Gamma) \cup \text{fvs}(P)}{P \mid \Gamma \vdash M:\forall t.\sigma} [\forall \text{ I}] \quad \frac{P \mid \Gamma \vdash M:\forall t.\sigma}{P \mid \Gamma \vdash M:[\tau/t]\sigma} [\forall \text{ E}]$$

$$\frac{P \mid \Gamma_x, x:\tau \vdash M:\tau'}{P \mid \Gamma \vdash \lambda x.M:\tau \rightarrow \tau'} [\rightarrow \text{ I}] \quad \frac{P \mid \Gamma \vdash M:\tau \rightarrow \tau' \quad P \mid \Gamma \vdash N:\tau}{P \mid \Gamma \vdash MN:\tau'} [\rightarrow \text{ E}]$$

$$\frac{P, \pi \mid \Gamma \vdash M:\rho}{P \mid \Gamma \vdash M:\pi \Rightarrow \rho} [\Rightarrow \text{ I}] \quad \frac{P \mid \Gamma \vdash M:\pi \Rightarrow \rho \quad P \Rightarrow \pi}{P \mid \Gamma \vdash M:\rho} [\Rightarrow \text{ E}]$$

$\pi \Rightarrow \rho$: π qualifies ρ $P \Rightarrow \pi$: P entails π

Background Work: Quill

Quill[7]: Language with qualified types for linear types and first class polymorphism

Three Predicates:


- $\text{Un } \tau$ If τ does not have resources or can be copied or dropped easily.
- $\text{Fun } \tau$ If τ is a function type
- $\tau \geq \tau'$ If τ less restricting than τ'

Background Work: Quill

- Unrestricted Types: `Un Int`, `Un Bool`
- Restricted or Linear Types: `FileHandle`
- Function Types: `Fun (Int → Int)`, `Fun (String → String)`

Background Work: Logic of Bunched Implications (*BI*)

- Contexts as trees, called bunches[9]
- Two connective used to combine contexts: $A; B$ or A, B



Background Work: Logic of *BI*

- Context connective guides choice of implication

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \multimap B} [\multimap I]$$

$$\frac{\Gamma; A \vdash B}{\Gamma \vdash A \multimap B} [\multimap I]$$

- Contraction

$$\begin{array}{ll} A; B \vdash A & A; B \vdash B \\ A, B \nvdash A & A, B \nvdash B \end{array}$$

- Weakening

$$\begin{array}{ll} A; B \vdash A; B; B & A; B \vdash A; A; B \\ A, B \nvdash A, B, B & A, B \nvdash A, A, B \end{array}$$

Background Work: Logic of *BI*

Background Work: $\alpha\lambda$ -calculus

Curry-Howard interpretation of logic of **BI**[8]

Language

Context $\Gamma, \Delta ::= \{\}_m \mid \{\}_a \mid x : \tau \mid \Gamma, \Delta \mid \Gamma; \Delta$

Types $\tau, \upsilon ::= t \mid \iota \mid \tau \rightarrow \tau \mid \tau \multimap \tau$

Expressions $M, N ::= x \mid \lambda x. M \mid \alpha x. M \mid MN$

Typing rules

$$\begin{array}{c} \frac{x : \tau \in \Gamma}{\Gamma \vdash x : \tau} [\text{VAR}] \quad \frac{\Gamma; \Gamma \vdash M : \tau}{\Gamma \vdash M : \tau} [\text{CTR}] \quad \frac{\Gamma \vdash M : \tau}{\Gamma; \Delta \vdash M : \tau} [\text{WKN}] \\[10pt] \frac{\Gamma_x, x : \tau \vdash M : \tau'}{\Gamma \vdash \lambda x. M : \tau \multimap \tau'} [*I] \quad \frac{\Gamma \vdash M : \tau \multimap \tau' \quad \Delta \vdash N : \tau}{\Gamma, \Delta \vdash MN : \tau'} [*E] \\[10pt] \frac{\Gamma_x; x : \tau \vdash M : \tau'}{\Gamma \vdash \alpha x. M : \tau \rightarrow \tau'} [\rightarrow I] \quad \frac{\Gamma \vdash M : \tau \rightarrow \tau' \quad \Delta \vdash N : \tau}{\Gamma; \Delta \vdash MN : \tau'} [\rightarrow E] \end{array}$$

- Quill: Qualified types for type system based on linear logic
- QuB: Qualified types for type system based on logic of ***BI***

QuB: Types and Predicates

Types $\tau, v, \phi ::= t \mid \iota \mid \tau \rightarrow \tau$

where $\rightarrow \in \{ \overset{!}{\rightarrow}, \multimap, \multimap, \multimap, \multimap \}$

Predicates $\pi, \omega ::= \text{Un } \tau \mid \text{SeFun } \tau \mid \text{ShFun } \tau \mid \tau \geq \tau'$

Qualified Types $\rho ::= \tau \mid \pi \Rightarrow \rho$

Type schemes $\sigma ::= \rho \mid \forall t. \sigma$

- $\text{SeFun } \tau$: τ is a function that is separate from its argument
- $\text{ShFun } \tau$: τ is a function that is in sharing with its argument
- $\text{Un } \tau$: τ does not have resources or they can be copied/dropped easily

QuB: Types and Predicates

Types $\tau, v, \phi ::= t \mid \iota \mid \tau \rightarrow \tau$

where $\rightarrow \in \{ \overset{!}{\rightarrow} *, \rightarrow *, \overset{!}{\rightarrow} \rightarrow, \rightarrow \rightarrow \}$

Predicates $\pi, \omega ::= \text{Un } \tau \mid \text{SeFun } \tau \mid \text{ShFun } \tau \mid \tau \geq \tau'$

Qualified Types $\rho ::= \tau \mid \pi \Rightarrow \rho$

Type schemes $\sigma ::= \rho \mid \forall t. \sigma$

- $\rightarrow *$: Function type that is separate with its argument
- $\rightarrow \rightarrow$: Function type that is in sharing with its argument
- $\overset{!}{\rightarrow} *, \overset{!}{\rightarrow} \rightarrow$: unrestriced versions of $\rightarrow *$ and $\rightarrow \rightarrow$



Term Variables $x, y, z \in \text{Var}$

Expressions $M, N ::= x \mid \lambda^* x.M \mid \lambda^{\rightarrow} x.M \mid MN \mid \text{let } x = M \text{ in } N$

- $\lambda^* x.M$: Introduces \rightarrow^* function
- $\lambda^{\rightarrow} x.N$: Introduces \rightarrow function

QuB: Typing Environment

- Logic of **BI**: Contexts are trees
- QuB: Contexts are flattened sharing graphs



- Sharing relation Ψ

$\forall_{x \in \text{dom}(\Psi)} x \in \Psi(x)$ (reflexive)

$\forall_{x,y \in \text{dom}(\Psi)} \text{ if } y \in \Psi(x) \text{ then } x \in \Psi(y)$ (symmetric)

$\forall_{x,y,z \in \text{dom}(\Psi)} \text{ if } y \in \Psi(x) \text{ and } z \in \Psi(y) \not\Rightarrow z \in \Psi(x)$ (non-transitive)

QuB: Typing Environment

“ x of type σ is in sharing with \vec{y} ”

$$(x, \sigma, \vec{y}) \in \Gamma$$

Typing Context $\Gamma, \Delta ::= \epsilon \mid \Gamma, x^{\vec{y}} : \sigma$

$$\text{Vars}(\Gamma, x^{\vec{y}} : \tau) = \text{Vars}(\Gamma) \cup \{x\}$$

$$\text{Shared}(\Gamma, x^{\vec{y}} : \tau) = \text{Shared}(\Gamma) \cup \{\vec{y}\}$$

$$\text{Used}(\Gamma) = \text{Vars}(\Gamma) \cup \text{Shared}(\Gamma)$$

$$(\Gamma, x^{\vec{y}} : \tau)^{[a \mapsto \vec{b}]} = \begin{cases} a \notin \vec{y} & (\Gamma^{[a \mapsto \vec{b}]}, x^{\vec{y}} : \tau) \\ a \in \vec{y} & (\Gamma^{[a \mapsto \vec{b}]}, x^{(\vec{y} \setminus a) \cup \vec{b}} : \tau) \end{cases}$$

$$\Gamma^{[\vec{a} \mapsto \vec{b}]} = (\dots ((\Gamma^{[a_1 \mapsto \vec{b}]})^{[a_2 \mapsto \vec{b}]}) \dots)^{[a_n \mapsto \vec{b}]}$$

$$\Gamma \otimes \Gamma' = \Gamma \sqcup \Gamma' \quad \text{if } \text{Vars}(\Gamma) \# \text{Used}(\Gamma') \wedge \text{Vars}(\Gamma') \# \text{Used}(\Gamma)$$

$$\Gamma \oplus \Gamma' = \Gamma \sqcup \Gamma' \quad \text{if } \text{Used}(\Gamma) = \text{Used}(\Gamma')$$

Structural Rules

$$\frac{}{P \mid x^{\vec{y}} : \sigma \vdash x : \sigma} \text{[ID]}$$

$$\frac{P \mid \Gamma \oplus \Delta \oplus \Delta \vdash M : \sigma \quad P \vdash \Delta \text{ un}}{P \mid \Gamma \oplus \Delta \vdash M : \sigma} \text{[CTR-UN]} \quad \frac{P \mid \Gamma \oplus \Delta \oplus \Delta \vdash M : \sigma}{P \mid \Gamma \oplus \Delta \vdash M : \sigma} \text{[CTR-SH]}$$

$$\frac{P \mid \Gamma \vdash M : \sigma \quad P \vdash \Delta \text{ un}}{P \mid \Gamma \oplus \Delta \vdash M : \sigma} \text{[WKN-UN]} \quad \frac{P \mid \Gamma \vdash M : \sigma}{P \mid \Gamma \oplus \Delta \vdash M : \sigma} \text{[WKN-SH]}$$

Connective Rules

$$\frac{P \mid \Gamma \vdash M : \sigma \quad P' \mid \Gamma'_x, x : \sigma \vdash N : \tau}{P \cup P' \mid \Gamma \sqcup \Gamma' \vdash (\text{let } x = M \text{ in } N) : \tau} [\text{LET}]$$

$$\frac{P \mid \Gamma \vdash M : \sigma \quad t \notin \text{fvs}(\Gamma) \cup \text{fvs}(P)}{P \mid \Gamma \vdash M : \forall t. \sigma} [\forall \text{ I}]$$

$$\frac{P \mid \Gamma \vdash M : \forall t. \sigma}{P \mid \Gamma \vdash M : [\tau \backslash t] \sigma} [\forall \text{ E}]$$

$$\frac{P, \pi \mid \Gamma \vdash M : \rho}{P \mid \Gamma \vdash M : \pi \Rightarrow \rho} [\Rightarrow \text{ I}]$$

$$\frac{P \mid \Gamma \vdash M : \pi \Rightarrow \rho \quad P \vdash \pi}{P \mid \Gamma \vdash M : \rho} [\Rightarrow \text{ E}]$$

$$\frac{P \Rightarrow \text{ShFun } \phi \quad P \vdash \Gamma \geq \phi \quad P \mid \Gamma[\emptyset \mapsto \{x\}], x^{\text{Vars}(\Gamma)} : \tau \vdash M : \tau'}{P \mid \Gamma \vdash \lambda^{\rightarrow} x. M : \phi \tau \tau'} [\rightarrow \text{ I}]$$

$$\frac{P \Rightarrow \text{ShFun } \phi \quad P \mid \Gamma \vdash M : \phi \tau \tau' \quad P \mid \Gamma' \vdash N : \tau}{P \mid \Gamma \oplus \Gamma' \vdash MN : \tau'} [\rightarrow \text{ E}]$$

$$\frac{P \Rightarrow \text{SeFun } \phi \quad P \vdash \Gamma \geq \phi \quad P \mid \Gamma, x^{\emptyset} : \tau \vdash M : \tau'}{P \mid \Gamma \vdash \lambda^{*} x. M : \phi \tau \tau'} [* \text{ I}]$$

$$\frac{P \Rightarrow \text{SeFun } \phi \quad P \mid \Gamma \vdash M : \phi \tau \tau' \quad P \mid \Gamma' \vdash N : \tau}{P \mid \Gamma \otimes \Gamma' \vdash MN : \tau'} [* \text{ E}]$$

QuB: Typing Terms

$$\begin{array}{c}
 \frac{}{\emptyset \mid y^{\emptyset} : \tau' \vdash y : \tau'} \text{[ID]} \quad \frac{}{\emptyset \mid x^{\emptyset} : \tau \vdash x : \tau} \text{[ID]} \quad \frac{}{\emptyset \mid f^{\emptyset} : \tau \multimap \tau' \multimap v \vdash f : \tau \multimap \tau' \multimap v} \text{[ID]} \\
 \hline
 \frac{}{\emptyset \mid x^{\emptyset} : \tau \oplus f^{\emptyset} : \tau \multimap \tau' \multimap v \vdash fx : (\tau' \multimap v)} \text{[*E]} \\
 \hline
 \frac{}{\emptyset \mid y^{\emptyset} : \tau' \oplus x^{\emptyset} : \tau \oplus f^{\emptyset} : \tau \multimap \tau' \multimap v \vdash fxy : v} \text{[*E]} \\
 \hline
 \frac{}{\emptyset \mid x^{\emptyset} : \tau \oplus y^{\emptyset} : \tau' \oplus f^{\emptyset} : \tau \multimap \tau' \multimap v \vdash fxy : v} \text{[EXCH]} \\
 \hline
 \frac{}{\emptyset \mid x^{\emptyset} : \tau \oplus y^{\emptyset} : \tau' \vdash \lambda^* f. fxy : (\tau \multimap \tau' \multimap v) \multimap v} \text{[* I]} \\
 \hline
 \frac{}{\emptyset \mid x^{\emptyset} : \tau \vdash \lambda^* y. \lambda^* f. fxy : \tau' \multimap (\tau \multimap \tau' \multimap v) \multimap v} \text{[* I]} \\
 \hline
 \frac{}{\emptyset \mid I \vdash \lambda^* x. \lambda^* y. \lambda^* f. fxy : \tau \multimap \tau' \multimap (\tau \multimap \tau' \multimap v) \multimap v} \text{[=]}
 \end{array}$$

QuB: Typing Terms

$$\begin{array}{c}
 \frac{}{\emptyset \mid y^{xf} : \tau' \vdash y : \tau'} \text{[ID]} \quad \frac{}{\emptyset \mid x^{fy} : \tau \vdash x : \tau} \text{[ID]} \quad \frac{}{\emptyset \mid f^{xy} : \tau \rightarrow \tau' \rightarrow v \vdash f : \tau \rightarrow \tau' \rightarrow v} \text{[ID]} \\
 \hline
 \frac{}{\emptyset \mid x^{xy} : \tau \oplus f^{xy} : \tau \rightarrow \tau' \rightarrow v \vdash fx : (\tau' \rightarrow v)} \text{[* E]} \\
 \hline
 \frac{}{\emptyset \mid y^{xf} : \tau' \oplus x^{yf} : \tau \oplus f^{xy} : \tau \rightarrow \tau' \rightarrow v \vdash fxy : v} \text{[EXCH]} \\
 \frac{}{\emptyset \mid x^{yf} : \tau \oplus y^{xf} : \tau' \oplus f^{xy} : \tau \rightarrow \tau' \rightarrow v \vdash fxy : v} \text{[}\rightarrow \text{I]} \\
 \frac{}{\emptyset \mid x^y : \tau \oplus y^x : \tau' \vdash \lambda^{\rightarrow} f. fxy : (\tau \rightarrow \tau' \rightarrow v) \rightarrow v} \text{[}\rightarrow \text{I]} \\
 \frac{}{\emptyset \mid x^{\emptyset} : \tau \vdash \lambda^{\rightarrow} y. \lambda^{\rightarrow} f. fxy : \tau' \rightarrow (\tau \rightarrow \tau' \rightarrow v) \rightarrow v} \text{[* I]} \\
 \hline
 \emptyset \mid I \vdash \lambda^* x. \lambda^{\rightarrow} y. \lambda^{\rightarrow} f. fxy : \tau * \tau' \rightarrow (\tau \rightarrow \tau' \rightarrow v) \rightarrow v
 \end{array}$$

Term structure \leftrightarrow Typing Rule

QuB: Syntax Directed Typing Rules

$$\frac{P \vdash \Gamma_{\bar{y}} \text{ un} \quad (P \Rightarrow \tau) \sqsubseteq \sigma}{P \mid \Gamma, x^{\bar{y}} : \sigma \vdash^s x : \tau} [\text{VAR}^s]$$

$$\frac{Q \mid (\Gamma'_x \oplus \Gamma''_x) \otimes \Delta \vdash^s M : v \quad P \vdash \Delta \text{ un} \quad P \mid (\Gamma_x, x^{\emptyset} : \sigma) \oplus \Gamma''_x \otimes \Delta \vdash^s N : \tau \quad \sigma = \text{Gen}(\{\Gamma' \oplus \Gamma''_x \otimes \Delta\}, Q \Rightarrow v)}{P, Q \mid (\Gamma \otimes \Gamma') \oplus \Gamma'' \otimes \Delta \vdash^s (\text{let } x = M \text{ in } N) : \tau} [\text{Let}^s]$$

$$[\text{VAR}^s] \equiv [\text{ID}] + [\forall E] + [\Rightarrow E]$$

$$[\text{LET}^s] \equiv [\text{LET}] + [\forall I] + [\Rightarrow I]$$

QuB: Syntax Directed Typing Rules

$$\frac{P \Rightarrow \text{SeFun } \phi \quad P \vdash \Gamma \geq \phi \quad P \mid \Gamma \otimes x^{\emptyset} : \tau \vdash^s M : v}{P \mid \Gamma \vdash^s \lambda^{*} x. M : \phi \tau v} \quad [*I^s] \quad \frac{P \Rightarrow \text{ShFun } \phi \quad P \vdash \Gamma \geq \phi \quad P \mid \Gamma[\emptyset \mapsto \{x\}] \oplus x^{\text{Vars}(\Gamma)} : \tau \vdash^s M : v}{P \mid \Gamma \vdash^s \lambda^{\rightarrow} x. M : \phi \tau v} \quad [\rightarrow I^s]$$

$$\frac{P \mid \Gamma \otimes \Delta \vdash^s M : \phi v \tau \quad P \mid \Gamma' \otimes \Delta \vdash^s N : v \quad P \vdash \Delta \text{ un} \quad (\Gamma \tilde{\oplus} \Gamma' \wedge (P \Rightarrow \text{ShFun } \phi)) \vee (\Gamma \tilde{\otimes} \Gamma' \wedge (P \Rightarrow \text{SeFun } \phi))}{P \mid \Gamma \sqcup \Gamma' \otimes \Delta \vdash^s MN : \tau} \quad [\text{App}^s]$$

Context Operations

$$\Gamma \tilde{\otimes} \Delta = \text{Used}(\Gamma) \# \text{Vars}(\Delta) \wedge \text{Used}(\Delta) \# \text{Vars}(\Gamma)$$

$$\Gamma \tilde{\oplus} \Delta = \text{Used}(\Gamma) = \text{Used}(\Delta)$$

$$[\rightarrow I] \equiv [\rightarrow I] \quad [*I] \equiv [*I]$$

$$[\text{APP}^s] \equiv [\rightarrow E] + [*E]$$

Theorem (Soundness of \vdash^s)

If $P \mid \Gamma \vdash^s M : \tau$ then $P \mid \Gamma \vdash M : \tau$

Theorem (Completeness of \vdash^s)

If $P \mid \Gamma \vdash M : \sigma$ then $\exists Q, \tau$ such that $Q \mid \Gamma \vdash^s M : \tau$ and $(P \mid \sigma) \sqsubseteq \text{Gen}(\Gamma, Q \Rightarrow \tau)$

Original Type System \equiv Syntax Directed Typing Rules

Proof in Original Type System \equiv Proof in Syntax Directed Typing Rules

$$\boxed{\mathcal{M}(S, \Psi, \Gamma \vdash M : \tau) = P, S', \Sigma, \Psi'}$$

$$\begin{aligned} \mathcal{M}(S, \Psi, \Gamma \vdash x : \tau) &= ([\vec{u}/\vec{t}]P), S' \circ S, \{x\}, \Psi \\ \text{where} \quad (x : \forall \vec{t}. P \Rightarrow v) &\in S\Gamma \\ S' &= \mathcal{U}([\vec{u}/\vec{t}]v, S\tau) \end{aligned}$$

$$\begin{aligned} \mathcal{M}(S, \Psi, \Gamma \vdash \lambda^{\rightarrow} x. M : \tau) &= \{P \cup Q\}, S', \Sigma \setminus x, \Psi'' \\ \text{where} \quad P; S'; \Sigma; \Psi' &= \mathcal{M}(\mathcal{U}(\tau, u_1 u_2 u_3) \circ S, \Psi, \Gamma, x : u_2 \vdash M : u_3) \\ \Psi'' &= \{\forall_{y \in \text{dom}(\Psi')}. \Psi'(y) + x\} \cup \{(x, \{y \mid y \in \text{dom}(\Gamma)\})\} \\ Q &= \{\text{ShFun } u_1\} \cup \text{Leq}(u_1, \Gamma \upharpoonright_{\Sigma}) \cup \text{Weaken}(x, u_2, \Sigma, \Psi'') \end{aligned}$$

$$\begin{aligned} \mathcal{M}(S, \Psi, \Gamma \vdash \lambda^* x. M : \tau) &= \{P \cup Q\}, S', \Sigma \setminus x, \Psi'' \\ \text{where} \quad P; S'; \Sigma; \Psi' &= \mathcal{M}(\mathcal{U}(\tau, u_1 u_2 u_3) \circ S, X; \Gamma, x : u_2 \vdash M : u_3) \\ \Psi'' &= \Psi' \cup \{(x, \{x\})\} \\ Q &= \{\text{SeFun } u_1\} \cup \text{Leq}(u_1, \Gamma \upharpoonright_{\Sigma}) \cup \text{Weaken}(x, u_2, \Sigma, \Psi'') \end{aligned}$$

$$\mathcal{M}(S, \Psi, \Gamma \vdash M : \tau) = P, S', \Sigma, \Psi'$$

$$\mathcal{M}(S, \Psi, \Gamma \vdash MN : \tau) = \{P \cup P' \cup Q\}, R', \Sigma \cup \Sigma', \Psi''$$

$$\text{where } P; R; \Sigma; \Psi' = \mathcal{M}(S, \Psi, \Gamma \vdash M : u_1 u_2 \tau)$$

$$P'; R'; \Sigma'; \Psi'' = \mathcal{M}(SR, \Psi', S\Gamma \vdash N : u_2)$$

$$\text{if } \mathcal{C}(\Gamma, \Psi'', \Sigma) = \mathcal{C}(\Gamma, \Psi'', \Sigma')$$

$$\text{then } Q = \{\text{ShFun } u_1\}$$

$$\text{else if } (\Sigma \# \mathcal{C}(R\Gamma, \Psi'', \Sigma') \text{ and } \Sigma' \# \mathcal{C}(R\Gamma, \Psi'', \Sigma))$$

$$\text{then } Q = \{\text{SeFun } u_1\}$$

$$\mathcal{M}(S, \Psi, \Gamma \vdash \text{let } x = M \text{ in } N : \tau) = (P \cup Q), R', \Sigma \cup \{\Sigma' \setminus x\}, \Psi''$$

$$\text{where } P; R; \Sigma; \Psi' = \mathcal{M}(S, \Psi, \Gamma \vdash M : u_1)$$

$$\sigma = \text{GenI}(R\Gamma; R(P \Rightarrow u_1))$$

$$P'; R'; \Sigma'; \Psi'' = \mathcal{M}(R, \Psi', \Gamma, x : \sigma \vdash N : \tau)$$

$$Q = \text{Un}(\Gamma|_{\Sigma \cap \Sigma'}) \cup \text{Weaken}(x, \sigma, \Sigma', \Psi'')$$

Theorem (Soundness of \mathcal{M})

if $\mathcal{M}(S, \Psi, \Gamma \vdash M : \tau) = P, S', \Sigma, \Psi'$ then $S'P \mid S'(\Gamma|_{\Sigma}) \vdash M : S'\tau$

Algorithm \mathcal{M} \rightarrow Type system

Examples: Basic Structures

- Multiplicative Product

$$\begin{aligned}\tau \otimes \tau' &= \tau \multimap \tau' \multimap (\tau \multimap \tau' \multimap v) \multimap v \\ (,) &= \lambda^* x. \lambda^* y. \lambda^* f. fxy\end{aligned}$$

- Additive Product

$$\begin{aligned}\tau \& \tau' &= \tau \multimap \tau' \multimap (\tau \multimap \tau' \multimap v) \multimap v \\ (;) &= \lambda^* x. \lambda^{\multimap} y. \lambda^{\multimap} f. fxy\end{aligned}$$

- Sums

$$\begin{aligned}\tau \oplus \tau' &= (\tau \rightarrow v) \rightarrow (\tau' \rightarrow v) \rightarrow v \\ \text{case } c \text{ of } \{f; g\} &= \lambda^* c. \lambda^{\multimap} f. \lambda^{\multimap} g. c f g\end{aligned}$$

$$\text{inl} : \tau \multimap (\tau \oplus \tau')$$

$$\text{inr} : \tau' \multimap (\tau \oplus \tau')$$

$$\text{inl} = \lambda^* x. \lambda^{\multimap} f. \lambda^{\multimap} g. f x$$

$$\text{inr} = \lambda^* y. \lambda^{\multimap} f. \lambda^{\multimap} g. g y$$

- User defined types and type classes

- User defined types and type classes
- Kind System with type constructors

Type Variables $t, u \in \text{Type Variables}$

Kinds $\kappa ::= \star \mid \kappa' \rightarrow \kappa$

Types $\tau^\kappa ::= t^\kappa \mid T^\kappa \mid \tau^{\kappa' \rightarrow \kappa} \tau^{\kappa'}$

Type Constructors $T^\kappa \in \mathcal{T}^\kappa$ where $\{\otimes, \&, \oplus, \frac{1}{\ast}, \ast, \multimap, \Rightarrow\} \subseteq \mathcal{T}^{\star \rightarrow \star \rightarrow}$

Predicates $\pi, \omega ::= \text{Un } \tau \mid \text{SeFun } \tau \mid \text{ShFun } \tau \mid \tau \geq \tau'$

Qualified Types $\rho ::= \tau^\star \mid \pi \Rightarrow \rho$

Type schemes $\sigma ::= \rho \mid \forall t. \sigma$

Conclusion and Future Work

What next?

Thank You!

Q & A

- [1] Amal Ahmed, Matthew Fluet, and Greg Morrisett. L^3 : A linear language with locations. *Fundamenta Informaticae*, 77(4):397–449, 2007.
- [2] Jean-Philippe Bernardy, Mathieu Boespflug, Ryan R. Newton, Simon Peyton Jones, and Arnaud Spiwack. Linear haskell: Practical linearity in a higher-order polymorphic language. *Proc. ACM Program. Lang.*, 2:5:1–5:29, 2017.
- [3] Jean-Yves Girard. Linear logic. *Theoretical Computer Science*, 50(1):1–101, 1987.
- [4] Mark P. Jones. A theory of qualified types. *Science of Computer Programming*, 22(3):231 – 256, 1994.
- [5] Sheng Liang, Paul Hudak, and Mark Jones. Monad transformers and modular interpreters. In *Proceedings of the 22Nd ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '95, pages 333–343. ACM, 1995.

- [6] Karl Mazurak and Steve Zdancewic. Lollipop: To concurrency from classical linear logic via curry-howard and control. In *Proceedings of the 15th ACM SIGPLAN International Conference on Functional Programming*, ICFP '10, pages 39–50. ACM, 2010.
- [7] J. Garrett Morris. The best of both worlds: Linear functional programming without compromise. In *Proceedings of the 21st ACM SIGPLAN International Conference on Functional Programming*, ICFP 2016, pages 448–461. ACM, 2016.
- [8] Peter W. O'Hearn. On bunched typing. *Journal of functional Programming*, 13(4):747–796, 2003.
- [9] Peter W. O'Hearn and David J. Pym. The logic of bunched implications. *The Bulletin of Symbolic Logic*, 5(2):215–244, 1999.

- [10] Philip Wadler. A taste of linear logic. In Andrzej M. Borzyszkowski and Stefan Sokolowski, editors, *Mathematical Foundations of Computer Science 1993: 18th International Symposium, MFCS'93 Gdańsk, Poland, August 30–September 3, 1993 Proceedings*, pages 185–210. Springer Berlin Heidelberg, 1993.