

QuB

A Resource Aware Functional Programming Language

Apoorv Ingle

The University of Kansas

Table of Contents

- 1 Introduction and Motivation
- 2 Background Work
- 3 QuB
- 4 Examples
- 5 Conclusion and Future Work

- Hard problem: Resource Management in evolving production code
- Resources: Files, database connections, anything that represents a shared state in the program

- Modified File Handling API

```
openFile :: FilePath → IO FileHandle
```

```
closeFile :: FileHandle → IO ()
```

```
readLine :: FileHandle → IO (String, FileHandle)
```

```
writeFile :: String    → FileHandle  
           → IO ((), FileHandle)
```

```
upper    :: String    → String
```

- File Handling

```
do f ← openFile "sample.txt"  
    (s, f) ← readLine f  
    let c = upper s  
    ((), f) ← writeLine f c  
    .  
    .  
    .  
    () ← closeFile f
```

- File Handling Gone Wrong (Part I)

```
do f ← openFile "sample.txt"
    (s, f) ← readLine f
    let c = upper s
    ((), f) ← writeLine f c
    .
    .
    .
    () ← closeFile f
    .
    .
    .
    () ← closeFile f
    return c
```

- File Handling Gone Wrong (Part I)

```
do f <- openFile "sample.txt"
    (s, f) <- readLine f
    let c = upper s
    ((), f) <- writeLine f c
    .
    .
    .
    () <- closeFile f
    .
    .
    .
    () <- closeFile f
    return c
```

- File is closed twice: Run time crash

- File Handling Gone Wrong (Part II)

```
do f ← openFile "sample.txt"  
    (s, f) ← readLine f  
    let c = upper s  
    ((), f) ← writeLine f c  
    .  
    .  
    .  
return c
```


- File Handling Gone Wrong (Part II)

```
do f ← openFile "sample.txt"
    (s, f) ← readLine f
    let c = upper s
    ((), f) ← writeLine f c
    .
    .
    .
    return c /*File not closed!!*/
```

- File not closed: Memory leak

- `MonadError`[5] in Haskell

```
class Monad m => MonadError e m | m -> e where  
    throwError :: e -> m a  
    catchError :: m a -> (e -> m a) -> m a
```

- `throwError` starts exception processing
- `catchError` exception handler

- MonadError in Haskell

```
do f ← openFile "sample.txt"
  ((s, f) ← readLine f
   let c = upper s
   () ← closeFile f
   return $ Right c) `catchError` (\_ →
                                   return $ Left "Error in reading file")
```

- Execution path for exception 🐞 file not closed 🐞 Memory leak

'Well typed programs do not go wrong.'

Robin Milner

'Well typed programs do not go wrong.'

Robin Milner

- Can we do better? Can types guide us?

Hinley-Milner (**HM**) type system Algorithm $\mathcal{M}[1]$ Algorithm $\mathcal{W}[4]$

Curry Howard Correspondence:

HM type system is equivalent to second order propositional logic.
Propositions are not Resources.

Background Work

Substructural Logics: Make structural rules explicit

Background Work

Linear Logic[2, 8]

restrict weakening and contraction

Propositions act like resources

- Modality !
- Additive pair: $\&$
- Multiplicative pair: $\otimes \multimap$
- \oplus

Theory of qualified types: Polymorphism using Predicates **HM**[3]

Quill: Linear Logic using with Qualified Types[6]

Logic of Bunched Implications (**BI**)[7]

- Sharing implication \rightarrow
- Separating implication \multimap

QuB Core Language: Syntax and Types

Multiplicative Products

Additive Products

Multiplicative Implication

Additive Implication

Conclusion and Future Work

Thank You!

Q & A

References I

- [1] Luis Damas and Robin Milner. Principal type-schemes for functional programs. In *Proceedings of the 9th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '82, pages 207–212. ACM, 1982.
- [2] Jean-Yves Girard. Linear logic. *Theoretical Computer Science*, 50(1):1–101, 1987.
- [3] Mark P. Jones. A theory of qualified types. *Science of Computer Programming*, 22(3):231 – 256, 1994.
- [4] Oukseh Lee and Kwangkeun Yi. Proofs about a folklore let-polymorphic type inference algorithm. *ACM Trans. Program. Lang. Syst.*, 20(4):707–723, 1998.
- [5] Sheng Liang, Paul Hudak, and Mark Jones. Monad transformers and modular interpreters. In *Proceedings of the 22Nd ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '95, pages 333–343. ACM, 1995.

- [6] J. Garrett Morris. The best of both worlds: Linear functional programming without compromise. In *Proceedings of the 21st ACM SIGPLAN International Conference on Functional Programming, ICFP 2016*, pages 448–461. ACM, 2016.
- [7] Peter W. O’Hearn and David J. Pym. The logic of bunched implications. *The Bulletin of Symbolic Logic*, 5(2):215–244, 1999.
- [8] Philip Wadler. A taste of linear logic. In Andrzej M. Borzyszkowski and Stefan Sokolowski, editors, *Mathematical Foundations of Computer Science 1993: 18th International Symposium, MFCS’93 Gdańsk, Poland, August 30–September 3, 1993 Proceedings*, pages 185–210. Springer Berlin Heidelberg, 1993.