

Eberhard Karls Universität Tübingen
Mathematisch-Naturwissenschaftliche Fakultät
Wilhelm-Schickard-Institut für Informatik

Master Thesis Informatik

Investigations on Backbone Computation

Jonas Bollgrün

September 23, 2019

First Examiner

Prof. Dr. Wolfgang Küchlin
Wilhelm-Schickard-Institut für Informatik
Arbeitsbereich Symbolisches Rechnen
Universität Tübingen

Second Examiner

Prof. Dr. Michael Kaufmann
Wilhelm-Schickard-Institut für Informatik
Arbeitsbereich Algorithmen
Universität Tübingen

Supervisor

Dr. Thore Kübart
Steinbeis-Transferzentrum Objekt-
und Internet-Technologien an der
Universität Tübingen

Bollgrün, Jonas:

Investigations on Backbone Computation

Master Thesis Informatik

Eberhard Karls Universität Tübingen

Processing Period: April 1st - September 30th

Selbstständigkeitserklärung

Hiermit versichere ich, dass ich die vorliegende Masterarbeit selbständig und nur mit den angegebenen Hilfsmitteln angefertigt habe und dass alle Stellen, die dem Wortlaut oder dem Sinne nach anderen Werken entnommen sind, durch Angaben von Quellen als Entlehnung kenntlich gemacht worden sind. Diese Masterarbeit wurde in gleicher oder ähnlicher Form in keinem anderen Studiengang als Prüfungsleistung vorgelegt.

Jonas Bollgrün (Matrikelnummer 3353424), September 23, 2019

Abstract

This thesis is meant as an overview on the computation of backbones of propositional formulas in conjunctive normal form, being a problem situated in the domain of SAT solving. An introduction into this general domain is given to allow understanding without deep prior knowledge of the field. Various algorithms, which are grouped into approaches on the problem, are listed and subsequently also methods on how to improve these algorithms. A special emphasis is given on the concept of preferences, where underlying SAT solving algorithms are guided in their search to speed up the computation of backbones. Various methods are proposed to resolve performance issues of the preferences approach and subsequently tested on multiple benchmarks of varying difficulty to verify their effectiveness. In closing, using an in-depth analysis of the results, specialized backbone algorithms for some of the same benchmarks are constructed.

Contents

1	Introduction	13
1.1	Disambiguation	13
1.1.1	Terminology	13
1.1.2	CDCL	14
2	Base Algorithms	19
2.1	Enumeration algorithms	19
2.1.1	Model Enumeration	19
2.1.2	Upper Bound Reduction	19
2.2	Iterative algorithms	21
2.2.1	Testing every literal	21
2.2.2	Combining with Enumeration	21
2.3	Preferences	23
2.4	Further approaches	24
3	Optimizations	27
3.1	Model Reduction	27
3.1.1	Prime Implicant	27
3.1.2	Rotations	29
3.2	Cheap Identification of backbone literals	30
3.2.1	Axiomatic literals	30
3.2.2	Unit Implication	31
3.2.3	Implication through Cooccurrence	32
3.3	Assumptions	32
4	Experiments with Preferences	35
4.1	Tested modifications	35
4.1.1	Forgetting preferences	35
4.1.2	Subsets	36
4.1.3	Nudging	36
4.1.4	Approaching lower and upper bounds	37
4.2	Implementation notes for Sat4J	37
5	Results	39
5.1	Tested Backbone algorithms	39
5.2	SAT Competition Benchmark	40
5.2.1	Importance of reusing learned clauses	41

Contents

5.2.2	Benefits of unit implication	42
5.2.3	Effect of subset preferences	43
5.2.4	Duration of last SAT call	44
5.2.5	Benefits of forgetting preferences	45
5.3	Industrial benchmark	46
5.3.1	Performance measurement and Discussion	47
5.3.2	Specialized algorithm	48
5.3.3	Efficiency over all assumptions	49
5.4	Second Industrial benchmark	51
6	Conclusion	53

List of Tables

3.1	Comparison of number of backbone literals identified through cooccurrence in comparison to the number identified through unit implication and the overall number of backbone literals in the formula. . .	32
5.1	Averages of 64 testfiles taken from sat competitions. The columns indicate: The full time that the calculation took in seconds; The time that was spent in the sat solver; The time that the last sat computation took; The number of sat calls (all values are averages).	40
5.2	Backbone computation time of the <i>IBB</i> algorithm, once with keeping learned clauses (t_{keep}) and once discarding learned clauses between every sat call($t_{discard}$)	41
5.3	Benchmark results for a selection of files with a focus on the benefit of unit implication. Rows indicate: Calculation time and number of SAT calls for the <i>BB</i> solver ; Calculation time, time spent in SAT solver and number of SAT calls for the <i>KBB</i> solver ; Number of backbone literals identified through unit implication (in <i>KBB</i>) ; Number of backbone variables in formula.	42
5.4	Ratio between the average duration of a SAT call and the duration of the last SAT call. Calculation is based on the values in table 5.1	43
5.5	Average of the complete backbone computation for variants of <i>PrefBones</i> with and without forgetting preferences.	45
5.6	Performance results for computation of the backbone of a product formula. Values are not averaged, but summed up over 407 different executions, each with a different assumption.	46
5.7	Results of specialized backbone algorithm on product formula benchmark.	48
5.8	Second Industrial benchmark. Values are not averaged, but summed up over 948 different benchmarks.	51
5.9	Preptime and number of learned clauses	52

List of Algorithms

1	CDCL ALGORITHM	17
2	ENUMERATION-BASED BACKBONE COMPUTATION	19
3	ITERATIVE ALGORITHM WITH COMPLEMENT OF BACKBONE ESTIMATE	20
4	ITERATIVE ALGORITHM (TWO TESTS PER VARIABLE)	21
5	ITERATIVE ALGORITHM (ONE TEST PER VARIABLE)	22
6	BB-PREF: BACKBONE COMPUTATION USING PREF-SAT	24
7	BB-PREF: BACKBONE COMPUTATION USING PREF-SAT AND BLOCKING CLAUSE	25
8	BASE APPROACH TO COMPUTE A PRIME IMPLICANT	28
9	LITERAL ROTATION IN MODELS	30
10	SPECIALIZED ALGORITHM FOR INDUSTRIAL APPLICATION	49
11	FUNCTION $required(M, F, bb_l)$	49

1 Introduction

Imagine a discussion about a certain issue where the case gets complicated by the fact that the two parties cannot even agree on factual real world data, but can at least both agree on logical relationships between certain hypothetical concepts that may or may not be the case. In this case, you have the opportunity to set up a boolean formula that expresses the issue, with one all deciding boolean variable that decides who of the parties is right. If one of the parties should be lucky, it will turn out that it would actually be impossible that that formula would judge in favor of their opponent, no matter what the facts were, as long as the formula itself was correctly stated and applied. For this you would calculate the backbone of the formula and simply check whether it contained the all deciding variable with either positive or negative assignment.

TODO introduction wofür brauche ich backbones

wer hat sich damit beschäftigt

welche paper waren relevant

wie ist die thesis strukturiert,

was wurde in den sechs monaten gemacht

use cases von backbones: - formel reduktion um fixe variablen -

hab prefbones erfunden

haben prefbones paper rausgesucht

was kann ich mit prefbones noch so anstellen

wie sehen die praktischen nutzen der prefbones varianten aus.

introduction soll aus perspektive vor dem schreiben geschrieben werden (absichten)

extra chap mit related work nutzen für endnutzer und wirtschaft.

1.1 Disambiguation

1.1.1 Terminology

This thesis is an investigation on the calculation of backbones for boolean formulas in conjunctive normal form (or CNF in short). A CNF formula F is a conjunction of a set of clauses $C(F)$, meaning that all of these clauses have to be satisfied to satisfy the formula. A clause c in turn is a disjunction of a set of literals, meaning at least one of said literals must be fulfilled. A literal l can be defined as the occurrence of a boolean variable v which may or not be negated and to fulfill such a literal, its variable must be assigned \perp for negated literals and \top for those literals without negation. The same variable can occur in multiple clauses of the same formula but must have the

same assignment in all occurrences, either (\perp) or (\top). A complete assignment of all variables of F (written as $Var(F)$) that leads to the formula being fulfilled is called a model. A formula for which no model can be found is called unsatisfiable. Any set of assignments that is sufficient to satisfy a formula is called an implicant and if has no subset that isn't itself an implicant it is called a prime implicant. The variables that do not occur in an implicant are called optional.

When we want to know whether a model M satisfies a formula F , clause c or literal l , we write $F\langle M \rangle \rightarrow \{\top, \perp\}$ or $c\langle M \rangle$ and $l\langle M \rangle$ respectively. The result is \top if the assignment satisfies what it is applied to or \perp if it doesn't.

The exact terminology can differ depending on the paper and project that you read. A formula can be called a problem and the assignment of a variable can be called it's phase. Sometimes assignment and literal are used interchangeably, as they both consist of a variable and a boolean value. Clauses can also be called constraints and sometimes sentences. A synonym for a formula, clause or literal being fulfilled is it being satisfied. Models can also be called solutions of formulas. The terminology for \top or \perp can be (T, F) , $(true, false)$ or $(1, 0)$.

The backbone is a formula specific set of literals that contains all literals that occur in every model of said formula. We can also say that a variable is not part of the backbone, if neither it's positive or it's negative assignment is in the backbone. If we have an unsatisfiable formula, it's backbone can be considered undefinable, which is why this thesis concerns itself only with satisfiable CNF formulas.

For the context of CNF formulas, on which this thesis focuses, the term "subsumption" should to be explained. A clause c_1 subsumes another clause c_2 of the same formula, if and only if $c_1 \subseteq c_2$, in prose if all the literals that occur in c_1 also occur in c_2 ¹. If c_1 subsumes c_2 in formula F then this means that you can remove c_2 from F because in terms of satisfying models, $F \setminus \{c_2\}$ is equivalent to F as $\{c_1\}$ is equivalent to $\{c_1, c_2\}$. This is because in this case an assignment that satisfies c_1 also satisfies c_2 automatically. There is no possible assignment that satisfies clause c_1 that doesn't satisfy it's subsuming clause c_2 .

A program that determines whether a boolean formula is satisfiable or not is called a *SAT solver*. Typically this is done by finding a model for said formula.

1.1.2 CDCL

All the methods to generate a backbone of a formula F that are described in this thesis essentially rely on calculating various models of F , so it makes sense to describe a method to do that in depth. The current state-of-the-art algorithm to do this is the *Conflict Driven Clause Learning* algorithm, or *CDCL* for short. This algorithm was

¹ One can filibuster whether c_1 would have to be a true subset of c_2 . If a formula has two occurrences of the exact same clause, then one of the occurrences would be redundant, so the same rule could be applied here as well. In practice it makes more sense to filter out duplicates of clauses before running any computation on the formula. Similarly, you can safely drop all clauses where both literals of the same variable occur, as that clause would be satisfied in each and every possible model.

first published as “GRASP” in [SS96]. An earlier algorithm for the SAT problem, which CDCL is essentially based upon is the DPLL algorithm [DLL62] published in 1962. However for this thesis I worked with the CDCL implementation available in the *Sat4J* library that is heavily based on *MiniSAT* which you can read about in [ES03a].

In this algorithm, a so-called *CDCL table* is used as a special dataset, to store the state of the SAT solver. This table, which behaves like a stack, stores the succession of assignments with four values for each assignment.

- The *level* of the assignment. This level increases with each decision and starts at 0, where unit assignments before any decision are stored.
- The affected variable.
- The value that the variable was assigned to.
- The reason for the assignment. This can be one of two cases, either *Unit* or *Decision*.

Unit assignments happen, when a clause has all but one of its literals unsatisfied. Since all clauses have to be satisfied for a CNF formula to be satisfied, that last literal must be assigned a value that satisfies it and its clause. Entries in the CDCL table that refer to a unit assignment also store a reference to the clause that required the assignment. A clause that fulfills the above condition and requires an assignment can be called a *unit clause* or that it *is unit*.

Decisions happen when no clause is in the unit state. In theory, in this case you are free to pick any variable and assign it either \top or \perp .

The purpose of unit assignments is to reduce the search space. The solving process for a formula can be modeled as the traversal of a search tree, where each node corresponds to an individual assignment and every leaf node to a complete assignment that might be satisfying or not². However, given that you can stop to search once a single clause is unsatisfied, you can disqualify many branches of the tree early, for example when the assignments in your tree path so far require some additional assignment for some clause, which would be a *unit clause*. Going the other way in the tree at that particular node will never result in a satisfying model.

The solver will now fill the table with assignments, unit assignments if possible or decisions otherwise, until one of two things happens. Either the formula became satisfied³ in which case we can return the assignments that are stored in the table.

The other possibility is that you run into a contradiction. Here a unit clause requires that a variable is assigned a value b , but it is already assigned $\neg b$. If the assignments have a reason (a unit clause), then some of the variables in these clauses

² Sadly the size of such a tree makes it impractical to actually implement SAT solving like this.

³ In this case only an implicant is returned. If you want a complete model, you can keep making decisions until all variables are assigned and return the assignments after that. However once you have an implicant, you are free to assign the remaining variables to anything you want, as the formula is already satisfied and further assignments cannot change that.

must be assigned differently (since they were unit then), so we can connect the reasons for our conflict to other assignments. Repeating this we sometimes meet decisions instead of unit clauses as reason. Collecting these decisions, we end with the precise combination of assignment decisions that resulted in the conflict.

$F := \{(\neg c), (a, e), (b, \neg d), (b, c, d)\}$

Level	Var	Value	Reason
0	c	\perp	$\{\neg c\}$
1	a	\perp	Decision
1	e	\top	$\{a, e\}$
2	b	\perp	Decision
2	d	\perp	$\{b, \neg d\}$
2	d	\top	$\{b, c, d\}$




Figure 1.1: Example of a resolution. Shown is a formula, the content of the CDCL table at the point of conflict in variable d and the resolution graph.

This process of following assignments through their reasons is called *resolution* and can be briefly explained with the following formula:

$$r_\lambda(c_1, c_2) = (c_1 \setminus \{\lambda\}) \cup (c_2 \setminus \{\neg\lambda\})$$

The resolvent r consists of all literals of the two clauses that are resolved, where in this case c_1 contains λ and c_2 contains $\neg\lambda$. This precondition is given in this case, because c_1 is the reason for the assignment of λ to \top and c_2 the reason for assigning λ to \perp .

Figure 1.1 shows this with an example, where a conflict in variable d happened. First the clauses $\{b, \neg d\}$ and $\{c, b, d\}$ are resolved over the variable d . Then b is extracted for the learned clause, as it's reason was a decision and not a unit clause. Finally $\{c\}$ and $\{\neg c\}$ are resolved over c , resulting in the empty set. The learned clause is $\{b\}$. An alternative resolution scheme would leave literals that stem from decisions in the working set until the end, but here they are extracted on first extraction. Otherwise, these literals would be inspected multiple times.

Once collected, this set of decisions must be taken back, by reversing the assignments up until the first of these decisions, as this path through the search tree results in a conflict and will not end in models.

We also add the clause to our formula as a *learned clause*. This clause serves to prevent the particular combination of assignments that led to our conflict. The resulting formula will still be completely equivalent to before. It merely stores the information that we gained through analysis of our conflict to prevent it from happening again.

However it is also possible that we end up with reasons for assignments that do not end in a decision. This would mean that all reasons were axiomatic assignments, for example when a formula contains a clause with only a single literal in it⁴. In this case the formula implies a contradiction and the clause that we would learn from this would be empty, unsatisfiable.

Concerning the decisions, depending on the particular formula, it is possible that some assignments make it easier to solve the formula than others and some decisions

⁴A simple example: A formula contains the two clauses $\{a\}$ and $\{\neg a\}$. Resolving these two results in the empty set.

Algorithm 1: CDCL ALGORITHM

Input: A formula F in CNF**Output:** A CDCL table which implies an implicant for F , or \perp if F is not satisfiable

```

1  $level \leftarrow 0$ 
2  $table \leftarrow emptyList$ 
3 while 1 do
4    $table.pushAll(F.getUnits())$ 
5   if  $\exists$  conflicting assignment then
6     if  $level = 0$  then
7        $\perp$  return  $\perp$ 
8     else
9        $level \leftarrow backtrackAndLearn(F, table)$ 
10  else if  $F$  is fulfilled then
11     $\perp$  return  $table$ 
12  else
13     $level++$ 
14     $l \leftarrow any\ free\ variable$ 
15     $l.assign(either\ \top\ or\ \perp)$ 
16     $table.pushDecision(l)$ 

```

might lead to a completely unsatisfied clause. A lot of research has been done to prevent this by setting up heuristics that try to pick a variable and corresponding assignment that would lead to a satisfying model without complications. A typical heuristic would be to measure the activity of a variable, which is an estimate of how often it was involved in conflicts. The heuristic would then always pick the variable with the lowest activity, since it would most likely be unproblematic to assign one or the other value to it. To choose the boolean value that should be assigned to it, a good strategy can be to remember the value that each variable was assigned to on the last occasion and this time give it the opposite one. When a variables assignment is removed through conflict resolution, going in the complete opposite direction with the assignments has a good chance to work out better.

As is usually done in literature, calls to SAT solvers such as CDCL in code listings are written as $(outc, v) = SAT(F)$. Here, two values are returned. *outc* is a boolean value that simply states whether *F* was satisfiable to begin with. Only if it equals to \top , the second return parameter *v* can have a meaningful value, which would be the model that was found and satisfies *F*. In some of the algorithms listed in this thesis, one of the return parameters is not used at all. In that case I write $(_, v) = SAT(F)$ or $(outc, _) = SAT(F)$ to indicate that either *outc* or *v* is discarded.

2 Base Algorithms

The backbone algorithms that I investigated for this thesis can be grouped very broadly into two approaches, which I will describe in the following two sections.

2.1 Enumeration algorithms

2.1.1 Model Enumeration

A simple definition of the backbone is that it is the intersection of all models of it's formula. If a literal is not part of the backbone, there must exist a model that contains the negation of that literal. Therefore if we had a way to iterate over every single model of the formula and, starting with the set of both literals for every variable and removing every literal from that set that was missing in one of these models, that set would end up being the backbone of the formula. [MSJL10] as well as [MSJL15] list an algorithm that does exactly this.

Algorithm 2: ENUMERATION-BASED BACKBONE COMPUTATION

Input: A satisfiable formula F

Output: Backbone of F , v_r

```
1  $v_r \leftarrow \{x|x \in \text{Var}(F)\} \cup \{\neg x|x \in \text{Var}(F)\}$ 
2 while  $v_r \neq \emptyset$  do
3    $(\text{outc}, v) \leftarrow \text{SAT}(F)$ 
4   if  $\text{outc} = \perp$  then
5      $\text{return } v_r$ 
6    $v_r \leftarrow v_r \cap v$ 
7    $\omega_B \leftarrow \bigvee_{l \in v} \neg l$ 
8    $F \leftarrow F \cup \omega_B$ 
9 return  $v_r$ 
```

Here, found models are prevented from being found again by adding a blocking clause of said model and the algorithm terminates once all models are prohibited and the formula became unsatisfiable through this.

2.1.2 Upper Bound Reduction

Clearly, calculating every single model of a formula leaves room for optimization. Most models of a common boolean formula differ by small, independent differences

that can just as well occur in other models. Therefore the intersection of only a handful of models can suffice to result in the backbone, as long as these models are chosen to be as different as possible. This was achieved in [MSJL15] as is described in algorithm 3.

Algorithm 3: ITERATIVE ALGORITHM WITH COMPLEMENT OF BACKBONE ESTIMATE

Input: A satisfiable formula F
Output: Backbone of F , v_r

```

1  $(outc, v_r) \leftarrow SAT(F)$ 
2 while  $v_r \neq \emptyset$  do
3    $bc \leftarrow \bigvee_{l \in v_r} \neg l$ 
4    $(outc, v) \leftarrow SAT(F \cup \{bc\})$ 
5   if  $outc = \perp$  then
6     return  $v_r$ 
7    $v_r \leftarrow v_r \cap v$ 
8 return  $v_r$ 

```

It generates an upper bound v_r of the backbone by intersecting found models and inhibits this upper bound instead of individual models. This blocking clause is much more powerful, because it enforces not only that a new model is found, but also that this new model will reduce the upper bound estimation of the backbone in each iteration.

This is because what remains after the intersection of a handful of models, are the assignments that were the same in all these models and from that we make a blocking clause that prohibits the next model to contain that particular combination of assignments. The next model will then have to be different from all previous models for at least one of the variables in the blocking clause to satisfy it.

Eventually v_r will be reduced to the backbone. This can be easily recognized, because the blocking clause of the backbone or any of it's subsets makes the formula unsatisfiable, except in the case that the formulas backbone would be empty.

Note that it is not particularly important for the algorithm whether the blocking clauses remain in F or get replaced by the next blocking clause, because the new blocking clause bc_{i+1} always subsumes the previous one bc_i , meaning that every solution that is prohibited by bc_{i+1} is also prohibited by bc_i and $F \cup \{bc_i, bc_{i+1}\}$ is equivalent to $F \cup \{bc_{i+1}\}$ concerning the set of models.

This algorithm is implemented in the *Sat4J* library under the designation *IBB*, except that prime implicants are used instead of models. For specifics on these, see chapter 3.1.1.

2.2 Iterative algorithms

2.2.1 Testing every literal

Alternatively, you can define the backbone as all literals that occur with the same assignment in all models of it's problem, which implies that enforcing a backbone literal to it's negation should make the formula unsatisfiable. This definition already leads to a simple algorithm that can calculate the backbone, by checking both assignments of every literal for whether it would make the formula unsatisfiable, see algorithm 4. This algorithm is referenced in [MSJL10]

Algorithm 4: ITERATIVE ALGORITHM (TWO TESTS PER VARIABLE)

Input: A satisfiable formula F in CNF
Output: All literals of the backbone of F v_r

```

1  $v_r \leftarrow \emptyset$ 
2 for  $x \in \text{Var}(F)$  do
3    $(\text{outc}_1, \_) \leftarrow \text{SAT}(F \cup \{x\})$ 
4    $(\text{outc}_2, \_) \leftarrow \text{SAT}(F \cup \{\neg x\})$ 
5   assert  $(\text{outc}_1 = \top \vee \text{outc}_2 = \top)$  // Otherwise  $F$  would be unsatisfiable
6   if  $\text{outc}_1 = \perp$  then
7      $v_r = v_r \cup \{\neg x\}$ 
8      $F = F \cup \{\neg x\}$ 
9   else if  $\text{outc}_2 = \perp$  then
10     $v_r = v_r \cup \{x\}$ 
11     $F = F \cup \{x\}$ 
12 return  $v_r$ 

```

The two calls to the *SAT* function return a pair which consists first of whether the given function was satisfiable at all and, secondly, the found model, which in this case is discarded. There is no good algorithm that can tell whether a boolean formula is satisfiable or not without trying to find a model for said formula, but we can use it to greatly improve the algorithm above by combining this approach with that of the enumeration algorithms.

2.2.2 Combining with Enumeration

First observe that any model of F would already reduce the set of literals to test by half, because for every assignment missing in the model, we know that it cannot be part of the backbone, so there is no need to test it.

This can be repeated with every further model that we find. The following algorithm 5 is another one that is listed in both [MSJL10] and [MSJL15] and is implemented in the *Sat4J* library as *BB*¹.

¹With the exception of using prime implicants instead of models, similar to the *IBB* algorithm.

Algorithm 5: ITERATIVE ALGORITHM (ONE TEST PER VARIABLE)

Input: A satisfiable formula F in CNF
Output: All literals of the backbone of F v_r

```

1   $(outc, v) \leftarrow SAT(F)$ 
2   $\Lambda \leftarrow v$ 
3   $v_r \leftarrow \emptyset$ 
4  while  $\Lambda \neq \emptyset$  do
5       $l \leftarrow \text{pick any literal from } \Lambda$ 
6       $(outc, v) \leftarrow SAT(F \cup \{\neg l\})$ 
7      if  $outc = \perp$  then
8           $v_r \leftarrow v_r \cup \{l\}$ 
9           $\Lambda \leftarrow \Lambda \setminus \{l\}$ 
10          $F \leftarrow F \cup \{l\}$ 
11      else
12           $\Lambda \leftarrow \Lambda \cap v$ 
13 return  $v_r$ 

```

Note that both possible results of the call to the SAT solver are converted to useful information. In the else branch, the formula together with the blocked literal l was still solvable. In this case v is still a valid model for F , so we can search through it to look for more assignments that don't need to be checked. Note that here v must contain $\neg l$, as it was enforced. Therefore l will be removed from Λ in this case as well.

In the other case, we identified l as a backbone literal. In that case it will be added to the returned set, removed from the set of literals to test and, lastly, added to the problem F , which increases performance in subsequent solving steps. However it would be even better, not only to reuse the learned backbone literals, but all learned clauses.

It is possible to apply the concept of preferences described in section 2.3 to the iterative algorithms listed here. However, this is less beneficial than adding it to the enumeration approach of *IBB*, because in the *BB* algorithm many SAT calls are supposed to return *UNSAT* to positively identify an assignment as backbone. However, this case does not give us a model, so the extra effort of trying to find a more valuable model is often wasted here.

Another difficulty with the *BB* algorithm in comparison to *IBB* is that here it is more difficult to reuse learned clauses. These are based on a subset of the clauses in F . Their existence is virtual so to speak, implied through these base clauses but difficult to find. Adding more clauses to the formula does not remove a learned clause, as the set of base clauses is untouched. At most it might be possible to subsume it with another learned clause. However if a clause is removed from F , it might be that the learned clause is no longer implied through the formula, therefore making it invalid.

Example: Using the iterative approach on formula F which contains the clause $\{(a, b, c)\}$ we temporarily add the blocking clause $(\neg a)$. In this case, the clause (b, c) is implied. CDCL could learn this new clause by making the resolution of $\{(a, b, c)\}$ with the blocking clause $\{\neg a\}$. Should we now change the blocking clause, this learned clause must be discarded. Otherwise when we test with a different blocking clause $(\neg b)$, together with (b, c) it would imply (c) , making c a backbone of F , which it clearly isn't.

2.3 Preferences

The previous approaches still leave much of their efficiency to chance. Theoretically the solver might return models with only the slightest differences from each other, when other models could reduce the set of backbone candidates much more. For example the blocking clause can be satisfied with only one literal in it being satisfied, but if we were to find a model that satisfies all literals in the blocking clause, we can immediately tell that the backbone is empty and we would be finished. So it would be a good approach for backbone computation if we could direct our SAT solver to generate models that disprove as many of the literals in the blocking clause as possible. Precisely this has been described by [PJ18], but has also been proposed much earlier by [KK01].

[PJ18] describe an algorithm called *BB – PREF* or *Prefbones*, which makes use of a slightly modified SAT solver based on CDCL, which is called *prefSAT* in the algorithm below. It can be configured with a set of preferred literals *prefs*. As already stated, when the CDCL algorithm reaches the point where it has the freedom to decide the assignment of a variable, it consults a heuristic that tries to predict the best choice of variable and assignment to reach a model. Instead, *prefSAT* uses two separate instances of these heuristics h_{pref} and h_{tail} , which by themselves may work just as the single heuristic used in the ordinary CDCL solver. The key difference in *prefSAT* is, that h_{pref} , which contains the literals in *prefs*, is consulted first for decisions, and only when all variables with a preferred assignment are already assigned, h_{tail} is used to pick the most agreeable literal, meaning that it would most likely not result in a conflict.

This algorithm also differs from *IBB* in that it does not add blocking clauses, and that is also why it cannot use the case when F becomes unsatisfiable to terminate the algorithm. Instead it relies on the preferences to be taken into account. Except for the case where a formula has only one singular and immediately obvious model, CDCL must make at least one decision. That decision must come from h_{pref} , except for the case that CDCL learned axiomatic assignments for all variables in *prefs*. Depending on whether the learned value for the variables in *prefs* contradicts all preferences it may take another call to *prefSAT*, but at the latest then no more changes will happen to v_r and the algorithm terminates. The return condition also covers the case when the backbone turns out to be empty, because then v_r was reduced to \emptyset and that is a subset of every set. This algorithm stands out from all the others because it has

Algorithm 6: BB-PREF: BACKBONE COMPUTATION USING PREF-SAT

Input: A satisfiable formula F in CNF
Output: All literals of the backbone of F , v_r

```

1  $(\_, v_r) \leftarrow SAT(F)$ 
2 Repeat
3    $prefs \leftarrow \{\neg l : l \in v_r\}$ 
4    $(\_, v) \leftarrow prefSAT(F, prefs)$ 
5   if  $v \supseteq v_r$  then
6     return  $v_r$                                 // No preference was applied
7    $v_r \leftarrow v_r \cup v$ 

```

the unique property, that the formula of which the backbone is calculated is never modified in any way, not even temporarily. Later in section 5.2.4, I will point out how this trait can be useful.

Note that the algorithm was written slightly different from what is listed in [PJ18] to make the relation with common enumeration algorithms more apparent and also make it easier to read.

The return condition makes this algorithm inflexible, as the preferences have to be taken into account without exception. If not, a model might be returned that terminates the algorithm prematurely, because it did not properly test a variable assignment, instead taking a shortcut to save time in the calculation of a model. Since the purpose of this thesis was to experiment with solvers and I was interested in the concrete effects of preferences by themselves on the backbone computation, I created a variation of Prefbones, that uses the previous approach of upper bound reduction, adding a blocking clause to F in every iteration and terminating when F would become unsatisfiable. This made the preferences algorithmically completely optional and allowed to experiment with many variations on the concept. Coincidentally, the added blocking clause happens to be the exact same set as that of the preferred variables.

Later in the results section I will show how this variant faired against the previous algorithm from [PJ18].

2.4 Further approaches

DNF konversion -> schnitt (komplexität raussuchen) gabs in SAT4J nicht chunking

Algorithm 7: BB-PREF: BACKBONE COMPUTATION USING PREF-SAT AND BLOCKING
 CLAUSE

Input: A formula F in CNF

Output: All literals of the backbone of F, v_r

```

1  $(\_, v_r) \leftarrow SAT(F)$ 
2 Repeat
3    $bc \leftarrow \bigvee_{l \in v_r} \neg l$ 
4    $F \leftarrow F \cup \{bc\}$ 
5    $prefs \leftarrow \{\neg l : l \in v_r\}$ 
6    $(outc, v) \leftarrow prefSAT(F, prefs)$ 
7   if  $outc = \perp$  then
8     return  $v_r$ 
9    $v_r \leftarrow v_r \cap v$ 
```

3 Optimizations

The following chapter elaborates on methods to enhance the algorithms that were described in the previous chapter. Depending on the particular combination of algorithm and enhancement, applying the optimization can be considered a no brainer. However, experimental results show that this is not true without exception and in individual cases we will give thoughts why that is. Other improvements can only be applied to some algorithms due to the data that is available.

3.1 Model Reduction

The algorithms described in section 2 all boil down to testing for each variable whether there exist two models where one assigns the variable to \top and the other to \perp . This section describes two strategies to reduce the model that is returned by the SAT solver to a subset that tells us more for the purpose of calculating a backbone. Both methods are essentially about using implicants instead of models.

Having a single implicant I that leaves some variables optional immediately tells us, that every possible combination of assignments of the optional literals can make a model, if we just add the assigned literals in I . You could say that an implicant implies a large set of models.

Without any further information, a single implicant I tells us, that every one of the optional variables in it cannot be part of the backbone.

Starting with complete models, implicants can be subsets of other implicants, by removing more and more assignments that are not essential. This way you will eventually reach an implicant where all of it's assignments are required and removing any further literal from it, would leave some clause unsatisfied. This would be called a prime implicant I_π .

3.1.1 Prime Implicant

[DFLBM13] describes an algorithm that allows to calculate the prime implicant from a model in linear time over the number of literal occurrences in the formula. This algorithm works best if you generate the model of a variable with the CDCL algorithm for multiple reasons.

First, it takes advantage of data structures that you also need in a good implementation of CDCL, namely a lookup from each variable to all clauses that contain either literal of that variable. In CDCL this lookup table improves the performance of unit propagation, because you can check exactly the set of clauses that might be affected

by the assignment to determine whether one of the clauses has become exhaustively unsatisfied or implies another assignment¹. Here, the lookup is used to determine whether a literal is required in the implicant that you are in the process of generating, by looking for clauses that only contain a single satisfying literal anymore, which then must be part of the prime implicant. You can even reuse the watched literals² of the clauses, however you would have to change the way in which the propagate, since you take assignments away instead of adding them.

The second fit with CDCL is that it not only generates a model, but also a table containing information on how that model was generated. This information can be used in this algorithm to reduce the number of literals that need to be checked on whether they are required in the resulting prime implicant. You can quickly generate the input I_r by going through the table generated by CDCL and noting down every assignment that happened through unit propagation. These must be part of the prime implicant because to have been assigned through unit propagation at some point in time there must have been a clause that required that particular assignment.

The only assignments that you really have to test here are those that were decisions. Additionally, you can avoid many decided assignments if you configure your CDCL SAT solver to stop once the formula is satisfied instead of stopping once every variable was assigned. Once the formula is satisfied, no more assignment is necessary, so all further ones are arbitrary decisions that are not necessary in the implicant.

It is sufficient to go over the remaining set of assignments only once each. After having determined that a literal is required to satisfy the formula, it cannot become optional later. After all, for this the algorithm would have to add assignments instead of taking them away. And after having discarded a literal from our implicant it cannot become required again. For this to happen we would have to drop a literal from our implicant where that was the last one that satisfied some particular clause. This fits the description of a required literal and we do not drop those.

Algorithm 8: BASE APPROACH TO COMPUTE A PRIME IMPLICANT

Input: A formula F , a model I_m, I_r containing some required literals in I_m

Output: I_r , reduced to a primeimplicant of F , being a subset of I_m

```

1 while  $\exists l \in I_m \setminus I_r$  do
2   if  $\exists c \in F : Req(I_m, l, c)$  then
3      $I_r \leftarrow I_r \cup \{l\}$ 
4   else
5      $I_m \leftarrow I_m \setminus \{l\}$ 
6 return  $I_r$ 

```

¹The unit case

² These are used in CDCL to determine and store the information on whether a clause is satisfied, unsatisfied, unit or neither of them. This is done by having two pointers that rest on unassigned literals in each clause. In this algorithm you can let these pointers rest on satisfying literals.

Since the same model could be calculated in different ways by CDCL, depending on the particular order in which the variables in it were assigned values, the partition between decided assignments and unit assignments can be different for the same model. Therefore, this method can give you different prime implicants for the same model depending on the CDCL table that you use. Additionally, the order in which you check the decided literals can also make a difference.

The function $Req(I_m, l, c)$ in line 2 of algorithm 8 tells, whether the assignment l in the implicant I_m is required to satisfy c . In other words, is l the only literal in c that also occurs in I_m .

3.1.2 Rotations

There is a model reduction method that is even more powerful than calculating the prime implicant. Even better, the concept is much simpler than calculating the prime implicant.

Any model of a CNF formula can contain multiple implicants and even prime implicants³, so if we could find out from only a single model M_0 of F , which of these literals occurred in all implicants that that model covered, with each model we could reduce the set of backbone candidates even more than with just one of its prime implicants.

Doing this is actually pretty simple. Instead of generating a small set of various prime implicants, you check for each assignment a in M_0 , whether it is required in M_0 , by checking whether $(M_0 \setminus a)$ is still an implicant that satisfies F . If so, we know that a is not part of the backbone, because we found an implicant without it. This approach was described in [MSJL15].

You can do this reduction faster if you make use of the lookup table described in the previous section, where each literal is mapped to the set of clauses where it occurs. After all, you already know that M_0 satisfies F , so it is sufficient to check only the clauses that contain the tested literal a , whether they are satisfied in a different way in $M_0 \setminus \{a\}$. Unaffected clauses must still be satisfied without a .

Additionally, if you happen to use a computation strategy, where you have a set of positively identified backbone literals (for example an iterative algorithm as described in section 2.2, or when you make use of axiomatic literals as described in the next section), then of course these don't have to be tested either.

The performance benefit of this approach depends on the particular example. If the individual models of a formula contain very few prime implicants or even only one, then looking for rotatable literals might not give a benefit over calculating the prime implicants. However formulas where individual models contain many prime implicants with large differences, the benefit can be extreme. See section 5 for experimental results.

³As an example imagine any formula with only clauses of size two, where the first literals are disjunct from the second literals. This formula has at least two prime implicants I_1 and I_2 that you can generate by collecting either the first literal of every clause for I_1 or the second literal for I_2 . Since the literals in I_1 are disjunct from those in I_2 , you can build a model of the combination of I_1 and I_2 .

Algorithm 9: LITERAL ROTATION IN MODELS

Input: A formula F , a model M
Output: R , the required literals of all implicants in M

```

1  $R \leftarrow \emptyset$ 
2 for  $a \in M$  do
3    $I_a \leftarrow M \setminus a$ 
4   if  $\exists c \in F : c \langle I_a \rangle = \perp$  then
5      $R \leftarrow R \cup \{a\}$ 
6 return  $R$ 

```

3.2 Cheap Identification of backbone literals

This section describes various ways that allow you to recognize backbone literals without an additional satisfiability check. Knowing these backbone literals early can speed up the individual calls to the SAT solver, because enforcing the backbone literals prevents the solver from trying to find solutions containing the negation of backbone literals, which by definition don't exist. Specifically for algorithms that apply preferences, knowing backbone literals explicitly can be helpful, because then you can remove some of those preferences that go against the backbone and could never be satisfied anyway.

3.2.1 Axiomatic literals

The most straightforward method to quickly identify backbone literals is to scan the formula for clauses with only a single literal. Since these clauses have only one possible way to become satisfied, that assignment must be used in every model of the formula and is therefore backbone.

Additionally you should check the CDCL table that your solver creates. If you look at this table you might find variable assignments through unit implication which happened before any decision. This includes all assignments from the paragraph above, but also those that are implied through these⁴.

It makes sense to do this check after every SAT computation, as every different way that leads to a different model brings different learned clauses, that may sometimes consist of a single literal. The number of these clauses depends on the structure of your formula. If it is easy to solve, very few conflicts will occur and in turn, very few clauses will be learned.

An expansion on this would be to look for pairs of clauses (a, b) , $(a, \neg b)$ for any two variables of the formula. The only way to fulfill this pair of clauses is to assign a to \top ⁵. This scheme can theoretically be applied to any clause size, but then you would require a quadratically increasing number of clauses to determine a backbone which

⁴Example: Formula $\{\{a\}, \{\neg a, b\}\}$ has the backbone $\{a, b\}$, but only a is immediately obvious.

⁵Which fits the resolution formula described in section 1.1.2

would first increase computation time and secondly decrease the chance that the necessary set of clauses was available.

3.2.2 Unit Implication

When you have some backbone literals identified, there are some methods that you can apply on this set, which can potentially expand it without a complete model calculation.

One method becomes obvious, if you recall the CDCL algorithm, specifically unit propagation. Suppose you have a clause where all but one of it's variables turned out to be part of the backbone, however all of them with the exact opposite sign from that in the clause, so that the clause is still not satisfied by them. In this case you are forced to assign the remaining literal in a way that it does satisfy the clause and you have to do this in every possible model, since what forces you to do that are backbone literals. Therefore, this unit implied assignment is in the backbone.

An efficient algorithm for this would be as follows: Keep a counter for each of the clauses in your formula that indicates the number of not satisfying backbone literals in said clause. When you identify a new backbone literal, increment all the counters where that literal occurs in negation. You can drop the counter completely for clauses where the newly identified backbone literal occurs with the same sign so that it satisfies the clause⁶. If the counter reaches the length of it's clause minus one, then you know that to satisfy this particular clause, the remaining literal in it has to be in the backbone. In this case you can compare it's literals with your current inventory of backbone literals to identify the remaining one. This algorithm should be done inbetween every SAT computation with only those backbone literals that were identified in the last iteration.

Without an efficient implementation, this search for unit implied backbone literals might consume a lot of time. If you try to find the backbone of a formula where the computation takes many SAT calls which each return relatively quickly, the time spent to search for unit implied backbone literals can actually exceed the time spent in the SAT solver if it's implemented inefficiently.

I have tested this method in two solvers, *BB* and a variant of *PB1* that identifies backbone literals only through the learned literals. The tested files were from a SAT competition. Here it showed, that for the method described in this section it is important to supply a sufficient number of already known backbone literals for it to have a positive impact on runtime. The learned backbone literals alone could rarely supply this, before the *PrefBones* algorithm terminated from other conditions. However the iterative approach of the *BB* solver, testing every yet unidentified literal individually, was much faster at providing positively identified backbone literals that you would need to imply other backbone literals through unit implication.

For further investigation on the effects of this method see section 5.2.2.

⁶ In fact, you could remove the whole clause from your formula, since it will always be satisfied through the backbone literal. You could say, it get's subsumed by a clause with only the backbone literal.

3.2.3 Implication through Cooccurrence

Another method to recognize backbone literals from other ones is described in [WBX⁺05] and the rationale goes as follows:

Lemma 1 Given a backbone literal a and another literal b . If b occurs in all clauses that also contain a , then $\neg b$ must be part of the backbone.

Proof: Assuming $\neg b$ was not in the backbone, then there would have to exist a model that contained b . Given that all clauses that contain b also contain a , a cannot be part of the backbone.

File	n_{unit}	n_{coocc}	n_{BB}
dimacs-hanoi5.cnf	1465	47	1931
grieu-vmcpc-s05-25.cnf	565	0	625
grieu-vmcpc-s05-27.cnf	142	0	677
fla-barthel-200-2.cnf	33	0	78
fla-barthel-200-3.cnf	43	0	97
fla-barthel-220-1.cnf	149	0	184
fla-barthel-220-2.cnf	0	0	4
fla-barthel-220-4.cnf	0	0	6
fla-barthel-240-2.cnf	61	0	128
fla-qhid-280-1.cnf	1	0	15
fla-qhid-280-3.cnf	251	2	274
fla-qhid-300-1.cnf	260	0	291
fla-qhid-300-4.cnf	270	0	293
fla-qhid-320-1.cnf	296	0	318
fla-qhid-320-2.cnf	0	0	2
fla-qhid-320-5.cnf	283	2	312
fla-qhid-340-2.cnf	310	0	332
fla-qhid-340-3.cnf	309	3	333
fla-qhid-340-4.cnf	301	4	335
fla-qhid-360-1.cnf	326	0	335
fla-qhid-360-5.cnf	321	0	349
fla-qhid-380-1.cnf	344	2	372
fla-qhid-400-3.cnf	366	0	393
fla-qhid-400-4.cnf	359	0	392
smallSatBomb.cnf	0	0	9

Table 3.1: Comparison of number of backbone literals identified through cooccurrence in comparison to the number identified through unit implication and the overall number of backbone literals in the formula.

In other words, if we determine a new backbone literal, and all clauses that contain it also contain another literal, then we can add the negation of the latter to our backbone set.

However this strategy does not seem to be very effective, at least for the benchmark that I tested it on. Table 3.1 shows the number of literals that were identified through this method in comparison to those that were identified through unit implication and the number of variables in the formula. It is probably very rare that a variable should always occur together with another one.

3.3 Assumptions

A sub problem of calculating backbones is to calculate a backbone under an assumption. This means, that we actually want to know the Backbone of $F \cup \{l\}$ where F is our base formula and l is some variable of F .

The most straightforward way to implement this is to simply call the SAT solver that we use with the same assumptions every time. However depending on the way

that assumptions are implemented in your solver, the set of learned clauses may have to be discarded or at least filtered. Reusing learned clauses is very useful when you calculate a backbone through repeating calls to the SAT solver, as table 5.2 shows.

In a CDCL SAT solver, assumptions can be implemented in two ways. You could simply add a clause for each literal that you want to assume, with the clause containing only that literal.

Alternatively, you can do a trick with in your CDCL table by starting the SAT computation with decisions that correspond to your assumptions. Then once you have to backtrack these decisions, you know that your formula is unsatisfiable with your assumptions.

The latter technique has a very special benefit over the first. If the solver runs into a conflict, it will create a learned clause to prevent the same conflict to occur again. But the content of this learned clause differs depending on the implementation of assumptions.

With the first method your assumption is taken as ground truth, as part of your formula. The resolution step for the variable associated with the assumption will remove it from the learned clause. Without the clause that implemented the assumption, that learned clause would be too strong.

However with the latter method, where this assumption is involved with a conflict a corresponding literal will simply be added to the learned clause. That way the learned clause will later only come into effect under the circumstance that the variable that has now an assumption is then assigned the same value.

If you later want to solve the same formula with different assumptions (or with none at all), then the first strategy might result in invalid learned clauses, which would restrict the set of models of the formula. This is something a learned clause should never do.

Having a sound implementation of assumptions is especially relevant for the *BB* algorithm, because this algorithm uses a different assumption in nearly every one of its SAT calls.

4 Experiments with Preferences

4.1 Tested modifications

As is mentioned in [PJ18], the concept of preferences has not experienced much research as of yet. That is why I experimented a lot with various modifications on the concept for the purpose of this thesis.

All of the following modifications were implemented on top of algorithm 7 (*PB1*). Algorithm 6 (*PB0*) depends on that all available preferences are taken into account strictly, so there is not much space to experiment there without making the algorithm unreliable.

4.1.1 Forgetting preferences

During the course of solving a CNF formula with the CDCL algorithm, many assignment conflicts occur which must be resolved through backtracking. This means that some assignments need to be taken back. Looking at this from the other direction, it can very well happen, that the same variable can occur in decisions multiple times over such a calculation. If a variable assignment is even slightly involved in a conflict, then, lacking any further knowledge, it is a good strategy to simply try its negation in the future. It is not guaranteed, but simply more likely that the other assignment resolves the conflict that occurred with the previous assignment.

The default way in that preferences are implemented stands in the way of this. If you tell the SAT solver to always assign the same boolean value to a specific variable, then the strategy above cannot be applied. That is why I have implemented an option to *PB1* where preferences are forgotten after the first time when they are taken into account. This means that when a variable is selected for a decision, it is removed from the primary heap that is consulted first for this selection¹.

The secondary heap always contains all used variables for selection, but in the default configuration where preferences are not forgotten the preferred variables would already be assigned at the point in time when it is consulted. Here this means, that once a preference was forgotten, the associated variables can still occur in decisions after they were reverted through backtracking and can potentially be assigned a different value.

¹ In the *Sat4J* library, what decides the order of decisions and what decides the value assigned in these decisions are actually two separate data structures. This means that this removal must be written in two separate places.

The most important effect of this strategy is, that the solver quickly falls back to his default behaviour when it turns out that the formula is difficult to solve when preferences for the resulting model are to be taken into account.

It is quite likely that a formula contains models that are relevant for the backbone, because they contain the only occurrence of some literal. However, if they contradict the current set of preferred literals in many other places, giving these preferences to the SAT solver can actually make it difficult to find said model.

4.1.2 Subsets

During benchmarking it showed itself, that all solvers that did not employ any preferences at all were the fastest ones when it came to difficult formulas. So it might be interesting to test some algorithm that can be configured with a floating point number, where a ground value of 0.0 would be equivalent to having no preferences at all and then allowing to enable preferences in very small increments.

The simplest way to do this would be to restrict the number of preferences that could be set for each SAT call. The parameter above is multiplied with the number of variables in the formula and then the number of preferred literals is pruned in each iteration to have at most that size, without of course discarding the set of assignments that has yet to be tested.

Aside from the straightforward implementation, I also created a variant, where extra care is taken to use different subsets for the preferences for each SAT call. To do this, all preferences given to the SAT solver are remembered and not picked again until all of them were tried once. At this point the memory of previously used preferences is cleared so that it builds up again.

4.1.3 Nudging

The previous approach to scalable preferences still works against the decision heuristic because before the SAT solver even starts, the preferred variables are chosen. What subset of the preferred variables would be easiest for the solver to take into account cannot be said upfront. Therefore it should be much more efficient to "nudge" the existing decision heuristic in the direction of the preferences while it's running.

To do this, I implemented a different kind of preference strategy. Here, similar to the previous method, you can pass a floating point number f between 0.0 and 1.0 in addition to the set of preferred variables. When a decision happens in the CDCL algorithm, the selection heuristic sorts all variables by an activity value, which is typically based on how often it was involved in conflicts. Then the resulting array is scanned, beginning with the variable with the lowest activity until one is found that is not yet assigned.

Here this activity value is multiplied with $1 - f$ during this sorting step where a variable is preferred. Therefore, if you pass 0 as value for f , the order that is returned from sorting the activities would be completely unaffected. Very small values of f

would only affect the selection heuristic if a preferred value was already deemed very important but only in second or third place with a small distance to the first one.

However, this factor f can only influence the order of variables for decisions. Which value is then assigned can not be weighted². That is why the default strategy for deciding the phase was left in place.

The purpose of this scheme was to see, whether benefits of preferences would rise up faster than the drawbacks with very low values of f .

4.1.4 Approaching lower and upper bounds

I also tried an idea that was shortly mentioned in [MSJL10, Chapter 3.4]:

Another approach consists of executing enumeration and iteration based algorithms in parallel, since enumeration refines upper bounds on the size of the backbone, and iteration refines lower bounds. Such algorithm could terminate as soon as both bounds become equal.

You could argue that *BB* (see algorithm 5) matches this concept, since it reduces the set of literals to further examine with every found model, while simultaneously checking individual literals. It removes both the identified backbone literals and the found models from the set of literals to test and once that becomes empty, it terminates.

However, since [MSJL10] also lists the *BB* algorithm, the authors probably ment to run two different algorithms concurrently. Still, making use of both approaches makes sense, so I tried this out in combination with preferences, by checking the set of learned literals in each iteration, as proposed in section 3.2.1.

4.2 Implementation notes for Sat4J

TODO

- wo kommen spezial selektionsheuristiken hin (Klassenname)
- genaue adresse der Backbone klasse
- internal/dimacs literals
- vecint toArray bug
- keine doku
- prime implicant bug bei Prefbones

TODO PB1x besser als IBB, unterschied ?????

habe irgendwo footnote dass beim benchmarken der erste call immer schlecht ist, wegen der hardware, der muss hierhin.

keine explizit auftauchenden unit klauseln, musste selber handeln und zum resetten rausnehmen

²Except if there was a heuristic for that, which can give a confidence value

5 Results

5.1 Tested Backbone algorithms

This chapter contains a couple of benchmarks that were all tested against a series of backbone algorithms. There is a slight focus on the preferences approach. Since this is not as thoroughly examined as other approaches in literature, most of these variants are slight modifications of algorithm 7, where preferences are combined with blocking clauses.

For clarity, the used benchmarks are listed here. All algorithms unless otherwise stated reduce the models that they find to prime implicants with the method described in section 3.1.1.

- **BB**: *Sat4J* implementation of algorithm 5.
- **IBB**: *Sat4J* implementation of algorithm 3.
- **KBB**: Algorithm *BB* in combination with unit implication as described in section 3.2.2.
- **PB0**: *PrefBones* after [PJ18]. See algorithm 6.
- **PB1**: *PrefBones* with blocking clause. See algorithm 7.
- **PB1(amnes)**: *PB1* with forgetting preferences as described in section 4.1.1.
- **PB1(model)**: *PB1* without any model reduction.
- **PB1x**: *TODOweg PB1* without preferences. Structurally identical with *IBB*¹
- **PB1a**: *TODO* nötig?
- **PB1b**: *TODOweg PB1* where preferences can only affect the selection order. Given for the purpose of comparison with *PB2*.
- **PB1c**: *PB1* with a limited number of preferences, as described in section 4.1.2. Listed with three different size restrictions.
- **PB1d**: Like *PB1c*, but with more diverse preferences in each iteration.

¹There are slight differences in the performance measurements between these two implementations. These probably stem from differences in the implementation. The differences divided by the number of sat calls is relatively comparable, implying that the two implementations scale comparably.

- **PB1e**: PB1 in combination with approaching upper and lower bounds as described in section 4.1.4. The lower bound is made up of learned literals.
- **PB1f**: Based on PB1e, but sollte eigentlich weg
- **PB2**: Uses scalable preferences as described in section 4.1.3.
- **PB3**: PB1 with model reduction through rotation. TODO rename

5.2 SAT Competition Benchmark

For the first benchmark, I collected a set of 64 files from the 2017 SAT competition². The SAT competitions generally use problems that are difficult to solve compared to other problems of the same file size. This is in order to encourage development of solving strategies that reliably have good performance and not only for most of them. To save time during benchmarking, files that took longer than around one minute for a single model computation were excluded, resulting in files that are generally around 30 kilobytes large. Additionally, problems where the duration for backbone computation averaged below one second were excluded, because here the small differences in the measurements could just as well be explained with external factors like the CPU throttling for a short time. To get meaningful testresults for such files, multiple testpasses should be conducted.

	t_{full}	t_{sat}	t_{last}	n_{sat}
BB	8.63	8.628	-	254
IBB	4.946	4.944	1.911	9
KBB	8.713	8.687	-	36
PB0	31.78	31.779	1.17	4
PB1	17.49	17.488	6.998	5
PB1(amnes)	10.867	10.865	4.781	6
PB1(model)	25.794	25.793	8.677	5
PB1x	5.064	5.062	1.562	9
PB1a	11.241	11.239	5.351	8
PB1b	9.785	9.783	1.921	6
PB1c(50%)	25.312	25.311	12.909	5
PB1c(5%)	1064.097	1064.095	797.244	6
PB1d(50%)	26.746	26.745	11.284	5
PB1e	17.187	16.591	6.796	6
PB1f	15.971	15.97	4.333	6
PB2(50%)	10.135	10.133	6.428	10
PB2(5%)	5.232	5.229	1.737	9
PB2(0.5%)	5.251	5.249	1.816	9
PB3	20.927	20.922	8.912	4

Table 5.1: Averages of 64 testfiles taken from sat competitions. The columns indicate: The full time that the calculation took in seconds; The time that was spent in the sat solver; The time that the last sat computation took; The number of sat calls (all values are averages).

² To be more precise the *essential* folder from the *incremental* package, available at <https://baldur.iti.kit.edu/sat-competition-2017/benchmarks/incremental.zip>

The averaged time to compute the backbones of these 64 testfiles can be seen in 5.1. The second column shows the time that was only spent in the SAT solver. This gives a hint on whether a particular algorithm configures it's SAT solver well and whether it loses computation time in things besides the SAT calls, for example through model reduction.

Taking a look at this table, we can quickly see that for these instances, all solvers that employed preferences as part of their algorithm performed much worse than those that did not. These would be *BB*, *IBB*, *KBB* and *PB1x*. This impression is further supported by the performance results of the three configurations of the *PB2* algorithm. Here the effect of preferences was reduced incrementally, eventually reaching a computation time close to that of *IBB* where no preferences were set.

5.2.1 Importance of reusing learned clauses

Table 5.2 shows a comparison of individual benchmarks to highlight the importance of reusing learned clauses. While working with the *Sat4J* library I noticed that the *IBB* backbone algorithm was accidentally configured in a way that learned clauses would always be discarded between SAT computations. However, these learned clauses are still valid in later iterations of the *IBB* algorithm. The only difference that the formula goes through during this algorithm, is that the blocking clause that ensures a new model repeatedly loses some of its literals. As long as the set of solutions for a formula is only reduced, the learned clauses of that formula stay valid.³

File	t_{keep}	$t_{discard}$
brock400-2.cnf	0.233	0.252
dimacs-hanoi5.cnf	1.41	1.596
griew-vmpc-s05-25.cnf	71.945	78.964
griew-vmpc-s05-27.cnf	554.52	648.697
fla-barthel-200-2.cnf	0.634	6.019
fla-barthel-200-3.cnf	0.619	2.16
fla-barthel-220-1.cnf	2.511	9.572
fla-barthel-220-2.cnf	7.497	17.759
fla-barthel-220-4.cnf	2.24	14.113
fla-barthel-240-2.cnf	3.632	50.552
fla-qhid-320-1.cnf	6.61	6.575
fla-qhid-320-2.cnf	9.227	101.17
fla-qhid-320-5.cnf	7.861	7.962
fla-qhid-340-2.cnf	11.922	13.688
fla-qhid-340-3.cnf	11.796	17.157
fla-qhid-340-4.cnf	9.454	9.297
fla-qhid-360-1.cnf	39.998	39.797
fla-qhid-360-5.cnf	10.698	10.849
fla-qhid-380-1.cnf	189.895	249.003
fla-qhid-400-4.cnf	55.213	52.811
smallSatBomb.cnf	0.011	0.022

Table 5.2: Backbone computation time of the *IBB* algorithm, once with keeping learned clauses (t_{keep}) and once discarding learned clauses between every sat call ($t_{discard}$)

³Example: With a formula without any clauses but three variables a, b and c you can create eight models. With only the clause $\{a\}$ in your formula you can have four models, with only the clause $\{a \vee b\}$ you can have 6 models, with only the clause $\{a \vee b \vee c\}$ you can have 7 models.

File	$t_{BB}[n_{sat}]$	$t_{KBB}(t_{sat})[n_{sat}]$	n_{unit}	$n_{backbone}$
brock400-2.cnf	0.04[254]	0.04(0.03)[254]	0	0
fla-komb-400-3.cnf	1276.71[381]	1241.12(1241.11)[45]	336	379
dimacs-hanoi5.cnf	1.94[1931]	1.84(1.23)[281]	1650	1931
vonThore42.cnf	0.02[398]	0.01(0.01)[51]	345	346
grieu-vmopc-s05-27.cnf	261.09[678]	281.08(277.1)[536]	142	677
fla-komb-360-4.cnf	14.94[337]	14.94(14.9)[45]	292	333
fla-qhid-360-1.cnf	74.96[355]	76.03(76.03)[29]	326	355
grieu-vmopc-s05-25.cnf	182.84[625]	179.91(179.44)[51]	574	625
fla-qhid-360-5.cnf	20.68[350]	20.89(20.89)[29]	321	349
fla-barthel-220-4.cnf	3.55[32]	2.74(2.73)[32]	0	6
9012345.cnf	4.18[1483]	6.73(5.92)[813]	670	1478
fla-barthel-220-2.cnf	8.18[23]	8.11(8.11)[23]	0	4
1098765.cnf	1.21[938]	1.29(0.83)[493]	444	921
smallSatBomb.cnf	0.01[26]	0.01(0.01)[19]	7	9

Table 5.3: Benchmark results for a selection of files with a focus on the benefit of unit implication. Rows indicate: Calculation time and number of SAT calls for the *BB* solver ; Calculation time, time spent in SAT solver and number of SAT calls for the *KBB* solver ; Number of backbone literals identified through unit implication (in *KBB*) ; Number of backbone variables in formula.

The information contained in learned clauses is very valuable, as it prevents the solver from repeating invalid combinations of assignments that might even be likely to occur again. But if already learned clauses can guide the SAT solver away from possible conflicts, it could ideally return a model without any backtracking.

5.2.2 Benefits of unit implication

This section evaluates the effects of trying to recognize backbone literals through unit implication as described in section 3.2.2. Table 5.1 interestingly shows no performance benefit for this technique, even though the number of sat calls is much smaller.

Table 5.3⁴ shows individual performance differences between the *BB* solver supplied by *Sat4J* and my own *KBB* solver for comparison, as well as the backbone's

⁴ In this table the pure sat calculation time for the *BB* column is missing. The *BB* algorithm actually spends almost no time outside of the SAT solver in the case of the listed formulas.

Most of the performance differences in this table can be explained with other reasons than actual algorithmic differences. *fla-barthel-220-4.cnf* for example should not be faster with *KBB* since here no backbone literal was determined through unit propagation. However I was able to reproduce this performance difference just through the order of what was called first, i.e. if the two solvers are called the other way around the difference in timing between the first and second call are the same. A possible explanation could be a power saving feature in modern processors.

size and the number of backbone literals identified through unit implication. The time columns also contain the number of sat calls that were committed. Its content matches the results of table 5.1. Occasional cases where *KBB* trumps in performance over *BB* get balanced out by cases where this is the other way round, but the number of sat calls is always better with the *KBB* algorithm. And this is true in spite of the fact that almost all identifications happened through unit implication.

This indicates that the effect from scanning for unit implied backbone literals also appears in the *BB* solver, only not quite as obvious. When you look at line 10 of algorithm 5, you see that *BB* actually takes identified backbone literals up into the formula to speed up the solving process. Now imagine what happens, if the unit implication case happens during the course of the *BB* algorithm. You have a clause that is not satisfied, even though all but one of its literals are already assigned through the learned backbone literals. When *BB* tests the last of that clause's literals with an assumption against it, the clause becomes immediately unsatisfied⁵, proving that the last remaining literal in the clause is part of the backbone.

The results shown in the following chapter (5.3) paint a slightly different picture. Here the pure SAT time of *KBB* is actually smaller than that of *BB*, however even *BB* loses around a third of its calculation time outside of pure SAT calls. This could be explained by the much higher number of SAT calls for this benchmark and the overhead that comes with preparations and cleanups for a SAT call, which apparently became relevant at that point. Given good conditions (like in that benchmark) *KBB* can identify many backbone literals in a single search, which also requires less data structures around it compared to a complete SAT computation.

In summary, searching for backbone literals through unit implication can be a more efficient strategy than testing each individual literal through a SAT call, however only if the search for unit literals is implemented in a very efficient way. Also note that the problem of having too many SAT calls can just as well be resolved by using an enumeration algorithm like *IBB* instead of an iterative approach.

5.2.3 Effect of subset preferences

The algorithms where the set of preferences was restricted in size (*PB1c* and *PB1d*) compared relatively bad to the base algorithm *PB1* and this is most pronounced in the case of *PB1c*(5%) where the restriction is the strongest. This means that, at least for this benchmark, restricting the number of preferences completely backfired. The decrease in performance can be traced beginning with *PB1* which is equivalent to *PB1*(100%) towards the 50% and 5% configuration.

For a possible explanation I should begin with a

⁵Remember that *BB* tests by trying to disprove a potential backbone literal.

	t_{last}/t_{avg}	
IBB	3.479	
PB0	0.147	
PB1	2.000	
PB1(amnes)	2.640	
PB1(model)	1.682	
PB1x	2.777	
PB1a	3.808	
PB1b	1.178	
PB1c(50%)	2.550	
PB1c(5%)	4.495	
PB1d(50%)	2.109	
PB1e	2.457	
PB1f	1.627	
PB2(50%)	6.343	43
PB2(5%)	2.989	
PB2(0.5%)	3.113	
PB3	1.703	

Table 5.4: Ratio between the average duration of a SAT call and the duration of the last SAT call. Calcula-

reminder about the exact way in which preferences are implemented in *PB1*. Here two decision heuristics coexist, h_{pref} and h_{tail} , whereas under normal circumstances a CDCL SAT solver would only use one to pick a literal for a decision. In *PB1*, h_{pref} is always consulted first, and only if all the variables that it offers for an assignment are already assigned to a value, h_{tail} is queried. Both h_{pref} and h_{tail} contain a heuristic to choose the optimal variable for a decision, but in h_{pref} the set to choose from is restricted and what that variable would then be assigned to, is fixed. In contrast, h_{tail} is free to choose any remaining free variable and give it either boolean value, depending on what it deems better to satisfy the formula.

When a decided literal is involved with a conflict, it will be pushed back in it's decision heuristic. That way an opportunity is given to variables that might not be so difficult to be assigned a good value and the problematic variables might be assigned a necessary value through unit implication. However this can only happen if enough other variables are available in the same heuristic to take it's place and with it's strong size restriction, *PB1c*(5%) doesn't have them.

Additionally, the more that you restrict the size of the preferences, the more likely it becomes that all preferred literals are negated backbone literals. In this case, all decisions made based on h_{pref} prevent you from finding a model and must eventually be reverted.

Even worse, since the preferred assignments have to be done before all the others, they occur at the beginning of the CDCL table. This means that in case of a conflict with other assignments, the preferred decisions will not be reverted if there is any other decision available to be reverted, since the strategy of CDCL is usually to revert only the youngest decision involved with the conflict. But if this preference actually goes against a backbone literal of the formula, it must eventually be reverted to reach a valid model. This can only happen by a unit propagation, since otherwise a decision would just take the preference into account again. And since no decision can happen before the preferred decisions, to counter a preference a unit propagation requires the maximum amount of information so that it can happen without a prior decision. You would need to do an amount of learning that is actually equivalent to directly identifying a backbone literal.

5.2.4 Duration of last SAT call

A similar effect to the previous is hinted by the performance results listed in the third column t_{last} of table 5.1. Many of these timings are larger than the average computation would take. The observation coincides exactly with whether the last

SAT call would be unsatisfiable. The *PB0* solver does not apply blocking clauses and still performs well in the last iteration, whereas the *IBB* solver that does not employ preferences performs badly.⁶ This indicates that the problem lies in the fact, that in this last sat call, the formula is unsatisfiable.

That *PB0* performs so well in the last SAT call is actually quite interesting, as here the last SAT call is about seven times faster than it's own average. This could be explained by the fact that since the formula is never really changed in the case of *PB0*, the clauses that it learns never become outdated. In contrast, in the typical model enumeration schemes, they may not become invalid but at least less useful over time, because they might only affect the generation of implicants that are later excluded from the formula through a stronger blocking clause. The information stored in these learned clauses can be put to use especially well in the last iteration. Theoretically, the preferences at that point in time are all impossible to implement and should slow down that particular calculation. But the solver has already spent a lot of time with conflicts that stem from them and should thus have learned many clauses that involve the backbone literals, possibly even directly identifying them as such. In that particular case, the corresponding preference is overridden immediately and *PB0* merely needs to get the remainder of the formula to satisfy, just like any other backbone algorithm.

TODO alte these ausgraben: backbone literale stehen in CDCL tabelle vor erster decision, beweisen, oder einfach weg

5.2.5 Benefits of forgetting preferences

Table 5.5 lists a comparison of multiple backbone algorithms once with ordinary, permanent preferences and in a forgetting scheme as described in section 4.1.1. Preferences in general resulted in worse performance for this benchmark. However, *PB1(amnes)*, where the preferences are configured to immediately drop those that were involved in a conflict, reduced the penalty to an acceptable level in all examples.⁷

Table 5.6 in the upcoming section shows results for a formula that is more beneficent to preferences. Here we see,

	Permanent	Forgetting
PB1	20.251	12.426
PB1c(50%)	25.708	13.109
PB1c(5%)	1080.724	14.483
PB2(50%)	13.023	7.025
PB2(5%)	6.283	6.348
PB3	21.255	13.154

Table 5.5: Average of the complete backbone computation for variants of *PrefBones* with and without forgetting preferences.

⁶The *BB* and *KBB* solvers are excluded from this table, because as they are iterative algorithms. Algorithmically the first and last SAT calls do not differ that much.

⁷ In earlier executions of my benchmark setup, I also tested *PB1c* with 0.5% as preference size restriction, however only in combination with forgetting preferences. Without forgetting them, this configuration turned out to be completely unreasonable to test within an acceptable time frame and was dropped.

that in such a case, forgetting preferences still work as intended. If these results turn out to be reproducible for other formulas as well, forgetting preferences could be a viable strategy to compute the backbone of any formula without prior knowledge about it, since the penalty for difficult formulas would be relatively low but the speedup for easy ones very high.

5.3 Industrial benchmark

Another benchmark I applied the various backbone algorithms to, was a formula for a real world application from the automobile industry. The purpose of this formula F_{conf} was to describe a product in the context of options or features available to the customer. Some of these options can be combined, others exclude or require each other. Most of the variables in F_{conf} correspond to a boolean parameter that is set to \top if the associated feature is requested by the customer. If the formula would become unsatisfiable under such assumptions equal to the requested configuration, then the combination of these features would be impossible. Looking at it from the other side, the set of models of F_{conf} matches exactly the set of possible product configurations that are available to the customer. F_{conf} further contains a small set of additional variables to model more complex relationships between options.

The particular use case that I examined was to find the implications in the formula, i.e. if a customer requests feature a , would he also have to pick feature b . A primitive way to calculate this would be to iterate over all possible pairs of features and check for satisfiability of F_{conf} under the condition that a is \top and b is \perp . If this was unsatisfiable, then a would imply b . However, with 407 literals to choose from, you would have to do 165,242⁸ sat calls.

A more efficient approach is to only go over the 407 options once and for each variable a of them calculate the backbone of $F_{conf} \cup \{a\}$ or in other words F_{conf} under

⁸407 times 406

	t_{calc}	t_{sat}	n_{sat}
BB	11.117	7.235	159545
IBB	6.353	2.316	15748
KBB	13.747	2.11	15266
PB0	3.659	1.469	6531
PB1	3.918	1.611	6531
PB1(amnes)	4.067	1.682	6531
PB1(model)	2.148	1.59	6531
PB1x	7.596	2.94	15748
PB1a	5.096	2.112	9335
PB1b	7.754	3.199	15248
PB1c(50%)	5.376	2.248	9680
PB1c(5%)	7.026	2.693	13955
PB1d	4.464	1.804	7386
PB1e	3.524	1.354	6387
PB1f	3.603	1.526	6369
PB2(50%)	8.341	3.457	15752
PB2(5%)	8.313	3.484	15752
PB2(0.5%)	8.364	3.529	15752
PB3	3.872	1.204	4471

Table 5.6: Performance results for computation of the backbone of a product formula. Values are not averaged, but summed up over 407 different executions, each with a different assumption.

the assumption a . If a feature b occurs in all models when a is assumed, then a implies b in some way.

5.3.1 Performance measurement and Discussion

Table 5.6 lists experimental results with the same set of algorithms that were run on the files from the SAT competition. In the following, I will list some observations about these results.

- We immediately see that preferences give a great benefit to performance other than in the previous benchmark with the files from the SAT competition. Here, all cases where I tried to soften the effects of preferences ($PB1(amnes)$, $PB1c$, $PB2$) had worse results than the base algorithm $PB1$.
- The fastest algorithm overall ($PB1(model)$) is the one that does not reduce the models at all. The number of SAT calls is even exactly the same as that of that variant with prime implicant reduction. However the time that was spent in the SAT solver is very similar to that execution with prime implicant reduction ($PB1$), so the difference must be the time that was spent to reduce the model and the benefit, namely the number of optional variables in the prime implicant, was very small.

Still, this does not mean that model reduction wouldn't be useful at all in this benchmark, as the next point will show. It merely implies that the benefit of applying any special strategy may very well be outweighed by the extra performance cost that comes with it, since here all of this work would have to be done a very large number of times.

- The fastest implementation when it comes to pure SAT solver time as well as number of SAT calls was $PB3$, which differs from the others in that it uses literal rotation to reduce models instead of prime implicant computation. Apparently the models that occur in this formula actually do contain many optional assignments. However these are spread over many different prime implicants with little distance to the model.

A previous variant of this algorithm took around 250 seconds to compute overall. This version did not use the lookup from literal to containing clauses (as described in later paragraphs in section 3.1.2), but iterated over all clauses in the formula. Such a drastic effect of an efficient implementation did not occur for the SAT competition benchmark.

This has primarily two reasons. First, the number of SAT calls per instance is twice as much in this benchmark compared to those from the SAT competitions⁹, therefore the model reduction happens twice as often. Secondly, the formula of this benchmark is much larger than those from the SAT competition, with the filesize being around twenty times as large. Therefore there are much more clauses to search through.

⁹The 4471 calls span over 407 problem instances.

- The two algorithms in third place of overall computation time were *PB1e* and *PB1f*. Both of these make use of learned literals so apparently the backbone literals in this formula are easy to identify by checking the set of literals that the solver learns when it computes new models.
In fact, on inspection, all literals that later turn out to be part of the backbone occur in this set after the very first SAT call (with an exception of the forced literal, which can be extracted by searching the formula for clauses with only one literal).
- Another noteworthy algorithm is the *KBB* algorithm that uses unit implication to identify backbone literals. The implementation of this algorithm was based on that of the *BB* algorithm and here the number of SAT calls with *KBB* is a tenth of the number in the case of *BB*. However this advantage is not expressed equally strong when it comes to the time spent in the SAT solver (around a fourth), which means that the identification through calculating a new model can sometimes be more efficient than regularly checking unit implications, as was already explained in the previous section (5.2.2).
Finally, the overall computation time of *KBB* is actually worse than that of *BB*, meaning that the benefit through cheap backbone literal identification is less than the time that it takes to check the clauses for the unit case.

5.3.2 Specialized algorithm

With the findings from the last section and some experimentation, I devised a specialized algorithm *PB4* for this use case which is listed in algorithm 10. For comparison with the other implementations, the performance results can be seen in table 5.7.

First of all, since it is very effective here to check the literals that the solver learns as backbones through conflict resolution, the scheme of approaching upper and lower bounds as described in section 4.1.4 is applied here. The

	$t_{calc}(\text{sec})$	$t_{sat}(\text{sec})$	NSatCalls
PB4	1.482	0.863	4064

Table 5.7: Results of specialized backbone algorithm on product formula benchmark.

lower bound bb_l of the backbone consists of all learned literals, whereas its upper bound bb_u consists of the intersection of found models or reductions of them. Having both upper and lower bound not only allows to potentially stop the loop before the last sat call. It also accelerates the reduction of the first model to its required literals, because if I know that a literal is in the lower bound of the backbone, I don't need to explicitly test, whether it should be in its upper bound. This behaviour is listed in algorithm 11.

Secondly, it turned out, that only the first model reduction in line 3 was worth its computational effort. The reduction of subsequent models did not give performance benefits that would have outweighed the time it took to do. That is why in line 11

the upper bound is intersected with the complete model instead of a reduction of it.

For the preferences, the typical scheme was applied, where the solver was configured to disprove as many of the backbone candidates as possible, while the same set was added as a blocking clause to ensure that the loop would eventually terminate.

Algorithm 10: SPECIALIZED ALGORITHM FOR INDUSTRIAL APPLICATION

Input: A satisfiable formula F in CNF
Output: All literals of the backbone of F

```

1  $(outc, model, learnt) \leftarrow SAT(F)$ 
2  $bb_l \leftarrow learnt$ 
3  $bb_u \leftarrow required(model, F, bb_l)$ 
4 while  $bb_l \neq bb_u$  do
5    $blocker \leftarrow \bigvee_{l \in bb_u} \neg l$ 
6    $prefs \leftarrow \{\neg l : l \in bb_u\}$ 
7    $(outc, model, learnt) \leftarrow prefSAT(F \cup blocker \cup bb_l, prefs)$ 
8   if  $\neg outc$  then
9     return  $bb_u$ 
10   $bb_l = bb_l \cup learnt$ 
11   $bb_u = bb_u \cap model$ 
12 return  $bb_u$ 

```

Algorithm 11: FUNCTION $required(M, F, bb_l)$

Input: A model M for formula F , a lower bound bb_l of the backbone of F
Output: All unrotatable literals in M as an upper bound of the backbone of F

```

1  $R \leftarrow bb_l$ 
2 for  $l \in M$  do
3   if  $l \in bb_l \vee \exists c \in F : c \langle M \setminus l \rangle = \perp$  then
4      $R \leftarrow R \cup \{l\}$ 
5 return  $R$ 

```

5.3.3 Efficiency over all assumptions

Since for this benchmark, the almost same formula is worked on 407 times, it makes sense to think about ways how to make this outer loop efficient as well.

The first consideration was to first compute information of the base formula and reuse it in all subsequent computations, where the backbone under an assumption was calculated. However this was not possible.

One interesting piece of information would have been the set of clauses that were learned during the computation of a model of the base formula F_{conf} . However this

set was empty. Apparently the formula is simple enough, that the model can be found without a single conflict. The solver returned without having learned any new clause for the formula.

Another thing I thought about was the backbone of the base formula. If you can determine backbone literals of F_{conf} , then you can safely assume, that all of these are part of any restricted formula $F_{conf} \cup \{a\}$. This is because, when a clause gets added to a CNF formula, it's set of models can only shrink, no new model can be induced through an additional clause¹⁰. This implies that an assignment that didn't occur in the models before will also not appear in the new smaller set of models, in turn implying that if a variable always occurred with the same assignment in F_{conf} , it will also do so in $F_{conf} \cup \{a\}$.

However this set was empty as well and for a good reason in this particular case. The backbone of a formula consists of all assignments that have to be done to end up in a model. In the context of a product formula, which we have here, this would mean, that a specific feature of the product would always have to be selected. In other words, the product has an option that is not optional.

What remained was to see, if the loop over the assumptions could be sped up. In fact whereas the backbone computations¹¹ took a sum of 1.5 seconds, this loop overall took 3.9 seconds. The difference consisted of primarily the copying of the formula(2.2 seconds) and writing down benchmark information(around 150 milliseconds).

To do this in *Sat4J* you must first of all reset the formula object¹². In the case of model enumeration algorithms like *IBB* or *PB1*, this incorporates removing all the blocking clauses because they modify the formula. If you don't do this, all backbone computations after the first one will immediately fail, because the final blocking clause makes the formula unsatisfiable. Additionally, you must flush the set of learned clauses and literals because some of these may be based on the blocking clauses. Therefore, if you would leave them in place, they could reproduce most of the effects that the blocking clause had. Take care that all of this happens in a way that during the individual backbone computation, the learned clauses stay in place. *Sat4J* supplies a special function to remove a clause under the expectation that it will immediately become subsumed or already is, which you can use to remove old blocking clauses during the loop without flushing the learned clauses. Alternatively you could remove all of them at the end. The ordinary function to remove a clause in *Sat4J* triggers the cleanup automatically.

Additionally, it makes sense to revert the decision heuristic if you replaced it with something that allows to implement preferences and you want to reuse the formula object with a backbone solver without preferences. The typical behaviour throughout the *Sat4J* library, including the *BB* and *IBB* backbone solvers, is to assume that such a data structure is already set up correctly.

One last bit of state inside the formula object that I noticed were two floating point

¹⁰ Assuming that no new variable was introduced.

¹¹ Of only the new *PB4* solver

¹² The class name in *Sat4J* is *Solver* or *ISolver*.

numbers called *claInc* and *claDecay*. These influence the scale in which the activity values inside the decision heuristic grow and shrink. They merely influenced the exact behaviour of the solver, but not the calculation result.

With all of this taken care of, the duration of the outermost loop over the assumptions took just as long as the sum of the durations of the backbone computations.

5.4 Second Industrial benchmark

TODO text dazu, beschreibung, vergleich mit erstem industrie benchmark analyse

		t_{calc}	t_{sat}	t_{last}	n_{sat}
• PB4 bringt nix	BB	1007.665	712.676	-	2063982
	IBB	1291.489	866.561	-	432408
• präferenzen immer besser	KBB	1253.658	445.423	-	417846
	PB0	442.172	285.674	2.139	129943
• gelernte literale bringen nichts.	PB1	523.182	331.089	0.211	146349
	PB1(amnes)	504.572	315.742	0.229	143503
	PB1(model)	391.147	340.538	0.252	151119
• rotieren < primimplikante < model bzgl calcTime, in pureSat andersrum, aber logisch, weil stärkere reduktion. model reduktion hier anscheinend völlig nutzlos und verschwendet zeit	PB1x	1420.34	910.275	1.675	440355
	PB1a	948.42	646.993	2.576	239787
	PB1b	1421.294	869.288	0.617	460292
	PB1c(50%)	533.995	334.392	0.232	146799
	PB1c(5%)	614.968	377.302	3.648	198227
	PB1d	542.427	332.594	0.217	146430
	PB1e	523.955	324.705	1.164	148096
• PB0 besser als PB1.	PB1f	522.015	327.188	1.244	147614
	PB2(50%)	1660.442	1123.058	4.227	438298
• PB0 komischerweise schlechtere last sat time TODO entweder begründen oder einfach weglassen	PB2(5%)	1591.691	1052.998	2.039	439801
	PB2(0.5%)	1586.361	1049.304	2	439140
	PB3	572.575	325.808	0.265	141076
	PB4	2478.283	2361.488	0.2	297,192

Table 5.8: Second Industrial benchmark. Values are not averaged, but summed up over 948 different benchmarks.

- PB1(amnes) geht auch gut

PB0 geht mit (model), leider nicht auch mit (amnes) Basis formel hat backbone literale, also de num backbones of base formula is 1449

durch die bank 10% bessere performance mit prerun

Chapter 5. Results

	t_{full}	t_{sat}	t_{last}	n_{sat}
With backbones and learned clauses				
BB	894.491	615.687	-	2064493
PB0	393.149	243.261	2.004	129908
PB0(model)	275.352	241.019	2	129854
PB1	459.353	279.284	0.217	144057
PB1(model)	341.306	290.019	0.244	148868
Without preperation				
BB	905.379	626.052	-	2063982
PB0	413.299	261.777	1.985	129943
PB0(model)	293.795	259.836	1.957	130099
PB1	489.417	305.337	0.191	146349
PB1(model)	366.219	314.409	0.2	151119

	t_{calc}	$n_{learned}$
BB	1.122	1898
PB0	0.703	2214
PB0(model)	0.494	2244
PB1	0.835	2738
PB1(model)	0.626	2965

Table 5.9: Preptime and number of learned clauses

6 Conclusion

TODO prefbones ist besser für echtwelt beispiele, ohne prefs zuverlässiger bei komplizierten beispielen

kombination aus strategien auf fallbeispiel optimieren(?)

Guiding the behaviour of the SAT solver using preferences can be very beneficial in the case of real world applications and where it would be disadvantageous, the penalty can be kept under control.

future work dazu machen

Bibliography

- [DFLBM13] David Déharbe, Pascal Fontaine, Daniel Le Berre, and Bertrand Mazure. Computing prime implicant. *2013 Formal Methods in Computer-Aided Design, FMCAD 2013*, pages 46–52, 10 2013.
- [DLL62] Martin Davis, George Logemann, and Donald Loveland. A machine program for theorem-proving. *Commun. ACM*, 5(7):394–397, July 1962.
- [ES03a] Niklas Een and Niklas Sörensson. An extensible sat-solver [ver 1.2]. 2003.
- [ES03b] Niklas Een and Niklas Sörensson. Temporal induction by incremental sat solving. *Electronic Notes in Theoretical Computer Science*, 89:543–560, 12 2003.
- [KK01] Andreas Kaiser and Wolfgang Küchlin. Detecting inadmissible and necessary variables in large propositional formulae. In *Proceedings of International Joint Conference on Automated Reasoning, IJCAR 2001*, 2001.
- [MSJL10] João Marques-Silva, Mikoláš Janota, and Inês Lynce. On computing backbones of propositional theories. *Frontiers in Artificial Intelligence and Applications*, 215:15–20, 01 2010.
- [MSJL15] João Marques-Silva, Mikoláš Janota, and Inês Lynce. Algorithms for computing backbones of propositional formulae. *AI Commun.*, 28(2):161–177, April 2015.
- [PJ18] Alessandro Previti and Matti Järvisalo. A preference-based approach to backbone computation with application to argumentation. In *Proceedings of the 33rd Annual ACM Symposium on Applied Computing, SAC '18*, pages 896–902, New York, NY, USA, 2018. ACM.
- [SS96] João P. Marques Silva and Karem A. Sakallah. *GRASP - a New Search Algorithm for Satisfiability*, pages 220–227. ICCAD '96. IEEE Computer Society, Washington, DC, USA, 1996.
- [WBX⁺05] Zipeng Wang, Yiping Bao, Junhao Xing, Xinyu Chen, and Sihan Liu. Algorithm for computing backbones of propositional formulae based on solved backbone information. In *2016 International Conference on Applied Mathematics, Simulation and Modelling*. Atlantis Press, 2016/05.

Bibliography

- [WKS01] Jesse Whittemore, Joonyoung Kim, and Karem Sakallah. Satire: A new incremental satisfiability engine. *Proceedings - Design Automation Conference*, pages 542 – 545, 02 2001.