



Masters Thesis

Investigations on Backbone Computati- on

Eberhard Karls Universität Tübingen
Mathematisch-Naturwissenschaftliche Fakultät
Wilhelm-Schickard-Institut für Informatik
Symbolisches Rechnen
Jonas Bollgrün, jonas.bollgruen@posteo.de, 2019

Bearbeitungszeitraum: April 1st-October 30th

Betreuer/Gutachter: Prof. Dr. Wolfgang Küchlin, Universität Tübingen
Zweitgutachter: Prof. Dr. Michael Kaufmann, Universität Tübingen

Selbstständigkeitserklärung

Hiermit versichere ich, dass ich die vorliegende Bachelorarbeit selbständig und nur mit den angegebenen Hilfsmitteln angefertigt habe und dass alle Stellen, die dem Wortlaut oder dem Sinne nach anderen Werken entnommen sind, durch Angaben von Quellen als Entlehnung kenntlich gemacht worden sind. Diese Bachelorarbeit wurde in gleicher oder ähnlicher Form in keinem anderen Studiengang als Prüfungsleistung vorgelegt.

Jonas Bollgrün (Matrikelnummer 3353424), 4. August 2019

Abstract

Template

Acknowledgments

If you have someone to Acknowledge ;)

Inhaltsverzeichnis

1. Introduction	11
2. Disambiguation	13
3. Base Algorithms	15
3.1. Probing algorithms	15
3.2. Intersection algorithms	16
3.3. Combining both approaches	16
3.4. Problem Statement	16
A. Blub	17

1. Introduction

introduction

wofür brauche ich backbones

wer hat sich damit beschäftigt

welche paper waren relevant

2. Disambiguation

definiere formel,klausel,literal,variable,prim implikante ,satisfiable/unsatisfiable

This thesis is an investigation on the calculation of backbones for boolean formulas in conjunctive normal form (or CNF in short). A CNF formula F is a conjunction of a set of clauses $C(F)$, meaning that all of these clauses have to be satisfied (or fulfilled) to satisfy the formula. A clause c in turn is a disjunction of a set of literals, meaning at least one of said literals must be fulfilled. A literal l can be defined as the occurrence of a boolean variable v which may or not be negated and to fulfill such a literal, it's variable must be assigned \perp for negated literals and \top for those literals without negation. The same variable can occur in multiple clauses of the same formula and must have the same assignment in all occurrences. A complete assignment of all variables of F (written as $Var(F)$) that leads to the formula being fulfilled is called a model. A formula for which no model can be found is called unsatisfiable.

The exact terminology can differ depending on the paper and project that you read. A formula can be called a problem and the assignment of a variable can be called it's phase. Clauses can also be called constraints and sometimes sentences. A synonym for a formula, clause or literal being fulfilled is it being satisfied. Models can also be called solutions of formulas

The backbone is a problem specific set of literals that contains all literals that occur in every model of that problem. We can also say that a variable is not part of the backbone, if neither it's positive or it's negative assignment is in the backbone. If we have an unsatisfiable formula, it's backbone can be considered undefinable, which is why this thesis concerns itself only with satisfiable CNF formulas. (TODO ref unsat backbone, aber keine einigkeit drüber)

3. Base Algorithms

The algorithms that I investigated for this thesis can be grouped very broadly into two approaches, which I will describe in the following two sections.

3.1. Probing algorithms

You can define the backbone as all literals that occur with the same assignment in all models of it's problem, which implies that enforcing that variable to either True or False should make the formula unsatisfiable. This definition already leads to a simple algorithm that can calculate the backbone, by checking both assignments of every literal for whether it would make the formula unsatisfiable, see Algorithm 1. This algorithm is referenced in TODO ref BB paper

Algorithm 1: ITERATIVE ALGORITHM (TWO TESTS PER VARIABLE)

Input: A formula F in CNF

Output: All literals of the backbone of F v_r

$v_r \leftarrow \emptyset$

for $x \in \text{Var}(F)$ **do**

$(\text{outc}_1, v) \leftarrow \text{SAT}(F \cup \{x\})$

$(\text{outc}_2, v) \leftarrow \text{SAT}(F \cup \{\neg x\})$

if $\text{outc}_1 = \perp \wedge \text{outc}_2 = \perp$ **then**

$\text{return } \emptyset$

else if $\text{outc}_1 = \perp$ **then**

$v_r = v_r \cup \{\neg x\}$

$F = F \cup \{\neg x\}$

else if $\text{outc}_2 = \perp$ **then**

$v_r = v_r \cup \{x\}$

$F = F \cup \{x\}$

return v_r

As is commonly written in literature about boolean satisfiability, the two calls to the *SAT* function return a pair which consists first of whether the given function was satisfiable at all and, secondly, the found model, which in this case is discarded.

There is no good algorithm that can tell whether a boolean formula is satisfiable or not without trying to find a model for said formula. We will see after the next section how we can make use of these models.

3.2. Intersection algorithms

An alternative definition of the backbone is the intersection of all models. If a literal is not part of the backbone, there must exist a model that contains the negation of that literal.

3.3. Combining both approaches

BB

What is this all about?

Cite like this: [?]

3.4. Problem Statement

A. Blub