

emo·ji for all (LaTeX engines)

Robert Grimm

Version v0.2a1 (2023/03/21)

Abstract

emo implements the `\emo{<emoji-name>}` command for including color emoji such as `\emo{desert-island}` for 🏖️ or `\emo{parrot}` for 🦜 in your documents independent of LaTeX engine. The implementation uses the Noto color emoji font if the engine supports it and includes PDF graphics otherwise. The latter are automatically derived from Noto's SVG sources, so the visual appearance is very similar. The source repository is at <https://github.com/apparebit/emo>. Emo may come in particularly handy when dealing with academic publishers that provide only minimal support for non-Latin scripts (cough, ACM, cough).

Contents

1	Installation	1
2	Usage	2
2.1	Emoji Names	3
2.2	Extras	3
3	Configuration	5
3.1	Update Configuration	5
4	Copyright and Licensing	5
5	Implementation	6
5.1	Package Options	6
5.2	Dependencies	7
5.3	The Emoji Table	7
5.4	Internal Macros	8
5.5	User Macros	8

1 Installation

Installation of the emo package is fairly straightforward, though it does involve a lot more files than usual.

1. Start by extracting this package's files from `emo.dtx` by running:

```
$ pdftex emo.dtx
```

Do *not* use `tex`; it mangles the embedded `README.md`. `pdflatex` also extracts the files and then builds the documentation.

2. Build the package documentation with change and symbol indices by running:

```
$ source build.sh
```

The shell script invokes `pdflatex emo.dtx` thrice and `makeindex` once each for the change and symbol indices to produce `emo.pdf`.

3. Get started reconfiguring supported emoji by running:

```
$ python config/emo.py -h
```

For more detailed instructions, see §3 below.

4. Put the following files somewhere LaTeX can find them. In a pinch, your current project's directory will do. However, `emo`'s installation potentially comprises thousands of files. So, you probably want to use a dedicated directory and add that to the search path for LaTeX, e.g., by setting the `TEXINPUTS` environment variable.

- (a) `emo.sty` with the package implementation;
- (b) `emo.def` with the emoji table;
- (c) `emo-lingchi.otf` with the glyphs for `\lingchi`;
- (d) *all* PDF files in the `emo-graphics` directory.

TeX Live requires that each package's files have unique names. For that reason, the PDF graphics in the `emo-graphics` directory start with the `emo-` prefix as well.

When running on the LuaLaTeX engine, the `emo` package also uses the Noto color emoji (`NotoColorEmoji.ttf`) and Linux Libertine (`LinLibertine_R.otf`) fonts, with the latter used for rendering `\YHWH` only. Neither file is included with `emo`'s distribution, since both of them are distributed with major TeX distributions already. If they are not included with your LaTeX distribution, you can find them on CTAN. The `emo-lingchi.otf` font distributed with `emo` is a two glyph subset of `NotoSerifTC-Regular.otf`, i.e., the traditional Chinese version of Noto serif.

2 Usage

As usual, you declare your document's dependency on `emo` with `\usepackage{emo}`. In addition to the unadorned form, `emo` takes up to two options:

extra Also define the `\lingchi` and `\YHWH` macros, which produce 凌遲 and יהוה, respectively, and are documented below.

index Create an emoji index tagged `emo` with the `.edx` extension for the raw index and the `.end` extension for the processed index. This option relies on the `index` package, generates the raw `.edx` file, but does not build or use the processed index.

`\emo` An `\emo{<emoji-name>}` invocation expands to the named emoji. For LuaLaTeX, it uses the Noto color emoji font. For all other engines, it uses PDF graphics. That way, `\emo{desert-island}` results in 🏝️ and `\emo{parrot}` results in 🦜.

Since LaTeX tends to produce a lot of command line noise about underfull boxes and loaded fonts, it's a easy to miss meaningful warnings. For that reason, `\emo` expands to an attention-seeking error message upon undefined emoji names. For example, `\emo{boo}` produces Bad \emo{boo}.

2.1 Emoji Names

With some exceptions, `emo`'s names for emoji are automatically derived from their Unicode names, with letters converted to lowercase, punctuation such as commas, colons, quotes, and parentheses stripped, and interword spaces replaced by dashes. Furthermore, instead of the rather verbose `dark-skin-tone`, `medium-dark-skin-tone`, etc modifiers, `emo` uses the more succinct `darkest`, `darker`, `medium`, `lighter`, and `lightest`.

For some emoji names, `emo` goes further by hard-coding shorter names. Those names are listed in Table 1.

`Emo`'s `emo.def` contains the names and codepoints of all currently supported emoji. Its distribution also includes the `emoji-test.txt` file, which is part of [Unicode TR-51](#) and contains the names and codepoints of all *potentially* supported emoji, i.e., all emoji. It further organizes emoji into groups and subgroups, with the current (sub)group being the one named on the closest line above the emoji that starts with `# (sub)group:`. As described in the next section, the group and subgroup names can be used during configuration for concisely naming a large number of emoji.

2.2 Extras

`\lingchi` The `\lingchi` and `\YHWH` macros take no arguments and produce 凌遲 and יהוה, respectively. They are only available if `emo` is used with the `extra` option. The former renders the Chinese term for “death by a thousand cuts.” While originally an execution method, the term applies to surprisingly many software systems as well. The latter produces the Tetragrammaton, the Hebrew name for God. Observant Jews never utter what's written, not even in their thoughts, substituting `Adonai` (“My Lord”), `Elohim` (“God”), or `HaShem` (“The Name”) instead. In my mind, that nicely mirrors the very incomprehensibility of יהוה. Both macros preserve a subsequent space as space, no backslash needed.

Table 1: Exceptional emoji names

Transformed Unicode Name	Emo Replacement Name
a-button-blood-type	a-button
ab-button-blood-type	ab-button
b-button-blood-type	b-button
o-button-blood-type	o-button
bust-in-silhouette	bust
busts-in-silhouette	busts
flag-european-union	eu
globe-showing-america	globe-america
globe-showing-asia-australia	globe-asia-australia
globe-showing-europe-africa	globe-africa-europe
hear-no-evil-monkey	hear-no-evil
index-pointing-at-the-viewer	index-pointing-at-viewer
index-pointing-at-the-viewer-darkest	index-pointing-at-viewer-darkest
index-pointing-at-the-viewer-darker	index-pointing-at-viewer-darker
index-pointing-at-the-viewer-medium	index-pointing-at-viewer-medium
index-pointing-at-the-viewer-lighter	index-pointing-at-viewer-lighter
index-pointing-at-the-viewer-lightest	index-pointing-at-viewer-lightest
keycap-*	keycap-star
keycap-#	keycap-hash
keycap-0	keycap-zero
keycap-1	keycap-one
keycap-2	keycap-two
keycap-3	keycap-three
keycap-4	keycap-four
keycap-5	keycap-five
keycap-6	keycap-six
keycap-7	keycap-seven
keycap-8	keycap-eight
keycap-9	keycap-nine
keycap-10	keycap-ten
magnifying-glass-tilted-left	loupe-left
magnifying-glass-tilted-right	loupe-right
palm-down-hand	palm-down
palm-down-hand-darkest	palm-down-darkest
palm-down-hand-darker	palm-down-darker
palm-down-hand-medium	palm-down-medium
palm-down-hand-lighter	palm-down-lighter
palm-down-hand-lightest	palm-down-lightest
palm-up-hand	palm-up
palm-up-hand-darkest	palm-up-darkest
palm-up-hand-darker	palm-up-darker
palm-up-hand-medium	palm-up-medium
palm-up-hand-lighter	palm-up-lighter
palm-up-hand-lightest	palm-up-lightest
rolling-on-the-floor-laughing	rofl
see-no-evil-monkey	see-no-evil
speak-no-evil-monkey	speak-no-evil

3 Configuration

Emo’s implementation is split over two files, `emo.sty` and `emo.def`. The former file defines the substance of the package, its options, its helper macros, and the user-visible `\emo`, `\lingchi`, and `\YHWH` macros. The latter file defines the table of supported emoji. For each such emoji, the table contains a command `\emo@emoji@⟨emoji-name⟩` with the emoji’s codepoints as value. `emo.sty` includes the table during loading and thereafter relies on it for validating emoji names and rendering emoji in LuaLaTeX. It may be possible to combine the two files into one, but that avoids at most a few disc reads and hence doesn’t seem worth the trouble.

3.1 Update Configuration

Invoke `config/emo.py` to automatically reconfigure emo’s supported emoji:

```
$ python3 config/emo.py <selector> <selector> ...
```

Each selector may be:

- The literal ALL (case-sensitive) for *all* emoji.
- Name of a group in `emoji-test.txt` lowercased and with spaces replaced by dashes and ampersand & replaced by an and; e.g., `travel-and-places`.
- Name of a group, a double colon `::`, and name of a subgroup, again lowercased and with spaces replaced by dashes and & by an and; e.g., `travel-and-places::place-geographic`.
- The name of an emoji; e.g., `desert-island`.

For conjunctive group names, such as “Smileys & Emotion” (`emoji-test.txt`) or “smileys-and-emotion” (`emo.py`), the configuration script also accepts either of the two nouns as a shortcut, e.g., “smileys” or “emotion.”

For data safety, `emo.py` does not overwrite PDF graphics and hence can only add emoji to the configuration. To remove emoji, simply remove their PDF graphics from `emo-graphics` and then run `emo.py`, which updates the emoji table accordingly.

`emo.py` effectively treats `emoji-test.txt` as registry of all emoji and the file-names of PDF graphics in `emo-graphics` as emo’s current inventory. For all emoji named by selector arguments but not in the inventory, `emo.py` converts the SVG source graphic from the Noto color emoji sources to a PDF file and deletes the `/Page /Group` object from the the PDF again, since that object trips up `pdflatex`. And yeah, `emo.py` automatically downloads the Noto color emoji sources if necessary.

4 Copyright and Licensing

Since emo’s distribution includes not only LaTeX code but also a substantial Python script, Unicode data about emoji, as well as graphics and fonts derived

from Google’s Noto project, a number of different licenses apply. All of them are [OSI approved](#) and non-copyleft:

- This package’s LaTeX code is © Copyright 2023 by Robert Grimm and has been released under the [LPPL v1.3c](#) or later.
- The `config/emo.py` script also is © Copyright 2023 by Robert Grimm but has been released under the [Apache 2.0 license](#).
- The `[config/emoji-test.txt]` configuration file is a data file from [Unicode TR-51](#) and hence subject to the [Unicode License](#).
- The `emo-lingchi.otf` font is a two-glyph subset of the traditional Chinese version of Google’s [Noto serif](#) and hence subject to the [SIL Open Font License v1.1](#).
- The PDF graphics in the `emo-graphics` directory are derived from the sources for [Noto’s color emoji](#) and hence subject to the Apache 2.0 license.

5 Implementation

Now that we understand how to configure `emo`, we are ready for exploring the implementation in detail. Let’s get started:

```
1 <package>
```

Except, the package implementation started near the top of the `emo.dtx` file, so that version number and date are more visible and declared only once. But that’s also well before the documentation preamble and hence cannot be included in the annotated implementation. Nonetheless, we can simulate the lines:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{emo}
[2023/03/21 v0.2a1 emo.ji for all (LaTeX engines)]
```

And no, I didn’t repeat the version number, date, or package information. Check `emo.dtx`.

5.1 Package Options

Emo’s extra and index options are simple flags. So, we declare a `\newif` for each option and, if the package use includes an option, it just toggles the conditional’s state:

```
2 \newif\ifemo@extra\emo@extrafalse
3 \DeclareOption{extra}{\emo@extratrue}
4 \newif\ifemo@index\emo@indexfalse
5 \DeclareOption{index}{\emo@indextrue}
6 \ProcessOptions\relax
```

5.2 Dependencies

The dependency on `inputenc` effectively declares this file’s encoding to be UTF-8. The XeTeX and LuaTeX engines already expect files to be encoded that way and hence ignore the declaration. However, pdfTeX supports other (legacy) encodings and needs to be told.

```
7 \RequirePackage[utf8]{inputenc}
```

Depending on TeX engine, this package requires either `fontspec` or `graphicx` as the emoji-emitting backend. In turn, to tell the engines apart, it requires `iftex`.

```
8 \RequirePackage{iftex}
9 \ifluatex
10 \RequirePackage{fontspec}
11 \else
12 \RequirePackage{graphicx}
13 \fi
```

Emo requires `xcolor` for formatting highly visible error messages within the text. Always including another package that is only used when there are errors is not ideal. But when I tried calling `\RequirePackage` for `xcolor` from inside the error macro, it didn’t work. Alternatively, I could make in-text errors optional.

```
14 \RequirePackage{xcolor}
```

Finally, `emo`’s options also have dependencies, with `extra` requiring the `xspace` package and `index` requiring the `index` package:

```
15 \ifemo@extra
16 \RequirePackage{xspace}
17 \fi
18 \ifemo@indexing
19 \RequirePackage{index}
20 \fi
```

5.3 The Emoji Table

For each emoji with a PDF graphic in the `emo-graphics` directory, a macro named `\emo@emoji@<emoji-name>` expands to its Unicode sequence. With over 3,000 distinct emoji in Unicode 15, `emo` relies on a Python script for populating the graphics directory and writing the table to the `emo.def` file. Since the package code does not change after installation but the emoji table may very well change, they are kept separate for now. Alternatively, we could use `DocStrip` to assemble the package file from three parts, the code from the previous sections, then the contents of the emoji table in `emo.def`, and then all subsequent code.

```
21 \input{emo.def}
```

5.4 Internal Macros

`emo@error@fg` Define two colors and a function that uses the two colors for formatting an
`emo@error@bg` attention-grabbing error message. If you use an invalid emoji name and over-
`emo@error` look the warning in the console, you *will* notice the error message in the doc-
ument thusly formatted.

```
22 \definecolor{emo@error@fg}{rgb}{1,1,1}
23 \definecolor{emo@error@bg}{rgb}{.6824,.0863,.0863}
24 \def\emo@error#1{%
25     \colorbox{emo@error@bg}{%
26         \textcolor{emo@error@fg}{%
27             \textsf{Bad} \texttt{\textbackslash emo\{#1\}}%
28         }%
29     }%
30 }
```

`emo@ifdef` Validate the emoji name given as first argument. The macro expands to the
second argument if the name is valid and an error message otherwise. Its im-
plementation relies on the `emo@emoji` table.

```
31 \def\emo@ifdef#1#2{%
32     \ifcsname emo@emoji@#1\endcsname#2\else%
33         \PackageWarning{emo}{Unknown emoji name in ‘\string\emo{#1}’}%
34         \emo@error{#1}%
35     \fi%
36 }
```

`emo@index` If indexing is enabled, record the use of an emoji. Otherwise, do nothing.

```
37 \ifemo@indexing
38 \newindex{emo}{edx}{end}{Emoji Index}
39 \def\emo@index#1{\index[emo]{#1}}
40 \else
41 \def\emo@index#1{}
42 \fi
```

5.5 User Macros

`emo` Emit the named color emoji. Both the font-based version for LuaTeX and
the graphics-based fallback validate the emoji name and then invoke the
`\emo@index` macro. But they differ in how they actually display the emoji. The
LuaTeX version turns the emoji name into its Unicode sequence and wraps that
in a group that also uses the previously declared Noto color emoji font. The
fallback version instead includes a suitably sized PDF graphic.

```
43 \ifluatex
44 \newfontface\emo@font[Renderer=Harfbuzz]{NotoColorEmoji.ttf}
45 \newcommand\emo[1]{%
46     \emo@ifdef{#1}{%
47         \emo@index{#1}%
```



```

48      {\emo@font\csname emo@emoji@#1\endcsname}%
49    }%
50  }
51  \else
52  \newcommand\emo[1]{%
53    \emo@ifdef{#1}{%
54      \emo@index{#1}%
55      \raisebox{-0.2ex}{\includegraphics[height=1em]{emo-#1}}%
56    }%
57  }
58  \fi

```

lingchi The definitions for the optional \lingchi and \YHWH macros follow from that of YHWH \emo, except that (a) there are no arguments to validate and hence no equivalent to \emo@ifdef; (b) Hebrew is written right-to-left and hence \YHWH requires a \textdir TRT; (c) subsequent space should be preserved and hence both macros end with \xspace. While it would be nice to use Unicode inside the groups for the LuaTeX macros, doing so breaks the package documentation. So \char it is.

```

59 \ifemo@extra
60 \ifluatex
61 \newfontface\emo@chinese{emo-lingchi.otf}
62 \newfontface\emo@hebrew{LinLibertine_R.otf}
63 \newcommand\lingchi{%
64   \emo@index{lingchi}%
65   \begingroup\emo@chinese \char"51CC\char"9072\endgroup%
66   \xspace}
67 \newcommand\YHWH{%
68   \emo@index{YHWH}%
69   \begingroup\textdir TRT\emo@hebrew \char"5D9\char"5D4\char"5D5\char"5D4\endgroup%
70   \xspace}
71 \else
72 \newcommand\lingchi{%
73   \emo@index{lingchi}%
74   \raisebox{-0.2ex}{\includegraphics[height=1em]{emo-lingchi}}%
75   \xspace}
76 \newcommand\YHWH{%
77   \emo@index{YHWH}%
78   \raisebox{-0.2ex}{\includegraphics[height=1em]{emo-YHWH}}%
79   \xspace}
80 \fi
81 \fi

```

Et voilà. That's it!

```
82 </package>
```

Change History

0.2 – 2023-03-23	Include PDF graphics directly,
General: Extract with pdftex,	without directory 1
document with pdflatex 1	

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

C		P	
\colorbox	25	\emo@index . . .	37, 39, 41, 47, 54, 64, 68, 73, 77
D		\emo@indexingfalse . . .	4
\DeclareOption	3, 5	\emo@indexingtrue	5
\definecolor	22, 23	R	
E		\raisebox	55, 74, 78
\emo	33, <u>43</u>, 45, 52	\RequirePackage	7, 8, 10, 12, 14, 16, 19
\emo@chinese	61, 65	T	
\emo@error	22, 24, 34	\textcolor	26
\emo@error@bg	22	\textdir	69
\emo@error@fg	22	X	
\emo@extrafalse	2	\xspace	66, 70, 75, 79
\emo@extratrue	3	Y	
\emo@font	44, 48	\YHWH	59, 67, 76
\emo@hebrew	62, 69	N	
\emo@ifdef . . .	31, 31, 46, 53	\newfontface . . .	44, 61, 62
I		L	
\ifemo@extra	2, 15, 59	\lingchi	59, 63, 72
\ifemo@indexing . . .	4, 18, 37	Y	
\includegraphics . . .	55, 74, 78		
\input	21		