

Cheatsheet Programmierung II

Daniel Appenmaier, Juni 2026

Cheatsheet

java.lang

```
Boolean  int  compare(x: boolean, y: boolean)  // static
Boolean  Boolean  valueOf(s: String)  // static
Boolean  Boolean  valueOf(b: boolean)  // static
Comparable<T>  int  compareTo(o: T)
Double  int  compare(d1: double, d2: double)  // static
Double  Double  valueOf(s: String)  // static
Double  Double  valueOf(d: double)  // static
Integer  int  compare(x: int, y: int)  // static
Integer  Integer  valueOf(s: String)  // static
Integer  Integer  valueOf(i: int)  // static
Long  long  compare(x: long, y: long)  // static
Long  Long  valueOf(s: String)  // static
Long  Long  valueOf(l: long)  // static
Object  boolean  equals(object: Object)
Object  int  hashCode()
Object  String  toString()
Runnable  void  run()
String  char  charAt(index: int)
String  int  length()
String  String[]  split(regex: String)
String  String  toLowerCase()
String  String  toUpperCase()
System  long  currentTimeMillis()  // static
```

java.time

```
LocalDate  int  getDayOfMonth()
LocalDate  int  getDayOfYear()
LocalDate  Month  getMonth()
LocalDate  int  getMonthValue()
LocalDate  int  getYear()
LocalDate  LocalDate  now()  // static
LocalDate  LocalDate  of(year: int, month: int, dayOfMonth: int)  // static
LocalDate  LocalDate  parse(text: CharSequence)  // static
LocalTime  int  getHour()
LocalTime  int  getMinute()
LocalTime  int  getSecond()
LocalTime  LocalTime  now()  // static
LocalTime  LocalTime  of(hour: int, minute: int, second: int)  // static
LocalTime  LocalTime  parse(text: CharSequence)  // static
```

java.util

```
Aufzählung  Aufzählung  valueOf(arg0: String)  // static
Aufzählung  Aufzählung[]  values()  // static
Collections  void  sort(list: List<T>)  // static
Collections  void  sort(list: List<T>, c: Comparator<T>)  // static
Comparator<T>  int  compare(o1: T, o2: T)
Entry<K,V>  K  getKey()
```

```
Entry<K,V> V getValue()
Entry<K,V> V setValue(value: V)
List<E> boolean add(e: E)
List<E> void add(index: int, element: E)
List<E> boolean contains(o: Object)
List<E> void forEach(action: Consumer<T>)
List<E> E get(index: int)
List<E> List<E> of(elements: E...) // static
List<E> E remove(index: int)
List<E> boolean remove(o: Object)
List<E> List<T> reversed()
List<E> int size()
Map<K,V> boolean containsKey(key: Object)
Map<K,V> boolean containsValue(value: Object)
Map<K,V> Set<Entry<K,V>> entrySet()
Map<K,V> void forEach(action: BiConsumer<K,V>)
Map<K,V> V get(key: Object)
Map<K,V> Set<K> keySet()
Map<K,V> V put(key: K, value: V)
Map<K,V> V putIfAbsent(key: K, value: V)
Map<K,V> Collection<V> values()
Optional<T> Optional<T> empty() // static
Optional<T> T get()
Optional<T> void ifPresent(action: Consumer<T>)
Optional<T> void ifPresentOrElse(action: Consumer<T>, emptyAction: Runnable)
Optional<T> boolean isPresent()
Optional<T> Optional<T> of(t: T) // static
Optional<T> Optional<T> ofNullable(t: T) // static
Optional<T> T orElse(other: T)
OptionalDouble OptionalDouble empty() // static
OptionalDouble double getAsDouble()
OptionalDouble void ifPresent(action: DoubleConsumer)
OptionalDouble void ifPresentOrElse(action: DoubleConsumer, emptyAction: Runnable)
OptionalDouble boolean isPresent()
OptionalDouble OptionalDouble of(value: double) // static
OptionalDouble double orElse(other: double)
Random int nextInt(origin: int, bound: int)
```

java.util.function

```
BiConsumer void accept(t: T, u: U)
Consumer<T> void accept(t: T)
DoubleConsumer void accept(value: double)
Function<T,R> R apply(t: T)
Predicate<T> boolean test(t: T)
ToDoubleFunction<T,R> double applyAsDouble(value: T)
ToIntFunction<T,R> int applyAsInt(value: T)
```

java.util.stream

```
Collectors Collector<T,?,Map<K,List<T>>> groupingBy(classifier: Function<T,K>) //
static
```

```

DoubleStream OptionalDouble average()
DoubleStream double sum()
IntStream OptionalDouble average()
IntStream int sum()
Stream<T> boolean allMatch(predicate: Predicate<T>)
Stream<T> boolean anyMatch(predicate: Predicate<T>)
Stream<T> R collect(collector: Collector<T,A,R>)
Stream<T> long count()
Stream<T> Stream<T> distinct()
Stream<T> Stream<T> filter(predicate: Predicate<T>)
Stream<T> Optional<T> findAny()
Stream<T> Optional<T> findFirst()
Stream<T> void forEach(action: Consumer<T>)
Stream<T> Stream<T> limit(maxSize: long)
Stream<T> Stream<R> map(mapper: Function<T,R>)
Stream<T> DoubleStream mapToDouble(mapper: ToDoubleFunction<T,R>)
Stream<T> IntStream mapToInt(mapper: ToIntFunction<T,R>)
Stream<T> Optional<T> max(comparator: Comparator<T>)
Stream<T> Optional<T> min(comparator: Comparator<T>)
Stream<T> boolean noneMatch(predicate: Predicate<T>)
Stream<T> Stream<T> skip(n: long)
Stream<T> Stream<T> sorted()
Stream<T> Stream<T> sorted(comparator: Comparator<T>)
Stream<T> List<T> toList()

```

java.io

```

PrintStream void print(obj: Object)
PrintStream void println()
PrintStream void println(x: Object)

```

org.junit.jupiter.api

```

Assertions void assertEquals(expected: Object, actual: Object) // static
Assertions void assertFalse(condition: boolean) // static
Assertions void assertNotEquals(expected: Object, actual: Object) // static
Assertions void assertNotNull(actual: Object) // static
Assertions void assertNotSame(expected: Object, actual: Object) // static
Assertions void assertNull(actual: Object) // static
Assertions void assertSame(expected: Object, actual: Object) // static
Assertions T assertThrows(expectedType: Class<T>, executable: Executable) // static
Assertions void assertTrue(condition: boolean) // static
Executable void execute()

```

org.mockito / org.mockito.stubbing

```

Mockito OngoingStubbing<T> when(methodCall: T) // static
MockitoAnnotations AutoCloseable openMocks(testClass: Object) // static
OngoingStubbing<T> OngoingStubbing<T> thenReturn(value: T)

```