



## ***API for PMS***

*XML interface API for PMS communication towards Vertical Booking*

*08:085 - ver. 1.18*



A.E.C. ADVERTISING AND ELECTRONIC COMMERCE s.r.l.

Piazza Pontida, 7 – I-24122 Bergamo (Italy) - Tel. +39 035 232366 - Fax. +39 035 210500

E-mail: [xml@verticalbooking.com](mailto:xml@verticalbooking.com)

## Version History:

Version	Date	Author(s)	Notes
1.2	3-Feb-2011	Ing. Francesco Carsana	
1.3	8-Jun-2011	Ing. Francesco Carsana	
1.4	4-Jul-2011	Ing. Francesco Carsana	Added rates updates (for person prices)
1.5	6-Oct-2011	Dott. Luca Stucchi	Added destination channel tags for booking rules
1.6	24-Oct-2011	Dott. Luca Stucchi	Added booking retrieval reference section
1.7	10-Nov-2011	Ing. Francesco Carsana	Moved GuestCounts section in booking response
1.8	17-Jan-2012	Ing. Francesco Carsana	Added modified booking reference in booking response
1.9	20-Feb-2012	Ing. Francesco Carsana	Added Close to Departure documentation
1.10	05-Mar-2012	Ing. Francesco Carsana	Added Discount tag in booking retrieval
1.11	09-Jul-2012	Ing. Francesco Carsana	Reservations: Fixed day-by-day rates detail
1.12	31-Aug-2012	Dott. Luca Stucchi	Added price updates for adults in extra beds
1.13	06-Sep-2012	Dott. Luca Stucchi	Added Ping message
1.14	13-Jan-2014	Ing. Francesco Carsana	Added hotel code reference in reservation retrieval
1.15	27-Feb-2014	Dott. Luca Stucchi	Added Affiliation information in reservation retrieval
1.16	19-Jun-2014	Ing. Francesco Carsana	Added Services information in reservation retrieval
1.17	12-Aug-2015	Ing. Francesco Carsana	Added "Modify" status in reservation retrieval
1.18	10-May-2016	Ing. Francesco Carsana	Formatting



## Index


---

<b>1Introduction.....</b>	<b>5</b>
<b>2Set Up.....</b>	<b>5</b>
<b>3Ping Message.....</b>	<b>7</b>
3.1Request Reference.....	7
3.2Request Example.....	7
3.3Response Reference.....	9
3.4Response Example.....	9
<b>4Availability Update.....</b>	<b>10</b>
4.1Reference.....	10
4.2Request Example.....	10
4.3Response Example.....	12
<b>5Rates Update (per room prices).....</b>	<b>13</b>
5.1Reference.....	13
5.2Request Example.....	13
5.3Response Example.....	15
<b>6Rates Update (per person prices).....</b>	<b>16</b>
6.1Reference.....	16
6.2Request Example.....	17
6.3Response Example.....	18
<b>7Booking Rules Update.....</b>	<b>20</b>
7.1Reference.....	20
7.2Request Example.....	21
7.3Response Example.....	22
<b>8Booking Retrieval.....</b>	<b>24</b>
8.1Request Reference.....	24
8.2Request Example.....	24
8.3Response Reference.....	25
8.4Response Example.....	29
<b>9Booking Confirmation.....</b>	<b>35</b>
9.1Request Reference.....	35
9.2Request Example.....	35
9.3Response Example.....	36



## 1 Introduction

**Vertical Booking** is a complete and versatile online booking system with an integrated **IDS Channel Manager** and **GDS connectivity**. Simple for hoteliers to manage and incredibly easy to use for hotel guests, the system provides complete and up to date information for its users.



The following API allows a **PMS to connect** with Vertical Booking and all the way through to the IDS and GDS.



## 2 Set Up

In order to activate the interface the following parameters are necessary:

- User name
- Password
- Hotel Id
- Room codes
- Rate plan codes

## 3 Ping Message

### 3.1 Request Reference

Item	Type	Description	Values Format
<b>OTA_PingRQ</b>			
TimeStamp	DateTime		
Version	String		1.001
<b>EchoData</b>	String		

### 3.2 Request Example

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns1="http://www.opentravel.org/OTA/2003/05" xmlns:ns2="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:ns3="http://schemas.xmlsoap.org/ws/2004/08/addressing">
<SOAP-ENV:Header>
  <ns2:Security SOAP-ENV:mustUnderstand="1">
    <UsernameToken>
      <Username>username</Username>
      <Password>password</Password>
```



```
</UsernameToken>

</ns2:Security>

<ns3:MessageID>uuid:bc12ff01-2329-f0dc-84e9-12ae9b579f32</ns3:MessageID>

<ns3:To>https://www.aec-internet.it/booking\_engine/int/pms\_generic/OTA\_PMS.php</ns3:To>

<ns3:Action>OTA_Ping</ns3:Action>

<ns3:From>

  <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

</ns3:From>

</SOAP-ENV:Header>

<SOAP-ENV:Body>

  <ns1:OTA_PingRQ TimeStamp="2012-09-06T10:45:29+02:00" Version="1">

    <ns1:EchoData>Vertical Booking XML Ping</ns1:EchoData>

  </ns1:OTA_PingRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



### 3.3 Response Reference

Item	Type	Description	Values Format
OTA_PingRS EchoData	String		

### 3.4 Response Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope

xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns1="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:ns2="http://www.opentravel.org/OTA/2003/05">

  <SOAP-ENV:Header>

    <ns1:MessageID>uuid:4df96af4-c512-9983-a65d-64a80eeb4f6b</ns1:MessageID>

    <ns1:To>https://xml.verticalbooking.com/pms\_generic/OTA\_PMS.php</ns1:To>

    <ns1:From>

      <Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

    </ns1:From>

  </SOAP-ENV:Header>

  <SOAP-ENV:Body>

    <ns2:OTA_PingRS>

      <ns2:Success/>

      <ns2:EchoData>Vertical Booking XML Ping</ns2:EchoData>

    </ns2:OTA_PingRS>

  </SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



## 4 Availability Update

This method is used to update availability.

### 4.1 Reference

Item	Type	Description	Values Format
<b>OTA_HotelInvCountNotifRQ</b>			
TimeStamp	DateTime		
Version	String		1.001
<b>Inventories</b>			
HotelCode	Integer	Unique identifier for the hotel	
<b>Inventory</b>			
<b>StatusApplicationControl</b>			
Start	Date	Start date	YYYY-MM-DD
End	Date	End date; note that end date is inclusive	YYYY-MM-DD
InvTypeCode	String	Vertical Booking Room Code	
<b>InvCounts</b>			
<b>InvCount</b>			
CountType	Int		1
Count	Int		

### 4.2 Request Example

This example shows an inventory update for the MTDR room: on Nov 25<sup>th</sup> there are 10 rooms available, and on Nov 26th there are 5 rooms available.

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://www.opentravel.org/OTA/2003/05" xmlns:ns2 = "http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd" xmlns:ns3 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing">

  <SOAP-ENV:Header>

    <ns2:Security SOAP-ENV:mustUnderstand = "1">

      <UsernameToken>

        <Username>test</Username>

        <Password>test</Password>
```





```
</UsernameToken>

</ns2:Security>

<ns3:MessageID>uuid:84344d83-8078-e17f-a721-56e2facbf13d</ns3:MessageID>

<ns3:To>http://www.myhotel.com/ws/ota</ns3:To>

<ns3:Action>http://www.myhotel.com/ws/ota/OTA_ReadRQ</ns3:Action>

<ns3:From>

  <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

</ns3:From>

</SOAP-ENV:Header>

<SOAP-ENV:Body>

  <ns1:OTA_HotelInvCountNotifRQ TimeStamp = "2010-10-22T16:47:16+02:00" Version = "1.001">

    <ns1:Inventories HotelCode = "5071">

      <ns1:Inventory>

        <ns1:StatusApplicationControl Start = "2010-11-25" End = "2010-11-25" InvTypeCode =
"MTRD"/>

        <ns1:InvCounts>

          <ns1:InvCount CountType = "1" Count = "10"/>

        </ns1:InvCounts>

      </ns1:Inventory>

      <ns1:Inventory>

        <ns1:StatusApplicationControl Start = "2010-11-26" End = "2010-11-26" InvTypeCode =
"MTRD"/>

        <ns1:InvCounts>

          <ns1:InvCount CountType = "1" Count = "5"/>

        </ns1:InvCounts>

      </ns1:Inventory>

    </ns1:Inventories>

  </ns1:OTA_HotelInvCountNotifRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



### 4.3 Response Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:ns2 =
"http://www.opentravel.org/OTA/2003/05">

  <SOAP-ENV:Header>

    <ns1:MessageID>uuid:e73be007-3adb-cc93-8394-e56977350c3f</ns1:MessageID>

    <ns1:To>http://www.myhotel.com/ws/ota</ns1:To>

    <ns1:From>

<Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

    </ns1:From>

    <ns1:RelatesTo RelationshipType = "ns1:Reply">uuid:84344d83-8078-e17f-a721-
56e2facbf13d</ns1:RelatesTo>

    <ns1:Action>http://www.aec-
internet.it/booking_engine/int/myhotel/OTA_HotelInvCountNotifRS</ns1:Action>

  </SOAP-ENV:Header>

  <SOAP-ENV:Body>

    <ns2:OTA_HotelInvCountNotifRS>

      <ns2:Success/>

    </ns2:OTA_HotelInvCountNotifRS>

  </SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



## 5 Rates Update (per room prices)

This method is used to update rates (per room prices).

### 5.1 Reference

Item	Type	Description	Values Format
<b>OTA_HotelRateAmountNotifRQ</b>			
TimeStamp	datetime		
Version	String		1.000
<b>RateAmountMessages</b>			
HotelCode	Integer	Unique identifier for the hotel	
<b>RateAmountMessages</b>			
<b>RateAmountMessage</b>			
<b>StatusApplicationControl</b>			
Start	Date	Start date	YYYY-MM-DD
End	Date	End date; note that end date is inclusive	YYYY-MM-DD
InvTypeCode	String	Vertical Booking Room Code	
RatePlanCode	String	Vertical Booking Rate Code	
<b>Rates</b>			
<b>Rate</b>			
<b>BaseByGuestAmts</b>			
CurrencyCode	String	Hotel Currency	
AmountAfterTax	Float	Price	

### 5.2 Request Example

This example updates the rate for the MTRD room and BB\_BAR\_ROOM rate plan from Nov 25th to Nov 26th:

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://www.opentravel.org/OTA/2003/05" xmlns:ns2 = "http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd" xmlns:ns3 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing">

  <SOAP-ENV:Header>

    <ns2:Security SOAP-ENV:mustUnderstand = "1">

      <UsernameToken>
```



```
<Username>test</Username>

<Password>test</Password>

</UsernameToken>

</ns2:Security>

<ns3:MessageID>uuid:ee4f29bd-070d-a0d9-5e41-f06910676ff7</ns3:MessageID>

<ns3:To>http://www.myhotel.com/ws/ota</ns3:To>

<ns3:Action>http://www.myhotel.com/ws/ota/OTA_ReadRQ</ns3:Action>

<ns3:From>

  <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

</ns3:From>

</SOAP-ENV:Header>

<SOAP-ENV:Body>

  <ns1:OTA_HotelRateAmountNotifRQ TimeStamp = "2010-10-26T09:25:18+02:00" Version = "1.000">

    <ns1:RateAmountMessages HotelCode = "5071">

      <ns1:RateAmountMessage>

        <ns1:StatusApplicationControl Start = "2010-11-25" End = "2010-11-25" RatePlanCode =
"BB_BAR_ROOM" InvTypeCode = "MTRD"/>

        <ns1:Rates>

          <ns1:Rate>

            <ns1:BaseByGuestAmts>

              <ns1:BaseByGuestAmt AmountAfterTax = "123.00" CurrencyCode = "EUR"/>

            </ns1:BaseByGuestAmts>

          </ns1:Rate>

        </ns1:Rates>

      </ns1:RateAmountMessage>

      <ns1:RateAmountMessage>

        <ns1:StatusApplicationControl Start = "2010-11-26" End = "2010-11-28" RatePlanCode =
"BB_BAR_ROOM" InvTypeCode = "MTRD"/>

        <ns1:Rates>

          <ns1:Rate>

            <ns1:BaseByGuestAmts>

              <ns1:BaseByGuestAmt AmountAfterTax = "234.00" CurrencyCode = "EUR"/>

            </ns1:BaseByGuestAmts>

          </ns1:Rate>

        </ns1:Rates>

      </ns1:RateAmountMessage>

    </ns1:RateAmountMessages>

  </ns1:OTA_HotelRateAmountNotifRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



```
        </ns1:BaseByGuestAmts>

        </ns1:Rate>

        </ns1:Rates>

        </ns1:RateAmountMessage>

        </ns1:RateAmountMessages>

        </ns1:OTA_HotelRateAmountNotifRQ>

    </SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```

### 5.3 Response Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:ns2 =
"http://www.opentravel.org/OTA/2003/05">

    <SOAP-ENV:Header>

        <ns1:MessageID>uuid:952bf152-52e1-ede5-e16c-801bce155c60</ns1:MessageID>

        <ns1:To>http://www.myhotel.com/ws/ota</ns1:To>

        <ns1:From>

            <Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

        </ns1:From>

        <ns1:RelatesTo RelationshipType = "ns1:Reply">uuid:ee4f29bd-070d-a0d9-5e41-
f06910676ff7</ns1:RelatesTo>

        <ns1:Action>http://www.aec-
internet.it/booking_engine/int/myhotel/OTA_HotelRateAmountNotifRS</ns1:Action>

    </SOAP-ENV:Header>

    <SOAP-ENV:Body>

        <ns2:OTA_HotelRateAmountNotifRS>

            <ns2:Success/>

        </ns2:OTA_HotelRateAmountNotifRS>

    </SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



## 6 Rates Update (per person prices)

This method is used to update rates (per person prices).

### 6.1 Reference

Item	Type	Description	Values Format
<b>OTA_HotelRateAmountNotifRQ</b>			
TimeStamp	datetime		
Version	String		1.000
<b>RateAmountMessages</b>			
HotelCode	Integer	Unique identifier for the hotel	
<b>RateAmountMessages</b>			
<b>RateAmountMessage</b>			
<b>StatusApplicationControl</b>			
Start	Date	Start date	YYYY-MM-DD
End	Date	End date; note that end date is inclusive	YYYY-MM-DD
InvTypeCode	String	Vertical Booking Room Code	
RatePlanCode	String	Vertical Booking Rate Code	
<b>Rates</b>			
<b>Rate</b>			
<b>BaseByGuestAmts</b>			
CurrencyCode	String	Hotel Currency	
AmountAfterTax	Float	Price	
NumberOfGuests	Int	Number of guest	
AgeQualifyingCode	Int	7 – Infant 8 – Child 9 – Teenager 10 – Adult 12 – Adult in extra bed  In case you use 7,8,9, NumberOfGuests must be 1  In case you use 12 NumberOfGuests must be between 1 and 3	[7   8   9   10   12]



## 6.2 Request Example

This example updates the rate for the MTRD toom and BB\_BAR\_ROOM rate plan from Nov 25th to Nov 26<sup>th</sup>:

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://www.opentravel.org/OTA/2003/05" xmlns:ns2 = "http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd" xmlns:ns3 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing">

  <SOAP-ENV:Header>

    <ns2:Security SOAP-ENV:mustUnderstand = "1">

      <UsernameToken>

        <Username>test</Username>

        <Password>test</Password>

      </UsernameToken>

    </ns2:Security>

    <ns3:MessageID>uuid:ee4f29bd-070d-a0d9-5e41-f06910676ff7</ns3:MessageID>

    <ns3:To>http://www.myhotel.com/ws/ota</ns3:To>

    <ns3:Action>http://www.myhotel.com/ws/ota/OTA_ReadRQ</ns3:Action>

    <ns3:From>

      <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

    </ns3:From>

  </SOAP-ENV:Header>

  <SOAP-ENV:Body>

    <ns1:OTA_HotelRateAmountNotifRQ TimeStamp = "2010-10-26T09:25:18+02:00" Version = "1.000">

      <ns1:RateAmountMessages HotelCode = "5071">

        <ns1:RateAmountMessage>

          <ns1:StatusApplicationControl Start = "2010-11-25" End = "2010-11-25" RatePlanCode =
"BB_BAR_ROOM" InvTypeCode = "MTRD"/>

          <ns1:Rates>

            <ns1:Rate>

              <ns1:BaseByGuestAmts>

                <ns1:BaseByGuestAmt AmountAfterTax = "123.00" CurrencyCode = "EUR" NumberOfGuests =
"2" AgeQualifyingCode = "10"/>

              </ns1:BaseByGuestAmts>

            </ns1:Rate>

          </ns1:Rates>

        </ns1:RateAmountMessage>

      </ns1:RateAmountMessages>

    </ns1:OTA_HotelRateAmountNotifRQ>

  </SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



A.E.C. ADVERTISING AND ELECTRONIC COMMERCE s.r.l.

Piazza Pontida, 7 – I-24122 Bergamo (Italy) - Tel. +39 035 232366 - Fax. +39 035 210500

E-mail: [xml@verticalbooking.com](mailto:xml@verticalbooking.com)

```

        </ns1:BaseByGuestAmts>

        </ns1:Rate>

    </ns1:Rates>

</ns1:RateAmountMessage>

<ns1:RateAmountMessage>

    <ns1:StatusApplicationControl Start = "2010-11-26" End = "2010-11-28" RatePlanCode =
"BB_BAR_ROOM" InvTypeCode = "MTRD"/>

    <ns1:Rates>

        <ns1:Rate>

            <ns1:BaseByGuestAmts>

                <ns1:BaseByGuestAmt AmountAfterTax = "234.00" CurrencyCode = "EUR" NumberOfGuests =
"2" AgeQualifyingCode = "10"/>

            </ns1:BaseByGuestAmts>

        </ns1:Rate>

    </ns1:Rates>

</ns1:RateAmountMessage>

</ns1:RateAmountMessages>

</ns1:OTA_HotelRateAmountNotifRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>

```

### 6.3 Response Example

```

<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:ns2 =
"http://www.opentravel.org/OTA/2003/05">

    <SOAP-ENV:Header>

        <ns1:MessageID>uuid:952bf152-52e1-ede5-e16c-801bce155c60</ns1:MessageID>

        <ns1:To>http://www.myhotel.com/ws/ota</ns1:To>

        <ns1:From>

            <Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

        </ns1:From>

        <ns1:RelatesTo RelationshipType = "ns1:Reply">uuid:ee4f29bd-070d-a0d9-5e41-
f06910676ff7</ns1:RelatesTo>

```



A.E.C. ADVERTISING AND ELECTRONIC COMMERCE s.r.l.

Piazza Pontida, 7 – I-24122 Bergamo (Italy) - Tel. +39 035 232366 - Fax. +39 035 210500

E-mail: [xml@verticalbooking.com](mailto:xml@verticalbooking.com)



```
<ns1:Action>http://www.aec-  
internet.it/booking_engine/int/myhotel/OTA_HotelRateAmountNotifRS</ns1:Action>  
  
</SOAP-ENV:Header>  
  
<SOAP-ENV:Body>  
  
  <ns2:OTA_HotelRateAmountNotifRS>  
  
    <ns2:Success/>  
  
  </ns2:OTA_HotelRateAmountNotifRS>  
  
</SOAP-ENV:Body>  
</SOAP-ENV:Envelope>
```



## 7 Booking Rules Update

### 7.1 Reference

Item	Type	Description	Values Format
<b>OTA_HotelBookingRuleNotifRQ</b>			
TimeStamp	datetime		
Target	String		Production
Version	String		1.000
<b>RulesMessages</b>			
HotelCode	Integer	Unique identifier for the hotel	
<b>RuleMessages</b>			
<b>RuleMessage</b>			
<b>StatusApplicationControl</b>			
Start	Date	Start date	YYYY-MM-DD
End	Date	End date; note that end date is inclusive	YYYY-MM-DD
InvTypeCode	String	Vertical Booking Room Code	
RatePlanCode	String	Vertical Booking Rate Code	
<b>DestinationSystemCodes</b>			
<b>DestinationSystemCode</b>	Int	Vertical Booking Channel code	
<b>BookingRules</b>			
<b>BookingRule</b>			
<b>RestrictionStatus</b>			
Restiction	String	Master: stop sales on room code /rate code for the specified period, Arrival: closed to arrival room code /rate code for the specified period, Departure: closed to departure room code /rate code for the specified period	[Master   Arrival   Departure]
<b>Status</b>			Open/Close
<b>LengthsOfStay</b>			
<b>LengthOfStay</b>			
MinMaxMessageType	String		SetMinLOS
TimeUnit	String		Day



Time	Int		
------	-----	--	--

## 7.2 Request Example

This example updates the inventory for the DBL room and BAR rate plan from Jun 19th to Jun 20<sup>th</sup>, sets a minimum stay of 2 nights and opens the room for selling and to arrival.

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://www.opentravel.org/OTA/2003/05" xmlns:ns2 = "http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd" xmlns:ns3 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing">

  <SOAP-ENV:Header>

    <ns2:Security SOAP-ENV:mustUnderstand = "1">

      <UsernameToken>

        <Username>test</Username>

        <Password>test</Password>

      </UsernameToken>

    </ns2:Security>

    <ns3:MessageID>uuid:be91c51a-b605-102d-94d6-0030487c664c</ns3:MessageID>

    <ns3:To>http://www.myhotel.com/ws/ota</ns3:To>

    <ns3:Action>http://www.myhotel.com/ws/ota/OTA_ReadRQ</ns3:Action>

    <ns3:From>

      <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

    </ns3:From>

  </SOAP-ENV:Header>

  <SOAP-ENV:Body>

    <ns1:OTA_HotelBookingRuleNotifRQ TimeStamp = "2010-05-21T10:48:01+02:00" Target = "Production"
Version = "1.000">

      <ns1:RuleMessages HotelCode = "5071">

        <ns1:RuleMessage>

          <ns1:StatusApplicationControl Start = "2010-06-19" End = "2010-06-20" RatePlanCode = "BAR"
InvTypeCode = "DBL">

            <ns1:DestinationSystemCodes>

              <ns1:DestinationSystemCode>11</ns1:DestinationSystemCode>

              <ns1:DestinationSystemCode>15</ns1:DestinationSystemCode>

            </ns1:DestinationSystemCodes>

          </ns1:StatusApplicationControl>

        </ns1:RuleMessage>

      </ns1:RuleMessages>

    </ns1:OTA_HotelBookingRuleNotifRQ>

  </SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



```
</ns1:DestinationSystemCodes>

</ns1:StatusApplicationControl>

<ns1:BookingRules>

  <ns1:BookingRule>

    <ns1:LengthsOfStay>

      <ns1:LengthOfStay Time = "2" TimeUnit = "Day" MinMaxMessageType = "SetMinLOS"/>

    </ns1:LengthsOfStay>

  </ns1:BookingRule>

  <ns1:BookingRule>

    <ns1:RestrictionStatus Restriction = "Master" Status = "Close"/>

  </ns1:BookingRule>

  <ns1:BookingRule>

    <ns1:RestrictionStatus Restriction = "Arrival" Status = "Open"/>

  </ns1:BookingRule>

  <ns1:BookingRule>

    <ns1:RestrictionStatus Restriction = "Departure" Status = "Close"/>

  </ns1:BookingRule>

</ns1:BookingRules>

</ns1:RuleMessage>

</ns1:RuleMessages>

</ns1:OTA_HotelBookingRuleNotifRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```

### 7.3 Response Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:ns2 =
"http://www.opentravel.org/OTA/2003/05">

  <SOAP-ENV:Header>

    <ns1:MessageID>uuid:77bdaccb-e8cf-fb9f-5de6-0cb9f84a1f19</ns1:MessageID>

    <ns1:To>http://www.myhotel.com/ws/ota</ns1:To>
```



```
<ns1:From>

  <Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

</ns1:From>

  <ns1:RelatesTo RelationshipType = "ns1:Reply">uuid:be91c51a-b605-102d-94d6-
0030487c664c</ns1:RelatesTo>

  <ns1:Action>http://www.aec-
internet.it/booking_engine/int/myhotel/OTA_HotelBookingRuleNotifRQ</ns1:Action>

</SOAP-ENV:Header>

<SOAP-ENV:Body>

  <ns2:OTA_HotelBookingRuleNotifRS>

    <ns2:Success/>

  </ns2:OTA_HotelBookingRuleNotifRS>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```



## 8 Booking Retrieval

### 8.1 Request Reference

Item	Type	Description	Values Format
<b>OTA_ReadRQ</b>			
TimeStamp	datetime		
Version	String		1
<b>ReadRequests</b>			
<b>HotelReadRequest</b>			
HotelCode	Integer	Unique identifier for the hotel	

### 8.2 Request Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://www.opentravel.org/OTA/2003/05" xmlns:ns2 = "http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd" xmlns:ns3 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing">

  <SOAP-ENV:Header>

    <ns2:Security SOAP-ENV:mustUnderstand = "1">

      <UsernameToken>

        <Username>test</Username>

        <Password>test</Password>

      </UsernameToken>

    </ns2:Security>

    <ns3:MessageID>uuid:712e7f5b-8353-d6b9-1531-b27d5a53f6d7</ns3:MessageID>

    <ns3:To>http://www.myhotel.com/ws/ota</ns3:To>

    <ns3:Action>http://www.myhotel.com/ws/ota/OTA_ReadRQ</ns3:Action>

    <ns3:From>

      <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

    </ns3:From>

  </SOAP-ENV:Header>

  <SOAP-ENV:Body>

    <ns1:OTA_ReadRQ TimeStamp = "2010-10-22T16:26:02+02:00" Version = "1">
```



```

<ns1:ReadRequests>

  <ns1:HotelReadRequest HotelCode = "5071"/>

</ns1:ReadRequests>

</ns1:OTA_ReadRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>

```

### 8.3 Response Reference

Item	Type	Description	Values Format
<b>OTA_ResRetrievers</b>			
Version		1.000 [fixed]	
Timestamp	DateTime		ISO 8601
<b>Success</b>		Present only if request is correct	
<b>Errors</b>		Present only in case of errors	
<b>Error</b>	String	Error description	
Code	String	Error Code	
<b>ReservationsList</b>			
<b>HotelReservation</b>			
RoomStayReservation	Boolean	true [fixed]	
ResStatus	String	Reservation status	[Commit   Cancel   Modify]
CreateDateTime	DateTime	Creation time	ISO 8601
<b>UniqueID</b>			
Type	Integer	14 [fixed]	
ID_Context	String	CrsConfirmNumber [fixed]	
ID	String	Reservation CRS Code	
<b>RoomStays</b>			
<b>RoomStay</b>			
<b>RoomTypes</b>			
<b>RoomType</b>			
NumberOfUnits	Integer	Number of Rooms	
RoomTypeCode	String	Room Type Code	
<b>RatePlans</b>			
<b>RatePlan</b>			
RatePlanCode	String	Rate Plan Code	
<b>RoomRates</b>			
<b>RoomRate</b>			
RoomTypeCode	String	Room Type Code	
RatePlanCode	String	Rate Plan Code	
<b>Rates</b>			



<b>Rate</b>			
RateTimeUnit	String	Day [fixed]	
EffectiveDate	Date	Begin date	YYYY-MM-DD
ExpireDate	Date	End date	YYYY-MM-DD
<b>Base</b>			
AmountAfterTax	Float	Day-by-day price	
CurrencyCode	String		ISO 4217
<b>Discount</b>			
AmountAfterTax	Float	Discount value	
<b>DiscountReason</b>			
Text	String	Discount reason	
<b>GuestCounts</b>			
<b>GuestCount</b>			
AgeQualifyingCode	Integer		[10=Adult   8=Children]
Age	Integer	Age of the guest	
Count	Integer	Number of guests related with the current AgeQualifyCode	
<b>TimeSpan</b>			
Start	Date	Check in date	YYYY-MM-DD
End	Date	Check out date	YYYY-MM-DD
<b>BasicPropertyInfo</b>			
HotelCode	Integer	Hotel Code associated to the reservation	
<b>Services</b>			
<b>Service</b>			
ServiceInventoryCode	String	Service code	
ServicePricingType	String	Service type	[Per night   Per person per night]
Inclusive	Boolean	If true, services price is already added to the total reservation amount	
Quantity	Integer	Number of booked services	
<b>Price</b>			
<b>Base</b>			
AmountAfterTax	Float	Service price (per unit)	
CurrencyCode	String		ISO 4217
<b>ServiceDetails</b>			
<b>TimeSpan</b>			
Start	Date	Service start date/time	
End	Date	Service end date/time	
<b>ResGuests</b>			
<b>ResGuest</b>			





<b>Profiles</b>			
<b>ProfileInfo</b>			
<b>Profile</b>			
ProfileType	Integer	Code of the associated profile	[1=Reserver   21=Customer]
<b>Customer</b>			
<b>PersonName</b>			
GivenName	String	First (given) name of the guest	
Surname	String	Surname of the guest	
<b>Telephone</b>			
PhoneTechType	Integer	Type of telephone contact information	[1=Fixed line   5=Mobile]
PhoneNumber	String	Telephone number	
Email	String	Email address	
<b>Address</b>			
CityName	String	City name	
PostalCode	String	City ZIP code	
StateProv	String	Province	
CountryName	String	Country name	
<b>ResGlobalInfo</b>			
HotelReservationIDs		[optional]	Present only in case of modification
<b>HotelReservationID</b>			
ResID_Type		25 (=Associated reservation) [fixed]	
ResID_Value	String	Reservation CRS Code	Previous reservation code (replaced by this reservation)
<b>Comments</b>			
<b>Comment</b>			
Text	String	Comment string	
<b>Guarantee</b>			
<b>GuaranteesAccepted</b>			
<b>GuaranteeAccepted</b>			
PaymentTransactionTypeCode	String	charge [fixed]	charge
<b>PaymentCard</b>			
CardType		1 (=Credit) [fixed]	
CardCode		Credit Card Number	
CardNumber			[AX=American Express   BC=Bank Card   CB=Carte Blanche   BL=Carte Bleu   DN=Diners Club   DS=Discover Card   EC=Eurocard   JC=Japanese Credit



			Bureau Credit Card   MC=Master Card   TP=Universal Air Travel Card   VI=Visa]
ExpireDate		CC Expiration Date	
SeriesCode			
<b>CardHolderName</b>			
<b>Total</b>			
AmountAfterTax	Float	Total amount (gross), only if rates are commissionable	
CurrencyCode	String	Currency	ISO 4217
<b>Profiles</b>		Total number of guests	
<b>ProfileInfo</b>			
<b>UniqueID</b>			
Type	Integer	A unique identifying value assigned by the creating system	[7=Wholesaler   12=Hotel   13=Internet broker   18=Other   32=Merchant]
ID_Context	Integer	Source of the identifier	[CRS   IATA]
ID	Integer	A unique identifying value assigned by the creating system	
<b>Profile</b>			
ProfileType	Integer	Code of the associated profile	[2=GDS   3=Corporation   4=Travel agent   5=Wholesaler   10=Internet broker   12=Hotel   17=Affiliation]
<b>CompanyInfo</b>			
<b>CompanyName</b>			
CompanyShortName	String	Short name for the company	
Code	String	Company Code	
CodeContext	String	VerticalBooking	
<b>AddressInfo</b>			
<b>TelephoneInfo</b>			
PhoneTechType	Integer	Type of telephone contact information	1 – Fixed Line
PhoneNumber	String	Telephone number	
<b>TPA_Extentions</b>			
PrenRequestCode	Integer		



## 8.4 Response Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:ns2 =
"http://www.opentravel.org/OTA/2003/05">

  <SOAP-ENV:Header>

    <ns1:MessageID>uuid:6548d817-95bb-49e4-2192-9becc3c73294</ns1:MessageID>

    <ns1:To>http://www.gestionealbergo.com/ws/ota</ns1:To>

    <ns1:From>

      <Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

    </ns1:From>

    <ns1:RelatesTo RelationshipType = "ns1:Reply">uuid:712e7f5b-8353-d6b9-1531-
b27d5a53f6d7</ns1:RelatesTo>

    <ns1:Action>http://www.aec-internet.it/booking_engine/int/gestione
albergo/OTA_ResRetrieverRS</ns1:Action>

  </SOAP-ENV:Header>

  <SOAP-ENV:Body>

    <ns2:OTA_ResRetrieverRS>

      <ns2:Success/>

      <ns2:ReservationsList>

        <ns2:HotelReservation RoomStayReservation = "true" ResStatus = "Commit" CreateDateTime =
"2010-09-22T08:32:48+02:00">

          <ns2:UniqueID Type = "14" ID_Context = "CrsConfirmNumber" ID = "287329696/87030894|8953"/>

          <ns2:RoomStays>

            <ns2:RoomStay>

              <ns2:RoomTypes>

                <ns2:RoomType RoomTypeCode = "MTRD" NumberOfUnits = "1"/>

              </ns2:RoomTypes>

              <ns2:RatePlans>

                <ns2:RatePlan RatePlanCode = "BB_BAR"/>

              </ns2:RatePlans>

              <ns2:RoomRates>

                <ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
```



```
<ns2:Rates>
  <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-23" ExpireDate = "2010-
10-24">
    <ns2:Base AmountAfterTax = "200.0000" CurrencyCode = "EUR"/>
  </ns2:Rate>
</ns2:Rates>
</ns2:RoomRate>
<ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
  <ns2:Rates>
    <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-24" ExpireDate = "2010-
10-25">
      <ns2:Base AmountAfterTax = "102.0000" CurrencyCode = "EUR"/>
    </ns2:Rate>
  </ns2:Rates>
</ns2:RoomRate>
<ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
  <ns2:Rates>
    <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-25" ExpireDate = "2010-
10-26">
      <ns2:Base AmountAfterTax = "102.0000" CurrencyCode = "EUR"/>
    </ns2:Rate>
  </ns2:Rates>
</ns2:RoomRate>
<ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
  <ns2:Rates>
    <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-26" ExpireDate = "2010-
10-27">
      <ns2:Base AmountAfterTax = "85.0000" CurrencyCode = "EUR"/>
    </ns2:Rate>
  </ns2:Rates>
</ns2:RoomRate>
<ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
  <ns2:Rates>
```



```
10-28">      <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-27" ExpireDate = "2010-
10-28">
          <ns2:Base AmountAfterTax = "85.0000" CurrencyCode = "EUR"/>
        </ns2:Rate>
      </ns2:Rates>
    </ns2:RoomRate>
    <ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
      <ns2:Rates>
        <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-28" ExpireDate = "2010-
10-29">
          <ns2:Base AmountAfterTax = "72.2500" CurrencyCode = "EUR"/>
        </ns2:Rate>
      </ns2:Rates>
    </ns2:RoomRate>
    <ns2:RoomRate RoomTypeCode = "MTRD" RatePlanCode = "BB_BAR">
      <ns2:Rates>
        <ns2:Rate RateTimeUnit = "Day" EffectiveDate = "2010-10-29" ExpireDate = "2010-
10-30">
          <ns2:Base AmountAfterTax = "0.0000" CurrencyCode = "EUR"/>
          <ns2:Discount AmountAfterTax = "85.0000">
            <ns2:DiscountReason>
              <ns2:Text>7x6</ns2:Text>
            </ns2:DiscountReason>
          </ns2:Discount>
        </ns2:Rate>
      </ns2:Rates>
    </ns2:RoomRate>
  </ns2:RoomRates>
  <GuestCounts>
    <GuestCount AgeQualifyingCode = "10" Count = "2"/>
  </GuestCounts>
  <ns2:TimeSpan Start = "2010-10-23" End = "2010-10-30"/>
  <ns2:BasicPropertyInfo HotelCode = "5071"/>
```



```
</ns2:RoomStay>

</ns2:RoomStays>

<ns2:Services>

  <ns2:Service ServicePricingType = "Per night" ServiceInventoryCode = "SPA" Quantity =
"1">

    <ns2:Price>

      <ns2:Base AmountAfterTax = "15.00" CurrencyCode = "EUR"/>

    </ns2:Price>

    <ns2:ServiceDetails>

      <ns2:TimeSpan Start = "2010-10-25" End = "2010-10-25"/>

    </ns2:ServiceDetails>

  </ns2:Service>
</ns2:Services>

<ns2:ResGuests>

  <ns2:ResGuest>

    <ns2:Profiles>

      <ns2:ProfileInfo>

        <ns2:Profile ProfileType = "1">

          <ns2:Customer BirthDate = "1950-12-31">

            <ns2:PersonName>

              <ns2:GivenName>tizio</ns2:GivenName>

              <ns2:Surname>caio</ns2:Surname>

            </ns2:PersonName>

            <ns2:Telephone PhoneTechType = "1" PhoneNumber = "0123456789"/>

            <ns2:Email>prova@microsoft.com</ns2:Email>

            <ns2:Address>

              <ns2:AddressLine>via viole 15</ns2:AddressLine>

              <ns2:CityName>Roma</ns2:CityName>

              <ns2:PostalCode>12345</ns2:PostalCode>

              <ns2:StateProv>RM</ns2:StateProv>

              <ns2:CountryName>IT</ns2:CountryName>
```



```
</ns2:Address>

</ns2:Customer>

</ns2:Profile>

</ns2:ProfileInfo>

</ns2:Profiles>

</ns2:ResGuest>

</ns2:ResGuests>

<ns2:ResGlobalInfo>

  <ns2: HotelReservationIDs>

    <ns2: HotelReservationID ResID_Type = "25" ResID_Value = "287329696/87030881|8947"/>

  </ns2: HotelReservationIDs>

  <ns2:Comments>

    <ns2:Comment>

      <ns2:Text>

        GUEST NAME:Mario ROSSI

        Late arrive

        No smoking room

        Nr. guests: 2

        Commission Amount: 146.25

      </ns2:Text>

    </ns2:Comment>

  </ns2:Comments>

  <ns2:Guarantee>

    <ns2:GuaranteesAccepted>

      <ns2:GuaranteeAccepted PaymentTransactionTypeCode = "charge">

        <ns2:PaymentCard CardType = "1" CardCode = "MC" CardNumber = "0000000000099"
SeriesCode = "000" ExpireDate = "0911">

          <ns2:CardHolderName>tizio</ns2:CardHolderName>

        </ns2:PaymentCard>

      </ns2:GuaranteeAccepted>

    </ns2:GuaranteesAccepted>
```



```
</ns2:Guarantee>

<ns2:Total AmountAfterTax = "731.25" CurrencyCode = "EUR"/>

<ns2:Profiles>

  <ns2:ProfileInfo>

    <ns2:UniqueID Type = "32" ID_Context = "CRS" ID = "11"/>

    <ns2:Profile ProfileType = "10">

      <ns2:CompanyInfo>

        <ns2:CompanyName CompanyShortName = "BOOKINGS EUROPE B.V." Code = "9606020"
CodeContext = "IATA"/>

        <ns2:AddressInfo/>

        <ns2:TelephoneInfo PhoneTechType = "1" PhoneNumber = "0031-200005414"/>

        <ns2:BusinessLocale>

          <ns2:AddressLine>WETERINGSCHANS 28 - 4, 1017 SG</ns2:AddressLine>

          <ns2:CityName>AMSTERDAM</ns2:CityName>

          <ns2:PostalCode>1000</ns2:PostalCode>

          <ns2:CountryName>NL</ns2:CountryName>

        </ns2:BusinessLocale>

      </ns2:CompanyInfo>

    </ns2:Profile>

  </ns2:ProfileInfo>

</ns2:Profiles>

</ns2:ResGlobalInfo>

</ns2:HotelReservation>

</ns2:ReservationsList>

</ns2:OTA_ResRetrieveRS>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```





## 9 Booking Confirmation

### 9.1 Request Reference

Item	Type	Description	Values Format
<b>OTA_HotelResNotifRQ</b>			
<b>HotelReservations</b>			
<b>HotelReservation</b>			
<b>UniqueID</b>			
Type	Integer		14
ID_Context	String		CrsConfirmNumber
ID	String	Reservation ID to confirm	
<b>ResGlobalInfo</b>			
<b>HotelReservationIDs</b>			
<b>HotelReservationID</b>			
ResID_Type	Integer		10
ResID_Value	String	Reservation ID in PMS system	
ResID_Source	String		PMS
ResID_SourceContext	String		PmsConfirmNumber

### 9.2 Request Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://www.opentravel.org/OTA/2003/05" xmlns:ns2 = "http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd" xmlns:ns3 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing">

  <SOAP-ENV:Header>

    <ns2:Security SOAP-ENV:mustUnderstand = "1">

      <UsernameToken>

        <Username>test</Username>

        <Password>test</Password>

      </UsernameToken>

    </ns2:Security>

    <ns3:MessageID>uuid:712e7f5b-8353-d6b9-1531-b27d5a53f6d7</ns3:MessageID>

    <ns3:To>http://www.myhotel.com/ws/ota</ns3:To>

    <ns3:Action>http://www.myhotel.com/ws/ota/OTA_ReadRQ</ns3:Action>
```



```
<ns3:From>

  <ns3:Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</ns3:Address>

</ns3:From>

</SOAP-ENV:Header>

<SOAP-ENV:Body>

  <ns1:OTA_HotelResNotifRQ>

    <ns1:HotelReservations>

      <ns1:HotelReservation>

        <ns1:UniqueID Type = "14" ID_Context = "CrsConfirmNumber" ID = "287329696/87030894|8953"/>

        <ns1:ResGlobalInfo>

          <ns1:HotelReservationIDs>

            <ns1:HotelReservationID ResID_Type = "10" ResID_Value = "123456ABCD" ResID_Source =
"PMS" ResID_SourceContext = "PmsConfirmNumber"/>

          </ns1:HotelReservationIDs>

        </ns1:ResGlobalInfo>

      </ns1:HotelReservation>

    </ns1:HotelReservations>

  </ns1:OTA_HotelResNotifRQ>

</SOAP-ENV:Body>

</SOAP-ENV:Envelope>
```

### 9.3 Response Example

```
<?xml version="1.0" encoding="UTF-8"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV = "http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1 =
"http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:ns2 =
"http://www.opentravel.org/OTA/2003/05">

  <SOAP-ENV:Header>

    <ns1:MessageID>uuid:6548d817-95bb-49e4-2192-9becc3c73294</ns1:MessageID>

    <ns1:To>http://www.gestionealbergo.com/ws/ota</ns1:To>

    <ns1:From>

      <Address>http://schemas.xmlsoap.org/ws/2004/12/addressing/role/anonymous</Address>

    </ns1:From>
```



```
<ns1:RelatesTo RelationshipType = "ns1:Reply">uuid:712e7f5b-8353-d6b9-1531-  
b27d5a53f6d7</ns1:RelatesTo>  
  
  <ns1:Action>http://www.aec-internet.it/booking_engine/int/gestione  
albergo/OTA_ResRetrieveRS</ns1:Action>  
  
</SOAP-ENV:Header>  
  
<SOAP-ENV:Body>  
  
  <ns2:OTA_HotelResNotifRS>  
  
    <ns2:Success/>  
  
  </ns2:OTA_HotelResNotifRS>  
  
</SOAP-ENV:Body>  
</SOAP-ENV:Envelope>
```

