

On Free Memory

!

This thread has been locked. Questions are automatically locked after two months of inactivity, or sooner if deemed necessary by a moderator.



275

Apple platforms have APIs, inherited from Mach, that return low-level memory statistics [1]. Some third-party tools report those statistics as if they were relevant to app developers. In most cases they are not.

Specifically, any report on the amount of *free memory* is unlikely to be useful. This number is the size of the kernel's free memory pool. Most VM-based OSes attempt to keep a certain amount of free memory available to avoid running out of memory in critical circumstances (for example, when trying to allocate memory on the page out path). But the size of that pool has very little to do with the amount of memory pressure on the system. Remember that the kernel's goal is to keep the pool at a certain size, so it lets memory go to 'waste' until critical thresholds are crossed, as which point it starts cleaning up.

As a concrete example of this, consider an iPhone running Safari. When you press the Home button, you return to the home screen but the system leaves Safari loaded in memory. At this point the free memory is X, where X is slightly higher than the threshold where the system would remove Safari from memory. Now apply some memory pressure to the system. It responds by removing Safari from memory, whereupon the free memory jumps up to Y, where Y is much larger than X. So putting memory pressure on the system has resulted in a *larger* free memory value. If you were using this free memory value as a proxy for memory pressure, you'd end up drawing exactly the wrong conclusion.

Apple platforms have various standard techniques for handling memory pressure — memory warnings, `NSCache`, purgeable memory, `DISPATCH_SOURCE_TYPE_MEMORYPRESSURE`, and so on — and you should use those techniques rather than any sort of free memory value.

Finally, if you want to get a summary of how much memory your app is using, you should look at its *footprint*. If you're building an automated test suite, you can get this value programmatically. See [this post](#) for details.

Share and Enjoy

Quinn “The Eskimo!” @ Developer Technical Support @ Apple
`let myEmail = "eskimo" + "1" + "@" + "apple.com"`

[1] Specifically, the `host_statistics` API and the various structures defined in `<mach/vm_statistics.h>`.

Debugging

Asked 1 year ago by eskimo  

Reply to this question

This site contains user submitted content, comments and opinions and is for informational purposes only. Apple disclaims any and all liability for the acts, omissions and conduct of any third parties in connection with or related to your use of the site. All postings and use of the content on this site are subject to the [Apple Developer Forums Participation Agreement](#).

Discover	Design	Develop	Distribute	Support
macOS	Human Interface Guidelines	Xcode	Developer Program	Articles
iOS	Resources	Swift	App Store	Developer Forums
watchOS	Videos	Swift Playgrounds	App Review	Feedback & Bug Reporting
tvOS	Apple Design Awards	TestFlight	Mac Software	System Status
Safari and Web	Fonts	Documentation	Apps for Business	Contact Us
Games	Accessibility	Videos	Safari Extensions	Account Certificates, Identifiers & Profiles App Store Connect
Business	Internationalization	Downloads	Marketing Resources	
Education	Accessories		Trademark Licensing	
WWDC				