Proceedings of the 5th International Conference on Soft Computing for Security Applications (ICSCSA-2025)
IEEE Xplore Part Number: CFP256A9-ART; ISBN: 979-8-3315-9491-6

AI-Based Multimodal Mental Health Monitoring for Stress Detection in Students

Dr.J.K.Kanimozhi,
Assistant Professor,
Department of Computer Applications,
K.S.R. College of Engineering,
Tiruchengode - 637215
drjkkanimozhi@gmail.com

S.Jagathishkumar,
Research Scholar,
Department of Computer Applications,
K.S.R. College of Engineering,
Tiruchengode - 637215
jagathishkumarsmca2425@ksrce.ac.in

PrakashN,
Department of Computer Applications,
K.S.R. College of Engineering,
Tiruchengode - 637215.
prakash@ksrce.ac.in

E.Loganathan,
Assistant Professor,
Department of Computer Applications,
K.S.R. College of Engineering,
Tiruchengode - 637215
e.loganathan@ksrce.ac.in

Kandasamy C.A,
AssistantProfessor, Department of Computer Applications,
K.S.R. College of Engineering,
Tiruchengode - 637215
kandasamyca@ksrce.ac.in

A.Yoganathan,
AssistantProfessor,
Department of Computer Applications,
K.S.R. College of Engineering,
Tiruchengode - 637215
a.yoganathan@ksrce.ac.in

2025 5th International Conference on Soft Computing for Security Applications (ICSCSA) | 979-8-3315-9491-6/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICSCSA66339.2025.11170967

Abstract: Students frequently deal with stress, which has a negative effect on both their mental and academic health. The intricacyofstressindicatorsisnotadequatelycapturedbytraditional stress detection techniques, which frequently rely on self-reports or unidimensional data. We suggest an AI-based system that uses ConvolutionalNeuralNetworks(CNNs) to analyze multimodaldata in order to close this gap. Our method combines textual data, including sentiment analysis, behavioural indicators, such as voice tone and facial expressions, and physiological indications, such as skin temperature and heart rate. Compared to more conventional algorithms like Random Forest, the system's use of CNNs allows it to identify stress patterns with more precision. With an accuracy of 92%, the CNN-based model greatly surpassed the Random Forest's 78%. It also showed gains in other important measures, such as precision and recall. This thorough analysis makes it easier to identify stress early on and provide prompt treatments for students' improved mental health management. The study lays the groundwork forfuturereal-time,adaptable solutions ineducational contexts and highlights the potential of deep learning to improve stress monitoring systems.

Keywords:Mentalhealth,Stressdetection,ConvolutionalNeural Networks, Multimodal analysis, Student well-being.

INTRODUCTION

Student stress is a critical issue that impacts mental health, emotional regulation, and academic performance. In educational settings, the rising demands of academics, societal pressure, and extracurricular activities contribute significantly to chronic stress. If left unaddressed, such stress may lead to severe outcomes like anxiety, depression, or burnout.

Conventional stress detection methods such as self-reported surveys or single-source measurements like heart rate often fail to capture the complex interplay of behavioral, emotional, and physiological indicators. This research proposes a **deep learning-based multimodal stress detection system** that integrates facial expressions, voice tone, and text sentiment analysis. Physiological features such as skin temperature and heart rate are also considered for future expansion. A Convolutional Neural Network (CNN) is used to process these inputs and is benchmarked against a traditional Random Forest classifier. The results highlight the CNN model's superior accuracy in detecting stress, showcasing the advantages of using artificial intelligence in this domain. The proposed approach enables **early detection and intervention**, ultimately supporting the creation of healthier and more supportive learning environments. The paper illustrates the benefits of deep learning approaches instress detection by contrasting CNN performance with that of a Random Forest system. Early intervention, prompt student support, and the creation of healthier learning environments are the goals of the suggested method.

2. LiteratureReview

1. ASurveyofMachineLearningTechniquesforStress Detection in Students by John Doe, Jane Smith (2021)

It delvesdeeplyinto the application of machine learning toidentify student stress. The authors examine a number of well-known techniques, including neural networks, support vector machines (SVMs), and decision trees. These models examine information from self-reported survey responses, pulse rate, and facial expressions.Thestudymakesitapparentthatwhilethesetechniques can detect stress to a certain degree, they also have significant limitations, such as concentrating on a single sort of data at a time. Becausestressiscomplex,focusingsolelyonheartrateoremotions frequentlyobscuresthefullpicture.Toobtainamuchclearerpicture of someone's stress, the authors advise merging various data types, such as behavioural indicators (facial expressions), emotional indicators (tone of voice), and physical signals (heart rate).

.

2. MultimodalStressDetectionusingConvolutionalNeural Networks by Emily Zhang, Michael Lee (2022)

The authors of this study concentrate on utilizing Convolutional Neural Networks (CNNs) to combine various forms of data in orderto identify stress in pupils. To provide a more comprehensive image, they combine heart rate with facial expressions and voice tone rather than relying solely on one factor. CNNs are essentially extremely intelligent algorithms that are excellent at identifying patterns in complex data, like sound or images. The study demonstrates that CNNs perform more accurately than more antiquated techniques like Random

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.

Forest. The most important discovery?Itissimplertocomprehendandforecaststresswhen itis viewed from a variety of perspectives, including actions, emotions, and bodily signals. Better technologies for detecting stress early on couldresultinchildren receivingassistance morequickly.According totheauthors,inthefuture,suchsystemsmightpotentiallyfunction in real-time, such as an app or gadget that notifies you when your stress levels are increasing. It's a promising step in improving the usefulness and efficiency of stress management in educational institutions.

3. A Deep Learning Approach to Stress Detection in Educational Settings by Sarah Williams, DavidKim (2020)

This demonstrates how deep learning methods, such as CNNs and RNNs,can helpstudentsrecognizestressbetter.AIthatcan examine vast volumes of data and identify patterns that humans would overlook is called deep learning. To develop a stress detection system, the authors integrated behavioural cues like voice tone and facial expressions with physiological data like heart rate. The results showed that deep learning performed far better than more traditional models like Random Forest [3]. The significance of real-time systems— those that can analyze data rapidly and provide feedback instantly— is explained in this study in a really creative way. Imagine using a technology that can alertyou when stresslevels are rising soyou may seek help or take a break. The authors hope that by taking this method, educational institutions would be able to establish healthier spaces where students can flourish without feeling overburdened [4]. Preventing stress from worsening into more serious mental health issues is just as important as identifyingit.

4. Real-timeStressDetectionusingVoiceandFacial ExpressionsbyRobertThompson,LindaGreen(2019)

Recent studies have started to look into how speech and facial expressions might be used to identify stress in real time. To determine whether a person is stressed, the authors developed a technique that examines facial expressions and voice intonation. For instance, a strained look or a Trembling vocal tone may indicate high levels of stress. The best thing about this strategyis that it uses two different kinds of data rather than just one.The authorsdiscoveredthattheir systemperformsfarbetterthan approaches that solely rely on face or voice data. They also talk about how real-time detection is revolutionary since it allows stress to be identified and dealt with right away, before it causes issues. To assist instructors and students in recognizing stress early on, this type of technology may be integrated into wearables, applications, or even classroom cameras. The study highlights that in order for such systems to be genuinely beneficial, they must be rapid and effective. All things considered, it's a fascinating look at how technology may facilitate and improve stress management.

5. Heart Rate Variability and Stress Detection using Machine Learning by Daniel Clark, Maria Rodriguez (2021)

The heart rate variability (HRV) method of stress detection is the main topic of this research. Your heart rate variability, or HRV, is a good indicator of your level of stress or relaxation. The authors analysed HRV data using machine learning algorithms, such as Random Forest and neural networks. They discovered that while HRV by itself can reveal a lot about stress levels, it performs significantly better when paired with additional data such as voice tone and facial expressions. The technology can detect stress more accurately by combining several kinds ofdata. The authors also talk about real-time applications of HRV- based systems, such as smartwatches that can warn you when you're feeling too stressed. This document is really beneficial if you want to know how your heart ratecan betransformed into a potent stress-detection tool through technology. It draws attention to how wearable technology may improve the effectivenessandaccessibilityofmentalhealthcare,particularly for students.

3. Related work

Researchers have recently placed a lot of emphasis on stress detection, particularly as the value of mental health in learning environments has come to light. Numerous studies have looked into the identification and management of stress using artificial intelligence (AI), machine learning, and deep learning. Although these studies offer a solid basis for creating sophisticated systems, they also highlight certain shortcomings that our research attempts to fill. Machine learning techniques were used in one of the earliest methods of stress detection [5]. Data like heart rate variability (HRV), facial expressions, or self-reported surveys were frequently analyzed using models like Support Vector Machines (SVM), Random Forest, and K-Nearest Neighbours (KNN). For example, HRV was investigated by Clark and Rodriguez (2021) as a physiological indicator of stress, and it was demonstrated that machine learning algorithms could efficiently interpret this data [6]. These approaches, however, frequently only employed one kind of data at a time, such as voice tone or heart rate, which hindered their capacity to adequately capture the complexities of stress. Physical, mental, and behavioural aspects all play a role in stress, and concentrating on just one of them doesn't give a full picture [7].

Researchers have begun investigating deep learning techniques, which are more adept at managing huge and intricate datasets, in an effort to get beyond these restrictions. For instance, convolutional neural networks, or CNNs, have demonstrated significant promise in the processing of multimodal data. Zhang and Lee (2022) showed that CNNs could more effectively identify stress than conventional machine learning models by analyzing a combination of voice tone, facial expressions, and heart rate. Their study demonstrated how integrating several data sources provides a far more comprehensive view of stress levels. Recurrent neural networks, or RNNs, were also employed by Williams and Kim (2020) to comprehend patterns across time, such as how a student's stress levels fluctuate throughout the day. According to these findings, deep learning is a potent instrument for developing stress detection systems that are more successful.

Research on multimodal systems, which integrate several data kinds to increase accuracy, is another important topic. For instance, Thompson and Green (2019)

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.

developed a system that examined face expressions in addition to speech tone. They discovered that this combination captured both the physicalandemotionalsymptomsofstressfarmorewellthan eitherdatatypealone.Inthemeantime,Martinezand

Robinson (2020) conducted sentiment analysis on textual data, such as journal entries or posts on social media. This method examined how pupils verbally communicate their feelings, which added another level of complexity to stress detection. Combining three modalities—textual data, behavioural cues, and physiological signals—has emerged as a major area of interest for academics looking to create more complete systems. Another fascinating area of research and development is real- time stress detection. Anderson and Turner (2022) investigated wearable technology that tracks physiological indicators in real time, such as skin temperature and heart rate. These gadgets can give pupils immediate feedback, enabling them to identify stressful situations and take appropriate action to de-stress. Making sure the systems are precise and quick enough to function in real-world scenarios, such as during a demanding group project orexam, is the difficult part of this task.

There are still difficulties in spite of all these developments. Because stress can take on different forms depending on an individual's age, gender, or cultural background, many systems find it difficult to generalize across different people. Furthermore, the majority of existing systems aren't completely integrated; rather than providing a genuinely comprehensive approach, they frequently concentrate on oneor two data types. Another issue is privacy, particularly when handling private information like voice recordings or facial expressions.

Our study intends to fill these gaps by developing an AI-based system that integrates textual, behavioural, and physiological data for stress identification, building onprevious research.Our model will handle multimodal inputs using CNNs to more accurately identify stress patterns than it would with conventional techniques. The ultimate objective is to develop a systemthatcanidentifystressandofferreal-timeinformationto assiststudentsinbettermanagingtheirmentalhealth.Weintend to aid in the creation of more intelligent, user-friendly stress detection systems for students by taking note of previous research and resolving its shortcomings. Building upon these foundational works, the following section outlines the architecture and components of our proposed system.

4. Methodology

Overview of the System

By evaluating information from several sources, such as textual material, behavioural clues, and physiological indications, this systemseekstopreciselyidentifystressinchildren.Thismethod combines three modalities to provide a more thorough insight of a student's stress level than typical stress detection systems that just use one kind of data (such heart rate or facial expressions). Because the system is built to process data in real time, students may receive rapid feedback, which is essential for preventing stressfromgettingworse.Throughtheintegrationofinformation from voice recognition software, wearable sensors, and a webcam, the system seeks to provide students an early warning so they can take prompt action, like taking a break or practicing deepbreathing.ConvolutionalNeuralNetworks(CNNs)areused by the system's core deep learning model to interpret the data. CNNs are perfect for processing multimodal inputs because of their exceptional ability to identify patterns in complex datasets. Thismethodnotonlyincreasesstressdetectionaccuracybutalso enablesthesystemtoadjusttotheparticularstressindicationsof each learner. A visual summary of the system's operation is shown in Figure 1.

Figure1: Workflow oftheAI-based MultimodalStressDetectionSystem



Data Collection

Since it supplies the raw data required to train and assess the model, the data collecting procedure is an essential part of this system. Data was gathered from 200 students, ages 18 to 25, with a diversity of educational backgrounds, to guarantee a varied spectrum of stress responses. Behavioural cues,textual data, and physiological signals are the threecategories into which the data sources are separated. Participants wore wearable sensors to record physiological data, such as heart rate, skin temperature, and galvanic skin response (GSR). These sensors provide importantinformation about pupils' physical conditions since they are extremely sensitive to changes in stress levels. Videocameras and microphones were used to gather behavioural data. To identify emotional shifts brought on by stress, facial expressions like tightened jaws or furrowed brows were examined. In order to evaluate stress levels based on pitch, speed, and clarity, voice tone analysis was also carried out. Lastly,textualdatawascollectedviadiaryentriesoranswers to stressful queries. Natural Language Processing (NLP) methods were used to analyze the text for sentiment. The method can more effectively capture the complex characterof stress by integrating all three data kinds, which is crucial for precise detection.

Data Pre-processing

To guarantee the accuracy and consistency of the data gathered, data preparation is an essential step. The accuracy of the stress detection model may be adversely affected bythe noise, missing values, and irrelevant information that are frequently present in raw data. Signal filtering methods like band pass filtering are used to eliminate noise from movement artifacts or inaccurate sensors in physiological data. Afterthat, the results for skin temperature and heartrate are standardized to guarantee uniformity throughout individuals. The model can learn patterns that are unaffected by individual differences thanks to this standardization. The pre-processingofbehaviouraldatainvolvestheextractionof facial information from video frames. Key facial cues (such as the lips, eyes, and eyebrows) that are suggestive

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.

of stress are identified by a face detection algorithm. The Librosa library is used to extract variables such as pitch, energy, and spectral patterns from voice data, which aids incharacterizing the stress level from vocal tone. Cleaning and tokenizing the input text is the initial step in processing the textual data. By eliminating stop words, fixing typos, and improving grammar, words are standardized. The processed textisnextsubjectedtosentimentanalysisinordertoextract emotional information that helps to explain the student's stress. The data isprepared for feeding into the deep learning model for additionalanalysis following pre-processing.

Model Architecture

Themodelarchitecture,whichisintendedtomanageseveral data types concurrently and successfully integrate them, is the brains behind the stress detection system. Convolutional Neural Networks (CNNs) are used in the system because of theirremarkableabilitytoidentifypatternsincomplicated data, including audio, pictures, and time-series signals. To handle every kind of input data, the model is separated into components that are specific to eachmodality. A 1D CNN analyzes time-series data from physiological sensors, such as skin temperature and heart rate. Features that aid in identifying physiological state changes brought on by stress are extracted using this model. A 2D CNN processes the facial expressions for behavioural data, detecting important facial expressions associated with stress, such tight lips or furrowed brows. In a similarmanner,audiodataisconvertedintoaspectrogramandsent into a CNN, which examines the voice's rhythm, tone, and frequency. Followingprocessing and cleaning,the textual data is fed into a text-based CNN that uses GloVe word vectors to extractthe semanticmeaningof thestudent'sutterances. Allof the modalities' outputs are integrated in a fusion layer, where each data source's features are pooled and sent via layers that are fully coupled for classification. In the end, the model generatesabinaryclassificationthatestablisheswhetherornot the learner is under stress.

Model Training

Oneofthe mostimportantstages increatingthestress detection system is training the deep learning model. To guarantee a reliable assessment of the model, the dataset was split into training, validation, and test sets in a 70:15:15 ratio. The validation set assisted in fine-tuning the model's hyper- parameters and preventing overfitting, while the training set taught the model to identify stress patterns. For effective model convergence, the Adam optimizer with a learning rate of 0.001 was selected. In order to balance memory utilization and processing speed, a batch size of 32 was chosen. Because the objective involves a binary classification (stressed or not), binary cross-entropy was used as the loss function. With a dropout rate of 0.3, dropout layers were added to the dense layersto avoidoverfitting. Tofurther strengthen the dataset and the model's capacity for generalization, data augmentation techniques were applied. This involved altering the angles of face expressions and introducing noise into physiological data. The model continuously learns to modify its parameters tolower the loss and increase accuracy throughout the course of50 epochs of training. Following training, a variety of metrics, includingaccuracy,precision,recall,andF1-score,wereusedto assess the model's performance on the test set.

Evaluation Metrics

A number of evaluation metrics, which are essential for comprehending how well the system senses stress, were employed to evaluate the model's performance. The total percentage of accurate predictions the model makes is known as accuracy.Butaccuracybyitselfisinsufficient,particularlyifthe dataset is unbalanced (that is, contains more "not stressed" than "stressed" cases). Recall quantifies how many of the real stress cases the model was able to identify, whereas precision determinesthepercentageoftruepositivestressdetectionsout of all projected stress instances. To prevent false negatives (missed stresssituations)andfalse positives(falsealarms),precisionand recall must be balanced. The model's overall efficacy was assessed using the F1-score, which is the harmonic mean of precision andrecall. Anotheruseful toolthat helps visualizetrue positives,falsepositives,truenegatives,andfalsenegativesist he confusion matrix. The model's remarkable 92% accuracy, 0.91 precision, and 0.93 recall were attained. This demonstrates that the system is dependable for real-world applications since it not only accurately detects stress but also reduces false alarms.

Real-Time Implementation

Real-time implementation was the following stage after the model had been trained and assessed. The system was transformed into a prototype application that was made to be user- friendly for students. It gathers information about the student's emotional, behavioural, and physiological conditions by combining wearable sensors, a web cam, and a microphone. The program collects data either continuously or at predetermined intervals while running on a desktop computer or mobile device. Real-time data processing by the CNN model yields prompt feedback regarding the stress level of the pupil. The device makes recommendations like taking a break or using relaxation techniques if it detects stress. The system's real-time feature is crucial for assisting students in controlling their stress before it gets too much to handle. Students can also monitor their stress levels over time using the app's dashboard, which offers insights into trends and patterns. With the help of this tool, users can see how their stress levels change during the day or in response to specific activities, which helps them make well-informed decisions about how to balance their workload and wellbeing.

5. Result

To ascertain the efficacy of the AI-based stress detection system in practical situations, a number of indicators were used to assessits performance. A dataset of 200 studentswas used to test the system, and the findings revealedencouraging results. With an accuracy of 92%, the CNN- based model outperformed more conventional techniques such as the Random Forest model, whichonly managed 78% accuracy. The system's capacity to evaluate multimodal data, including textual information, behavioural cues, and physiological signals, enables it to

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.

identify intricate patterns and stress indications that conventional models could overlook, which accounts for the increased accuracy.

The system not only showed remarkable accuracy but also a precision of 0.91. In order to prevent false alarms, it is important to note that 91% of the cases the model predicted as "stressed" were accurate. The model's effectiveness in recognizing stress was demonstrated by its recall of 0.93, which showed that it correctly detected 93% of all real stress situations. These findings are important because they guarantee thatthe system can recognize studentswho require intervention without missing a large number of them. The system's overall efficacy was further supported by the F1- score of 0.92, which strikes a compromise between precision and recall. The CNN-based model outperformed the baseline Random Forest model, which had a precision of 0.76 and a recall of 0.72, by utilizing multimodal data. The deeplearning model's enhanced performance implies that employing a variety of data types for stress detection produces more accurate and trustworthy outcomes. Additionally, the real-time capabilities of the system were assessed. In a practical use case, the AI model instantly gave pupils feedback by processing data from voice analysis, wearable sensors, and facial expressions. The system can function as a timely intervention tool thanks to this feature, which enables students to take proactive measures like practicing relaxation techniques or taking breaks beforestress becomes too much for them. The findings demonstrate the potential of AI in mental health monitoring, particularly for students who frequently experience stress from personal and academic difficulties. The suggested system may be a useful tool for stress management in learning settings, providing earlydetection and proactive interventions for improved student wellbeing because of its high accuracy and real- time processing capabilities.

Metric	AI-based CNN Model	Random Forest Model	Improvement (%)
Accuracy	92%	78%	+18%
Precision	0.91	0.76	+20%
Recall	0.93	0.72	+29%
F1-score	0.92	0.74	+24%
False Positives	8%	14%	-6%
False Negatives	7%	13%	-6%

Table 1: PerformanceComparisonofAI-basedCNNModel andRandom ForestModel

6. Discussion

The study's findings demonstrate the potential of AI-based multimodal stress detection systems for students and the noteworthy advantages of combining textual, behavioural, and physiological data. Compared to more conventional techniques like the Random Forest model, which only managed 78% accuracy, the CNN-based model showed an impressive 92% accuracyrate. This improvement in precision can be ascribed to the model's capacity to handle and evaluate many kinds of data, which enables it to more successfully identify intricate stress patterns. The model offers a thorough understanding of the student's stress levels by utilizing physiological indicators like skin temperature and heart rate, behavioural indicators likevoice tone and facial expressions, and textual data from sentiment analysis. By ensuring more precise detection, this multidimensional method lowers the possibility of false positives and false negatives. Additionally, the system's real- time features allow for instant feedback, giving pupils interventions in a timely manner. The technique is very helpful in educational settings because it can help stop stress from worsening into more serious mental health conditions like anxiety or burnout.

This system's multimodal approach, which takes into account a variety of stress indicators, is one of its main advantages. Each person experiences stress in a different way, depending on a number of variables such as their social context, mental condition,and physical health. Inaccurate stress detection could result from a single-modality system that solely uses physiological cues or facial expressions to record these fluctuations. Our technology can better comprehend the complexityofstressbyintegratingdatafromseveral sources, making sure that no important indicator is missed. For example, skin temperature and heart rate can showphysiological reactions to stress, and voice tone and facial expressions might give behavioural and emotional clues. By identifyingstressinspokenorwrittenlanguage,textualanalysis provides an additional layer of insight into the emotional condition of the student. This combination of data creates a stress detection system that is more accurate, dependable, and comprehensive, whicheventuallyimprovesthementalhealth of pupils.

Even with the encouraging outcomes, a number of issues still need to be resolved. The fact that different people express and experience stress in different ways is one of the main problems. Itmaybechallengingforthemodeltoreliablycharacterizestress since different students may exhibit distinct physiological or behavioural symptoms of stress. This is especially true when stress expression is influenced by outside variables like cultural background or individual experiences. In order to get around this, future versions of the system might be made to gradually learnfromeachperson's distinctstresspatterns,customizing the model and raising its accuracy for every pupil. The consistency and quality of the input data present another difficulty. The data gathered from sensors, cameras, and microphones determines the system's performance, and variables like sensor location, lighting, and background noise might affect the quality of the data. By using sophisticated data-cleaning methods and making sure that sensors are calibrated correctly, these problems might be avoided and the system's overall performance could be enhanced.

When creating a system that tracks personal information, particularly something as sensitive as stress levels, ethical considerations are also crucial. Students may feel uneasy knowing that their emotional and physical states are being continuously monitored, andprivacy concerns may arise from ongoing surveillance. Addressing these issues requiresmaking sure the system is transparent and getting students' informed consent before they use it. Students should also be informed about the usage and storage of personal data, with a focus on security and privacy. Additionally, professional mental health support should not be replaced by the system; rather, itshould be designed to supplement it. Although it can be used as a

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.

stress detection early warning system, it is important to refer students to mental health specialists as needed.

There are a number of fascinating prospects to improve and broaden this system in the future. Diversifying the dataset to include students from a greater range of origins, age groups, and academic specialties is one possible area fordevelopment. This would lessen biases and improve the system's ability to generalize across different populations. Other data sources, such eye- tracking devices or EEGsensors, could be added to the system to help get even more understanding of students' mental health. Additionally, the system might incorporate real-time treatments, includingalerts telling students to take breaks, work on their relaxation skills, or partake in other stress-relieving activities. Students would be better equipped to handle their stress thanks to this proactive approach. Furthermore, the system might provide tailored suggestions to assist students in striking a balance between their workload and emotional health by establishinga correlation between their stress levels and their academic achievement or other individual characteristics.

To sum up, the AI-based multimodal stress detection systemis a major advancement in the field of student mental health monitoring. The system surpasses conventional techniques in terms of performance and real-time applicability byintegrating physiological, behavioural, and textual data to provide a more comprehensive and accurate approach tostress detection. The system's potential to enhance student well-being is evident, despite several obstacles, such as individual differences in stress responses and data quality. With additional work and improvement, this approach may prove to be an essential instrument for early intervention in learning settings, assisting students in controlling their stress levels before they worsen and cause more significant mental health problems. As the system develops, it might play a significant role in providing students with all-encompassing mental health care, promoting better academic and personal outcomes.

Conclusion and Future Work

An important development in the field of student mental health monitoring is the AI-based multimodal stress detection system created in this work. In contrast to conventional techniques that depend on individual modalities, the system provides a more thorough method of stress detection by combining many data kinds, such as physiological signals, facial expressions, voice tone, and textual sentiment analysis. The studies' outcomes unequivocally show that the CNN-based model performs better than conventional machine learning algorithms like Random Forest in terms of accuracy, precision, recall, and F1-score. According to these results, deep learning methods—in particular, CNNs—are very good at processing and interpreting complicated, multimodal data, which makes them perfect for applications like stress detection where it's necessary to comprehend several signals at once. The effectiveness of this model offers a novel approach to early identification andprompt student stress management, which is essential for averting more serious mental health conditions like anxiety, burnout, and depression.

Future revisions of this system must solve a number of issues, despite the encouraging outcomes. The fact that differentpeople experience stress in different ways is one of the main issues. Every student may display stress in a different way, whether it is through words, facial gestures, or physiological reactions. The model may have trouble correctly categorizing stress in every situation as a result of this unpredictability. Future research couldconcentrate oncustomizing thesystem so that it can gradually learn and adjust to each person's particular stress patterns in order to lessen this. This could improve accuracy and user experience by making the model more accurateandusefulforeveryuser.Furthermore, itisessentialto make sure that the data gathering procedure is reliable and precise because the system is built to handle a variety of data kinds. Environmental elements that can impact the quality ofthe data obtained and, consequently, the system's performance include noise levels, lighting conditions, and sensor placement. Future research should look into ways to enhance data collection,suchasimprovingsensorsandalgorithmstointerpret data in real time under different circumstances.

Concerns about privacy and ethical ramifications are another topic. Important concerns regarding consent, data security, and misuse are brought up by the ongoing monitoring of pupils' emotional and physical states. Even when intended to benefit students, students may feel uneasy knowing that their physical and mental health is being monitored all the time. Addressing these issues requires putting in place explicit procedures for informed consent as well as making sure that all data is anonymized and kept in a secure location. Furthermore, rather thantakingtheroleofexpertmentalhealthcare,thesystemneed to be viewed as an additional resource.
Another topic is privacy concerns and ethical implications. The continuous monitoring of students' emotional and physicalstates raises significant issues with consent, data security, and misuse. Students may feel uneasy knowing that their physical and mentalhealth isalwaysbeing watched,even ifitis fortheir benefit. Establishing clear protocols for informed permission and ensuring that all data is anonymized and stored in a secure location are necessary to address these problems. Furthermore, the system should be seen as an extra resource rather than assuming the job of professional mental health care.

Withaneyetowardthefuture,therearemanychancestoexpand this system's capabilities. Increasing the size of the dataset used to train the model is one possible enhancement. Students from a wider range of age groups, academic disciplines, and cultural backgrounds would be included in the dataset, which would improvegeneralization andlessen biases. Thiswould enhance the model's accuracy across different populations and enableit to learn from a greater variety of stress indicators. The dependability of the model might be further increased by incorporating additional data sources, such as brainwave analysis or eye tracking, which could offer even moreaccurate insights into a student's stress levels. Additionally, real-time intervention capabilities could be increased. For example, the system might offer students tailored suggestions according to their stress levels, such relaxation techniques, breaks, or even academic support if stress is connected to managing workload.

Furthermore, a more comprehensive educational

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.

framework might be used to assess the system's effects. For instance, the system mayprovide tailored adviceonhowto strikeabalance between study and leisure by integrating the model with academic performance data,which couldhelp avoid academic burnout. Additionally, by analyzing the relationship between stress levels and academic performance, the system may be able to identify students who might be experiencing stress-related difficulties, resulting in more focused and proactive support. Adding more reliable data sources and intervention techniques could guarantee that the system continues to be a useful instrument for promoting students' long-termwellbeing.Furthermore,thesystemmightbeextendedoutside of educational settings to include workplaces, where stress management and monitoring are just as important.

To sum up, the AI-based multimodal stress detection system has a lot of potential as a toolfor tracking and treating student stress.Thesystemprovidesanovelapproachtothechallenges of stress detection by integrating several data kinds and applying deep learning techniques. The potential advantagesof such a system in enhancing student mental health are evident, despite certain obstacles, such as data quality and ethical issues. With additional development, this system has the potential to become a vital component of educational and professional settings, offering prompt, individualized interventions to enhance mental health and avert more severe mentalhealthproblems.Thesystem'scapabilitiesmaygrowto provide even more in-depth insights and treatments as technology advances, guaranteeing that stress management will always be a useful and accessible tool for anyone. Binary classification was chosen to simplify initial deployment and maximize interpretability for educational stakeholders. Future workmayexploremulti-classstressintensitylevels.Thebatch size of 32 and dropout of 0.3 were selected empirically after testing for trade-offs between speed and overfitting.

REFERENCES

[1] Chen, X., Zhang, Y., et al., "A Survey on Machine Learning for Big Data Analytics in Wireless Networks," IEEE Access, vol. 7, pp. 77980–78001, 2019.

[2] Jouzdani,M., and Asad, S.M., "ANovelDeep Learning Model for Real-Time Stress Detection Using Wearable Sensors," IEEE Transactions on Neural Systems and RehabilitationEngineering,vol.28,no.7,pp.1551–1561,2020.

[3] Mrs. Sumathi K and Dr. Kanimozhi J.K., "Enhancing QOS-Based Routing in Manets through Hybridization of Greywolf of Optimization and Ant Colony Optimization Algorithms", Journal of Emerging Technologies and Innovative Research (JETIR), Vol. 11, Issue No. 01, PP. b779 – b785, Jan' 2024, IF No.: 7.95, [ISSN: 2349 – 5162].

[4] Mr. Sureshkumar C and Dr. Kanimozhi J.K., "TSAO: Twitter Sentiment Analysis using Deep Learning with Optimization Techniques", International Journal of Intelligent Systems and Applications in Engineering, Vol. 12, Issue No. 07, PP. 625 – 642, Dec' 2023, IF No.: 4.711, [ISSN: 2147 - 6799].

[5] Mrs. Sumathi K and Dr. Kanimozhi J.K., "Analysis of Optimizing QoS-based Routing in MANET using Hybrid Krill Herd and Genetic Algorithms", International Journal for Modern Trends in Science and Technology, Vol. 10, Issue No. 01, PP. 51 – 58, Dec' 2023, IF No.: 4.124, [ISSN: 2455 – 3778].

[6] Mrs. Sumathi K and Dr. Kanimozhi J.K., "Analysis of QOS Routing in Mobile AdHoc Networks using Anthocnet, Shuffled Frog Leap, Firefly and Lion Optimization Algorithms", Journal of Theoretical and Applied Information Technology, Vol. 101, Issue No. 15, PP. 6178 -6189, Aug' 2023, IF No.:0.195 , [ISSN: 1992 – 8645, E-ISSN: 1817 - 3195].

[7] Dr. Kanimozhi J.K and all., "Data Security Analysis of PHY Layer using Artificial Intelligence and Machine Learning", IEEE Xplore Scopus Indexed Journal, Aug' 2023.

[8] Mr. Sureshkumar C and Dr. Kanimozhi J.K., "Enhanced LDA Based Input Selection towards the Sentimental Analysis", International Journal of Design Engineering, Vol. 01, Issue No. 08, PP. 311 – 321, Dec' 2021, IF No.: 1.923, [ISSN: 0011 - 9342],

[9] Chakraborty,S.,andPadhy,S.,"MultimodalApproaches to Stress Detection in Educational Settings," IEEE Transactionson AffectiveComputing,vol.12,no.3,pp. 718–728, 2021.

[10] Sengupta,S.,etal.,"DeepLearningModelsforStress andMentalHealthAnalysis:ASystematicReview,"IEEE Access, vol. 8, pp. 211485–211497, 2020.

Physiological Signals and Machine Learning: A Review," IEEE Transactions on Artificial Intelligence, vol. 2, no. 1, pp. 50–59, 2021.

[11] Green, M., etal., "TheRole ofPhysiologicalData in Stress Monitoring for Mental Health Applications," IEEE Reviews in Biomedical Engineering, vol. 13, pp. 1–15, 2020.

[12] Choudhury, T., et al., "Multimodal Sensing and Machine Learning forStressMonitoring in College Students,"IEEE Transactions on Human-Machine Systems, vol. 49,no.5, pp.537–544,2019.

[13] Patel, V., and Young, W., "Real-Time Stress Detection Using Wearable Sensors and Machine Learning," IEEE Transactions on Biomedical Engineering, vol. 68, no. 4, pp.951–960,2021.

[14] Sharma, P., and Gupta, V., "Using Deep Learning forStress Detection in Classroom Environments," IEEE Access, vol. 9, pp. 44767–44779, 2021.

[15] Choudhury, T., et al., "Wearable Computing forMonitoring Stress and Anxiety in Real-World Settings," IEEE Transactions on Mobile Computing, vol. 19, no. 5, pp.1139–1148,2020.

[16] Liu, S., et al., "Stress Detection Using

[17] Tang, Y., and Liu, Z., "A Deep Neural Network Approach for Real-Time Stress Detection," IEEE Transactions on NeuralNetworksand Learning Systems, vol. 32, no. 8, pp. 3531–3541, 2021.

[18] Wang, H., and Li, F., "Analysis of Stress Level Using Multimodal Data for College Students,"IEEETransactions on Consumer Electronics, vol. 65, no. 2, pp. 246–254, 2019.

[19] Patel, S., et al., "Advances in Stress Detection Using Multimodal Techniques," IEEE Transactions on Affective Computing, vol. 8, no. 2, pp. 106–119, 2017.

[20] Zhang, Y., et al., "A Hybrid Deep Learning Approach for Stress Recognition Using Facial Expressions and Physiological Signals,"IEEETransactions on Cybernetics, vol. 51, no. 10, pp. 4839–4849, 2021.

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:21:48 UTC from IEEE Xplore. Restrictions apply.