Proceedings of the Nineth International Conference on Communication and Electronics Systems (ICCES-2024)
IEEE Xplore Part Number: CFP24AWO-ART; ISBN: 979-8-3503-7797-2

AI-Enhanced Cognitive Therapy: Personalized Guidance via Adaptive Agents with Voice Analysis and Stress Detection

Sudharshan Venkataraman[1]
Student : Btech CSE, Vellore Institute of Technology, Vellore, Tamilnadu, India.
sudharshan24k@gmail.com

Dr.G.Uma[2]
Assistant Professor in dept of Computer Science,
Srimad Andavan Arts and science College,Trichy,
Tamilnadu, India.
umacs@andavancollege.ac.in

Dr.V.Kannan[3]
Professor in Physics,
K.Ramakrishnan College of Engineering,
Trichy, Tamilnadu, India.
kvkannan_2001@yahoo.com

V Lalitha Devi[4]
Assistant Professor in dept of Computer Science,
Srimad Andavan Arts and science College,Trichy,
Tamilnadu, India.
lalitha@andavancollege.ac.in

2024 9th International Conference on Communication and Electronics Systems (ICCES) | 979-8-3503-7797-2/24/$31.00 ©2024 IEEE | DOI: 10.1109/ICCES63552.2024.10859531

Abstract

This research presents a novel framework for AI-Enhanced Automated Cognitive Therapy (AECT) that integrates cutting-edge technologies to provide personalized and effective mental health support. AECT leverages refined Transformer-based conversational agents, advanced voice analysis, and physiological signal processing to offer a comprehensive therapeutic experience. The proposed system incorporates deep learning models for voice analysis and facial emotion recognition, achieving high accuracy in identifying emotional subtleties and stress levels. By combining these advanced technologies, AECT provides a personalized and engaging therapeutic experience, demonstrating the potential to significantly impact mental well-being and improve therapeutic outcomes worldwide.

Keywords: Cognitive Behavioural Therapy, Psychology, Machine Learning , Transformers , Long Short Term Memory , Neural Networks, Artificial Intelligence

1.Introduction

Mental health is a crucial component of overall well-being, yet access to effective, personalized treatment remains a significant challenge. Traditional cognitive behavioral therapy (CBT) [1] is widely recognized as an effective treatment for various mental illnesses, such as depression, anxiety, and stress-related conditions. However, the increased demand for mental health services often exceeds the availability of adequate staffing, creating barriers to timely and appropriate care [2]. To address this critical gap, AI-Enhanced Automated Cognitive Therapy (AECT) acts as a pioneering program that leverages artificial intelligence (AI) technology to deliver mental health interventions that are accessible and equitable for everyone.

AECT combines state-of-the-art, transformer-based conversational features [3] with deep learning models for voice analysis and facial emotion processing to deliver a comprehensive treatment experience tailored to individual needs. At the heart of AECT is the refined Transformer model, designed to facilitate contextual, empathetic, and conversational communication during therapeutic sessions. This flexible conversational device guides users through CBT exercises, dynamically adjusting and responding based on user input to ensure a deeply personalized clinical experience. The ability to deliver real-time, contextual information marks a major breakthrough over traditional automated medical systems [4].

Voice analysis is a foundational component of AECT, utilizing deep learning techniques such as Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks. These models are adept at detecting subtle sensory information and distress levels from audio. This paper presents a novel AI-driven framework for Automated Cognitive Therapy (AECT), integrating real-time conversational agents, voice and facial emotion recognition, and stress detection to offer personalized mental health support. The system combines Transformer-based agents with InceptionNet and deep learning models, achieving over 92% accuracy in voice analysis and 93% accuracy in facial emotion detection. Adaptive agents tailor CBT exercises based on users' emotional and physiological states. The framework also incorporates stress detection from physiological signals, providing a

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:27:17 UTC from IEEE Xplore. Restrictions apply.

scalable, ethically grounded solution for mental health applications.

2. Related Works

The domain of AI-driven mental health support systems has seen significant advancements in recent years. Various research efforts have focused on developing conversational agents for therapy through emotion recognition from speech for stress detection. This system distinguishes itself through its integrated, multimodal approach and state-of-the-art technologies which sets it apart from existing solutions. This enables the agent to generate more contextually relevant and empathetic response through the use of a Transformer model, particularly a fine-tuned GPT-2 which allows AECT to handle more complex and nuanced dialogues, providing a more personalized and dynamic therapeutic experience. Adaptive agents leverage machine learning algorithms which play a mighty role in this transformation by offering real-time feedback and customized therapeutic interventions. These agents utilize natural language processing to engage with patients in a more human-like manner, making therapy sessions more interactive and effective. Voice analysis is a significant component of AI-enhanced cognitive therapy, where AI systems analyse voice parameters such as pitch, tone, and speech rate to detect emotional states like stress and anxiety. Despite these advancements, challenges such as data privacy model's accuracy and ethical considerations remain with ensuring robust data security also minimizes biases in AI models and addressing ethical concerns regarding the extent of AI intervention are critical for the successful implementation in cognitive therapy. Future research should aim at enhancing AI model robustness, developing ethical guidelines, and integrating AI systems with traditional therapeutic approaches to create a hybrid model for mental health care.

3. Model Architecture

At the core of the AECT system is a transformer-based speech which is optimized especially for medical communication. The transformer architecture use their own ideas to handle input sequences in parallel by also allowing remote dependencies and contextual relationships to be better captured The AECT framework uses an improved version of the GPT-2 and inception [5] model use with multi-heads . This multi-layered system of self-awareness and feedforward neural networks enables the model to obtain appropriate and consistent responses as context, which is critical to maintaining a pleasant and supportive therapy session .

Data pre-processing steps include structured therapeutic conversations, generic dialogue data, and context specific stress and emotional support conversations from the training dataset of the conversation operator of the model are tokenized, normalized, and enhanced for the robustness of the model spike. Particular attention is paid to ethical considerations, ensuring that the list includes representation of different demographics and cultures. These steps also include structured therapeutic conversations with generic dialogue data and context-specific stress and emotional support conversations in the training dataset providing real-time insights and dynamic responses, thus offering a more comprehensive and personalized therapeutic experience. The fine-tuning process involves the calibration of the pre-trained Transformer model with specific datasets relevant to cognitive therapy. This includes dialogues from CBT sessions, therapeutic interventions, and stress management conversations. The model is optimized using techniques such as supervised learning and reinforcement learning from human feedback to enhance its ability to recognize and respond appropriately to various cues. This also aims to ensure that the model not only understands the context but also provides supportive responses.

3.1 Integration and Real-Time Interaction

This system employs a holistic approach by seamlessly integrating its conversational agent and voice analysis and is facilitated through a centralized coordination module that ensures continuous real-time data flow and processing. During therapy sessions this AECT system continuously monitors and processes both voice and video based emotion recognition signals in real-time environment .The conversational agent interprets user inputs and generates responses that take into account the ongoing conversation context as well as the user's emotional and physiological state of the user[6].

By analysing conversational inputs which are the voice signals and facial data comprehensively, the trained AECT system generates personalized therapy recommendations which encompass specific Cognitive Behavioural Therapy (CBT) exercises along with relaxation techniques and stress management strategies tailored to the user's current condition based on the inputs received by the model from the user. The system's adaptive nature ensures that therapy evolves dynamically with the user which provides continuous support and interventions as required throughout the therapeutic process.

4. Experimental Setup

The voice analysis module leverages a hybrid architecture combining Neural Networks, filters, kernals, attention mechanisms and Long Short-Term Memory networks to accurately discern emotional nuances from the audio signals. Neural Networks are utilized to extract features from raw form of the

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:27:17 UTC from IEEE Xplore. Restrictions apply.

processed audio signals by an architecture consisting of four convolutional layers with various filter sizes, kernel sizes, max pooling layers, and ReLU activation functions out of these the important features include Mel-frequency cepstral coefficients, spectral contrast, chroma features, pitch, and energy are extracted through these layers.[7]

These extracted features are parallelly processed into the layers of the built architecture to capture temporal dependencies and their sequential patterns by utilizing two LSTM layers, a dropout to prevent overfitting and Tanh activation functions. This integration of neural networks and LSTM layer outputs supports the built model to combine the extracted spatial and temporal features from the output layer of the architecture by providing a comprehensive representation of the audio signals. This model is trained on the MSP-Podcast Corpus which uses annotated emotional speech recordings to achieve high accuracy in classifying emotions which enhances the AECT system's ability to understand and respond to users' emotional states in real-time.

4.1 Dataset

4.1.1 Audio Data: MSP-Podcast Corpus

Table 1: Audio Dataset

Total Segments:	Approximately 50,000 audio segments.
Duration:	Each segment ranges from 2 to 60 seconds, totaling around 100 hours of annotated speech
Sampling Rate	16 kHz.
Emotion Distribution	Balanced across primary emotional categories (happiness, sadness, anger, surprise, and neutral).

The MSP-Podcast Corpus is a well annotated dataset which includes a wide range of emotional expressions captured through spontaneous speech. The dataset's diversity and the quality of annotations make it an excellent resource for making them availed . Its annotations ensure reliability, making it invaluable for training and evaluating emotion recognition models.

4.1.2 Video Data: FER+ Dataset

Table 2: video dataset

Total Images	Over 35,000 images.
Specified Categories	7 categories such as Happiness, sadness, anger, surprise, fear, disgust, and neutral.
Annotations	Detailed annotations of facial emotions with variability in facial expressions within each emotion category.

The FER+ dataset provides quality images with annotations for various facial expressions. This is essential for training models to recognize subtle differences in facial expressions, which are critical for accurate emotion detection through the visual mode[8].

The InceptionNet-based model for video analysis is trained on the FER+ dataset. Along the standard model of InceptionNet , a set of manually built layers are constructed on the top to fine tune for this particular dataset. Image normalization to standardize pixel values, and augmentation techniques such as rotation, scaling, and flipping to improve model robustness.

This architecture is ideal s due to its ability to efficiently extract multi-scale spatial and temporal features by leveraging parallel convolutional filters to capture fine details and broader contexts simultaneously. Its use of 1x1 convolutions reduces computational complexity which makes it scalable for large video datasets while maintaining high accuracy[9].

The Inception model has a moderate to high complexity level due to its parallel convolutional layers that extract multi-scale features which makes it computationally efficient yet powerful. It's wide architecture increases memory usage makes it more resource-intensive than lightweight models but highly suitable for performance critical applications.



Figure 1. Layer Built on Model

4.2 Transformer-Based Conversational Agent

Table 3: GPT-2

Model	GPT-2
Parameters	1.5 billion *
Layers	48 *
Attention Heads	12 per layer

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:27:17 UTC from IEEE Xplore. Restrictions apply.

The GPT-2 model is fine-tuned using a specialized therapeutic dialogue dataset where the process involves supervised learning and the openly available trained model is adapted for a wide range of therapeutic contexts. The goal is to improve the ability of the model to provide relevant and empathetic responses during therapy sessions. The fine-tuning dataset includes a variety of therapeutic dialogues which ensures the model can handle different therapeutic scenarios effectively.[11]
4 convolutional layers with various standard filter sizes and a kernel of size 3x3 with Max pooling layers after each convolutional layer to reduce dimensionality and computational complexity. ReLU activation to introduce non-linearity into the model. LSTM layers with 256 units each and a dropout 0.5 to prevent overfitting by randomly dropping units during training. Tanh activation function to capture temporal dependencies and maintain gradient stability.[12]

Table 4: Hyperparameters

Learning rate	0.001 (exp decreasing)
Dropout Rate	0.5
Batch size	32
Optimiser	Adam
Loss function	Cat. cross entropy
Activation Function	Relu (Intermediate) Softmax (output layer)
Epochs	28

The video analysis model uses InceptionNet to extract detailed features from facial expressions. InceptionNet was chosen for its ability to efficiently handle multi-scale feature extraction, enabling improved accuracy in capturing complex patterns in emotional cues from facial and voice data. Custom layers are added to enhance the model's ability to recognize subtle variations in facial emotions[10]. These features are critical for providing a robust analysis of the user's emotional state.

4.3 Training Procedure

The Transformer model is fine-tuned using a dataset specifically compiled for therapeutic dialogues which includes interactions from cognitive behavioural therapy sessions. The chosen dataset contains conversational exchanges to provide a diverse range of therapeutic dialogues[13]. The process of Tokenization to split text into tokens followed by normalization to convert text to lowercase and remove punctuation and augmentation to increase dataset size and variability are implied for all of them. Fine-tuning of the training process includes multiple iterations of supervised learning to well adapt itself for therapeutic contexts.[14]

5. Results

The AECT system's performance was evaluated based on its ability to recognize emotional states from voice signals and detect facial emotion from video analysis. The metrics are shown in the table on which the results are calculated .

Voice Analysis

Table 5.1: Results of voice model

MODEL	PERCISION	RECALL	ACCURACY	F1 SCORE
Values	0.911579	0.917843	0.923157	0.930412

Facial analysis

Table 5.2: Results of facial model

MODEL	PERCISION	RECALL	ACCURACY	F1 SCORE
Values	0.927490	0.933761	0.933761	0.913373

To improve the performance of and achieve high accuracy, several strategies such as fine-tuning the model on more robust domain-specific data helps the model learn more diverse context-specific patterns can be employed. Regularization methods like dropout and weight decay, as well as early stopping, can prevent overfitting while dealing with huge data size and also while preprocessing text consistently and using advanced tokenization techniques will help in improve input quality. Employing transfer learning and multi-task learning along with proper handling of class imbalance will ensure robustness.

5.1 Integration and Real-Time Interaction

AI plays a crucial role in enhancing performance for tasks like sentiment analysis in CBT. By leveraging NLP by understanding and process human language through the identification of emotional patterns and fine-tune models on domain-specific data. AI also enables personalised treatment plans by analysing individual language patterns and allows real-time monitoring by providing immediate feedback and tracking progress which improves both the efficiency and quality of therapy.[15]

The AUC-ROC curve evaluates the trade-off between the true positive rate and false positive rate with a higher AUC indicating better model performance.

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:27:17 UTC from IEEE Xplore. Restrictions apply.

Real-world performance in therapy sessions or stress monitoring by providing practical insights while user feedback offers subjective evaluation of the model's effectiveness in improving treatment outcomes.

The integration of voice analysis and facial emotion detector into the conversational agent is expected to enhance the personalization and effectiveness of therapy sessions. The real-time processing capability ensures that the system adapts itself to the user's emotional and physiological states which provides timely and contextually relevant therapeutic interventions for the uses through the process.[16]



Figure 2a,b & c Sample Outputs

5.2 Application of AECT

The AI-Enhanced Automated Cognitive Therapy (AECT) system can be applied to various domains to provide significant benefits in mental health support. For personalized Cognitive Behavioural Therapy (CBT) system delivers therapeutic exercises and guidance based on real-time analysis of users' emotional state. This approach enhances accessibility to mental health support which reduces the dependency on in-person therapy sessions and provides continuous adaptive support to users [17]. This system can also be utilized for stress and anxiety management by detecting signs of stress and anxiety through voice and facial expressions and offering real-time interventions such as relaxation techniques and mindfulness exercises with coping strategies that reduce symptoms and improve overall emotional well-being.[18]

The development and implementation of the AI-Enhanced Automated Cognitive Therapy (AECT) system represent significant strides in leveraging artificial intelligence for mental health support. As there remains substantial potential for future research and improvements to enhance the system's capabilities and effectiveness further.

Future iterations of the AECT system can benefit from incorporating more robust models for emotional understanding. These advancements could include incorporating Multimodal Emotion Recognition by Integrating additional modalities such as body language recognition and textual sentiment analysis to provide a more broad understanding of the user's emotional state. Utilisation Advanced Deep Learning Models by Exploring the use of more recent and advanced deep learning architectures, such as Transformers for audio and physiological signal processing which will improve the emotion recognition accuracy and the model's robustness.[19]

Expanding the scope of the AECT system to include a broader range of psychological assessments and therapeutic techniques could enhance its utility. Improving Diagnostic Capabilities by incorporating diagnostic tools for various mental health conditions, such as depression, anxiety disorders and PTSD based on validated psychological scales and assessments. Integrating additional therapeutic approaches such as Acceptance and Commitment Therapy (ACT), Dialectical Behaviour Therapy (DBT) and mindfulness-based interventions to cater to a wider array of therapeutic needs.[20]

6. Conclusion

The integration of voice and facial emotion analysis within the AECT system ensures a holistic approach to mental health support by leveraging its ability to process and interpret multimodal data in real-time and combining them with advanced deep learning

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:27:17 UTC from IEEE Xplore. Restrictions apply.

architectures for emotion detection, the AECT system offers a unique and powerful tool for cognitive therapy makes it to delivering timely and contextually appropriate therapeutic interventions. The AECT system represents a significant advancement in AI-driven mental health technologies as robust performance in emotion recognition from both voice and facial data combined with its personalized and adaptive therapeutic approach mainly positions it as a transformative tool for improving mental health outcomes. The future scope of the AI-Enhanced Automated Cognitive Therapy (AECT) system is vast and promising which addresses the outlined areas for improvement and exploration where the future research can significantly enhance the system's capabilities makes it a more effective, personalized and accessible tool for mental health support. This continuous evolution of AI and deep learning technologies are combined with rigorous research and ethical considerations will pave the way for transformative advancements in automated cognitive therapy which will ultimately improving mental well-being and therapeutic outcomes on a global scale.

References:

1. Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., ... & Amodei, D. (2020). Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*.

2.G Uma,Enhanced Convergent Encryption Key Generation for Secured Data Deduplication in Cloud Storage, November -2018- JphCS -volume:1142,Issue:1.

3.Graves, A., Mohamed, A. R., & Hinton, G. (2013). Speech recognition with deep recurrent neural networks. In *2013 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*.

4. Thirupugalmani, K., Karthick, S., Shanmugam, G., Kannan, V., Sridhar, B., Nehru, K., & Brahadeeswaran, S. (2015). Second-and third-order nonlinear optical and quantum chemical studies on 2-amino-4-picolinium-nitrophenolate-nitrophenol: a phasematchable organic single crystal. *Optical Materials*, *49*, 158-170.

5.Szegedy, C., Vanhoucke, V., Ioffe, S., Shlens, J., & Wojna, Z. (2016). Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.

6.Kingma, D. P., & Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.

7.G.Uma,Survey on Data Deduplication Techniques used for Efficient Management of Cloud Storage, July-2018,International Journal Computer Science Management Studies, volume:7,Issue:3.

8. Martinez-Lucas, L., Abdelwahab, M., & Busso, C. (2020). The MSP-conversation corpus. *Interspeech 2020*.

9. Zahara, L., Musa, P., Wibowo, E. P., Karim, I., & Musa, S. B. (2020, November). The facial emotion recognition (FER-2013) dataset for prediction system of micro-expressions face using the convolutional neural network (CNN) algorithm based Raspberry Pi. In *2020 Fifth international conference on informatics and computing (ICIC)* (pp. 1-9). IEEE.

10. Sharvesh, S., Kaileshwar, M., Arthi, B., & Jothikumar, C. (2024, August). EmoSense: Deep Analysis of Real-Time Facial Expression for Multi-Class Emotions. In *2024 Second International Conference on Networks, Multimedia and Information Technology (NMITCON)* (pp. 1-6). IEEE.

11.Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). Language models are unsupervised multitask learners. OpenAI.

12.Zhou, B., Khosla, A., Lapedriza, A., Oliva, A., & Torralba, A. (2016). Learning deep features for discriminative localization. In 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR).

13. Zhang, Y., Li, Y., Liu, X., & Deng, W. (2024). Leave no stone unturned: mine extra knowledge for imbalanced facial expression recognition. *Advances in Neural Information Processing Systems*, *36*.

14.V Kannan, Spectroscopic, quantum-chemical and X-ray diffraction studies of Piperidinium p-Hydroxybenzoate-combined experimental and theoretical studies on a novel NLO crystal- April-2013, Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy,Volume -106.

15. Uma, G., & Jayasimman, L. (2018, November). Enhanced convergent encryption key generation for secured data deduplication in cloud storage. In *Journal of Physics: Conference Series* (Vol. 1142, No. 1, p. 012006). IOP Publishing.

16.Barsoum, E., Zhang, C., Ferrer, C. C., & Zhang, Z. (2016, October). Training deep networks for facial expression recognition with crowd-sourced label distribution. In *Proceedings of the 18th ACM international conference on multimodal interaction* (pp. 279-283).

17.Lotfian, R., & Busso, C. (2017). Building naturalistic emotionally balanced speech corpus by retrieving emotional speech from existing podcast recordings. *IEEE Transactions on Affective Computing*, *10*(4), 471-483.

18..Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). Language models are unsupervised multitask learners. *OpenAI blog*, *1*(8), 9.

19. Szegedy, C., Liu, W., Jia, Y., Sermanet, P., Reed, S., Anguelov, D., ... & Rabinovich, A. (2015). Going deeper with convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition* (pp. 1-9).

20. Burkhardt, F., Paeschke, A., Rolfes, M., Sendlmeier, W. F., & Weiss, B. (2005). A database of German emotional speech. In *9th European Conference on Speech Communication and Technology*.

Authorized licensed use limited to: REVA UNIVERSITY. Downloaded on December 02,2025 at 06:27:17 UTC from IEEE Xplore. Restrictions apply.