

EasyCommit: A Non-blocking Two-phase Commit Protocol

**Presentation for ECS 265:
Distributed Database Systems**


Presented by Likang Yin

October 4, 2018

Roadmap


- **1. Background**
- **2. Two-phase Commit (2PC) Protocol**
- **3. Three-phase Commit (3PC) Protocol**
- **4. EasyCommit Protocol**
- **5. Comparison and Analysis**

Two-phase Commit (2PC) Protocol




Source: EasyCommit: A Non-blocking Two-phase Commit Protocol. EDBT'18.


Blocking Problem in 2PC Protocol



Three-phase Commit (3PC) Protocol




(a) Time span of 2PC Protocol



(b) Time span of 3PC Protocol

Source: EasyCommit: A Non-blocking Two-phase Commit Protocol. EDBT'18.

EasyCommit Protocol



(c) Time span of EC Protocol

Source: EasyCommit: A Non-blocking Two-phase Commit Protocol. EDBT'18.

Termination Protocol

Three different situations:

- 1. Coordinator Timeout in WAIT State**
- 2. Cohort Timeout in INITIAL State**
- 3. Cohort Timeout in READY State**

Independent Recovery

EasyCommit Protocol can do the independent recovery when:

- 1. If a cohort fails before transmitting its vote, then on recovery, it can simply abort the transaction.**
- 2. If the coordinator fails before transmitting the global decision, then it aborts the transaction on recovery.**
- 3. If either coordinator or participant fail after transmitting the global decision and writing the log, then on recovery they can use this entry to reach the consistent state.**

Conclusion

The easy commit protocol takes the advantages of both 2PC Protocol and 3PC Protocol. It is able to:

- 1. Handle commit transactions efficiently (Two phases).**
- 2. Resolve the transactions safely if the coordinator fails (Non-blocking).**
- 3. Execute independent recovery in three different cases. (Independent recovery).**