


Mapping Precincts to Counties

Aligning Polygons with R's Geospatial Packages

Cascadia R Conference - June 3, 2017




Scott Came
Principal
Cascadia Analytics LLC

The Challenge



#election-transparency

2016 Presidential Election Result




Only one state publishes results at the precinct, rather than the county, level...

The Solution

Polygon source shapefiles:

- County-equivalents: Census TIGERLine
- Precincts: Alaska Division of Elections



Red borders: > 5 sq mi outside assigned CE

Labeled precincts: > 10% of precinct area outside assigned CE

19 Boroughs
10 Census Areas




441 Election Precincts

Could we reliably assign precincts to “county equivalents” by overlaying polygons?

The Tools: `rgeos::gIntersection()` & `rgeos::gArea()`

```
1 library(tidyverse)
2 library(sp)
3 library(rgeos)
4
5 m <- matrix(c(1,1.25,1,2.25,3,2.25,3,1.25), nrow=4, byrow = TRUE)
6 sps <- SpatialPolygons(list(Polygons(list(Polygon(m))), 1)))
7 spsDf <- fortify(sps)
8
9 m2 <- matrix(c(2,1,2,2,4,2,4,1), nrow=4, byrow = TRUE)
10 sps2 <- SpatialPolygons(list(Polygons(list(Polygon(m2))), 1)))
11 sps2Df <- fortify(sps2)
12
13 i <- gIntersection(sps, sps2) ←
14 iDf <- fortify(i)
15
16 ggplot() +
17   geom_polygon(data=spsDf, aes(x=long, y=lat), fill='blue', alpha=.3) +
18   geom_polygon(data=sps2Df, aes(x=long, y=lat), fill='red', alpha=.3) +
19   geom_polygon(data=iDf, aes(x=long, y=lat), fill='green', alpha=.3) +
20   labs(x=NULL, y=NULL)
```



```
> gArea(i)
[1] 0.75
```

The process:


```
maxArea = 0

for each p in [Precincts]:
    for each c in [County Equivalents]:
        i = intersection(c, p)
        a = area(i)
        if (a > maxArea) then:
            maxArea = a
            assignTo(c, p)
maxArea = 0
```


Testing the hypothesis...

35 / 441 Precincts
have more than 5
square kilometers
outside the assigned
CE


8 Precincts have
more than 10% area
outside the assigned
CE




Not perfect...but
plenty good enough!



Two examples



Central (Precinct 06-015): 16% outside assigned CE
Natural / meaningful geographic partition (Kandik River)



Bettles (Precinct 40-328): .3% outside assigned CE
Mismatch due to resolution / mapping error

Resources

Notebook: <https://rawgit.com/scottcame/elections-analyses/master/CascadiaR-notebook.nb.html>
<https://github.com/scottcame/elections-analyses> (PRs welcome!)

Data for Democracy: <http://datafordemocracy.org/>

D4D `uselections` package: <https://github.com/Data4Democracy/election-transparency/tree/master/r-packages/uselections>
AK precinct mapping is in `/R/util.R`, function `getAlaskaPrecinctCountyMapping()`

D4D ET on data.world: <https://data.world/data4democracy/election-transparency>

Alaska Elections: <http://www.elections.alaska.gov/>

Precinct Shapefiles: <http://elections.alaska.gov/Core/districtmaps.php>

Me:

scott@cascadia-analytics.com
@scottcame / @cascadialytics

<https://github.com/scottcame>
<http://www.cascadia-analytics.com>

