

Computer Graphics Framebuffers



Oregon State
University

Mike Bailey

mjb@cs.oregonstate.edu




This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)



Oregon State
University

Computer Graphics

The Framebuffers




glutSwapBuffers()

```
// swap the double-buffered framebuffers:
```


```
glutSwapBuffers( );
```

```
glutInitDisplayMode( GLUT_RGBA | GLUT_DOUBLE | GLUT_DEPTH );
```

```
glDrawBuffer( GL_BACK );
```



The Video Driver




The Video Driver


- N *refreshes/second* (N is between 50 and 100)
- The framebuffer contains the R,G,B that define the color at each pixel
- Because of the double-buffering, **Refresh** is asynchronous from **Update**, that is, the monitor gets refreshed at N (60) frames per second, no matter how fast or slowly you update the back buffer.



The Framebuffer Uses RGB Colors



The Framebuffer: Integer Color Storage



Bits/color

Intensities per color

8

$2^8 = 256$ ← “Typical”

10

$2^{10} = 1024$ ← High Dynamic

12

$2^{12} = 4096$

Range (HDR)

Bits/pixel Total colors:

24

$2^{24} = 16.7 \text{ M}$

30


$2^{30} = 1 \text{ B}$

36

$2^{36} = 69 \text{ B}$



- 16- or 32-bit floating point for each color component



Why so many bits?

Many modern algorithms do arithmetic on the framebuffer color components, or treat the framebuffer color components as data. They need the extra precision during the arithmetic.

However, the display system cannot display all of those possible colors.




The Framebuffer

- **Alpha** values
 - Transparency per pixel
 $\alpha = 0$. is invisible
 $\alpha = 1$. is opaque
 - Represented in 8-32 bits
(integer or floating point)
 - Alpha blending equation:

$$Color = \alpha C_1 + (1 - \alpha) C_2$$

$$0.0 \leq \alpha \leq 1.0$$


Note: this is really **blending**, not transparency!



The Framebuffer

- **Z-buffer**

- Used for hidden surface removal
- Holds pixel depth
- Typically 32 bits deep
- Integer or floating point



Bits / Z
32

Total Z Values:
 $2^{32} = 4B$

