

Day 27 : filter, set , reducer, map and set

In-Depth Guide: Modern JavaScript Array Methods

The methods we are about to cover are called **Higher-Order Functions**. This is a fancy term that simply means they are functions that take *another function* as an argument (this is the "callback" function you provide).

The Core Idea: Instead of manually writing a `for` loop every time, you tell the array *what* you want to do, and the array method handles the looping for you.

Let's use this sample array for our examples:

```
const products = [
  { id: 1, name: "Laptop", category: "Electronics", price: 1200, inStock: true },
  { id: 2, name: "Book", category: "Books", price: 30, inStock: true },
  { id: 3, name: "Coffee Maker", category: "Appliances", price: 150, inStock: false },
  { id: 4, name: "Headphones", category: "Electronics", price: 200, inStock: true }
];
```

1. `.forEach()` - The Simple Looper

- **First Thought:** "I want to walk along the conveyor belt and do something with each item, but I'm not creating a new line of items."
- **Core Purpose:** To execute a function once for each element in the array. It's a modern alternative to a `for` loop.
- **Key Characteristics:**
 - It does **not** return anything (it returns `undefined`).

- It does **not** create a new array.
- You **cannot** `break` out of it or `continue` to the next iteration.
- **Syntax:** `array.forEach((element, index) => { /* ... your code ... */ });`
 - `element`: The current item being processed in the array.
 - `index` (Optional): The index of the current item.
- **Detailed Example:** Just logging the name of each product.

```
console.log("--- Our Products ---");
products.forEach(product => {
  console.log(`- ${product.name}`);
});
```

Output:

```
--- Our Products ---
- Laptop
- Book
- Coffee Maker
- Headphones
```

- **When to Use:** When you need to "do something" for each item but you don't need to create a new array from the results. Examples: logging, updating a UI, saving each item to a database.

2. `.map()` - The Transformer

- **First Thought:** "I have a list of raw materials. I want to put each one through a machine to create a **new list** of finished products."
- **Core Purpose:** To create a **new array** by transforming every element from an original array.
- **Key Characteristics:**
 - It **always** returns a **new array**.

- The new array will **always** have the **same length** as the original array.
- It is **non-mutating**; it does not change the original array.
- **Syntax:** `const newArray = array.map((element, index) => { return /* new value */; });`
The `return` value from your callback function becomes the element in the new array at that same position.
- **Detailed Example:** Let's create a new array containing just the names of the products for display.

```
const productNames = products.map(product => {
  return product.name;
});

console.log(productNames); // ["Laptop", "Book", "Coffee Maker", "Headphones"]
console.log(products);    // The original `products` array is unchanged!
```

- **When to Use:** When you need a new array that is a modified version of the original. This is one of the most-used array methods.

3. `.filter()` - The Sieve / The Bouncer

- **First Thought:** "I have a big list of items. I want to run each one through a test and create a **new, shorter list** containing only the items that pass the test."
- **Core Purpose:** To create a **new array** containing only the elements from the original array that meet a specific condition.
- **Key Characteristics:**
 - It **always** returns a **new array**.
 - The new array can have the **same length or be shorter** than the original. It will never be longer.
 - It is **non-mutating**.
- **Syntax:** `const newArray = array.filter((element, index) => { return /* true or false */; });`
If your callback function returns `true`, the element is kept. If it returns `false`, the

element is discarded.

- **Detailed Example:** Let's create a new array of only the products that are in stock and are in the "Electronics" category.

```
const availableElectronics = products.filter(product => {  
  // The condition must evaluate to true or false.  
  // We combine two conditions here.  
  return product.inStock === true && product.category === "Electronics";  
});  
  
console.log(availableElectronics);  
// [  
//   { id: 1, name: "Laptop", ... },  
//   { id: 4, name: "Headphones", ... }  
// ]
```

- **When to Use:** Whenever you need to select a subset of data from an array based on one or more conditions.

4. **.reduce()** - The Accumulator / The Snowball

- **First Thought:** "I want to roll up this entire list into a **single final value**." (e.g., Summing a list of numbers, counting items, etc.)
- **Core Purpose:** To execute a "reducer" function on each element of the array, resulting in a single output value.
- **Key Characteristics:**
 - It is the most powerful and flexible of the iteration methods.
 - It can return **any type of value**: a number, a string, an object, another array.
 - It is **non-mutating**.
- **Syntax:** `const finalValue = array.reduce((accumulator, currentValue, index) => { /* ... */ return newAccumulator; }, initialValue);`

- **accumulator**: The value that is "accumulated" or carried over from the previous iteration. It's the snowball.
- **currentValue**: The current element being processed.
- **initialValue**: The **starting value** for the accumulator (the small snowball you start with). This is a crucial argument.
- **Detailed Example:** Let's calculate the total value of all the items that are currently in stock.

```
const totalStockValue = products.reduce((total, product) => {
  console.log(`Current Total: ${total}, Current Product: ${product.name}, Price: ${product.price}`);

  if (product.inStock) {
    // The return value of this step becomes the 'total' for the NEXT step.
    return total + product.price;
  }
  // If not in stock, just return the current total without adding anything.
  return total;
}, 0); // Our initial value for the total is 0.

console.log(`\nFinal Total Stock Value: $$${totalStockValue}`);
```

Trace of the Output:

```
Current Total: 0, Current Product: Laptop, Price: 1200
Current Total: 1200, Current Product: Book, Price: 30
Current Total: 1230, Current Product: Coffee Maker, Price: 150
Current Total: 1230, Current Product: Headphones, Price: 200

Final Total Stock Value: $1430
```

- **When to Use:** When you need to derive a single summary value from an array. Examples: sum, average, finding the most expensive item, grouping items into an object.

5. Other Essential Methods for Finding & Testing

- `.find()` : Like `.filter()` , but it **stops** and returns the **very first element** that matches the condition. If nothing matches, it returns `undefined` .

```
const coffeeMaker = products.find(product => product.name === "Coffee Maker");
console.log(coffeeMaker); // The coffee maker object
```

- `.some()` : Checks if **at least one** element in the array passes the test. Returns `true` or `false` . It stops as soon as it finds one.

```
const hasOutOfStockItems = products.some(product => product.inStock === false);
console.log(hasOutOfStockItems); // true
```

- `.every()` : Checks if **all** elements in the array pass the test. Returns `true` or `false` . It stops as soon as it finds one that *doesn't* pass.

```
const areAllItemsInStock = products.every(product => product.inStock === true);
console.log(areAllItemsInStock); // false
```

Set and Map

Part 1: The `Set` Object

First Thought: A `Set` is a list that enforces uniqueness. It's a collection of items where duplicates are impossible.

Think of it like a members-only club. You can add a person to the member list, but you can't add the same person twice. The `Set` automatically handles this for you.

A. The Basics of Set

1. Creating a Set

You create a `Set` with `new Set()`. You can optionally pass in an iterable (like an array) to pre-populate it. Duplicates are automatically removed.

```
// Create an empty Set
const mySet = new Set();

// Create a Set from an array (duplicates are ignored)
const numbersArray = [1, 2, 3, 3, 4, 2, 5];
const numbersSet = new Set(numbersArray);

console.log(numbersSet); // Set(5) { 1, 2, 3, 4, 5 }
```

2. Core Methods (CRUD)

- `.add(value)`: Adds a new element. If the element already exists, it does nothing. It returns the `Set` object, so you can chain `.add()` calls.
- `.has(value)`: Checks if an element exists. Returns `true` or `false`.
- `.delete(value)`: Removes a specific element.
- `.clear()`: Removes all elements from the `Set`.

```
const userRoles = new Set();

// Add elements (chaining)
userRoles.add("editor").add("viewer");
console.log(userRoles); // Set(2) { "editor", "viewer" }

// Add a duplicate - nothing happens
userRoles.add("editor");
console.log(userRoles); // Still Set(2) { "editor", "viewer" }

// Check for an element
console.log(userRoles.has("admin")); // false
console.log(userRoles.has("editor")); // true
```

```
// Delete an element
userRoles.delete("viewer");
console.log(userRoles.has("viewer")); // false

// Clear the entire Set
userRoles.clear();
console.log(userRoles); // Set(0) {}
```

3. The `.size` Property

Unlike arrays which have `.length`, a `Set` has a `.size` property to tell you how many items it contains.

```
console.log(numbersSet.size); // 5
```

B. Iterating Over a `Set`

Sets are iterable. The best way to loop over a `Set` is with a `for...of` loop. The items are iterated in **insertion order**.

```
const permissions = new Set(["read", "write", "execute"]);

for (const permission of permissions) {
  console.log(permission);
}

// Outputs:
// read
// write
// execute
```

You can also use `.forEach()`.

C. Real-World Use Cases (Why use a `Set` ?)

1. **Removing Duplicates from an Array (The #1 Use Case):** This is a powerful and concise one-liner.


```
const duplicateEmails = ["a@a.com", "b@b.com", "a@a.com"];

// Convert to a Set to remove duplicates, then spread it back into a new array.
const uniqueEmails = [...new Set(duplicateEmails)];

console.log(uniqueEmails); // ["a@a.com", "b@b.com"]
```

2. **Checking for Uniqueness / Existence:** `Set.has()` is much faster than `Array.includes()` for very large datasets. If you just need to track if you've "seen" an item before, a `Set` is far more performant.

```
// Imagine tracking unique visitors to a page
const visitedUsers = new Set();

function userVisits(userId) {
  if (!visitedUsers.has(userId)) {
    console.log(`Welcome, new visitor #${userId}!`);
    visitedUsers.add(userId);
  } else {
    console.log(`Welcome back, visitor #${userId}!`);
  }
}

userVisits(101); // Welcome, new visitor #101!
userVisits(102); // Welcome, new visitor #102!
userVisits(101); // Welcome back, visitor #101!
```

Use...	When you need...
<code>Array</code>	An ordered list where duplicates are allowed and you need index-based access (<code>arr[0]</code>).
<code>Set</code>	A collection of unique values where the main task is adding, deleting, and checking for existence.

Part 2: The `Map` Object

First Thought: A `Map` is like an object, but its keys can be *anything* (not just strings).

This is the most critical difference. In a standard object `{}`, keys are automatically converted to strings. A `Map` preserves the key's type, allowing you to use objects, functions, or any other data type as a key.

A. The Basics of `Map`

1. The Problem with Plain Objects

```
let myObject = {};  
let keyObject1 = { id: 1 };  
let keyObject2 = { id: 2 };  
  
// Both keyObject1 and keyObject2 get converted to the SAME string: "[object  
Object]"  
myObject[keyObject1] = "Value for key 1";  
myObject[keyObject2] = "Value for key 2";  
  
// The second assignment overwrote the first!  
console.log(myObject); // { "[object Object]": "Value for key 2" }
```

2. Creating a `Map`

You create a `Map` with `new Map()`. You can pre-populate it with an array of `[key, value]` pairs.

```
// Create an empty Map  
const myMap = new Map();  
  
// Create a Map with initial values  
const userMap = new Map([  
  ["name", "Alice"],  
  [true, "is verified"],  
]);
```

```
[100, "points"]
]);
```

3. Core Methods (CRUD)

- `.set(key, value)` : Adds or updates a key-value pair. Returns the `Map` , so you can chain it.
- `.get(key)` : Retrieves the value for a given key. Returns `undefined` if the key doesn't exist.
- `.has(key)` : Checks if a key exists. Returns `true` or `false` .
- `.delete(key)` : Removes a key-value pair.
- `.clear()` : Removes all key-value pairs.

```
const metadata = new Map();
let user1 = { name: "Alice" };
let user2 = { name: "Bob" };

// Set values using objects as keys
metadata.set(user1, { lastLogin: "2023-10-27" });
metadata.set(user2, { lastLogin: "2023-10-26" });

// Get a value using the exact same object reference
console.log(metadata.get(user1)); // { lastLogin: "2023-10-27" }

console.log(metadata.has(user2)); // true
```

4. The `.size` Property

Like `Set` , a `Map` has a `.size` property.

```
console.log(metadata.size); // 2
```

B. Iterating Over a `Map`

A `Map` is also iterable. The best way to loop is with `for...of` and **destructuring**. The items are iterated in **insertion order**.

```
const userMap = new Map([
  ["name", "Alice"],
  ["age", 30]
]);

// Use destructuring to unpack the [key, value] pair
for (const [key, value] of userMap) {
  console.log(`${key} → ${value}`);
}
// Outputs:
// name → Alice
// age → 30
```

You can also use `.keys()`, `.values()`, and `.entries()` to get iterators, or `.forEach()`.

C. Real-World Use Cases (Why use a `Map`?)

1. **Storing Metadata for Objects:** This is the killer use case. You can "attach" data to an object without actually modifying the object itself. This is great for keeping DOM elements clean.

```
const elementData = new Map();
const button1 = document.querySelector("#btn1");

// Associate some metadata with this specific button element
elementData.set(button1, { clicks: 0, lastClickTime: null });

// Now you can store and retrieve data about `button1` without
// ever doing `button1.mydata = ...`, which pollutes the DOM object.
```

2. **High-Performance Caching:** If you have a function that performs a complex calculation, you can use a `Map` to cache the results. The arguments to the function can be the key, and the result can be the value.

3. **When You Need a "Dictionary" with Non-String Keys:** Any time your keys are not simple strings, a `Map` is the correct and only choice.

Use...	When you need...
<code>Object</code>	A simple, fixed set of string-based keys . Great for storing the structure of a single entity (like a <code>user</code>).
<code>Map</code>	A collection of key-value pairs where keys can be of any type , you need to iterate in insertion order, or you need to get the size quickly.

Part 3: Advanced - `WeakSet` and `WeakMap`

First Thought: A "weak" version is a `Map` or `Set` that doesn't prevent its items from being garbage collected.

- A normal `Map` or `Set` holds a **strong reference** to its items. As long as an object is in a `Map`, it will **never be garbage collected**.
- A `WeakMap` or `WeakSet` holds a **weak reference**. If an object is the key in a `WeakMap` and it's the *only* reference left in your entire program, the garbage collector is free to destroy it, and it will be automatically removed from the `WeakMap`.

Use Case: Caching. In the DOM element example above, if you remove `button1` from the page, you want its metadata in the `elementData` map to be automatically deleted to prevent a **memory leak**. If you used a `Map`, the data would stay there forever. If you use a `WeakMap`, it cleans itself up.

Limitations:

- You can only store **objects** in a `WeakSet` or as keys in a `WeakMap` (not primitives).
- You **cannot iterate** over them (because the items could disappear at any moment during the loop). They only have `.has()`, `.get()`, `.set()`, and `.delete()`.