

Day 29 : DOM Manipulation

In-Depth Guide to DOM Manipulation

Once you have selected an element and stored it in a variable, you have a powerful object that gives you full control over that part of your webpage. Let's cover the three main categories of manipulation:

1. **Editing What's Inside (Content & HTML)**
2. **Editing the Tag Itself (Attributes, Classes, and Styles)**
3. **Editing the Page Structure (Creating, Adding, and Removing Elements)**

Part 1: Editing the Content Inside an Element

This is about what the user sees *inside* an element's opening and closing tags.

HTML Snippet for this section:

```
<div id="welcome-box">
  Please log in to see your messages.
</div>
```

```
// We've selected our target element
const welcomeBox = document.getElementById('welcome-box');
```

A. **.textContent** (For Plain Text - The Safe Default)

- **What it does:** Gets or sets the **pure text** content of an element. It ignores and strips out all HTML tags.
- **Use Case:** This should be your **default choice** for changing text on the page.

```
// Reading the text content
console.log(welcomeBox.textContent); // "Please log in to see your message
s."
```

```
// Writing new text content
welcomeBox.textContent = "Welcome back, Alice!";
```

The Security Benefit: When you set `.textContent`, the browser treats your string as plain text. This is **safe** because it prevents malicious code from being executed.

```
// Even if this string came from a hacker...
const maliciousInput = "<script>alert('hacked!');</script>";

welcomeBox.textContent = maliciousInput;
// The browser will LITERALLY display the text: "<script>alert('hacked!');</script>"
// It will NOT run the script.
```

B. `.innerHTML` (For HTML - Powerful but Dangerous)

- **What it does:** Gets or sets the **full HTML markup** inside an element.
- **Use Case:** Use this **only when you need to generate HTML** and the content is from a **trusted source** (i.e., you, the developer).

```
// Let's create a more complex message
const welcomeMessage = `
  <h2>Welcome back, Alice!</h2>
  <p>You have <strong>5</strong> new messages.</p>
`;

// Writing new HTML content
welcomeBox.innerHTML = welcomeMessage;
```

The Security Risk (XSS - Cross-Site Scripting): Never use `.innerHTML` with content provided by a user (like a comment or a username). If a user enters malicious `<script>` code, `.innerHTML` will execute it, allowing the user to attack your website and its visitors.

Part 2: Editing the Element's Tag Itself

This is about changing the attributes of the tag, like its `id`, `class`, or `style`.

HTML Snippet for this section:

```
<div id="profile-pic-container" class="card">
  
</div>
```

```
const profileContainer = document.getElementById('profile-pic-container');
const profileImage = profileContainer.querySelector('img');
```

A. Changing Common Attributes (Direct Properties)

For standard attributes, you can often change them directly as properties on the element object.

```
// Change the image source
profileImage.src = 'images/alice.png';

// Change the alt text for accessibility
profileImage.alt = 'A photo of Alice';

// Change the ID of the container
profileContainer.id = 'user-123-avatar';
```

B. Changing CSS Classes (The `.classList` Toolbox)

This is the **best and safest way** to manage an element's classes. Forget about `.className`.

- `.add('className')` : Adds a new class.
- `.remove('className')` : Removes a class.
- `.toggle('className')` : Adds the class if it's missing, removes it if it's there.
- `.contains('className')` : Checks if an element has a class (returns `true` or `false`).

```
// Let's highlight the profile picture when the user is active
profileContainer.classList.add('is-active'); // Adds the 'is-active' class

// Let's remove the generic 'card' class
profileContainer.classList.remove('card');

// We can toggle a 'selected' state
profileContainer.classList.toggle('selected'); // Adds 'selected'
profileContainer.classList.toggle('selected'); // Removes 'selected'
```

Best Practice: Define your styles in a CSS file and use JavaScript's `.classList` to apply or remove those styles. This keeps your presentation (CSS) and logic (JS) separate.

C. Changing Inline Styles (The `.style` Property)

This allows you to directly apply CSS styles to an element's `style` attribute.

- **CRITICAL RULE:** CSS properties with a hyphen are converted to **camelCase**.
 - `background-color` becomes `backgroundColor`.
 - `font-size` becomes `fontSize`.

```
const profileContainer = document.getElementById('profile-pic-container');

profileContainer.style.border = '2px solid blue';
profileContainer.style.borderRadius = '50%'; // Note the camelCase
profileContainer.style.width = '150px';    // Values must be strings with units
profileContainer.style.height = '150px';
```

Use Case: Best for dynamic styles that are calculated at runtime (e.g., setting an element's position based on the mouse). For static styles, prefer using `.classList`.

Part 3: Editing the Page Structure

This is the most powerful form of DOM manipulation.

A. Creating a New Element: `document.createElement()`

This creates a new element node in memory. It is **not yet on the page**.

```
// Create a new paragraph, but it's just floating in memory.
const newParagraph = document.createElement('p');

// Now, we configure it.
newParagraph.textContent = "This is a brand new paragraph created by Java
Script.";
newParagraph.classList.add('info-text');
```

B. Adding the New Element to the Page

HTML:

```
<div id="parent-container">
  <p id="first-child">First Paragraph</p>
  <p id="reference-element">I am the reference point.</p>
  <p id="last-child">Last Paragraph</p>
</div>
```

JavaScript:

```
// This is the new element we want to add.
const newElement = document.createElement('h2');
newElement.textContent = "I AM THE NEW ELEMENT";

// This is our main reference point for the examples.
const referenceElement = document.getElementById('reference-element');
```

Here are all the different ways you can add `newElement` to the page.

1. Adding Inside a Parent (as a Child)

These methods place the new element *inside* the boundaries of another element.

.append(...nodes) (Modern & Recommended)

- **What it does:** Inserts the node as the **very last child** of the parent.
- **Use Case:** The default way to add an item to the end of a list or container.

```
const parent = document.getElementById('parent-container');  
parent.append(newElement);
```

Resulting HTML:

```
<div id="parent-container">  
  <p id="first-child">...</p>  
  <p id="reference-element">...</p>  
  <p id="last-child">...</p>  
  <h2>I AM THE NEW ELEMENT</h2> <!-- Appended here →  
</div>
```

.prepend(...nodes) (Modern & Recommended)

- **What it does:** Inserts the node as the **very first child** of the parent.
- **Use Case:** Adding a new item to the top of a feed or a list.

```
const parent = document.getElementById('parent-container');  
parent.prepend(newElement);
```

Resulting HTML:

```
<div id="parent-container">  
  <h2>I AM THE NEW ELEMENT</h2> <!-- Prepended here →  
  <p id="first-child">...</p>  
  <p id="reference-element">...</p>  
  <p id="last-child">...</p>  
</div>
```

.appendChild(node) (Classic)

- **What it does:** Same as `append`, but it's the older syntax. It can only add one node at a time and returns the appended node.

```
const parent = document.getElementById('parent-container');
parent.appendChild(newElement); // Same result as append
```

.insertBefore(newNode, referenceNode) (Classic & Powerful)

- **What it does:** Inserts `newNode` into the `parentElement` **right before** the `referenceNode`. This is the classic way to insert into the middle of a list of children.
- **Use Case:** Inserting an element at a specific position in a list.

```
const parent = document.getElementById('parent-container');
const referenceNode = document.getElementById('reference-element');
parent.insertBefore(newElement, referenceNode);
```

Resulting HTML:

```
<div id="parent-container">
  <p id="first-child">...</p>
  <h2>I AM THE NEW ELEMENT</h2> <!-- Inserted before the reference →
  <p id="reference-element">...</p>
  <p id="last-child">...</p>
</div>
```

2. Adding Next to an Element (as a Sibling)

These methods place the new element *outside* the boundaries of the reference element, at the same level in the DOM tree.

.after(...nodes) (Modern & Recommended)

- **What it does:** Inserts the node **immediately after** the reference element, as its next sibling.
- **Use Case:** Adding a new element directly following another one.

```
const referenceElement = document.getElementById('reference-element');
referenceElement.after(newElement);
```

Resulting HTML:

```
<div id="parent-container">
  <p id="first-child">...</p>
  <p id="reference-element">...</p>
  <h2>I AM THE NEW ELEMENT</h2> <!-- Inserted here, as a sibling →
  <p id="last-child">...</p>
</div>
```

.before(...nodes) (Modern & Recommended)

- **What it does:** Inserts the node **immediately before** the reference element, as its previous sibling.
- **Use Case:** Adding a new element directly preceding another one.

```
const referenceElement = document.getElementById('reference-element');
referenceElement.before(newElement);
```

Resulting HTML:

```
<div id="parent-container">
  <p id="first-child">...</p>
  <h2>I AM THE NEW ELEMENT</h2> <!-- Inserted here, as a sibling →
  <p id="reference-element">...</p>
  <p id="last-child">...</p>
</div>
```

.insertAdjacentElement(position, element) (The Most Versatile)

- **What it does:** This is a highly flexible method that can do the job of all the others. You specify a `position` relative to the target element and the `element` to insert.

- **The Four Positions:**

1. `'beforebegin'` : Inserts the new element as a sibling, right before the target element (same as `.before()`).
2. `'afterbegin'` : Inserts the new element as the first child of the target element (same as `.prepend()`).
3. `'beforeend'` : Inserts the new element as the last child of the target element (same as `.append()`).
4. `'afterend'` : Inserts the new element as a sibling, right after the target element (same as `.after()`).

Example (replicating `.after()`):

```
const referenceElement = document.getElementById('reference-element');
referenceElement.insertAdjacentElement('afterend', newElement);
```

Example (replicating `.prepend()`):

```
const parent = document.getElementById('parent-container');
// Note: we are calling this on the parent to insert AS A CHILD
parent.insertAdjacentElement('afterbegin', newElement);
```

There is also a related method, `.insertAdjacentHTML()` , which works like `.innerHTML` for these specific positions, but it carries the same security risks.

Summary Table: Which Method to Use?

Goal	Best Modern Method	Classic Method
Add as the LAST child	<code>parent.append(el)</code>	<code>parent.appendChild(el)</code>
Add as the FIRST child	<code>parent.prepend(el)</code>	<code>parent.insertBefore(el, parent.firstChild)</code>
Add BEFORE another element	<code>referenceEl.before(el)</code>	<code>parent.insertBefore(el, referenceEl)</code>
Add AFTER another element	<code>referenceEl.after(el)</code>	<code>parent.insertBefore(el, referenceEl.nextElementSibling)</code>

Recommendation: Stick to the modern methods (`append` , `prepend` , `before` , `after`) whenever possible. They are more intuitive, more flexible (can handle multiple nodes and text), and cover almost every use case you will encounter. Use `insertBefore` when you need to support older browsers or have a specific reference node to insert before.

C. Removing an Element

- `.remove()` : The simplest and most modern way. You call it directly on the element you want to remove.

```
// Let's say we want to remove the profile image.  
const profileImage = document.querySelector('#user-123-avatar img');  
  
// First, check if the element was actually found before trying to remove it.  
if (profileImage) {  
  profileImage.remove(); // The image is now gone from the page.  
}
```

This comprehensive set of tools (`.textContent` , `.classList` , `.style` , `createElement` , `append` , `remove`) gives you everything you need to transform a static HTML page into a fully dynamic application.

Optimization

The First Thought:

"Every time I touch the live webpage, it's expensive. I should do all my work 'offline' on a temporary, invisible scratchpad, and then attach the finished result

to the live page in one single, efficient step."

That "invisible scratchpad" is a `DocumentFragment`.

The Problem: The High Cost of Touching the "Live" DOM

The DOM that is visible on the webpage is "live." Every time you change it—by appending a child, changing a style that affects size, etc.—you force the browser to do work.

1. **DOM Update:** The element is added to the tree.
2. **Reflow/Layout:** The browser may have to recalculate the position and size of many elements on the page.
3. **Repaint:** The browser has to repaint the pixels for the updated part of the screen.

Now, imagine you need to add **1,000** items to a list.

The Inefficient "Bad" Way:

This code touches the live DOM in a loop.

```
const list = document.getElementById('my-list'); // This is a "live" DOM element.

// START THE TIMER
console.time("Loop without fragment");

for (let i = 0; i < 1000; i++) {
  const newItem = document.createElement('li');
  newItem.textContent = `Item ${i + 1}`;

  // This is the expensive part. We are modifying the live DOM 1,000 times.
  // This can cause up to 1,000 separate reflows and repaints.
  list.appendChild(newItem);
}
```

```
// STOP THE TIMER
console.timeEnd("Loop without fragment");
```

If you run this, you might notice a brief stutter or freeze in the browser. You are forcing the browser to do a massive amount of repetitive work. Each `appendChild` is a separate transaction with the rendering engine.

The Solution: The `DocumentFragment`

A `DocumentFragment` is a **lightweight, in-memory DOM node that is not part of the main document tree**. It's a temporary, invisible container.

- It has the same API as a regular element: you can `.appendChild()` or `.append()` to it.
- The key difference: Modifying a `DocumentFragment` is **extremely cheap**. Since it's not part of the visible page, changing it **does not trigger any reflows or repaints**.

The Efficient "Good" Way:

This code does all the heavy lifting "offline" and then updates the live DOM only once.

```
const list = document.getElementById('my-list');

// START THE TIMER
console.time("Loop WITH fragment");

// 1. Create the invisible "scratchpad".
const fragment = document.createDocumentFragment();

// 2. Do all your work on the scratchpad.
// This loop is now very fast because it's only changing things in memory,
// not on the visible page.
for (let i = 0; i < 1000; i++) {
  const newItem = document.createElement('li');
  newItem.textContent = `Item ${i + 1}`;

  // We append to the fragment, not the live list.
```

```

fragment.appendChild(newItem);
}

// 3. Now, attach the entire finished result to the live DOM in ONE single operation.
list.appendChild(fragment); // This causes only ONE reflow and repaint!

// STOP THE TIMER
console.timeEnd("Loop WITH fragment");

```

If you run both of these code blocks, you will see that the version using the `DocumentFragment` is significantly faster.

The "Magic" of Appending a Fragment

When you append a `DocumentFragment` to another node, a special thing happens:

- The `DocumentFragment` itself is **not** added to the DOM tree.
- Instead, all of the **children** of the fragment are moved into the target element.
- The `DocumentFragment` is left empty.

This makes it a perfect, single-use container for batching DOM updates.

Summary

Feature	<code>DocumentFragment</code>
What is it?	An in-memory, "offline" DOM container.
Why use it?	To batch multiple DOM updates (adds, moves) into a single operation.
The Benefit	Dramatically improves performance by minimizing the number of expensive reflows and repaints .
How to use it?	1. <code>document.createDocumentFragment()</code> . 2. Append all your new elements to the fragment in a loop. 3. Append the single fragment to the live DOM element.
When should I use it?	Always use a <code>DocumentFragment</code> when you need to add a large number of elements to the DOM in a loop.