

Fully implicit, finite-differences resolution of variably saturated flow in 1D with Python.

23 mai 2014

1 Soil hydraulic properties

In unsaturated conditions, water content θ can be expressed with the closed-form equation provided by [Van Genuchten \[1980\]](#) :

$$\theta(h) = \theta_r + (\theta_s - \theta_r) (1 + |\alpha h|^n)^{-m} \quad (1)$$

where θ_r , θ_s , α and n are soil characteristics and $m = 1 - 1/n$. h [L] is pressure head, counted as negative in unsaturated conditions. For any $h > 0$, $\theta(h) = \theta_s$.

The derivative of Eq. 1 with respect to h reads :

$$\frac{d\theta}{dh}(h) = mn\alpha^n h^{n-1} (\theta_s - \theta_r) (1 + |\alpha h|^n)^{-m-1} \quad (2)$$

Though apparently different, this expression is equivalent to Eq. 23 in [Van Genuchten \[1980\]](#). The derivative was obtained with the condition $h < 0$.

Following [Van Genuchten \[1980\]](#), the relative permeability K_r is expressed as follows [[Van Genuchten, 1980](#)] :

$$K_r(h) = \frac{(1 - |\alpha h|^{n-1} (1 + |\alpha h|^n)^{-m})^2}{(1 + |\alpha h|^{m/2})} \quad (3)$$

2 Model implementation

We consider the mixed-form equation for variably saturated flow proposed by [Celia et al. \[1990\]](#) and modified by [Clement et al. \[1994\]](#) :

$$S_s \frac{\theta}{\eta} \frac{\partial h}{\partial t} + \frac{\partial \theta}{\partial t} = \frac{\partial}{\partial z} \left(-K(\theta) \frac{\partial H}{\partial z} \right) + q \quad (4)$$

where S_s [L⁻¹] is the specific storage, H [L] is the hydraulic head, θ [-] is the water content, η [-] is the porosity, K [LT⁻¹] is the hydraulic conductivity and q [T⁻¹] the source term. Contrary to the original Richards' equation, Eq. 4 accounts for the effect of specific storage, which makes it valid for transient saturated flow.

The hydraulic head is defined by $H = h + z$, where h is the pressure head and z the coordinate along the (Oz) vertical upward axis. Eq. 4 yields :

$$S_s \frac{\theta}{\eta} \frac{\partial h}{\partial t} + \frac{\partial \theta}{\partial t} = \frac{\partial}{\partial z} \left(K \frac{\partial h}{\partial z} \right) + \frac{\partial K}{\partial z} \quad (5)$$

Spatial derivation is obtained with a central differences scheme as follows :

$$\begin{aligned} \frac{\partial}{\partial z} \left(K \frac{\partial h}{\partial z} \right) + \frac{\partial K}{\partial z} \approx & \frac{1}{dz} \left\{ \left(\frac{K_i^{n+1,m} + K_{i+1}^{n+1,m}}{2} \right) \left(\frac{h_{i+1}^{n+1,m+1} - h_i^{n+1,m+1}}{dz} \right) \right. \\ & - \left. \left(\frac{K_i^{n+1,m} + K_{i-1}^{n+1,m}}{2} \right) \left(\frac{h_i^{n+1,m+1} - h_{i-1}^{n+1,m+1}}{dz} \right) \right\} \\ & + \frac{1}{dz} \left(\left(\frac{K_i^{n+1,m} - K_{i+1}^{n+1,m}}{2} \right) - \left(\frac{K_i^{n+1,m} + K_{i-1}^{n+1,m}}{2} \right) \right) \end{aligned} \quad (6)$$

where n denotes the n th discrete time level, when the solution is known, dt is the time step, K_i is the value of hydraulic conductivity at the i th node and h_i the value of pressure head at the i th node. The current and previous Picard iteration are denoted as $m + 1$ and m , respectively.

A backward finite-difference expression is used for temporal derivative :

$$S_s \frac{\theta}{\eta} \frac{\partial h}{\partial t} \approx \frac{S_s}{\eta} \theta_i^{n+1,m} \left(\frac{h_i^{n+1,m+1} - h_i^n}{dt} \right) \quad (7)$$

After [Celia et al. \[1990\]](#) and [Clement et al. \[1994\]](#), time derivative of water content is approximated as follows :

$$\frac{\partial \theta}{\partial t} \approx \left(\frac{\theta_i^{n+1,m} - \theta_i^n}{dt} \right) + C_i^{n+1,m} \left(\frac{h_i^{n+1,m+1} - h_i^{n+1,m}}{dt} \right) \quad (8)$$

where C is the derivative of the water content with respect to the pressure head (Eq. 2)

Eqs. 6, 7 and 8 can be re-arranged to form a system of linear algebraic equations :

$$m_1 h_{i-1}^{n+1,m+1} + m_2 h_i^{n+1,m+1} + m_3 h_{i+1}^{n+1,m+1} = -b_1 h_i^{n+1,m} - b_2 h_i^n + b_3 + b_4 \quad (9)$$

with :

$$m_1 = \left(\frac{K_i^{n+1,m} + K_{i-1}^{n+1,m}}{2dz^2} \right) \quad (10)$$

$$m_3 = \left(\frac{K_i^{n+1,m} + K_{i+1}^{n+1,m}}{2dz^2} \right) \quad (11)$$

$$b_1 = \frac{C_i^{n+1,m}}{dt} \quad (12)$$

$$b_2 = \frac{S_s \theta_i^{n+1,m}}{\eta dt} \quad (13)$$

$$b_3 = - \left(\frac{K_{i-1}^{n+1,m} - K_{i+1}^{n+1,m}}{2dz} \right) \quad (14)$$

$$b_4 = \left(\frac{\theta_i^{n+1,m} - \theta^n}{dt} \right) \quad (15)$$

$$m_2 = -(m_1 + m_3 + b_1 + b_2) \quad (16)$$

The following system should then be solved iteratively :

$$\mathbf{M}^{n+1,m} \mathbf{h}^{n+1,m+1} = \mathbf{B}^{n+1,m} \quad (17)$$

where \mathbf{M} is a sparse matrix containing in its central diagonals the coefficients m_1, m_2, m_3 and vector \mathbf{B} gather the second member of Eq. 9.

The resolution of the system is obtained with the Python `scipy.sparse.cg` function.

3 Boundary conditions

We consider a soil column subject to infiltration at the top. The boundary condition at the bottom is either a fixed-head or free drainage.

3.1 Fixed pressure head

For a fixed pressure head boundary condition at the **bottom** of the column, the boundary condition is expressed as follows :

$$h_1^{n+1,m} = h_{bot}^{n+1} \quad (18)$$

where h_{bot} is the value of the imposed pressure head at $t = t_{n+1}$. On the left side of Eq. 9, we have $m_1 = m_3 = 0$ and $m_2=1$. The right side of Eq. 9 is h_{bot}^{n+1} .

Similarly, for a fixed pressure head boundary condition at the **top** of the column, the boundary condition is expressed as follows :

$$h_I^{n+1,m} = h_{top}^{n+1} \quad (19)$$

where h_{top} is the value of the imposed pressure head at $t = t_{n+1}$. On the left side of Eq. 9, we have $m_1 = m_3 = 0$ and $m_2=1$. The right side of Eq. 9 is h_{top}^{n+1} .

3.2 Fixed flow

With a flux q_z [LT^{-1}] imposed to one of the boundaries of the soil column, Darcy law yields :

$$\begin{aligned} q_z = -K \frac{\partial H}{\partial z} &\iff q_z = -K \left(\frac{\partial h}{\partial z} + 1 \right) \\ &\iff \frac{\partial h}{\partial z} = -\frac{q_z}{K} - 1 \end{aligned} \quad (20)$$

If the flux q_{top} is imposed to the **bottom** of the column, Eq. 20 yields :

$$h_0 = h_1 + \frac{q_{bot}}{K_1} + 1 \quad (21)$$

where h_0 is pressure head at a virtual node out of the system. Inserting Eq. 21 into Eq. 9 yields :

$$(m_1+m_2)h_1^{n+1,m+1}+m_3h_2^{n+1,m+1} = -b_1h_1^{n+1,m}-b_2h_1^n+b_3+b_4+m_3dz \left(\frac{q_{bot}}{K_1} + 1 \right) \quad (22)$$

In turn, if the flux q_{top} is imposed to the **top** of the column, Eq. 20 yields :

$$h_{I+1} = h_I - \frac{q_{top}}{K_I} - 1 \quad (23)$$

where I is the total number of nodes and h_{I+1} is a virtual node out of the system. Inserting Eq. 23 into Eq. 9 yields :

$$m_1h_{I-1}^{n+1,m+1}+(m_2+m_3)h_I^{n+1,m+1} = -b_1h_I^{n+1,m}-b_2h_I^n+b_3+b_4-m_1dz \left(\frac{q_{top}}{K_I} + 1 \right) \quad (24)$$

Note that infiltration into the soil column is simulated with a negative q_{top} .

No flow boundary condition is a special case of the fixed flow boundary condition with $q_z = 0$.

3.3 Free drainage at the bottom of the column

Free drainage is expressed with a unit vertical hydraulic head gradient :

$$\begin{aligned}
\frac{\partial H}{\partial z} = 1 &\iff \frac{\partial}{\partial z}(z + h) = 1 \\
&\iff \frac{\partial h}{\partial z} = 0 \\
&\iff \frac{(h_1 - h_0)}{dz} = 0 \\
&\iff h_0 = h_1
\end{aligned} \tag{25}$$

Where h_0 is pressure head at a virtual node out of the system. In these conditions, Eq. 9 becomes :

$$(m_1 + m_2)h_1^{n+1,m+1} + m_3h_2^{n+1,m+1} = -b_1h_1^{n+1,m} - b_2h_1^n + b_3 + b_4 \tag{26}$$

4 Runoff estimation

When the rainfall rate exceeds the soil infiltration capacity, a pounding condition occurs at the top of a plane terrain. In time, the pounded water will infiltrate to the soil. Contrary, on sloping terrains the pounding condition is negligible while water is loss as runoff. Following [Herrada et al. \[2014\]](#), the pounding condition is reached when the upper soil surface saturates. A transient *fixed flow* is prescribed at the upper boundary [[Herrada et al., 2014](#)] :

$$In_n \equiv q(I, n) \equiv q_{rainfall} \equiv q_{top} \tag{27}$$

where In_n is the infiltration rate. According to [Herrada et al. \[2014\]](#), this condition applies when $\theta(I, n) < \theta_s$, if $\theta(I, n)$ reaches saturation, the boundary condition in Eq. 28 is replaced by $\theta(I, n) = \theta_s$. In our case, as we use the mixed form of the Richard's equation, our boundary conditions are different and the system resolution complex. Following the approach of [Herrada et al. \[2014\]](#), we use the saturation condition from the pressure head h to modify the upper boundary condition. When $h_I^{n+1} < 0$, the upper boundary condition is the Eq. 24. In the case where $h_I^{n+1} \geq 0$, the fixed flux upper boundary

condition switches to a fixed head condition (Eq. 19), where $h_{top}^{n+1} = 0$. On this scenario, the linear system is resolved again with the new conditions to obtain h^{n+1} . If we solve the Eq. 24 for q_{top} using $h_I^{n+1,m} = h_I^{n+1,m+1} = 0$ (a valid assumption after h_I^{n+1} is already known), Eq. 24 yields :

$$In = q_{top} = K \left[\frac{(m_1 h_{I-1}^{n+1} + b_2 h_{I-1}^n - b_3 - b_4)}{(m_3 dz)} - 1 \right] \quad (28)$$

where h_{I-1} is obtained from the solution of the linear system with the new conditions. Finally, surface runoff is calculated as [Herrada et al., 2014] :

$$q_{runoff} = q_{rainfall} - In \quad (29)$$

5 Root water uptake and actual transpiration

Root water uptake from the soil is used by the plants for transpiration purposes. Total potential transpiration is calculated independently and it is redistributed over the soil profile as follows :

$$S_p = b(z)T_p \quad (30)$$

where S_p [T^{-1}] is the potential water uptake rate in a soil unit, T_p [LT^{-1}] is the total potential transpiration rate and $b(z)$ is the normalized water uptake distribution [L^{-1}]. We considered two types of the $b(z)$ functions :

- Equally distributed over the root zone :

$$b(z) = \frac{1}{L_R} \quad (31)$$

- Using the function proposed by Hoffman and Van Genuchten [1983] similar to a trapezoid :

$$b(z) = \begin{cases} \frac{1.667}{L_R} & x \geq L - 0.2L_R \\ \frac{2.0833}{L_R} \left(1 - \frac{L-z}{L_R}\right) & L - L_R < z < L - 0.2L_R \\ 0 & x \leq L - L_R \end{cases} \quad (32)$$

where L is the soil depth and L_R is the root zone depth which is assumed constant. The water uptake rate is related to the available water in the soil unit. When not enough water is available, the potential rate cannot

be achieved. The actual water uptake is defined by *Feddes et al. [1978]* as follows :

$$S = \alpha(h)S_p \quad (33)$$

where S [T^{-1}] (known in Eq. 4 as q) is the actual water uptake and $\alpha(h)$ is a dimensionless stress response function. We used this function related to the water content instead of the pressure head and followed the approach proposed by *Food and Agriculture Organization of the United Nations [1998]* modified to soil units :

$$\alpha(\theta) = \begin{cases} 1 & \theta \geq \theta_{RWC} \\ \frac{\theta - \theta_{WP}}{\theta_{RAW}} & \theta_{WP} < \theta < \theta_{RWC} \\ 0 & \theta \leq \theta_{WP} \end{cases} \quad (34)$$

where θ_{wp} is the water content of the soil unit at the *wilting point* and θ_{RWC} is the readily extracted water content of the soil unit by the roots, obtained with the equation :

$$\theta_{RWC} = \rho(\theta_{FC} - \theta_{WP}) \quad (35)$$

where θ_{FC} is the water content of the soil unit at the *field capacity*, and ρ is the average fraction of the available extracted water content of the soil unit that can be depleted before moisture stress, and its usually 0.5 for many crops. Finally the actual transpiration rate T_p [LT^{-1}] is calculated with the following equation :

$$T_p = \sum_{i=1}^I \alpha(\theta)b(z)T_p \quad (36)$$

Note that T_p in Eq. 36 do not consider the effect of osmotic stress by the soil salinity nor the compensation by the root adaptability to increase the uptake from other parts when moisture stress occurs.

6 Time Step Optimization

The *time discretization* is associated to the the input time data related to the boundary conditions and the source term, and to the numerical solution. The *time steps* are variable and are calculated automatically by the program in order to reduce the computational time and induce stability to the calculations. We used the same approach used by *Simunek et al. [2013]*. The first time level is the prescribed initial time increment (Δt) from the input data. Then, Δt is automatically modify at each time level as follows

[Simunek et al., 2013] :

$$\Delta t^{n+1} = \begin{cases} 1.3\Delta t^n & M \leq 3 \\ \Delta t^n & 3 < M \leq 7 \\ 0.7\Delta t^n & 7 < M < M_{max} \\ \Delta t^n/3 & M = M_{max} \end{cases} \quad (37)$$

where, M is the number of iteration required to reach coverage at a particular time level and M_{max} is the prescribed maximum iteration number. Eventhough Δt is calculated using Eq. 37, it can be modified in order to coincide with the prescribed time levels in the input data, and to be in the range $[t_{min}, t_{max}]$, where t_{min} and t_{max} are prescribed values.

Références

- Celia, M. A., E. T. Bouloutas, and R. L. Zarba, A general mass-conservative numerical solution for the unsaturated flow equation, *Water resources research*, 26(7), 1483–1496, 1990.
- Clement, T., W. R. Wise, and F. J. Molz, A physically based, two-dimensional, finite-difference algorithm for modeling variably saturated flow, *Journal of Hydrology*, 161(1), 71–90, 1994.
- Feddes, R. A., P. J. Kowalik, and H. Zaradny, *Simulation of field water use and crop yield*, Centre for Agricultural Pub. and Documentation, Wageningen, 1978.
- Food and Agriculture Organization of the United Nations, *Crop evapotranspiration : guidelines for computing crop water requirements*, no. 56 in FAO irrigation and drainage paper, Food and Agriculture Organization of the United Nations, Rome, 1998.
- Herrada, M. A., A. Gutiérrez, and J. M. Montanero, Modeling infiltration rates in a saturated/unsaturated soil under the free draining condition, *Journal of Hydrology*, doi :10.1016/j.jhydrol.2014.04.026, 2014.
- Hoffman, G. J., and M. T. Van Genuchten, Soil properties and efficient water use : Water management for salinity control, *Limitations to Efficient Water Use in Crop Production*, *acsesspublicati*(limitationstoef), 73–85, 1983.

Simunek, J., M. Sejna, H. Saito, M. Sakai, and M. T. Van Genuchten, *The HYDRUS-1D software package for simulating the one-dimensional movement of water, heat, and multiple solutes in variably-saturated media*, Version 4.16, department of environmental sciences ed., University of California Riverside, Riverside, California, 2013.

Van Genuchten, M. T., A closed-form equation for predicting the hydraulic conductivity of unsaturated soils, *Soil Science Society of America Journal*, 44 (5), 892–898, 1980.