
Table of Contents

hw2_me501_Q2c.m	1
Setup: constants and initial conditions	1
Simulate to obtain trajectory - Numerical, approximated!	1
Exact Solution for comparison	2
Simulate as a discrete time linear system	2
Plot	3

hw2_me501_Q2c.m

(C) Andrew Sabelhaus, 2026

```
clear all;
close all;
clc;
```

```
disp('ME 501 HW2 simulation of pneumatic chambers dynamics, comparison
between MATLABs eig() output versus the eigenvectors and values found by
hand.')
```

*ME 501 HW2 simulation of pneumatic chambers dynamics, comparison between
MATLABs eig() output versus the eigenvectors and values found by hand.*

Setup: constants and initial conditions

```
tmax = 5;
dt = 0.05;
```

```
n = tmax/dt; % number of timesteps, for loop-ing
% somehow matlab doesn't round correctly. sometimes...
n = round(n);
```

```
% The matrix for our linear dynamics is
A = [-3  1  0;
      1 -2  1;
      0  1 -3];
```

```
%%%% Initial conditions:
```

```
p1_0 = 5;
p2_0 = 0;
p3_0 = 50;
x0 = [p1_0; p2_0; p3_0];
```

Simulate to obtain trajectory - Numerical, approximated!

```
% insert our initial condition as the 1st element in traj
% note that traj will have n+1 columns.
```

```
x_traj = zeros(size(x0,1), n+1);
x_traj(:,1) = x0;

% actual simulation! Use Forward Euler for now.
for t=1:n
    %%%% DYNAMICS
    bolddotx_t = A*x_traj(:,t);
    % Forward Euler
    x_traj(:,t+1) = x_traj(:,t) + dt*bolddotx_t;
end
```

Exact Solution for comparison

```
% The matrix of eigenvectors (V) and its inverse (V^-1) for this A, via
% matlab's calculation:
[V, D] = eig(A);

% The convenient MATLAB command here is:
Vinv = inv(V);

% let's precalculate for a one-to-one comparison
x_traj_exact = zeros(size(x0,1), n+1);
x_traj_exact(:,1) = x0;

% precalculate via iteration
for k=1:n
    % The exact solution is  $x(t) = e^{(At)}x_0 = V e^{(Dt)} V^{-1} * x_0$ 
    % Since "t" is inside the exponential, need to re-call this function
    % each iteration.
    t = k*dt; % here, k is index, dt is timestep, so total time is t.
    %%%% Using our eigenvector-eigenvalue decomposition:
    % Please arrange the eigenvalues in D from greatest to least, matching
    % the order of the columns in V.
    eDt = [exp(-4*t), 0, 0;
           0, exp(-3*t), 0;
           0, 0, exp(-1*t)];
    eAt = V*eDt*Vinv;
    x_traj_exact(:,k+1) = eAt*x0;
end
```

Simulate as a discrete time linear system

```
% Our claim is that  $x(k) = A_d^k x(0)$ , where  $A_d = e^{(A*\Delta T)}$ 
A_d = expm(A*dt);


% let's precalculate for a one-to-one comparison
x_traj_d = zeros(size(x0,1), n+1);
x_traj_d(:,1) = x0;

% the iteration is even simpler now!
for k=1:n
    x_traj_d(:,k+1) = A_d^k * x0;
    % For your own experiment: try this one out, you should get the same
```

```
% result! Can you reason out why that will happen, using linear
% algebra?
% x_traj_d(:,k+1) = A_d * x_traj_d(:,k);
end
```

Plot

```
% We can also plot the three time series trajectories of theta, dottheta,
% and u
figure;
hold on;
t = [0:dt:tmax];
subplot(3,1,1);
sgtitle('Trajectories of states');
% pressure 1
plot(t, x_traj(1,:), 'r');
hold on;
plot(t, x_traj_exact(1,:), 'b')
plot(t, x_traj_d(1,:), 'g')
legend(['Fwd Euler', 'Exact Soln via MATLAB eig()', 'Discretized System']);
xlabel('time (sec)');
ylabel('pressure 1 (Pa)');
% pressure 2
subplot(3,1,2);
plot(t, x_traj(2,:), 'r');
hold on;
plot(t, x_traj_exact(2,:), 'b')
plot(t, x_traj_d(2,:), 'g')
legend(['Fwd Euler', 'Exact Soln via MATLAB eig()', 'Discretized System']);
xlabel('time (sec)');
ylabel('Pressure 2 (Pa)');
% pressure 3
subplot(3,1,3);
plot(t, x_traj(3,:), 'r');
hold on;
plot(t, x_traj_exact(3,:), 'b')
plot(t, x_traj_d(3,:), 'g')
legend(['Fwd Euler', 'Exact Soln via MATLAB eig()', 'Discretized System']);
xlabel('time (sec)');
ylabel('Pressure 3 (Pa)');
```



Published with MATLAB® R2026a