

Particle Filter Segmentation

Vienna, Austria, July 2012


Zoltán Bárdosi

Donatella Granata

Gabor Lugos

Ahmad Pahlavan Tafti

Sanjay Saxena





Outline

- Introduction

- Model

 - ▣ Generative Shape model

- Training

 - ▣ Random forest

- Fitting


 - ▣ Cost Function

- Results



Introduction


S
h
a
p
e



Annotated
Shape Contour

PCA

m
o
d
e
l




Generative
shape model




Introduction

S
h
a
p
e




Annotated
Shape Contour

PCA



Generative
shape model


m
o
d
e
l





Introduction


S
h
a
p
e



Annotated
Shape Contour

PCA

m
o
d
e
l




Generative
shape model




Introduction

S
h
a
p
e



Annotated
Shape Contour


PCA




Generative
shape model

B
o
u
n
d
a
r
y

Haar-like
Features




f
e
a
t
u
r
e
s






Introduction

S
h
a
p
e



Annotated
Shape Contour


PCA




Generative
shape model

B
o
u
n
d
a
r
y

Haar-like
Features




f
e
a
t
u
r
e
s



F
i
t
t
i
n
g




Probability
map





Shape Model



Landmarks are derived from this manually annotated image contours.

$$v_i = \begin{bmatrix} l_{11} & l_{12} & \dots & l_{1d} \\ l_{21} & & & l_{2n} \\ \vdots & & & \vdots \\ l_{n1} & l_{n2} & \dots & l_{nd} \end{bmatrix}$$

$\forall i \in \{1, \dots, N_s\}$ annotated shapes
for d-dimensional landmarks

The training set is then aligned using Procrustes Analysis, which minimizes

$\sum (v_i - \bar{v})^2$ where \bar{v} is the mean of all vectors,
i. e. the mean of the shape



m=number of samples (i.e 50)

nd=nd denotes the number of landmarks
(i.e. n=64 and d=2)

$$\forall i \in \{1, \dots, nd\} \quad \text{normalized data set (with zero mean)}$$
$$A_i = A_i - \bar{A}_i \quad \text{where} \quad \bar{A}_i \quad \text{is the mean of each dimension or column}$$



Principal Component Analysis

$$\begin{bmatrix} S_1 \\ S_2 \\ \vdots \\ S_m \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} & \cdots & A_{nd} \\ A_{21} & & & A_{nd} \\ \vdots & & & \vdots \\ A_{m1} & A_{m2} & \cdots & A_{m(nd)} \end{bmatrix}$$

A

Normalization is crucial for PCA to assure that the data is centered around the origin, otherwise a wrong direction for the eigenvectors is calculated.


$\forall i \in \{1, \dots, nd\}$ normalized data set (with zero mean)

$A_i = A_i - \bar{A}_i$ where \bar{A}_i is the mean of each dimension or column



Principal Component Analysis


The eigenvector with the largest eigenvalue of the covariance matrix of the data is the data set's principle component.






Principal Component Analysis

The eigenvector with the largest eigenvalue of the covariance matrix of the data is the data set's principle component.





Input and mean shapes





Generative Shape Model

To generate new shapes v .

The actual point distribution model is built by applying PCA.

on $V = (V_1, \dots, V_{N_s})$ yielding eigenvectors $e_1, \dots, e_{\hat{e}}$ with $e_{\hat{e}} = \min(nd, N_s)$

Excluding the modes with small variance $e < \hat{e}$

Any shape v within the subspace spanned by the training set can be represented by:

$$v \approx \bar{v} + Eb$$



Generative Shape Model

To generate new shapes v .

The actual point distribution model is built by applying PCA.

on $V = (V_1, \dots, V_{N_s})$ yielding eigenvectors $e_1, \dots, e_{\hat{e}}$ with $e_{\hat{e}} = \min(nd, N_s)$

Excluding the modes with small variance $e < \hat{e}$

Any shape v within the subspace spanned by the training set can be represented by:

$$v \approx \bar{v} + Eb$$

shape within subspace



Generative Shape Model

To generate new shapes v .

The actual point distribution model is built by applying PCA.

on $V = (V_1, \dots, V_{N_s})$ yielding eigenvectors $e_1, \dots, e_{\hat{e}}$ with $e_{\hat{e}} = \min(nd, N_s)$

Excluding the modes with small variance $e < \hat{e}$

Any shape v within the subspace spanned by the training set can be represented by:

$$v \approx \bar{v} + Eb$$

shape within subspace

basis of the eigenspace



Generative Shape Model

To generate new shapes v .

The actual point distribution model is built by applying PCA.

on $V = (V_1, \dots, V_{N_s})$ yielding eigenvectors $e_1, \dots, e_{\hat{e}}$ with $e_{\hat{e}} = \min(nd, N_s)$

Excluding the modes with small variance $e < \hat{e}$

Any shape v within the subspace spanned by the training set can be represented by:

$$v \approx \bar{v} + Eb$$

shape within subspace

basis of the eigenspace

defines the parameters
for the deformable model



Generative Shape Model

To generate new shapes v .

The actual point distribution model is trained on the training set $V = (V_1, \dots, V_{N_s})$ yielding N_s modes being responsible for the highest variation, in descending order

Excluding the modes with small

Any shape v within the subspace spanned by the training set can be represented by:

$$v \approx \bar{v} + Eb$$


shape within subspace

basis of the eigenspace

defines the parameters
for the deformable model





New shape example






New shape example







Haar-like features





Haar-like features: two rectangle

**The difference between the
sum of pixels
within two rectangular regions**



The region have the same size and shape
And are horizontally or vertically adjacent




Integral Image

$$ii(x, y) = \sum_{x' \leq x, y' \leq y} i(x', y'),$$

original image

integral image




$$s(x, y) = s(x, y - 1) + i(x, y)$$

$$ii(x, y) = ii(x - 1, y) + s(x, y)$$

1 ➡ A
2 ➡ A + B
3 ➡ A + C
4 ➡ A + B + C + D

Calculating any
rectangle
sum with integral
image



Rectangle Sum
 $D = 4 - 3 - 2 + 1$



Random Forest Classification

- Build many decision trees
- Train each tree on a different subset of training data (bagging)
- At each tree node, split the data based on a different subset of features.
- Evaluate each tree using “out-of-bag” data (i.e., data not used to train tree).
- Aggregate results over all trees



Random Forest Classification

```
>> t= treBagger(32, X, Y);
```

predictors



P_1
 P_2
 P_3
 \vdots
 P_{12}
 P_{13}
 P_{14}
 \vdots
 P_{30}
 P_{31}
 P_{32}

```
>> [Y_pred, allpred]=predict(t,X_new);
```

response

\bar{p}





Cost function

2 translation coeffs

2 scaling coeffs


$$x = [b_1, \dots, b_8, t_x, t_y, r, s_1, s_2] \quad x \in R^{13}$$

8 PCA comps

1 rotation param

$$f(x) = 1 - \frac{\sum_{p_i \in \text{shape}(x)}^n p_i}{n}$$



$$\min_{x \in R^{13}} f(x)$$






Differential Evolution

- DE is an extension of classical GA algorithms
- It works with a set of candidate solutions (population).
- It uses a nature inspired search operator.
 - Mutation
 - Crossover
 - Selection
- It is dependent on the problem that we need to solve.






Results:







Results: Landmarks MSE





Results: Landmarks MSE





Thanks for your attention!!
Danke für Ihre Aufmerksamkeit!!
Köszönjük a figyelmet!!
आपका ध्यान के लिए धन्यवाद !!
!! با تشکر از توجه شما
Grazie per l'attenzione !!