

NAME

transmission-gtk — a bittorrent client

SYNOPSIS

transmission-gtk -?
transmission-gtk [**-pqm**] [*torrent-file* . . .]

DESCRIPTION

transmission-gtk is a fast and easy BitTorrent client.

BitTorrent is a peer-to-peer file transfer protocol which uses a metainfo file (usually with the .torrent file extension) and a central tracker to distribute file data amongst a group of peers. For more information on the BitTorrent protocol see <http://www.bittorrent.org/>

OPTIONS

-? **--help**
Show help options

-p **--paused**
Start with all torrents paused

-m **--minimized**
Start minimized in notification area

-g, **--config-dir***directory*
Where to look for configuration files. This can be used to swap between using the cli, daemon, gtk, and qt clients. See <https://github.com/transmission/transmission/wiki/Configuration-Files> for more information.

Multiple .torrent files may be added at startup by appending them on the command line. If **transmission-gtk** is already running, the torrents will be added to the running instance.

ENVIRONMENT

TRANSMISSION_HOME
Sets the default config-dir.

http_proxy
libcurl uses this environment variable when performing tracker announces. If set, this overrides the GNOME proxy preferences.

FILES

~/config/transmission
The config-dir used when neither **[TRANSMISSION_HOME]** nor **[-g]** is specified.

AUTHORS

transmission-gtk was written by Charles Kerr, Josh Elsasser, Eric Petit, Mitchell Livingston, and Mike Gelfand.

SEE ALSO

transmission-create(1), **transmission-daemon(1)**, **transmission-edit(1)**,
transmission-gtk(1), **transmission-qt(1)**, **transmission-remote(1)**,
transmission-show(1)
<https://transmissionbt.com/>