

**NAME**

rdma-link – rdma link configuration

**SYNOPSIS**

**devlink** [ *OPTIONS* ] **link** { *COMMAND* | **help** }

*OPTIONS* := { **-V**[*ersion*] | **-d**[*etails*] }

**rdma link show** [ *DEV/PORT\_INDEX* ]

**rdma link add** **NAME** **type** **TYPE** **netdev** **NETDEV**

**rdma link delete** **NAME**

**rdma link help**

**DESCRIPTION**

**rdma link show - display rdma link attributes**

*DEV/PORT\_INDEX* - specifies the RDMA link to show. If this argument is omitted all links are listed.

**rdma link add NAME type TYPE netdev NETDEV - add an rdma link for the specified type to the network device**

**NAME** - specifies the new name of the rdma link to add

**TYPE** - specifies which rdma type to use. Link types:

**rx**e - Soft RoCE driver

**si**w - Soft iWARP driver

**NETDEV** - specifies the network device to which the link is bound

**rdma link delete NAME - delete an rdma link**

**NAME** - specifies the name of the rdma link to delete

**EXAMPLES**

rdma link show

Shows the state of all rdma links on the system.

rdma link show mlx5\_2/1

Shows the state of specified rdma link.

rdma link add rx\_e\_eth0 type rx\_e netdev eth0

Adds a RXE link named rx\_e\_eth0 to network device eth0

rdma link del rx\_e\_eth0

Removes RXE link rx\_e\_eth0

**SEE ALSO**

**rdma(8)**, **rdma-dev(8)**, **rdma-resource(8)**, **rdma-statistic(8)**,

**AUTHOR**

Leon Romanovsky <leonro@mellanox.com>