

NAME

tipc-media – list or modify media properties

SYNOPSIS

tipc media set { **priority** *PRIORITY* | **tolerance** *TOLERANCE* | **window** *WINDOW* } **media** *MEDIA*

tipc media get { **priority** | **tolerance** | **window** } **media** *MEDIA*

tipc media list

OPTIONS

Options (flags) that can be passed anywhere in the command chain.

-h, --help

Show help about last valid command. For example **tipc media --help** will show media help and **tipc --help** will show general help. The position of the option in the string is irrelevant.

DESCRIPTION**Media properties****priority**

Default link priority inherited by all bearers subsequently enabled on a media. For more info about link priority see **tipc-link(8)**

tolerance

Default link tolerance inherited by all bearers subsequently enabled on a media. For more info about link tolerance see **tipc-link(8)**

window

Default link window inherited by all bearers subsequently enabled on a media. For more info about link window see **tipc-link(8)**

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

tipc(8), **tipc-bearer(8)**, **tipc-link(8)**, **tipc-nametable(8)**, **tipc-node(8)**, **tipc-peer(8)**, **tipc-socket(8)**

REPORTING BUGS

Report any bugs to the Network Developers mailing list <netdev@vger.kernel.org> where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

AUTHOR

Richard Alpe <richard.alpe@ericsson.com>